SAFETY DATA SHEET

1. Identification

Product identifier Insulcast 42 - Part B

Other means of identification

SKU# IE169H

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers
Address 130 Commerce Drive
Montgomeryville, PA 18936

United States

Telephone Customer Service 215-855-8450

Website www.itwperformancepolymers.com

E-mail Not available.

Contact person EHS Department

Emergency phone number CHEMTREC 800-424-9300

International 703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Acute toxicity, inhalation

Category 4

Skin corrosion/irritation

Category 1C

Serious eye damage/eye irritation

Category 1

Sensitization, skin

Category 1

Germ cell mutagenicity

Category 2

Reproductive toxicity

Category 1

Specific target organ toxicity, repeated

exposure

Environmental hazards Hazardous to the aquatic environment, acute Category 1

hazard

Hazardous to the aquatic environment, Category 1

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin

reaction. Causes serious eye damage. Harmful if inhaled. Suspected of causing genetic defects. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Precautionary statement

PreventionObtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink

and understood. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear

protective gloves/protective clothing/eye protection/face protection.

Material name: Insulcast 42 - Part B
IE169H Version #: 04 Revision date: 06-30-2018 Issue date: 03-26-2014

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all Response

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get

medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Wash

contaminated clothing before reuse. Collect spillage.

Store locked up. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information 13.47% of the mixture consists of component(s) of unknown acute dermal toxicity. 19.07% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 8.8% of

the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
DIBUTYL PHTHALATE		84-74-2	60 - 100
2,4,6-tris-(dimethylaminomethyl)-ph enol		90-72-2	5 - 10
NBETA(AMINOETHYL).GAMMA -AMINOPROPYLTRIMETHOXY SILANE		1760-24-3	5 - 10
DIISOOCTYL PHTHALATE		27554-26-3	1 - 5
DI-N-BUTYLTIN OXIDE		818-08-6	1 - 5
Other components below reportable	e levels		3 - 7

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Call a poison center or doctor/physician if you feel unwell.

Remove contaminated clothing immediately and wash skin with soap and water. Chemical burns Skin contact must be treated by a physician. In case of eczema or other skin disorders: Seek medical attention

and take along these instructions. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may

Most important symptoms/effects, acute and delayed

Indication of immediate

treatment needed

General information

Ingestion

media

Fire fighting

medical attention and special

include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects. Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water

immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Foam. Dry powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Material name: Insulcast 42 - Part B

equipment/instructions

SDS US IE169H Version #: 04 Revision date: 06-30-2018 Issue date: 03-26-2014

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

Value

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type

Components	Турс	value	
DIBUTYL PHTHALATE (CAS 84-74-2)	PEL	5 mg/m3	
DI-N-BUTYLTIN OXIDE (CAS 818-08-6)	PEL	0.1 mg/m3	
US. ACGIH Threshold Limit Val	ues		
Components	Туре	Value	
DIBUTYL PHTHALATE (CAS 84-74-2)	TWA	5 mg/m3	
DI-N-BUTYLTIN OXIDE (CAS 818-08-6)	STEL	0.2 mg/m3	
	TWA	0.1 mg/m3	
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	
DIBUTYL PHTHALATE (CAS 84-74-2)	TWA	5 mg/m3	
DI-N-BUTYLTIN OXIDE (CAS 818-08-6)	TWA	0.1 mg/m3	

Biological limit values No biological exposure limits noted for the ingredient(s).

Material name: Insulcast 42 - Part B

IE169H Version #: 04 Revision date: 06-30-2018 Issue date: 03-26-2014

Exposure guidelines

US - California OELs: Skin designation

DI-N-BUTYLTIN OXIDE (CAS 818-08-6) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

DI-N-BUTYLTIN OXIDE (CAS 818-08-6) Skin designation applies.

US - Tennessee OELs: Skin designation

DI-N-BUTYLTIN OXIDE (CAS 818-08-6) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

DI-N-BUTYLTIN OXIDE (CAS 818-08-6) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

DI-N-BUTYLTIN OXIDE (CAS 818-08-6) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Chemical respirator with organic vapor cartridge and full facepiece. Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

Observe any medical surveillance requirements. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Liquid. **Appearance** Liquid. Physical state **Form** Liquid. Clear to dark Color

Slight. Odor

Odor threshold Not available. Not available. Melting point/freezing point Not available. Initial boiling point and boiling 320 °F (160 °C)

range

Flash point 255.0 °F (123.9 °C)

Evaporation rate Not available. Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

Not available.

(%)

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available. Vapor pressure 1.1 mm Hg Not available. Vapor density Not available. Relative density

Solubility(ies)

Solubility (water)

Material name: Insulcast 42 - Part B

Not available.

Partition coefficient (n-octanol/water)

Not available.

Not available. **Auto-ignition temperature Decomposition temperature** Not available. **Viscosity** Not available.

Other information

8.67 lb/gal Density **Explosive properties** Not explosive.

Flammability class Combustible IIIB estimated

Oxidizing properties Not oxidizing.

1.04 Specific gravity

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Incompatible materials Nitrates.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled.

Skin contact Causes severe skin burns. May cause an allergic skin reaction.

Causes serious eye damage. Eye contact

Ingestion Causes digestive tract burns. Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

Information on toxicological effects

Harmful if inhaled. Harmful if swallowed. **Acute toxicity**

Components **Species Test Results**

DIBUTYL PHTHALATE (CAS 84-74-2)

Acute Dermal

LD50 Rabbit 4200 mg/kg

Inhalation

LC50 Rat 15.68 mg/l, 4 Hours

Oral

LD50 Rat 6300 mg/kg

DIISOOCTYL PHTHALATE (CAS 27554-26-3)

Acute

Oral

LD50 Rat 22600 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Material name: Insulcast 42 - Part B IE169H Version #: 04 Revision date: 06-30-2018 Issue date: 03-26-2014 **Germ cell mutagenicity** Suspected of causing genetic defects.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity May damage fertility or the unborn child.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

DIBUTYL PHTHALATE 4.9
DIISOOCTYL PHTHALATE 3 - 4

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D002: Waste Corrosive material [pH <= 2 or => 12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN3066 UN proper shipping name Paint

Transport hazard class(es)

Class 8
Subsidiary risk Label(s) 8
Packing group III

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions B52, IB3, T4, TP1, TP29

Packaging exceptions 154
Packaging non bulk 173
Packaging bulk 241

Material name: Insulcast 42 - Part B
IE169H Version #: 04 Revision date: 06-30-2018 Issue date: 03-26-2014

IATA

UN number UN3066 Paint UN proper shipping name

Transport hazard class(es)

Class 8 Subsidiary risk Packing group Ш **Environmental hazards** Yes **ERG Code** 8L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Not established.

Allowed with restrictions. Cargo aircraft only

IMDG

UN3066 **UN** number PAINT, MARINE POLLUTANT

UN proper shipping name Transport hazard class(es)

Class 8 Subsidiary risk Packing group Ш

Environmental hazards

Yes Marine pollutant F-A, S-B **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



Material name: Insulcast 42 - Part B

IE169H Version #: 04 Revision date: 06-30-2018 Issue date: 03-26-2014

Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

TSCA Chemical Action Plans, Chemicals of Concern

DIBUTYL PHTHALATE (CAS 84-74-2) Phthalates Action Plan DIISOOCTYL PHTHALATE (CAS 27554-26-3) Phthalates Action Plan

CERCLA Hazardous Substance List (40 CFR 302.4)

DIBUTYL PHTHALATE (CAS 84-74-2) Listed. DIISOOCTYL PHTHALATE (CAS 27554-26-3) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

DIBUTYL PHTHALATE (CAS 84-74-2)

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

DIBUTYL PHTHALATE (CAS 84-74-2)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

Classified hazard Acute toxicity (any route of exposure) Skin corrosion or irritation categories

Serious eye damage or eye irritation Respiratory or skin sensitization

Germ cell mutagenicity Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. DIBUTYL PHTHALATE 84-74-2 60 - 100

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

DIBUTYL PHTHALATE (CAS 84-74-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

California Proposition 65

WARNING: This product can expose you to chemicals including DIBUTYL PHTHALATE, which is known to the

State of California to cause birth defects or other reproductive harm. For more information go

to www.P65Warnings.ca.gov.

Material name: Insulcast 42 - Part B

California Proposition 65 - CRT: Listed date/Developmental toxin

DIBUTYL PHTHALATE (CAS 84-74-2) Listed: December 2, 2005 Methyl Alcohol (CAS 67-56-1) Listed: March 16, 2012

California Proposition 65 - CRT: Listed date/Female reproductive toxin

DIBUTYL PHTHALATE (CAS 84-74-2) Listed: December 2, 2005

California Proposition 65 - CRT: Listed date/Male reproductive toxin

DIBUTYL PHTHALATE (CAS 84-74-2) Listed: December 2, 2005

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

DIBUTYL PHTHALATE (CAS 84-74-2)

International Inventories

Taiwan

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory *A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

03-26-2014 Issue date 06-30-2018 **Revision date**

Version # 04

Health: 3* **HMIS®** ratings

Flammability: 1 Physical hazard: 1

Health: 3 NFPA ratings

Flammability: 1 Instability: 1

ITW Performance Polymers cannot anticipate all conditions under which this information and its Disclaimer

> product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: Insulcast 42 - Part B

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).