



**SAFETY DATA SHEET**  
**MA320/MA3940 EU ACTIVATOR**

Commission Regulation (EU) No 2015/830 of 28 May 2015.

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name** MA320/MA3940 EU ACTIVATOR

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** Activator.

**1.3. Details of the supplier of the safety data sheet**

**Supplier**

ITW Performance Polymers  
 Bay 150  
 Shannon Industrial Estate  
 Co. Clare  
 Ireland  
 V14 DF82  
 353(61)771500  
 353(61)471285  
 mail@itwpp.com

**1.4. Emergency telephone number**

**Emergency telephone** +44(0)1235 239 670 (24h)

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification (EC 1272/2008)**


**Physical hazards** Not Classified

**Health hazards** Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

**Environmental hazards** Aquatic Chronic 2 - H411

**2.2. Label elements**

**Pictogram**



**Signal word**

Warning

**Hazard statements**

H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H411 Toxic to aquatic life with long lasting effects.

## MA320/MA3940 EU ACTIVATOR

<b>Precautionary statements</b>	<p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
<b>Contains</b>	EPOXY RESIN (Number average MW <= 700 ), BENZOYL PEROXIDE
<b>Supplementary precautionary statements</b>	<p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p>

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

##### 3.2. Mixtures

<b>EPOXY RESIN (Number average MW &lt;= 700 )</b> <span style="float: right;"><b>30-60%</b></span> CAS number: 25068-38-6                      EC number: 500-033-5                      REACH registration number: 01-2119456619-26-0000
<b>Classification</b> Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411
<b>BENZOYL PEROXIDE</b> <span style="float: right;"><b>10-30%</b></span> CAS number: 94-36-0                      EC number: 202-327-6
<b>Classification</b> Org. Perox. B - H241 Eye Irrit. 2 - H319 Skin Sens. 1 - H317
<b>Styrene-ethylene/butylene-styrene block copolymer</b> <span style="float: right;"><b>5-10%</b></span> CAS number: 66070-58-4
<b>Classification</b> Not Classified

The full text for all hazard statements is displayed in Section 16.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
-------------------	---

## MA320/MA3940 EU ACTIVATOR

<b>Ingestion</b>	Get medical attention immediately. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Upper respiratory irritation. Vapours may cause headache, fatigue, dizziness and nausea.
<b>Ingestion</b>	Burning sensation in mouth. May cause stomach pain or vomiting.
<b>Skin contact</b>	Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. Mild dermatitis, allergic skin rash.
<b>Eye contact</b>	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain. Conjunctivitis, irritation, tearing.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with carbon dioxide or dry powder. Do not use water jet as an extinguisher, as this will spread the fire.
<b>Unsuitable extinguishing media</b>	Foam. Water spray.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m <sup>3</sup> . Oxides of carbon. Oxides of nitrogen.
-------------------------	--

### 5.3. Advice for firefighters

<b>Protective actions during firefighting</b>	Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Containers close to fire should be removed or cooled with water. Control run-off water by containing and keeping it out of sewers and watercourses.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes.
-----------------------------	--

### 6.2. Environmental precautions

<b>Environmental precautions</b>	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

### 6.3. Methods and material for containment and cleaning up

## MA320/MA3940 EU ACTIVATOR

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

### 6.4. Reference to other sections

**Reference to other sections** For waste disposal, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Avoid contact with skin and eyes.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store in closed original container at temperatures between 0°C and 40°C. Store away from incompatible materials (see Section 10).

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

#### **BENZOYL PEROXIDE**

Long-term exposure limit (8-hour TWA): WEL 5 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit

#### **EPOXY RESIN (Number average MW <= 700 ) (CAS: 25068-38-6)**

**DNEL** Workers - Dermal; Short term systemic effects: 8.33 mg/kg/day  
Workers - Inhalation; Short term systemic effects: 12.25 mg/m<sup>3</sup>

#### **BENZOYL PEROXIDE (CAS: 94-36-0)**

**DNEL** Workers - Inhalation; Long term systemic effects: 11.75 mg/m<sup>3</sup>  
Workers - Dermal; Long term systemic effects: 6.6 mg/kg/day

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

#### Eye/face protection

Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

## MA320/MA3940 EU ACTIVATOR

<b>Hand protection</b>	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The selected gloves should have a breakthrough time of at least 8 hours. To protect hands from chemicals, gloves should comply with European Standard EN374.
<b>Other skin and body protection</b>	Wear chemical protective suit.
<b>Hygiene measures</b>	Provide eyewash station and safety shower. No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.
<b>Respiratory protection</b>	If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear a respirator fitted with the following cartridge: Organic vapour filter. Gas filter, type A2. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140. Gas and combination filter cartridges should comply with European Standard EN14387.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Viscous liquid.
<b>Odour</b>	Slight.
<b>Melting point</b>	Not determined.
<b>Initial boiling point and range</b>	Not determined.
<b>Flash point</b>	>93.3°C
<b>Upper/lower flammability or explosive limits</b>	Not determined.
<b>Vapour pressure</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>Relative density</b>	1.0-1.25 @ °C
<b>Solubility(ies)</b>	Slightly soluble in water.
<b>Auto-ignition temperature</b>	Not determined.

#### 9.2. Other information

<b>Volatile organic compound</b>	Not determined. This product contains a maximum VOC content of .
----------------------------------	--

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

<b>Reactivity</b>	The following materials may react violently with the product: Strong oxidising agents.
-------------------	--

#### 10.2. Chemical stability

<b>Stability</b>	Unstable.
------------------	-----------

#### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	Not known.
---	------------

## MA320/MA3940 EU ACTIVATOR

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat. Avoid contact with the following materials: Strong oxidising agents. Avoid contact with acids and alkalis.

### 10.5. Incompatible materials

**Materials to avoid** Strong alkalis. Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Not known.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - inhalation

**ATE inhalation (gases ppm)** 90,000.0

**ATE inhalation (vapours mg/l)** 220.0

**ATE inhalation (dusts/mists mg/l)** 30.0

<b>Inhalation</b>	Irritating to respiratory system. Vapours may irritate throat/respiratory system. A single exposure may cause the following adverse effects: Coughing. Difficulty in breathing.
<b>Ingestion</b>	May cause internal injury. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. Gastrointestinal symptoms, including upset stomach.
<b>Skin contact</b>	Irritating to skin. Prolonged and frequent contact may cause redness and irritation. May cause sensitisation by skin contact.
<b>Eye contact</b>	Irritating to eyes. Repeated exposure may cause chronic eye irritation.
<b>Acute and chronic health hazards</b>	The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive individuals.
<b>Route of entry</b>	Inhalation Ingestion. Skin and/or eye contact
<b>Target organs</b>	Eyes Skin Respiratory system, lungs

## SECTION 12: Ecological Information

**Ecotoxicity** The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

### 12.1. Toxicity

**Toxicity** Not determined.

### 12.2. Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** Not determined.

### 12.4. Mobility in soil

**Mobility** The product is miscible with water and may spread in water systems.

### 12.5. Results of PBT and vPvB assessment

## MA320/MA3940 EU ACTIVATOR

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

### 12.6. Other adverse effects

**Other adverse effects** Not known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Waste class** 08 04 99

## SECTION 14: Transport information

**General** The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

### 14.1. UN number

Not applicable.

### 14.2. UN proper shipping name

Not applicable.

### 14.3. Transport hazard class(es)

#### **Transport labels**

No transport warning sign required.

### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

#### **Environmentally hazardous substance/marine pollutant**

No.

### 14.6. Special precautions for user

Not applicable.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

**Transport in bulk according to** Not applicable.

**Annex II of MARPOL 73/78 and the IBC Code**

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU legislation** Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

**MA320/MA3940 EU ACTIVATOR****SECTION 16: Other information**

<b>Revision date</b>	05/04/2018
<b>Revision</b>	6
<b>Supersedes date</b>	02/11/2017
<b>Hazard statements in full</b>	H241 Heating may cause a fire or explosion. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.