

# ALPHACOAT 1700 Sprayable Filler



**ALPHACOAT 1700** is a sprayable two-part polyester based filler/glazing compound that is VOC compliant. Excellent for application over iron, metal, aluminum, fiberglass, wood, and polyester fillers. MEKP catalyst is not included.

## PRODUCT FEATURES

- ✓ Offers high build capabilities and fast cure times
- ✓ Self leveling and extremely easy to sand
- ✓ Can be applied to a variety of substrates
- ✓ Corrosion resistant

## PRODUCT BENEFITS

- ✓ Speeds up production
- ✓ Reduces labor and material costs
- ✓ Won't clog sand paper
- ✓ Helps level uneven surfaces and reduce pinholes

## TECHNICAL SPECIFICATIONS

APPEARANCE	PACKAGING	APPLICATION METHOD	APPROXIMATE COVERAGE
Off-White	Drum	Sprayable	1,400 sq ft/gal/mil
STYRENE	MIX RATIO	PREFERRED RED DYE CATALYST	POT LIFE
20%	2% MEKP	MEKP-9H DDM-9	2.5 min
AIR DRY TO SAND	PEAK EXOTHERM (100G MASS)	APPLICATION DENSITY RANGE	VISCOSITY
60 min	n/a	9.20 -9.70 lbs/gal	1,400-1,700 cps (LVT #3 @30 rpm)

*All Properties are measured at 77°F/25°C*

## SprayCore®

ITW Performance Polymers

11701 56th Court North, Clearwater, Florida 33760

Toll Free: 1-866-470-1462 • Phone: 727-573-3545 • Fax: 727-299-9797 • Email: [spraycoreinfo@itwpp.com](mailto:spraycoreinfo@itwpp.com)

[www.itwpp.com](http://www.itwpp.com)