

AlphaCoat 1710 Sprayable Filler



AlphaCoat 1710 is a sprayable two-part polyester based filler/glazing compound that is VOC compliant. Excellent for application over iron, metal, aluminum, fiberglass, wood, and polyester fillers. MEKP catalyst is not included.

PRODUCT FEATURES

- ✓ Offers high-build capability, approximately 15 – 30 mils per dry coat
- ✓ Can be multiple coated with no sanding between coats
- ✓ Formulated for a self-leveling application
- ✓ Extremely easy sanding material that won't clog the sand paper
- ✓ Corrosion resistant
- ✓ Designed to cure quickly

PRODUCT BENEFITS

- ✓ Helps reduce material and labor costs
- ✓ Ready to spray through external mix spray equipment eliminating pot life
- ✓ Helps speed up production throughput
- ✓ Ideal for filling most major pits, grind marks, casting flaws, and surface imperfections

TECHNICAL SPECIFICATIONS

| APPEARANCE | PACKAGING | APPLICATION METHOD | APPROXIMATE COVERAGE |
|------------|----------------------------|---------------------------|------------------------------------|
| Off-White | Drum | Sprayable | 1400 sq ft/gal/mil |
| MIX RATIO | PREFERRED RED DYE CATALYST | GEL TIME | GEL TO PEAK RANGE |
| 2% MEKP | MEKP 9H DDM-9 | 2.5 min | 60 min |
| STYRENE | PEAK EXOTHERM (100G MASS) | APPLICATION DENSITY RANGE | VISCOSITY |
| 20% | N/A | 11.75-12.25 lbs/gal | 1,600-1,850 cps (LVT #3@30 rpm) |

All Properties are measured at 77°F/25°C

SprayCore®

ITW Performance Polymers

11701 56th Court North, Clearwater, Florida 33760

Toll Free: 1-866-470-1462 • Phone: 727-573-3545 • Fax: 727-299-9797 • Email: spraycoreinfo@itwpp.com

www.itwpp.com