

100009

# AlphaFill Lightweight Putty



**AlphaFill Lightweight** is a high quality, tack-free, lightweight putty with excellent adhesion to metal, galvanized metal, aluminum, fiberglass and wood. BPO catalyst is not included.

## PRODUCT FEATURES

- ✓ Smooth texture offers great spreading
- ✓ Excellent featheredge and clog-free sanding properties
- ✓ Great adhesion to corrosion treated metals
- ✓ Formulated for low exotherm

## PRODUCT BENEFITS

- ✓ Incredibly user friendly
- ✓ Metal preparation does not require coarse grinding, preserving the factory corrosion protection

## TECHNICAL SPECIFICATIONS

APPEARANCE	PACKAGING	APPLICATION METHOD	APPROXIMATE COVERAGE
Light Grey	Pail	Pumpable Hand Applied	N/A
MIX RATIO	PREFERRED RED DYE CATALYST	POT LIFE	GEL TO PEAK RANGE
2%	BPO	3-5 min	N/A
STYRENE	PEAK EXOTHERM (100G MASS)	APPLICATION DENSITY RANGE	VISCOSITY
15-20%	N/A	9.70 lbs/gal	102,000-120,000 cps (SSA W/T-E Bar @ 20 rpm)

*All Properties are measured at 77°F/25°C*

# SprayCore®

ITW Performance Polymers

11701 56th Court North, Clearwater, Florida 33760

Toll Free: 1-866-470-1462 • Phone: 727-573-3545 • Fax: 727-299-9797 • Email: [spraycoreinfo@itwpp.com](mailto:spraycoreinfo@itwpp.com)

[www.itwpp.com](http://www.itwpp.com)