

SC 900 Radius Compound



SC 900 is a ceramic compound resin used to prevent air voids between the gel coat and the fiberglass laminate, most commonly used in tight radii. Works well in open and closed mold processes. MEKP catalyst is not included.

PRODUCT FEATURES

- ✓ Helps eliminate trapped air and heat lines
- ✓ Prevents fiberglass "spring back" in the tight radii
- ✓ Laminate can be applied onto wet radius compound
- ✓ User friendly formula with great self leveling properties

PRODUCT BENEFITS

- ✓ Increases speed of production
- ✓ Reduces time required in the final finish of the product
- ✓ Helps save on labor costs
- ✓ Increased strength due to great bonding capabilities

TECHNICAL SPECIFICATIONS

APPEARANCE	PACKAGING	APPLICATION METHOD	APPROXIMATE COVERAGE
Neutral	Drum	Brushable Sprayable	N/A
STYRENE	MIX RATIO	PREFERRED RED DYE CATALYST	GEL TIME
25%	1.5% MEKP	HP-90 DHD-9 MEKP 900	15-20 min
GEL TO PEAK RANGE	PEAK EXOTHERM (100G MASS)	APPLICATION DENSITY RANGE	VISCOSITY
15-20 min	250-300° F	10.8-11.3 lbs/gal	15,000-18,000 cps (RVF#6@20 rpm)

All Properties are measured at 77°F/25°C

SprayCore®

ITW Performance Polymers

11701 56th Court North, Clearwater, Florida 33760

Toll Free: 1-866-470-1462 • Phone: 727-573-3545 • Fax: 727-299-9797 • Email: spraycoreinfo@itwpp.com

www.itwpp.com