

# SC 1500 LS Barrier Coat



**SC 1500 LS** is a sprayable premium vinyl ester barrier coat applied directly behind the gel coat. MEKP catalyst is not included.

## PRODUCT FEATURES

- ✓ Can be applied directly behind the gel coat
- ✓ Helps stop print through from the laminate skin coat
- ✓ Formulated for quick gel and cure time
- ✓ Spray-on application dramatically reduces air entrapment behind the gel coat
- ✓ Excellent flexural strength and fatigue resistance

## PRODUCT BENEFITS

- ✓ An ideal choice for high throughput production
- ✓ Dramatically improves part profile characteristics
- ✓ Helps reduce gel coat stress and impact cracks
- ✓ Lowers finishing and labor costs

## TECHNICAL SPECIFICATIONS

APPEARANCE	PACKAGING	APPLICATION METHOD	APPROXIMATE COVERAGE
Off-White	Drum	Sprayable	1550 sq ft/gal/mil
MIX RATIO	PREFERRED DYE CATALYST	GEL TIME	GEL TO PEAK RANGE
1.50% MEKP	DHD-9 MEKP-925	1-3 mins.	3-5 mins.
STYRENE	PEAK EXOTHERM (100 G MASS)	APPLICATION DENSITY RANGE	VISCOSITY
22%	350-400°F	10.80-11.30 lbs/gal	6,000-8,000 cps (HB#4@20 rpm)

All properties are measured at 77°F/25°C

# SprayCore®

ITW Performance Polymers

11701 56th Court North, Clearwater, Florida 33760

Toll Free: 1-866-470-1462 • Phone: 727-573-3545 • Fax: 727-299-9797 • Email: [spraycoreinfo@itwpp.com](mailto:spraycoreinfo@itwpp.com)

[www.itwpp.com](http://www.itwpp.com)

07/2019 Rev. 3