

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** PLEXUS® MA560-1 Adhesive

**Other means of identification**  
SKU# IT210

**Recommended use** Not available.

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufacturer**

**Company name** ITW Performance Polymers

**Address** 30 Endicott Street  
Danvers, MA 01923  
United States

**Telephone** Customer Service 978-777-1100

**Website** www.itwperformancepolymers.com

**E-mail** Not available.

**Contact person** EHS Department

**Emergency phone number** Chemtrec 800-424-9300  
International 703-527-3887

## 2. Hazard(s) identification

**Physical hazards** Flammable liquids Category 2

**Health hazards** Acute toxicity, inhalation Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2

Sensitization, skin Category 1A

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

**Environmental hazards** Hazardous to the aquatic environment, acute hazard Category 2

Hazardous to the aquatic environment, long-term hazard Category 2

**OSHA defined hazards** Not classified.

### Label elements



### Signal word

Danger

### Hazard statement

Highly flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

### Precautionary statement

#### Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/eye protection/face protection.

<b>Response</b>	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.
<b>Storage</b>	Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
<b>Supplemental information</b>	None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Methyl Methacrylate		80-62-6	40 - 60
DODECYL METHACRYLATE		142-90-5	2.5 - 10
Poly(2-chloro-1,3-butadiene)		9010-98-4	2.5 - 10
POLY(OXY-1,2-ETHANEDIYL), .ALPHA.-(2-METHYL-1-OXO-2-PROPENYL)-.O MEGA.-METHOXY-		26915-72-0	2.5 - 10
TETRADECYL METHACRYLATE		2549-53-3	2.5 - 10
HEXADECYL METHACRYLATE		2495-27-4	1 - 2.5
MALEIC ACID		110-16-7	1 - 2.5
Other components below reportable levels			20 - 40

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a poison center or doctor/physician if you feel unwell.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. Get medical attention if symptoms occur.
<b>Most important symptoms/effects, acute and delayed</b>	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Carbon dioxide (CO <sub>2</sub> ). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Highly flammable liquid and vapor.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	<p>Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.</p> <p>Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.</p> <p>Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.</p> <p>Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.</p>
<b>Environmental precautions</b>	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

## 7. Handling and storage

<b>Precautions for safe handling</b>	<p>Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.</p> <p>For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".</p>
<b>Conditions for safe storage, including any incompatibilities</b>	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Methyl Methacrylate (CAS 80-62-6)	PEL	410 mg/m <sup>3</sup>
		100 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
Methyl Methacrylate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Methyl Methacrylate (CAS 80-62-6)	TWA	410 mg/m <sup>3</sup>
		100 ppm

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Chemical respirator with organic vapor cartridge and full facepiece.

**Skin protection**

**Hand protection** Wear appropriate chemical resistant gloves.

**Other** Wear appropriate chemical resistant clothing.

**Respiratory protection** Chemical respirator with organic vapor cartridge and full facepiece.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

**9. Physical and chemical properties**

<b>Appearance</b>	Paste.
<b>Physical state</b>	Liquid.
<b>Form</b>	Paste.
<b>Color</b>	Off-white
<b>Odor</b>	Fragrant
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	-54.4 °F (-48 °C) estimated
<b>Initial boiling point and boiling range</b>	212.9 °F (100.5 °C) estimated
<b>Flash point</b>	50.0 °F (10.0 °C) estimated
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	1.7 %
<b>Flammability limit - upper (%)</b>	12.5 %
<b>Explosive limit - lower (%)</b>	Not available.

<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	44.11 hPa estimated
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	0.97 g/cm3 estimated
<b>Explosive properties</b>	Not explosive.
<b>Flammability class</b>	Flammable IB estimated
<b>Oxidizing properties</b>	Not oxidizing.
<b>Specific gravity</b>	0.97 estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents. Nitrates. Peroxides.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Harmful if inhaled.
<b>Skin contact</b>	Causes skin irritation. May cause an allergic skin reaction.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Knowledge about health hazard is incomplete.

**Symptoms related to the physical, chemical and toxicological characteristics** Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

### Information on toxicological effects

**Acute toxicity** Harmful if inhaled.

Components	Species	Test Results
DODECYL METHACRYLATE (CAS 142-90-5)		
<u>Acute</u>		
<b>Oral</b>		
LD50	Rat	> 5 g/kg
MALEIC ACID (CAS 110-16-7)		
<u>Acute</u>		
<b>Dermal</b>		
LD50	Rabbit	1560 mg/kg
<b>Oral</b>		
LD50	Rat	708 mg/kg

Components	Species	Test Results
Methyl Methacrylate (CAS 80-62-6)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Mouse	18.5 mg/l, 2 Hours
<b>Oral</b>		
LD50	Rat	7800 mg/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	
<b>Respiratory or skin sensitization</b>		
<b>ACGIH sensitization</b>		
METHYL METHACRYLATE (CAS 80-62-6)	Dermal sensitization	
<b>Respiratory sensitization</b>	Due to partial or complete lack of data the classification is not possible.	
<b>Skin sensitization</b>	May cause an allergic skin reaction.	
<b>Germ cell mutagenicity</b>	Due to partial or complete lack of data the classification is not possible.	
<b>Carcinogenicity</b>	Due to partial or complete lack of data the classification is not possible.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Methyl Methacrylate (CAS 80-62-6)	3 Not classifiable as to carcinogenicity to humans.	
Poly(2-chloro-1,3-butadiene) (CAS 9010-98-4)	3 Not classifiable as to carcinogenicity to humans.	
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)</b>		
Not listed.		
<b>US. National Toxicology Program (NTP) Report on Carcinogens</b>		
Not listed.		
<b>Reproductive toxicity</b>	Due to partial or complete lack of data the classification is not possible.	
<b>Specific target organ toxicity - single exposure</b>	May cause respiratory irritation.	
<b>Specific target organ toxicity - repeated exposure</b>	Due to partial or complete lack of data the classification is not possible.	
<b>Aspiration hazard</b>	Due to partial or complete lack of data the classification is not possible.	
<b>Chronic effects</b>	Prolonged inhalation may be harmful.	

## 12. Ecological information

<b>Ecotoxicity</b>	Toxic to aquatic life with long lasting effects.
<b>Persistence and degradability</b>	No data is available on the degradability of any ingredients in the mixture.
<b>Bioaccumulative potential</b>	
<b>Partition coefficient n-octanol / water (log Kow)</b>	
MALEIC ACID	-0.48
Methyl Methacrylate	1.38
<b>Mobility in soil</b>	No data available.
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	D001: Waste Flammable material with a flash point <140 F The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products**

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging**

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. Transport information**

**DOT**

<b>UN number</b>	UN1133
<b>UN proper shipping name</b>	Adhesives, containing a flammable liquid
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	3
<b>Packing group</b>	III
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	B1, B52, IB3, T2, TP1
<b>Packaging exceptions</b>	150
<b>Packaging non bulk</b>	173
<b>Packaging bulk</b>	242

**IATA**

<b>UN number</b>	UN1133
<b>UN proper shipping name</b>	Adhesives containing flammable liquid
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	III
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	3L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.

**IMDG**

<b>UN number</b>	UN1133
<b>UN proper shipping name</b>	ADHESIVES containing flammable liquid
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	III
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	F-E, S-D
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

**DOT**





## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration**

Methyl Methacrylate (CAS 80-62-6) % 1.0

**US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance**

Methyl Methacrylate (CAS 80-62-6) Listed.

**Toxic Substances Control Act (TSCA)**

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

MALEIC ACID (CAS 110-16-7) Listed.

Methyl Methacrylate (CAS 80-62-6) Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** Yes

**Classified hazard categories** Flammable (gases, aerosols, liquids, or solids)  
Acute toxicity (any route of exposure)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Respiratory or skin sensitization  
Specific target organ toxicity (single or repeated exposure)  
Hazard not otherwise classified (HNOC)

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Methyl Methacrylate	80-62-6	40 - 60

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Methyl Methacrylate (CAS 80-62-6)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Contains component(s) regulated under the Safe Drinking Water Act.

**FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

Methyl Methacrylate (CAS 80-62-6) Low priority



## US state regulations

### California Proposition 65



**WARNING:** This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer, and Ethylene Glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

#### California Proposition 65 - CRT: Listed date/Developmental toxin

DIISODECYL PHTHALATE (DIDP)  
(CAS 26761-40-0) Listed: April 20, 2007

Ethylene Glycol (CAS 107-21-1) Listed: June 19, 2015

#### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Methyl Methacrylate (CAS 80-62-6)

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 06-19-2019

**Version #** 01

**HMIS® ratings**  
Health: 2  
Flammability: 3  
Physical hazard: 0

**NFPA ratings**  
Health: 2  
Flammability: 3  
Instability: 0

**Disclaimer** ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.