SAFETY DATA SHEET

1. Identification

Product identifier PLEXUS® MA530 Activator

Other means of identification

IT205 SKU#

Recommended use Not available. Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information **ITW Performance Polymers** Company name

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Customer Service Contact person Telephone number 978-777-1100

Fax E-mail

Emergency telephone

number

800-424-9300

Supplier Not available.

2. Hazard identification

Physical hazards Flammable liquids Category 2 **Health hazards** Acute toxicity, inhalation Category 4 Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2B Sensitization, skin Category 1A Category 3 respiratory tract irritation

Specific target organ toxicity following single

exposure

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction.

Causes eye irritation. Harmful if inhaled. May cause respiratory irritation.

Precautionary statement Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Material name: PLEXUS® MA530 Activator

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF Response

INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTRE/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to

extinguish.

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Methyl methacrylate		80-62-6	40 - 70
Benzyl 3-isobutyryloxy-1-isopropyl-2,2-dim ethylpropyl Phthalate		16883-83-3	5 - 10
PYRIDINE, 3,5-DIETHYL-1,2-DIHYDRO-1-PHE NYL-2-P ROPYL-		34562-31-7	1 - 5
Other components below reportable le	evels		15 - 40

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Call a poison centre or doctor/physician if you feel unwell.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area, Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Do not use water jet as an extinguisher, as this will spread the fire.

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Material name: PLEXUS® MA530 Activator

Fire fighting equipment/instructions Specific methods General fire hazards In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. Highly flammable liquid and vapour.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values Components	Туре	Value	
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	

Material name: PLEXUS® MA530 Activator SDS CANADA

Components	Туре	Value	
METHYL METHACRYLATE (CAS 80-62-6)	STEL	410 mg/m3	
,		100 ppm	
	TWA	205 mg/m3	
		50 ppm	
Canada. British Columbia O Safety Regulation 296/97, as		for Chemical Substances, Occupational Health and	
Components	Туре	Value	
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
	g. 217/2006, The Workplace Safety A	nd Health Act)	
Components	Туре	Value	
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
	ntrol of Exposure to Biological or Che		
Components	Туре	Value	
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
Canada. Quebec OELs. (Mir Components	istry of Labor - Regulation respectin Type	g occupational health and safety) Value	
METHYL METHACRYLATE	TWA	205 mg/m3	
(CAS 80-62-6)		50 ppm	
0	. (0	• •	
Components	s (Occupational Health and Safety R. Type	egulations, 1996, Table 21) Value	
METHYL METHACRYLATE (CAS 80-62-6)	15 minute	100 ppm	
	8 hour	50 ppm	
logical limit values	No biological exposure limits noted for	r the ingredient(s).	
propriate engineering trols	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommence exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.		
- ·	such as personal protective equipm		
Eye/face protection	Chemical respirator with organic vapor	our cartridge and full facepiece.	
Skin protection Hand protection	Wear appropriate chemical resistant	gloves.	
Other	Wear appropriate chemical resistant clothing.		
Respiratory protection	Chemical respirator with organic vapo	-	
Thermal hazards	Wear appropriate thermal protective of	clothing, when necessary.	
neral hygiene siderations	When using do not smoke. Always ob after handling the material and before	eserve good personal hygiene measures, such as washin e eating, drinking, and/or smoking. Routinely wash work remove contaminants. Contaminated work clothing should	

9. Physical and chemical properties

Material name: PLEXUS® MA530 Activator

Appearance Paste.

Physical state Liquid. Form Paste.

Colour Not available.

Odour Fragrant
Odour threshold Not available.

pH Not available.

Melting point/freezing point -48 °C (-54.4 °F) estimated Initial boiling point and boiling 100.5 °C (212.9 °F) estimated

range

Flash point 10.0 °C (50.0 °F) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits Flammability limit - lower 1.7 %

(%)

Flammability limit - upper

12.5 %

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper Not available.

(%)

Vapour pressure 45.46 hPa estimated

Vapour density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 0.94 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Flammable IB estimated

Oxidising properties Not oxidising.

Specific gravity 0.94 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerisation does not occur.

reactions

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidising agents. Nitrates. Peroxides.

Hazardous decompositionNo hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes eye irritation.

Material name: PLEXUS® MA530 Activator
IT205 Version #: 03 Revision date: 28-April-2020 Issue date: 16-June-2019

Ingestion Knowledge about health hazard is incomplete.

Symptoms related to the physical, chemical and toxicological characteristics

Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

exicological characteristics Skill reaction. Definations.

Information on toxicological effects

Acute toxicity Harmful if inhaled.

Components Species Test Results

Methyl methacrylate (CAS 80-62-6)

Acute

Inhalation

LC50 Mouse 18.5 mg/l, 2 Hours

Oral

LD50 Rat 7800 mg/kg

Skin corrosion/irritation
Serious eye damage/eye

Causes skin irritation.
Causes eye irritation.

irritation

Respiratory or skin sensitisation

ACGIH sensitisation

Methyl methacrylate (CAS 80-62-6)

Dermal sensitization

Canada - British Columbia OELs: Respiratory or skin sensitiser

Methyl methacrylate (CAS 80-62-6) Capable of causing respiratory, dermal or conjunctival

sensitization.

Canada - Manitoba OELs Hazard: Dermal sensitization

Methyl methacrylate (CAS 80-62-6)

Dermal sensitization

Canada - Quebec OELs: Sensitizer

Methyl methacrylate (CAS 80-62-6)

Sensitiser.

Canada - Saskatchewan OELs Hazard Data: Sensitiser

Methyl methacrylate (CAS 80-62-6) Sensitiser.

Respiratory sensitisation Due to partial or complete lack of data the classification is not possible.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity

Due to partial or complete lack of data the classification is not possible.

Carcinogenicity

Due to partial or complete lack of data the classification is not possible.

ACGIH Carcinogens

Methyl methacrylate (CAS 80-62-6)

A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Methyl methacrylate (CAS 80-62-6)

Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Methyl methacrylate (CAS 80-62-6) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicityDue to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazardDue to partial or complete lack of data the classification is not possible.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Methyl methacrylate 1.38

Mobility in soil No data available.

Material name: PLEXUS® MA530 Activator

SDS CANADA

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

UN number UN1133

ADHESIVES containing flammable liquid **UN proper shipping name**

Transport hazard class(es)

Class 3 Subsidiary risk Packing group Ш

Not available. **Environmental hazards**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN1133 **UN number**

UN proper shipping name

Transport hazard class(es)

Adhesives containing flammable liquid

3 **Class** Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 3L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

Not established.

IMDG

UN number UN1133

UN proper shipping name Transport hazard class(es)

ADHESIVES containing flammable liquid

Class 3 Subsidiary risk Ш Packing group **Environmental hazards**

Marine pollutant No. F-E, S-D **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

Material name: PLEXUS® MA530 Activator IT205 Version #: 03 Revision date: 28-April-2020 Issue date: 16-June-2019

IATA; IMDG; TDG



15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*		
Australia	Australian Inventory of Chemical Substances (AICS)	Yes		
Canada	Domestic Substances List (DSL)	Yes		
Canada	Non-Domestic Substances List (NDSL)	No		
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes		
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes		
Europe	European List of Notified Chemical Substances (ELINCS)	No		
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No		
Korea	Existing Chemicals List (ECL)	Yes		
New Zealand	New Zealand Inventory	Yes		
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes		
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes		
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes		
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing				

16. Other information

country(s).

Issue date 16-June-2019 **Revision date** 28-April-2020

Material name: PLEXUS® MA530 Activator SDS CANADA

Version No. 03

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information Composition / Information on Ingredients: Component Summary

Material name: PLEXUS® MA530 Activator

SDS CANADA