# SAFETY DATA SHEET

# 1. Identification

**Product identifier** PLEXUS® MA3940 Adhesive

Other means of identification

IT504 SKU#

Recommended use Not available. Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information **ITW Performance Polymers** Company name

**Address** 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

**Customer Service Contact person** 978-777-1100 Telephone number

Fax E-mail

**Emergency telephone** 

number

800-424-9300

**Supplier** Not available.

# 2. Hazard identification

Physical hazards Flammable liquids Category 2 **Health hazards** Acute toxicity, inhalation Category 4 Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2B Sensitization, skin Category 1A Category 3 respiratory tract irritation

Specific target organ toxicity following single

exposure

**Environmental hazards** Not classified.

Label elements



Signal word Danger

**Hazard statement** Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction.

Causes eye irritation. Harmful if inhaled. May cause respiratory irritation.

**Precautionary statement** Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

Material name: PLEXUS® MA3940 Adhesive SDS CANADA Response IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF

INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTRE/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to

extinguish.

Storage Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Methyl methacrylate		80-62-6	40 - 70
Styrene/butadiene Copolymer		9003-55-8	10 - 30
DIISODECYL ADIPATE		27178-16-1	7 - 13
Ethanol, 2,2'- (4-methylphenyl)imino Bis-		3077-12-1	0.5 - 1.5
Other components below reportable	levels		10 - 30

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

# 4. First-aid measures

**Inhalation**Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a poison centre or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

#### 5. Fire-fighting measures

**Suitable extinguishing media** Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Material name: PLEXUS® MA3940 Adhesive
IT504 Version #: 02 Revision date: 03-May-2020 Issue date: 17-July-2019

Use standard firefighting procedures and consider the hazards of other involved materials. Highly flammable liquid and vapour.

#### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

# Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

### **Environmental precautions**

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

# 7. Handling and storage

#### Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

# Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### Occupational exposure limits

US. ACGIH Threshold Limit Values Components	з Туре	Value	
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	

Material name: PLEXUS® MA3940 Adhesive

Components	Туре	Value	
METHYL METHACRYLATE (CAS 80-62-6)	STEL	410 mg/m3	
		100 ppm	
	TWA	205 mg/m3	
		50 ppm	
Safety Regulation 296/97, as	s amended)	s for Chemical Substances, Occupational Health and	
Components	Туре	Value	
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
	eg. 217/2006, The Workplace Safety		
Components	Туре	Value	
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
	ntrol of Exposure to Biological or C	<u> </u>	
Components	Туре	Value	
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
Canada. Quebec OELs. (Mir Components	nistry of Labor - Regulation respecti Type	ng occupational health and safety) Value	
METHYL METHACRYLATE	TWA	205 mg/m3	
(CAS 80-62-6)		50 ppm	
Canada Saakatahawan OEI	_s (Occupational Health and Safety	•	
Components	Type	Value	
METHYL METHACRYLATE (CAS 80-62-6)	15 minute	100 ppm	
,	8 hour	50 ppm	
logical limit values	No biological exposure limits noted	for the ingredient(s).	
propriate engineering trols	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommende exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.		
vidual protection measures,	such as personal protective equipr		
Eye/face protection	Chemical respirator with organic vap	pour cartridge and full facepiece.	
Skin protection  Hand protection	Wear appropriate chemical resistan	t gloves.	
Other	Wear appropriate chemical resistan	t clothing.	
Respiratory protection	Chemical respirator with organic var	pour cartridge and full facepiece.	
Thermal hazards	Wear appropriate thermal protective	clothing, when necessary.	
neral hygiene siderations	after handling the material and befo	observe good personal hygiene measures, such as washing re eating, drinking, and/or smoking. Routinely wash work o remove contaminants. Contaminated work clothing should	

# 9. Physical and chemical properties

Material name: PLEXUS® MA3940 Adhesive

Appearance Paste.

Physical state Liquid. Paste. Form Colour Off-white. Fragrant Odour **Odour threshold** Not available. Not available.

Melting point/freezing point -48 °C (-54.4 °F) estimated Initial boiling point and boiling 100.5 °C (212.9 °F) estimated

range

Flash point

10.0 °C (50.0 °F) estimated

**Evaporation rate** Not available. Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

2.1 % estimated

Flammability limit - upper

(%)

12.5 % estimated

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper

(%)

28 mm Hg @ 20 °C Vapour pressure

Vapour density Not available. Not available. Relative density

Solubility(ies)

Not available. Solubility (water) Not available. **Partition coefficient** 

(n-octanol/water)

**Auto-ignition temperature** Not available. Not available. **Decomposition temperature** Not available.

Other information

**Viscosity** 

0.94 g/cm3 estimated Density

**Explosive properties** Not explosive.

Flammability class Flammable IB estimated

Not oxidising. **Oxidising properties** Specific gravity 0.94 estimated

#### 10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. **Chemical stability** Possibility of hazardous Hazardous polymerisation does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidising agents. Nitrates. Peroxides.

Hazardous decomposition No hazardous decomposition products are known.

products

# 11. Toxicological information

#### Information on likely routes of exposure

Inhalation Harmful if inhaled.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes eye irritation.

Material name: PLEXUS® MA3940 Adhesive IT504 Version #: 02 Revision date: 03-May-2020 Issue date: 17-July-2019 **Ingestion** Knowledge about health hazard is incomplete.

Symptoms related to the physical, chemical and toxicological characteristics

Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

oxicological characteristics skill reaction. Definations.

Information on toxicological effects

Acute toxicity Harmful if inhaled.

Components Species Test Results

Methyl methacrylate (CAS 80-62-6)

<u>Acute</u>

Inhalation

LC50 Mouse 18.5 mg/l, 2 Hours

Oral

LD50 Rat 7800 mg/kg

Skin corrosion/irritation Causes skin irritation.
Serious eye damage/eye Causes eye irritation.

irritation

Respiratory or skin sensitisation

**ACGIH** sensitisation

Methyl methacrylate (CAS 80-62-6)

Dermal sensitization

Canada - British Columbia OELs: Respiratory or skin sensitiser

Methyl methacrylate (CAS 80-62-6) Capable of causing respiratory, dermal or conjunctival

sensitization.

Canada - Manitoba OELs Hazard: Dermal sensitization

Methyl methacrylate (CAS 80-62-6)

Dermal sensitization

Canada - Quebec OELs: Sensitizer

Methyl methacrylate (CAS 80-62-6)

Sensitiser.

Canada - Saskatchewan OELs Hazard Data: Sensitiser

Methyl methacrylate (CAS 80-62-6) Sensitiser.

**Respiratory sensitisation** Due to partial or complete lack of data the classification is not possible.

**Skin sensitisation** May cause an allergic skin reaction.

Germ cell mutagenicity

Due to partial or complete lack of data the classification is not possible.

Carcinogenicity

Due to partial or complete lack of data the classification is not possible.

**ACGIH Carcinogens** 

Methyl methacrylate (CAS 80-62-6)

A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Methyl methacrylate (CAS 80-62-6)

Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Methyl methacrylate (CAS 80-62-6)

3 Not classifiable as to carcinogenicity to humans.

Styrene/butadiene Copolymer (CAS 9003-55-8)

3 Not classifiable as to carcinogenicity to humans.

**Reproductive toxicity**Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity - Due to partial

repeated exposure

Due to partial or complete lack of data the classification is not possible.

**Aspiration hazard** Due to partial or complete lack of data the classification is not possible.

**Chronic effects** Prolonged inhalation may be harmful.

12. Ecological information

**Ecotoxicity**The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Methyl methacrylate 1.38

Material name: PLEXUS® MA3940 Adhesive

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

#### 14. Transport information

**TDG** 

UN1133 **UN number** 

**UN proper shipping name** ADHESIVES containing flammable liquid

Transport hazard class(es)

**Class** 3 Subsidiary risk Ш Packing group

**Environmental hazards** Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

**UN number** UN1133

Adhesives containing flammable liquid **UN proper shipping name** 

Transport hazard class(es) Class 3 Subsidiary risk Ш Packing group **Environmental hazards** Nο

**ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Allowed with restrictions. Cargo aircraft only

**IMDG** 

**UN number** UN1133

UN proper shipping name Transport hazard class(es) ADHESIVES containing flammable liquid

3 Class Subsidiary risk Packing group Ш

**Environmental hazards** 

No.

Marine pollutant **EmS** F-E, S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

Material name: PLEXUS® MA3940 Adhesive

IT504 Version #: 02 Revision date: 03-May-2020 Issue date: 17-July-2019

# IATA; IMDG; TDG



# 15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

#### **Controlled Drugs and Substances Act**

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

**Greenhouse Gases** 

Not listed.

**Precursor Control Regulations** 

Not regulated.

#### International regulations

#### **Stockholm Convention**

Not applicable.

#### **Rotterdam Convention**

Not applicable.

**Kyoto Protocol** 

Not applicable.

# **Montreal Protocol**

Not applicable.

#### **Basel Convention**

Not applicable.

#### **International Inventories**

Country(s) or region	Inventory name On inventory (	(yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates that all compo	nents of this product comply with the inventory requirements administered by the governing country(s)	

#### 16. Other information

country(s).

Issue date 17-July-2019
Revision date 03-May-2020

Material name: PLEXUS® MA3940 Adhesive SDS CANADA

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

IT504 Version #: 02 Revision date: 03-May-2020 Issue date: 17-July-2019

Version No.

02

**Disclaimer** 

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: PLEXUS® MA3940 Adhesive SDS CANADA 9/9