SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® Wear Guard™ Fine Load Resin

Other means of identification

SKU# 0139

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number978-777-1100

Fax E-mail

= =-------

Emergency telephone

number

800-424-9300

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2A

Sensitization, skin Category 1

Environmental hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statement

Prevention Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace. Wear eye protection/face

protection. Wear protective gloves.

Response IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

SDS CANADA

Chemical name	Common name and synonyms	CAS number	%
Silicon Carbide (sic)		409-21-2	40 - 70
Epoxy Resin:reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)	Epoxy resin	25068-38-6	15 - 40
Aluminium oxide		1344-28-1	10 - 30
FORMALDEHYDE POLYMER WITH (CHLOROMETHYL) OXIRANE AND 4,4'-(1-METHYLETHYLIDENE) BIS[PHENOL]		28906-96-9	0.1 - 1
Other components below reportable	e levels		3 - 7

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

> Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

During fire, gases hazardous to health may be formed.

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions Use water spray to cool unopened containers.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial business are stices.

industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational	exposure	limits
--------------	----------	--------

ALUMINUM OXIDE (CAS TWA 1 mg/m3 Respirable fraction 344-28-1) Silicon Carbide (sic) (CAS TWA 0.1 fibers/cm3 Fiber. 10 mg/m3 Respirable fraction 10 mg/m3 Inhalable	JS. ACGIH Threshold Limit Value Components	s Type	Value	Form
Silicon Carbide (sic) (CAS TWA 0.1 fibers/cm3 Fiber. 109-21-2) A mg/m3 Respirable fraction of mg/m3 Inhalable Inh	ALUMINUM OXIDE (CAS 1344-28-1)		1 mg/m3	Respirable fraction.
Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) Components Type Value Form ALUMINUM OXIDE (CAS TWA 0.1 fibers/cm3 Fiber. 109-21-2) 3 mg/m3 Respirable partic 10 mg/m3 Total particulate. Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health & Safety Regulation 296/97, as amended) Components Type Value Form 10 mg/m3 Respirable partic 10 mg/m3 Total particulate. Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health & Safety Regulation 296/97, as amended) Components Type Value Form 10 mg/m3 Respirable faction 10 mg/m3 Respirable. 10 mg/m3 Respirable fraction 10 mg/m3 Inhalable Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form ALUMINUM OXIDE (CAS TWA 1 mg/m3 Respirable fraction 10 mg/m3 Inhalable fra	Silicon Carbide (sic) (CAS	TWA	0.1 fibers/cm3	Fiber.
Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) Components Type Value Form ALUMINUM OXIDE (CAS TWA 10 mg/m3 1344-28-1) Silicon Carbide (sic) (CAS TWA 0.1 fibers/cm3 10 mg/m3 10 mg/m3 10 mg/m3 10 mg/m3 10 mg/m3 10 mg/m3 10 tal particulate. Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health & Safety Regulation 296/97, as amended) Components Type Value Form Silicon Carbide (sic) (CAS TWA 0.1 fibers/cm3 10 mg/m3 10 mg/m3	,		3 mg/m3	Respirable fraction.
ALUMINUM OXIDE (CAS TWA 10 mg/m3 10 mg			10 mg/m3	Inhalable fraction.
344-28-1) Silicon Carbide (sic) (CAS TWA 0.1 fibers/cm3 Fiber.	Canada. Alberta OELs (Occupatio Components			Form
3 mg/m3 Respirable partic 10 mg/m3 Total particulate. Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health a Safety Regulation 296/97, as amended) Components Type Value Form Silicon Carbide (sic) (CAS TWA 0.1 fibers/cm3 Fiber. 10 mg/m3 Inhalable Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form ALUMINUM OXIDE (CAS TWA 1 mg/m3 Respirable fraction 10 mg/m3 Inhalable fraction 10 mg/m3 Respirable fraction 10 mg/m3 Total dust.	ALUMINUM OXIDE (CAS 1344-28-1)	TWA	10 mg/m3	
Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health of Safety Regulation 296/97, as amended) Components Type Value Form Silicon Carbide (sic) (CAS TWA 0.1 fibers/cm3 Fiber. 3 mg/m3 Respirable. 10 mg/m3 Inhalable Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form ALUMINUM OXIDE (CAS TWA 0.1 fibers/cm3 Fiber. 3 mg/m3 Respirable fraction 1344-28-1) 13 mg/m3 Respirable fraction 10 mg/m3 Inhalable fraction 10 mg/m3 Respirable fraction 10 mg/m3 Respi	Silicon Carbide (sic) (CAS 409-21-2)	TWA	0.1 fibers/cm3	Fiber.
Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health a Safety Regulation 296/97, as amended) Components Type Value Form Silicon Carbide (sic) (CAS TWA 0.1 fibers/cm3 Fiber. 10 mg/m3 Respirable. 10 mg/m3 Inhalable Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form ALUMINUM OXIDE (CAS TWA 1 mg/m3 Respirable fraction 1344-28-1) Silicon Carbide (sic) (CAS TWA 0.1 fibers/cm3 Fiber. 10 mg/m3 Respirable fraction 10 mg/m3 Inhalable fraction Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form Silicon Carbide (sic) (CAS TWA 0.1 fibers/cc Respirable fraction Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form			3 mg/m3	Respirable particles
Safety Regulation 296/97, as amended) Components Type Value Form Silicon Carbide (sic) (CAS 409-21-2) 3 mg/m3 Respirable. 10 mg/m3 Inhalable Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form ALUMINUM OXIDE (CAS 1344-28-1) Silicon Carbide (sic) (CAS 409-21-2) 3 mg/m3 Respirable fraction 10 mg/m3 Inhalable fraction Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form Canada. Ontario OELs. (CAS 1WA 0.1 fibers/cm3 Inhalable fraction Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form			10 mg/m3	Total particulate.
Type Value Form Silicon Carbide (sic) (CAS AU9-21-2) TWA O.1 fibers/cm3 Fiber. 3 mg/m3 Respirable. 10 mg/m3 Inhalable Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form ALUMINUM OXIDE (CAS 1344-28-1) Silicon Carbide (sic) (CAS AU9-21-2) TWA O.1 fibers/cm3 Fiber. 3 mg/m3 Respirable fraction 10 mg/m3 Inhalable fraction Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form Canada. Ontario OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form Canada. Ontario OXIDE (CAS TWA 10 mg/m3 Total dust. Total dust. Total dust.			for Chemical Substances, Oc	cupational Health and
3 mg/m3 Respirable. 10 mg/m3 Inhalable Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form ALUMINUM OXIDE (CAS TWA 1 mg/m3 Respirable fraction 1344-28-1) Silicon Carbide (sic) (CAS TWA 0.1 fibers/cm3 Fiber. 3 mg/m3 Respirable fraction 10 mg/m3 Inhalable fr	Components	-	Value	Form
Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form ALUMINUM OXIDE (CAS 1344-28-1) Silicon Carbide (sic) (CAS 109-21-2) TWA 1 mg/m3 Respirable fraction TWA 0.1 fibers/cm3 Fiber. 3 mg/m3 Respirable fraction 10 mg/m3 Inhalable fraction Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form Silicon Carbide (sic) (CAS 109-21-2) 3 mg/m3 Respirable fraction Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value Form ALUMINUM OXIDE (CAS TWA 10 mg/m3 Total dust. Total dust. Silicon Carbide (sic) (CAS TWA 10 mg/m3 Total dust.	Silicon Carbide (sic) (CAS 409-21-2)	TWA	0.1 fibers/cm3	Fiber.
Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Form ALUMINUM OXIDE (CAS TWA 1 mg/m3 Respirable fraction 3 mg/m3 Respirable fraction 10 mg/m3 Inhalable fraction Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form Cilicon Carbide (sic) (CAS TWA 0.1 fibers/cc Respirable. Form Cilicon Carbide (sic) (CAS TWA 0.1 fibers/cc Respirable. TWA 0.1 fibers/cc Respirable fraction 10 mg/m3 Respirable fraction 10 mg/m3 Inhalable fraction Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form ALUMINUM OXIDE (CAS TWA 10 mg/m3 Total dust.			3 mg/m3	Respirable.
Components Type Value Form ALUMINUM OXIDE (CAS 1344-28-1) Silicon Carbide (sic) (CAS 409-21-2) Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form Canada. Ontario (CAS 409-21-2) TWA O.1 fibers/cm3 Fiber. Silicon Carbide (sic) (CAS TWA O.1 fibers/cc Respirable fraction Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form Canada. Quebec (Sic) (CAS TWA O.1 fibers/cc Respirable. Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value Form ALUMINUM OXIDE (CAS TWA 10 mg/m3 Total dust. Total dust. Total dust. Silicon Carbide (sic) (CAS TWA 10 mg/m3 Total dust.			10 mg/m3	Inhalable
ALUMINUM OXIDE (CAS 1 MA 1 mg/m3 Respirable fraction 1344-28-1) Silicon Carbide (sic) (CAS 1 TWA 0.1 fibers/cm3 Fiber. 3 mg/m3 Respirable fraction 10 mg/m3 Inhalable fraction 10 mg/m3 Inhalable fraction 10 mg/m3 Respirable fraction 10 mg/m3 Inhalable fraction 10 mg/m3 Inhalable fraction 10 mg/m3 Respirable. Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form Silicon Carbide (sic) (CAS TWA 0.1 fibers/cc Respirable. 10 mg/m3 Respirable fraction 10 mg/m3 Inhalable fraction 10 mg/m3 Inhalable fraction 10 mg/m3 Inhalable fraction 10 mg/m3 Total dust. ALUMINUM OXIDE (CAS TWA 10 mg/m3 Total dust. Silicon Carbide (sic) (CAS TWA 10 mg/m3 Total dust.		-		_
Silicon Carbide (sic) (CAS TWA 0.1 fibers/cm3 Fiber.		Туре	Value	Form
3 mg/m3 Respirable fraction Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form Silicon Carbide (sic) (CAS 409-21-2) 3 mg/m3 Respirable. 3 mg/m3 Respirable. 3 mg/m3 Respirable fraction 10 mg/m3 Inhalable fraction Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value Form ALUMINUM OXIDE (CAS 1344-28-1) Silicon Carbide (sic) (CAS TWA 10 mg/m3 Total dust.	ALUMINUM OXIDE (CAS 1344-28-1)	TWA	1 mg/m3	Respirable fraction.
Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form Silicon Carbide (sic) (CAS 409-21-2) 3 mg/m3 Respirable. 10 mg/m3 Inhalable fraction Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value Form ALUMINUM OXIDE (CAS TWA 10 mg/m3 Total dust. Total dust. Total dust.	Silicon Carbide (sic) (CAS 409-21-2)	TWA	0.1 fibers/cm3	Fiber.
Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Form Silicon Carbide (sic) (CAS TWA 0.1 fibers/cc Respirable. 3 mg/m3 Respirable fraction 10 mg/m3 Inhalable fraction Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value Form ALUMINUM OXIDE (CAS TWA 10 mg/m3 Total dust. Total dust.			3 mg/m3	Respirable fraction.
Components Type Value Form Silicon Carbide (sic) (CAS 409-21-2) TWA 0.1 fibers/cc Respirable. 3 mg/m3 Respirable fraction 10 mg/m3 Inhalable fraction Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form ALUMINUM OXIDE (CAS 1344-28-1) Silicon Carbide (sic) (CAS TWA 10 mg/m3 Total dust.			10 mg/m3	Inhalable fraction.
Silicon Carbide (sic) (CAS TWA 0.1 fibers/cc Respirable. 3 mg/m3 Respirable fraction 10 mg/m3 Inhalable fraction Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form ALUMINUM OXIDE (CAS TWA 10 mg/m3 Total dust.) Silicon Carbide (sic) (CAS TWA 10 mg/m3 Total dust.		-		_
3 mg/m3 Respirable fraction 10 mg/m3 Inhalable fraction 10	Components		Value	Form
Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components ALUMINUM OXIDE (CAS TWA 10 mg/m3 Total dust. Total dust. Total dust. Total dust.	Silicon Carbide (sic) (CAS 409-21-2)	TWA	0.1 fibers/cc	Respirable.
Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Type Value Form ALUMINUM OXIDE (CAS TWA 10 mg/m3 Total dust. Silicon Carbide (sic) (CAS TWA 10 mg/m3 Total dust.			3 mg/m3	Respirable fraction.
ComponentsTypeValueFormALUMINUM OXIDE (CAS 1344-28-1)TWA10 mg/m3Total dust.Silicon Carbide (sic) (CASTWA10 mg/m3Total dust.			10 mg/m3	Inhalable fraction.
ALUMINUM OXIDE (CAS TWA 10 mg/m3 Total dust. 1344-28-1) Silicon Carbide (sic) (CAS TWA 10 mg/m3 Total dust.	Canada. Quebec OELs. (Ministry o Components		-	
Silicon Carbide (sic) (CAS TWA 10 mg/m3 Total dust.	ALUMINUM OXIDE (CAS 1344-28-1)		10 mg/m3	Total dust.
· · · · - · - /	Silicon Carbide (sic) (CAS 409-21-2)	TWA	10 mg/m3	Total dust.

Material name: DEVCON® Wear Guard™ Fine Load Resin

SDS CANADA

0139 Version #: 04 Revision date: 31-December-2020 Issue date: 29-May-2019

Canada. Saskatchewan OELs (Oc Components	ccupational Health and Safety Ro	egulations, 1996, Table 21) Value	Form
ALUMINUM OXIDE (CAS 1344-28-1)	15 minute	20 mg/m3	
	8 hour	10 mg/m3	
Silicon Carbide (sic) (CAS 409-21-2)	15 minute	6 mg/m3	Respirable fraction.
		20 mg/m3	Inhalable fraction.
	8 hour	0.1 fibers/cc	Respirable fibers.
		3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

Wear appropriate chemical resistant gloves. Hand protection

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Viscous. Liquid. **Appearance**

Physical state Solid.

Liquid. Viscous. **Form** Not available. Colour

Odour Slight.

Odour threshold Not available. pН Not available. Melting point/freezing point Not available.

Initial boiling point and boiling

range

320 °C (608 °F) estimated

129.4 °C (265.0 °F) estimated Flash point

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%)

Not available.

Explosive limit - upper

Not available.

(%)

Not available. Vapour pressure Not available. Vapour density

Not available. Relative density

Solubility(ies)

Solubility (water) Not available. Not available. **Partition coefficient**

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. **Viscosity**

Other information

Density 1.64 g/cm3 estimated

Not explosive. **Explosive properties** Not oxidising. **Oxidising properties** Specific gravity 1.64 estimated VOC 100 % Solids

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Strong oxidising agents. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Knowledge about health hazard is incomplete.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Knowledge about health hazard is incomplete.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

Information on toxicological effects

Not known. **Acute toxicity**

Causes skin irritation. Skin corrosion/irritation

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant Silicon Carbide (sic) (CAS 409-21-2)

Irritant

Respiratory sensitisation Due to partial or complete lack of data the classification is not possible.

Skin sensitisation May cause an allergic skin reaction.

Due to partial or complete lack of data the classification is not possible. Germ cell mutagenicity Carcinogenicity Due to partial or complete lack of data the classification is not possible.

ACGIH Carcinogens

Aluminium oxide (CAS 1344-28-1) A4 Not classifiable as a human carcinogen.

Silicon Carbide (sic) (CAS 409-21-2) A2 Suspected human carcinogen.

Canada - Alberta OELs: Carcinogen category

Silicon Carbide (sic) (CAS 409-21-2) Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Aluminium oxide (CAS 1344-28-1) Not classifiable as a human carcinogen.

Material name: DEVCON® Wear Guard™ Fine Load Resin 0139 Version #: 04 Revision date: 31-December-2020 Issue date: 29-May-2019 SDS CANADA

Silicon Carbide (sic) (CAS 409-21-2)

Suspected human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Silicon Carbide (sic) (CAS 409-21-2)

2A Probably carcinogenic to humans.

Reproductive toxicity

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard

Due to partial or complete lack of data the classification is not possible.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential Mobility in soil

No data available. No data available.

Other adverse effects

The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

UN number

UN3082

9L

UN proper shipping name

Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin:--reaction Product Of

Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))

Transport hazard class(es)

Class 9 Subsidiary risk Ш Packing group **Environmental hazards** Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN number

ERG Code

UN3082

UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:--reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)), MARINE POLLUTANT (Epoxy Resin:--reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))

Transport hazard class(es)

9 Class Subsidiary risk Ш Packing group

Environmental hazards

Marine pollutant Yes EmS F-A, S-F

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.


Epoxy Resin:--reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

IATA; IMDG



Marine pollutant



15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or regionInventory nameOn inventory (yes/no)*AustraliaAustralian Inventory of Chemical Substances (AICS)YesCanadaDomestic Substances List (DSL)Yes

Country(s) or region Inventory name On inventory (yes/no)* Canada Non-Domestic Substances List (NDSL) China Inventory of Existing Chemical Substances in China (IECSC) Yes European Inventory of Existing Commercial Chemical Europe No Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS) No Japan Inventory of Existing and New Chemical Substances (ENCS) No Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes **Philippines** Yes

Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information

29-May-2019 Issue date **Revision date** 31-December-2020

Version No.

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information Transport Information: Material Transportation Information

0139 Version #: 04 Revision date: 31-December-2020 Issue date: 29-May-2019

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® Wear Guard™ Fine Load Hardener

Other means of identification

SKU# 5367

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number978-777-1100

Fax E-mail

Emergency telephone

number

800-424-9300

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazards Acute toxicity, inhalation Category 4

Skin corrosion/irritation

Serious eye damage/eye irritation

Sensitization, skin

Category 1

Category 1

Category 1

Category 1

Category 2

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious

eye damage. Harmful if inhaled. Suspected of damaging fertility or the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe mist/vapours. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off

contaminated clothing and wash it before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
CORUNDUM		1302-74-5	30 - 60
ALUMINATE SILICATE		1327-36-2	10 - 30
4-TERT-BUTYLPHENOL		98-54-4	7 - 13
Benzene-1,3-dimethaneami	ne	1477-55-0	3 - 7
TRIMETHYLHEXAMETHYL DIAMINE	ENE	25620-58-0	3 - 7
Titanium dioxide	Titanium dioxide	13463-67-7	0.5 - 1.5
Other components below re	portable levels		10 - 30

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Call a poison centre or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a physician

or poison control centre immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Call a physician or poison control centre immediately.

Call a physician or poison control centre immediately. Rinse mouth, Do not induce vomiting, If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

General information

Ingestion

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapours. Do not get in eyes, on skin, or on clothing. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

119	ACGIH	Threshold	I imit	Value

Components	Туре	Value	Form
ALUMINATE SILICATE (CAS 1327-36-2)	TWA	1 mg/m3	Respirable fraction.
Benzene-1,3-dimethaneami ne (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value	
Benzene-1,3-dimethaneami ne (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
CORUNDUM (CAS 1302-74-5)	TWA	10 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

Canada, British Columbia OELs, (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
ALUMINATE SILICATE (CAS 1327-36-2)	TWA	1 mg/m3	Respirable.
Benzene-1,3-dimethaneami ne (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
CORUNDUM (CAS 1302-74-5)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Titanium dioxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Canada. Manitoba OELs (Reg. 217/2	006, The Workplace Safety	And Health Act)	
Components	Туре	Value	Form

1 mg/m3

0.1 mg/m3

TWA

Ceiling

Material name: DEVCON® Wear Guard™ Fine Load Hardener

ALUMINATE SILICATE

Benzene-1,3-dimethaneami

(CAS 1327-36-2)

ne (CAS 1477-55-0)

SDS CANADA

Respirable fraction.

5367 Version #: 02 Revision date: 04-May-2020 Issue date: 16-June-2019

Canada. Manitoba OELs (Re Components	Туре	Value	Form
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. Ontario OELs. (Cor	ntrol of Exposure to Biologic	cal or Chemical Agents)	
Components	Туре	Value	Form
ALUMINATE SILICATE (CAS 1327-36-2)	TWA	1 mg/m3	Respirable fraction.
Benzene-1,3-dimethaneami ne (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
CORUNDUM (CAS 1302-74-5)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. Quebec OELs. (Mir Components	nistry of Labor - Regulation ၊ Type	respecting occupational health and sa Value	afety) Form
Benzene-1,3-dimethaneami ne (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
CORUNDUM (CAS 1302-74-5)	TWA	10 mg/m3	Total dust.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Total dust.
Canada. Saskatchewan OEL Components	s (Occupational Health and Type	Safety Regulations, 1996, Table 21) Value	Form
ALUMINATE SILICATE (CAS 1327-36-2)	15 minute	20 mg/m3	Dust.
	8 hour	10 mg/m3	Dust.
Benzene-1,3-dimethaneami ne (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
CORUNDUM (CAS 1302-74-5)	15 minute	20 mg/m3	
	8 hour	10 mg/m3	
Titanium dioxide (CAS 13463-67-7)	15 minute	20 mg/m3	
	8 hour	10 mg/m3	
ogical limit values	No biological exposure limit	s noted for the ingredient(s).	
osure guidelines	Occupational Exposure Lim	its are not relevant to the current physica	al form of the product.
Canada - Alberta OELs: Skir	n designation		
Benzene-1,3-dimethanea Canada - British Columbia (,	Can be absorbed through the skin.	
Benzene-1,3-dimethanea Canada - Manitoba OELs: S	mine (CAS 1477-55-0)	Can be absorbed through the skin.	
Benzene-1,3-dimethanea Canada - Ontario OELs: Ski		Can be absorbed through the skin.	
Benzene-1,3-dimethanea Canada - Quebec OELs: Ski		Can be absorbed through the skin.	
Danzona 1 0 dimethanaa	mine (CAS 1477-55-0)	Can be absorbed through the skin.	
Canada - Saskatchewan OE			

Can be absorbed through the skin.

Benzene-1,3-dimethaneamine (CAS 1477-55-0)

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapour cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Chemical respirator with organic vapour cartridge and full facepiece. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Paste. Physical state Liquid. Paste. **Form** Colour White

Odour Mild. Ammoniacal. **Odour threshold** Not available. pН Not available. Melting point/freezing point Not available.

Initial boiling point and boiling

274 °C (525.2 °F) estimated

Flash point 96.0 °C (204.8 °F) estimated

Not available. **Evaporation rate** Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

range

Not available.

Flammability limit - upper

(%)

Not available.

Not available. Explosive limit - lower (%) Explosive limit - upper Not available.

(%)

Vapour pressure 0.05 hPa estimated

Not available. Vapour density Not available. Relative density

Solubility(ies)

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition temperature** Not available. **Viscosity**

Other information

1.11 g/cm3 estimated **Density**

Explosive properties Not explosive.

Combustible IIIB estimated Flammability class

Oxidising properties Not oxidising Specific gravity 1.11 estimated VOC 100 % Solids

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. **Chemical stability** Possibility of hazardous Hazardous polymerisation does not occur.

Conditions to avoid

reactions

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Alkali metals.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled.

Skin contact Causes severe skin burns. May cause an allergic skin reaction.

Eve contact Causes serious eve damage. Ingestion Causes digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Information on toxicological effects

Harmful if inhaled. Acute toxicity

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant

Irritant Benzene-1,3-dimethaneamine (CAS 1477-55-0) CORUNDUM (CAS 1302-74-5) Irritant Titanium dioxide (CAS 13463-67-7) Irritant

Respiratory sensitisation Due to partial or complete lack of data the classification is not possible.

May cause an allergic skin reaction. Skin sensitisation

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible. Carcinogenicity

ACGIH Carcinogens

ALUMINATE SILICATE (CAS 1327-36-2) A4 Not classifiable as a human carcinogen. Titanium dioxide (CAS 13463-67-7) A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

ALUMINATE SILICATE (CAS 1327-36-2) Not classifiable as a human carcinogen. Titanium dioxide (CAS 13463-67-7) Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

Suspected of damaging fertility or the unborn child. Reproductive toxicity

Specific target organ toxicity single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential

No data is available on the degradability of any ingredients in the mixture.

Mobility in soil

No data available.

Other adverse effects

The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

UN number UN2735

UN proper shipping name

Transport hazard class(es)

AMINES, LIQUID, CORROSIVE, N.O.S. (Benzene-1,3-dimethaneamine), Limited Quantity

Class 8 Subsidiary risk Ш Packing group

Not available. **Environmental hazards**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN2735 **UN number**

UN proper shipping name Transport hazard class(es)

Amines, liquid, corrosive, n.o.s. (Benzene-1,3-dimethaneamine)

8 Class Subsidiary risk Packing group Ш **Environmental hazards** No. **ERG Code** 8L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN2735 **UN number**

UN proper shipping name

AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(Benzene-1,3-dimethaneamine), MARINE POLLUTANT, Limited Quantity

Transport hazard class(es)

Class 8 Subsidiary risk Ш Packing group **Environmental hazards**

Marine pollutant Yes F-A, S-B

EmS

Transport in bulk according to Not established.


Annex II of MARPOL 73/78 and

the IBC Code

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.



IMDG; TDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region Inventory name
Australia Australian Inventory of Chemical Substances (AICS)

On inventory (yes/no)*

No

Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

Inventory name

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

16. Other information

Country(s) or region

Issue date16-June-2019Revision date04-May-2020

Version No. 02

Disclaimer ITV

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

On inventory (yes/no)*

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).