

ITW Performance Polymers

SAFETY DATA SHEET MA422/425 EU Activator

Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name MA422/425 EU Activator
Product number IT 159
UFI UFI: FW10-0008-900N-D8X3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Activator. Mixes With Adhesive In Nozzle - Apply By Gunning Out Of Cartridge

1.3. Details of the supplier of the safety data sheet

Supplier ITW Performance Polymers
Bay 150
Shannon Industrial Estate
Co. Clare
Ireland
V14 DF82
353(61)771500
353(61)471285
customerservice.shannon@itwpp.com

1.4. Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Eye Irrit. 2 - H319 Skin Sens. 1 - H317
Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Warning
Hazard statements H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

MA422/425 EU Activator

Precautionary statements	<p>P261 Avoid breathing vapour/ spray.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	--

Contains DIBUTYL MALEATE, BENZOYL PEROXIDE

Supplementary precautionary statements	<p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p>
---	---

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DIBUTYL MALEATE	10-30%
CAS number: 105-76-0	
Classification	
Skin Sens. 1 - H317	
BENZOYL PEROXIDE	10-30%
CAS number: 94-36-0	EC number: 202-327-6
Classification	
Org. Perox. B - H241	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Get medical attention immediately. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

MA422/425 EU Activator

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with carbon dioxide or dry powder. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid contact with skin and eyes.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away from heat, sparks and open flame. Store away from incompatible materials (see Section 10).

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

BENZOYL PEROXIDE

MA422/425 EU Activator

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit.

DIBUTYL MALEATE (CAS: 105-76-0)

DNEL

Workers - Inhalation; Long term systemic effects: 5.87 mg/m³

Workers - Inhalation; Short term systemic effects: 5.87 mg/m³

Workers - Inhalation; Long term local effects: 5.87 mg/m³

Workers - Dermal; Long term systemic effects: 0.42 mg/kg/day

Workers - Dermal; Short term systemic effects: 24.2 mg/kg/day

Workers - Dermal; Long term local effects: 4.12 mg/cm²

BENZOYL PEROXIDE (CAS: 94-36-0)

DNEL

Workers - Inhalation; Long term systemic effects: 11.75 mg/m³

Workers - Dermal; Long term systemic effects: 6.6 mg/kg/day

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Use approved respirator if air contamination is above an acceptable level. Ensure operatives are trained to minimise exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Wear protective gloves made of the following material: Rubber or plastic. To protect hands from chemicals, gloves should comply with European Standard EN374. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated. It is recommended that gloves are made of the following material: Butyl rubber. Laminate of polyethylene and ethylene vinyl alcohol (PE/EVOH). Neoprene. Frequent changes are recommended. The selected gloves should have a breakthrough time of at least 6 hours.

Other skin and body protection

Wear apron or protective clothing in case of contact.

Hygiene measures

Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P2. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked.

MA422/425 EU Activator

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Paste.
Colour	Blue.
Odour	Slight.
pH	pH (diluted solution): 7
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	1.08 @ °C
Solubility(ies)	Slightly soluble in water.
Auto-ignition temperature	Not determined.

9.2. Other information

Volatility	<1
Volatile organic compound	This product contains a maximum VOC content of <50 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	The following materials may react violently with the product: Strong oxidising agents.
------------	--

10.2. Chemical stability

Stability	Unstable.
-----------	-----------

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not known.
------------------------------------	------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat. Avoid contact with the following materials: Strong oxidising agents. Avoid contact with acids and alkalis.
---------------------	--

10.5. Incompatible materials

Materials to avoid	Strong alkalis. Strong oxidising agents. Strong acids.
--------------------	--

10.6. Hazardous decomposition products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation	Irritating to respiratory system. Vapours may irritate throat/respiratory system. A single exposure may cause the following adverse effects: Coughing. Difficulty in breathing.
------------	---

MA422/425 EU Activator

Ingestion	May cause internal injury. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. Gastrointestinal symptoms, including upset stomach.
Skin contact	Irritating to skin. Prolonged and frequent contact may cause redness and irritation. May cause sensitisation by skin contact.
Eye contact	Irritating to eyes. Repeated exposure may cause chronic eye irritation.
Acute and chronic health hazards	The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive individuals.
Route of exposure	Inhalation Ingestion. Skin and/or eye contact
Target organs	Eyes Skin Respiratory system, lungs

Toxicological information on ingredients.

DIBUTYL MALEATE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,730.0

Species Rat

ATE oral (mg/kg) 3,730.0

BENZOYL PEROXIDE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 7,710.0

Species Rat

ATE oral (mg/kg) 7,710.0

SECTION 12: Ecological information

Ecotoxicity The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity Not considered toxic to fish.

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

Bioaccumulative potential Not determined.

12.4. Mobility in soil

Mobility The product is miscible with water and may spread in water systems.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not known.

MA422/425 EU Activator

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

No information required.

14.2. UN proper shipping name

No information required.

14.3. Transport hazard class(es)

No information required.

Transport labels

No transport warning sign required.

14.4. Packing group

No information required.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

No information required.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to No information required.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 10/02/2021

Revision 9

MA422/425 EU Activator

Supersedes date	05/04/2018
Hazard statements in full	H241 Heating may cause a fire or explosion. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.