

SAFETY DATA SHEET PHILLYCLAD 8 RESIN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name PHILLYCLAD 8 RESIN

Product number Y0017

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Resin.

1.3. Details of the supplier of the safety data sheet

Supplier

ITW Performance Polymers

Bay 150

Shannon Industrial Estate

Co. Clare Ireland V14 DF82 353(61)771500 353(61)471285 mail@itwpp.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 1235 239670

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

Human health The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive

individuals.

2.2. Label elements

Pictogram





Signal word Warning

Hazard statements H315 Causes skin irritation.

> H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P261 Avoid breathing vapour/ spray.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Contains EPOXY RESIN (Number average MW <= 700)

Supplementary precautionary

P264 Wash contaminated skin thoroughly after handling.

statements P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EPOXY RESIN (Number average MW <= 700) 60-100%

CAS number: 25068-38-6 EC number: 500-033-5 REACH registration number: 01-

2119456619-26-0000

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

TITANIUM DIOXIDE <1%

CAS number: 13463-67-7 EC number: 236-675-5 REACH registration number: 01-

2119489379-17-0000

Classification

Not Classified

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Avoid contact with skin and eyes. In case of accident or if you feel unwell, seek medical

advice immediately (show the label where possible).

Revision date: 06/04/2018 Revision: 7 Supersedes date: 09/05/2016

PHILLYCLAD 8 RESIN

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. When breathing is difficult, properly trained personnel may assist affected person

by administering oxygen. Get medical attention.

Ingestion Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink.

Never give anything by mouth to an unconscious person. Do not induce vomiting. Get medical

attention immediately.

Skin contact Remove affected person from source of contamination. Wash skin thoroughly with soap and

water. Get medical attention if irritation persists after washing.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes and get medical attention. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards Irritating gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

Keep up-wind to avoid fumes. Avoid breathing fire gases or vapours.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near

spillage. Avoid contact with skin and eyes. Wear protective clothing as described in Section 8

of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled

discharges into watercourses must be reported immediately to the Environmental Agency or

other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste

disposal containers and seal securely. Containers with collected spillage must be properly

labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

sparks and open flame. Handle and open container with care. Avoid contact with skin and eyes. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap

and water before leaving the work site.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store away

from incompatible materials (see Section 10).

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

TITANIUM DIOXIDE

Long-term exposure limit (8-hour TWA): 10 mg/m3 total dust

Ingredient commentsNo exposure limits known for ingredient(s).

EPOXY RESIN (Number average MW <= 700) (CAS: 25068-38-6)

DNEL Workers - Dermal; Short term systemic effects: 8.33 mg/kg/day

Workers - Inhalation; Short term systemic effects: 12.25 mg/m³

8.2. Exposure controls

Protective equipment









Appropriate engineering controls

Eye/face protection The following protection should be worn: Chemical splash goggles. Personal protective

Provide adequate general and local exhaust ventilation.

equipment for eye and face protection should comply with European Standard EN166.

Hand protection Wear protective gloves made of the following material: Rubber or plastic. To protect hands

from chemicals, gloves should comply with European Standard EN374. The selected gloves

should have a breakthrough time of at least 8 hours.

Other skin and body

protection

Wear chemical protective suit.

Hygiene measures Provide eyewash station and safety shower. Keep away from food, drink and animal feeding

stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do

not eat, drink or smoke when using the product.

Revision date: 06/04/2018 Revision: 7 Supersedes date: 09/05/2016

PHILLYCLAD 8 RESIN

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Check that the respirator fits tightly and the filter is changed regularly. Wear a respirator fitted with the following cartridge: Gas filter, type A2. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Viscous liquid.

Colour White.

Odour Slight.

Melting point N/D°C

Initial boiling point and range >260°C @

Flash point > 204.4°C PMCC (Pensky-Martens closed cup).

Evaporation rate <<1 (BuAc=1)

Vapour pressure 0.03mmHg @ °C

Vapour density >1

Relative density 1.18 @ 20 °C °C

Solubility(ies) Slightly soluble in water.

9.2. Other information

Other information Not available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Acids. Strong oxidising agents. Amines.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

products

Not available.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods

of time. Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Strong oxidising agents. Strong acids. Amines.

Strong mineral acids. Alkalis - organic.

10.6. Hazardous decomposition products

Hazardous decomposition

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Vapours/gases/fumes of: Acids - organic. Aldehydes.

SECTION 11: Toxicological information

Revision date: 06/04/2018 Revision: 7 Supersedes date: 09/05/2016

PHILLYCLAD 8 RESIN

11.1. Information on toxicological effects

Skin contact Irritating to skin. Prolonged or repeated exposure may cause severe irritation. May cause

sensitisation by skin contact. May cause sensitisation or allergic reactions in sensitive

individuals.

Eye contact Irritating to eyes. A single exposure may cause the following adverse effects: Corneal

damage.

SECTION 12: Ecological Information

Ecotoxicity Avoid release to the environment. Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

12.1. Toxicity

Toxicity Very toxic to aquatic organisms.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility Do not discharge into drains or watercourses or onto the ground.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be

considered.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

Waste class 08 04 99

SECTION 14: Transport information

General No other information known.

14.1. UN number

UN No. (ADR/RID) 3082
UN No. (IMDG) 3082
UN No. (ICAO) 3082

14.2. UN proper shipping name

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN

(ADR/RID) (Number average MW <= 700))

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN

(Number average MW <= 700))

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN

(Number average MW <= 700))

Proper shipping name (ADN) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN

(Number average MW <= 700))

14.3. Transport hazard class(es)

ADR/RID class 9

ADR/RID label 9

IMDG class 9

ICAO class/division 9

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group

ICAO packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-A, S-F

Emergency Action Code •3Z

Hazard Identification Number 90

(ADR/RID)

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 06/04/2018

Revision 7

Supersedes date 09/05/2016

Hazard statements in full H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.