

REPAIR COMPOUND RESIN

1. Identification	
Product identifier	
Product name	REPAIR COMPOUND RESIN
Product number	Y0021
Recommended use of the che	emical and restrictions on use
Application	Resin.
Details of the supplier of the s	safety data sheet
Supplier	
	ITW Performance Polymers
	Bay 150 Shannon Industrial Estate
	Co. Clare
	Ireland
	V14 DF82
	353(61)771500
	353(61)471285 mail@itwpp.com
Emergency telephone numbe	<u>r</u>
Emergency telephone	+44(0)1235 239 670 (24h)
2. Hazard(s) identification	
Classification of the substanc	e or mixture
Physical hazards	Not Classified
Health hazards	Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Skin Sens. 1 - H317
Environmental hazards	Aquatic Chronic 2 - H411
Human health	The product contains an epoxy resin. May cause sensitization or allergic reactions in sensitive individuals.
Label elements	
Pictogram	
Signal word	Warning
Hazard statements	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.

1/7

30-60%

1-5%

REPAIR COMPOUND RESIN

Precautionary statements	 P261 Avoid breathing vapor/ spray. P264 Wash contaminated skin thoroughly after handling. P272 Contaminated work clothing must not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 If on skin: Wash with plenty of water. P312 Call a poison center/ doctor if you feel unwell. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. P501 Dispose of contents/ container in accordance with national regulations.
Contains	EPOXY RESIN (Number average MW <= 700), 1,4-BIS[(2,3- EPOXYPROPOXY)METHYL]CYCLOHEXANE

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

EPOXY RESIN (Number average MW <= 700)

CAS number: 25068-38-6

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE

CAS number: 14228-73-0

Classification

Skin Sens. 1 - H317

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures	
Description of first aid measures	
General information	Avoid contact with skin and eyes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Inhalation	Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
Ingestion	Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does no enter the lungs. Give plenty of water to drink. Never give anything by mouth to an unconscious person. Do not induce vomiting. Get medical attention immediately.
Skin Contact	Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.

Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if irritation persists after washing.
Most important symptoms and	effects, both acute and delayed
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Indication of immediate medicate	al attention and special treatment needed
Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
5. Fire-fighting measures	
Extinguishing media	
Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.
Special hazards arising from the	he substance or mixture
Specific hazards	Irritating gases or vapors.
Advice for firefighters	
Protective actions during firefighting	Avoid breathing fire gases or vapors. Keep up-wind to avoid fumes. Do not use water jet as an extinguisher, as this will spread the fire. Control run-off water by containing and keeping it out of sewers and watercourses.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
6. Accidental release measure	S
Personal precautions, protectiv	ve equipment and emergency procedures
Personal precautions	Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with skin and eyes.
Environmental precautions	
Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.
Methods and material for conta	ainment and cleaning up
Methods for cleaning up	Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labeled with correct contents and hazard symbol.
Reference to other sections	Wear protective clothing as described in Section 8 of this safety data sheet.
7. Handling and storage	
Precautions for safe handling	
Usage precautions	Use only in well-ventilated areas. Keep away from heat, sparks and open flame. Open drum carefully as content may be under pressure. Avoid contact with skin and eyes. Avoid eating, drinking and smoking when using the product. Good personal hygiene procedures should be implemented.
Conditions for safe storage, in	cluding any incompatibilities
Storage precautions	Store in tightly-closed, original container in a dry, cool and well-ventilated place.
Specific end uses(s)	

Specific end use(s)	The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection	
Ingredient comments	No exposure limits known for ingredient(s).
Exposure controls	
Protective equipment	
Appropriate engineering controls	Provide adequate general and local exhaust ventilation.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.
Hand protection	Wear protective gloves made of the following material: Rubber or plastic.
Other skin and body protection	Wear apron or protective clothing in case of contact.
Hygiene measures	Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

information on basic physical a	
Appearance	Paste.
Color	Blue.
Odor	Slight.
рН	pH (concentrated solution): 7 @ 20 °C
Melting point	N/D°C
Initial boiling point and range	>260°C @
Flash point	> 204°C
Evaporation rate	<<1 (BuAc=1)
Vapor pressure	0.03mmHg @ °C
Vapor density	>1
Relative density	1.45 @ 20 °C°C
Solubility(ies)	Slightly soluble in water.
Auto-ignition temperature	>300°C
Other information	Not available.
10. Stability and reactivity	

Reactivity	Acids. Amines. Strong oxidizing agents.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	Will not polymerize.
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time. Avoid exposure to high temperatures or direct sunlight.
Materials to avoid	Avoid contact with the following materials: Strong oxidizing agents. Strong acids. Amines.
Hazardous decomposition products	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Vapours/gases/fumes of: Acids - organic. Aldehydes.
11. Toxicological information	
Information on toxicological ef	fects
Acute toxicity - dermal ATE dermal (mg/kg)	1,100.0
Inhalation	No significant hazard at normal ambient temperatures. Heating may generate the following products: Irritating gases or vapors.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting.
Skin Contact	Irritating to skin. Prolonged and frequent contact may cause redness and irritation. May cause sensitisation by skin contact. May cause sensitization or allergic reactions in sensitive individuals.
Eye contact	Irritating to eyes. A single exposure may cause the following adverse effects: Corneal damage.
Acute and chronic health hazards	The product contains an epoxy resin. May cause sensitization or allergic reactions in sensitive individuals.
Route of entry	Inhalation Ingestion. Skin absorption
12. Ecological Information	
Ecotoxicity	Avoid release to the environment. The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
Toxicity	Very toxic to aquatic organisms.
Persistence and degradability	
Persistence and degradability	There are no data on the degradability of this product.
Bioaccumulative potential	
Bio-Accumulative Potential	No data available on bioaccumulation.
<u>Mobility in soil</u> Mobility	Do not discharge into drains or watercourses or onto the ground.
Other adverse effects	
Other adverse effects	Not available.

13. Disposal considerations	
Waste treatment methods	
General information	When handling waste, the safety precautions applying to handling of the product should be considered.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	08 04 99
14. Transport information	
General	No other information known.
UN Number	
UN No. (TDG)	3082
UN No. (IMDG)	3082
UN No. (ICAO)	3082
UN No. (DOT)	3082
UN proper shipping name	
Proper shipping name (TDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))
Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))
Proper shipping name (DOT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))
Transport hazard class(es)	
TDG class	9
TDG label(s)	9
IMDG Class	9
ICAO class/division	9
Transport labels	
e	
Packing group	
TDG Packing Group	III
IMDG packing group	III
ICAO packing group	III
DOT packing group	III

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

EmS

F-A, S-F

Transport in bulk according to No information required. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information	
16. Other information	
Revision date	4/6/2018
Revision	9
Supersedes date	8/27/2015
Hazard statements in full	H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.