



**SAFETY DATA SHEET**  
**ULTRATHANE 5410B BLACK**

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name** ULTRATHANE 5410B BLACK

**Product number** 05410B50

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** coating

**1.3. Details of the supplier of the safety data sheet**

**Supplier**

ITW Performance Polymers  
Bay 150  
Shannon Industrial Estate  
Co. Clare  
Ireland  
V14 DF82  
353(61)771500  
353(61)471285  
mail@itwpp.com

**1.4. Emergency telephone number**

**Emergency telephone** +44(0)1235 239 670 (24h)

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification (EC 1272/2008)**

**Physical hazards** Not Classified

**Health hazards** Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Elicitation - EUH208 STOT RE 2 - H373

**Environmental hazards** Aquatic Chronic 2 - H411

**Human health**

Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates. Persons with impaired lung function should not handle this product..

**2.2. Label elements**

**Pictogram**



**Signal word**

**Warning**

## ULTRATHANE 5410B BLACK

<b>Hazard statements</b>	<p>EUH208 Contains DIBUTYLTIN DILAURATE. May produce an allergic reaction.</p> <p>H315 Causes skin irritation.</p> <p>H319 Causes serious eye irritation.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> <p>H302+H312 Harmful if swallowed or in contact with skin.</p>
<b>Precautionary statements</b>	<p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P314 Get medical advice/ attention if you feel unwell.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p>
<b>Contains</b>	DIETHYLMETHYLBENZENEDIAMINE
<b>Supplementary precautionary statements</b>	<p>P260 Do not breathe vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P270 Do not eat, drink or smoke when using this product.</p> <p>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</p> <p>P312 Call a POISON CENTER/ doctor if you feel unwell.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P330 Rinse mouth.</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P391 Collect spillage.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>DIETHYLMETHYLBENZENEDIAMINE</b>	<b>10-30%</b>
CAS number: 68479-98-1                      EC number: 270-877-4 M factor (Acute) = 1                              M factor (Chronic) = 1	
<b>Classification</b> Acute Tox. 4 - H302 Acute Tox. 4 - H312 Eye Irrit. 2 - H319 STOT RE 2 - H373 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	
<b>N,N,N',N'-TETRAKIS(2-HYDROXYLPROPYL)ETHYLENEDIAMINE</b>	<b>10-30%</b>
CAS number: 102-60-3	
<b>Classification</b> Eye Irrit. 2 - H319	



## ULTRATHANE 5410B BLACK

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with foam, carbon dioxide or dry powder.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** In case of fire and/or explosion do not breathe fumes. Toxic gases or vapours.

#### 5.3. Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. Cool containers exposed to flames with water until well after the fire is out.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** No smoking, sparks, flames or other sources of ignition near spillage. Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation. Keep upwind.

#### 6.2. Environmental precautions

**Environmental precautions** Avoid or minimise the creation of any environmental contamination. Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Absorb spillage with sand or other inert absorbent. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water.

#### 6.4. Reference to other sections

**Reference to other sections** Wear protective clothing as described in Section 8 of this safety data sheet.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Avoid inhalation of vapours/spray and contact with skin and eyes. Avoid release to the environment.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry, cool and well-ventilated place. Protect from freezing and direct sunlight. Store away from incompatible materials (see Section 10).

#### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

### SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

**CARBON BLACK**

## ULTRATHANE 5410B BLACK

Long-term exposure limit (8-hour TWA): 3.5 mg/m<sup>3</sup>

**Ingredient comments** WEL = Workplace Exposure Limits

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

#### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.

#### Hand protection

It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 8 hours.

#### Other skin and body protection

Wear chemical protective suit.

#### Hygiene measures

Provide eyewash station and safety shower. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

#### Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear a respirator fitted with the following cartridge: Gas filter, type K. Gas filter, type A2. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Liquid.
<b>Colour</b>	Black.
<b>Odour</b>	Strong.
<b>pH</b>	Not available.
<b>Melting point</b>	Not available.
<b>Initial boiling point and range</b>	175°C @
<b>Flash point</b>	100°C No potentially hazardous reactions known.
<b>Evaporation rate</b>	Not available. «59» «184» «109020»
<b>Upper/lower flammability or explosive limits</b>	Not available.
<b>Vapour pressure</b>	1.94 kPa @ °C
<b>Vapour density</b>	Not available.

## ULTRATHANE 5410B BLACK

<b>Relative density</b>	0.98 @ 25 °C°C
<b>Solubility(ies)</b>	Insoluble in water.
<b>Partition coefficient</b>	Not available.
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Not available.

### 9.2. Other information

<b>Volatility</b>	29.16
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 29.16% .

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

<b>Reactivity</b>	Stable at normal ambient temperatures and when used as recommended. The following materials may react violently with the product: Strong oxidising agents.
-------------------	--

### 10.2. Chemical stability

<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended.
------------------	---

### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	Will not polymerise.
---	----------------------

### 10.4. Conditions to avoid

<b>Conditions to avoid</b>	Avoid heat, flames and other sources of ignition.
----------------------------	---

### 10.5. Incompatible materials

<b>Materials to avoid</b>	Avoid contact with oxidising agents.
---------------------------	--------------------------------------

### 10.6. Hazardous decomposition products

<b>Hazardous decomposition products</b>	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.
---	--

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

<b>ATE oral (mg/kg)</b>	500.0
-------------------------	-------

#### Acute toxicity - dermal

<b>ATE dermal (mg/kg)</b>	1,100.0
---------------------------	---------

#### **General information**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

#### **Inhalation**

Vapours may irritate throat/respiratory system. Symptoms following overexposure may include the following: Coughing.

#### **Ingestion**

Harmful: danger of serious damage to health by prolonged exposure if swallowed. May cause discomfort if swallowed. Gastrointestinal symptoms, including upset stomach.

#### **Skin contact**

Irritating to skin. Prolonged and frequent contact may cause redness and irritation.

#### **Eye contact**

Irritating to eyes.

## ULTRATHANE 5410B BLACK

**Route of entry** Inhalation Ingestion. Skin and/or eye contact

### SECTION 12: Ecological Information

**Ecotoxicity** Toxic to aquatic organisms. Dangerous for the environment. May cause long-term adverse effects in the aquatic environment.

#### 12.1. Toxicity

**Toxicity** Very toxic to aquatic organisms.

#### 12.2. Persistence and degradability

**Persistence and degradability** There are no data on the degradability of this product.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

#### 12.4. Mobility in soil

**Mobility** Avoid or minimise the creation of any environmental contamination. Avoid the spillage or runoff entering drains, sewers or watercourses.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

**Other adverse effects** Not available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**General information** When handling waste, the safety precautions applying to handling of the product should be considered.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Waste class** 08 04 99

### SECTION 14: Transport information

**General** No other information known.

#### 14.1. UN number

**UN No. (ADR/RID)** 3082

**UN No. (IMDG)** 3082

**UN No. (ICAO)** 3082

#### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DIETHYLMETHYLBENZENEDIAMINE)

**Proper shipping name (IMDG)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DIETHYLMETHYLBENZENEDIAMINE)

## ULTRATHANE 5410B BLACK

**Proper shipping name (ICAO)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(DIETHYLMETHYLBENZENEDIAMINE)

**Proper shipping name (ADN)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(DIETHYLMETHYLBENZENEDIAMINE)

### 14.3. Transport hazard class(es)

ADR/RID class 9

ADR/RID label 9

IMDG class 9

ICAO class/division 9

### Transport labels



### 14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



### 14.6. Special precautions for user

EmS F-A, S-F

Emergency Action Code •3Z

Hazard Identification Number 90  
(ADR/RID)

Tunnel restriction code (E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information required.

Annex II of MARPOL 73/78 and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU legislation** Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.



## ULTRATHANE 5410B BLACK

### SECTION 16: Other information

<b>Revision date</b>	05/04/2018
<b>Revision</b>	20
<b>Supersedes date</b>	29/04/2016
<b>Hazard statements in full</b>	<p>EUH208 Contains DIBUTYL TIN DILAURATE. May produce an allergic reaction.</p> <p>H302 Harmful if swallowed.</p> <p>H312 Harmful in contact with skin.</p> <p>H314 Causes severe skin burns and eye damage.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H318 Causes serious eye damage.</p> <p>H319 Causes serious eye irritation.</p> <p>H341 Suspected of causing genetic defects.</p> <p>H360 May damage fertility or the unborn child.</p> <p>H370 Causes damage to organs .</p> <p>H372 Causes damage to organs through prolonged or repeated exposure.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p> <p>H400 Very toxic to aquatic life.</p> <p>H410 Very toxic to aquatic life with long lasting effects.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.