



SAFETY DATA SHEET
WEAR GUARD (HIGH TEMP 450) HARDENER

1. Identification

Product identifier

Product name WEAR GUARD (HIGH TEMP 450) HARDENER

Product number 11480

Recommended use of the chemical and restrictions on use

Application Hardener.

Details of the supplier of the safety data sheet

Supplier

ITW Performance Polymers
Bay 150
Shannon Industrial Estate
Co. Clare
Ireland
V14 DF82
353(61)771500
353(61)471285
mail@itwpp.com

Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 3 - H412

Environmental

The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Label elements

Pictogram



Signal word

Danger

WEAR GUARD (HIGH TEMP 450) HARDENER

Hazard statements	H302+H312 Harmful if swallowed or in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P260 Do not breathe vapor/ spray. P261 Avoid breathing vapor/ spray. P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing must not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P310 If swallowed: Immediately call a poison center/ doctor. P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting. P302+P352 If on skin: Wash with plenty of water. P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a poison center/ doctor if you feel unwell. P321 Specific treatment (see medical advice on this label). P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P363 Wash contaminated clothing before reuse. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.
Contains	ISOPHORONEDIAMINE
Other hazards	

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

ISOPHORONEDIAMINE	60-100%
CAS number: 2855-13-2	
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
Aquatic Chronic 3 - H412	

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

General information Do not breathe vapor/spray. Avoid contact with skin and eyes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

WEAR GUARD (HIGH TEMP 450) HARDENER

Inhalation	Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
Ingestion	Do not induce vomiting. Drink a few glasses of water or milk. Never give anything by mouth to an unconscious person. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately.
Skin Contact	Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if irritation persists after washing.

Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

Indication of immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder. Water.
-------------------------------------	--

Special hazards arising from the substance or mixture

Specific hazards	Avoid breathing fire gases or vapors.
-------------------------	---------------------------------------

Advice for firefighters

Protective actions during firefighting	Keep up-wind to avoid fumes. Control run-off water by containing and keeping it out of sewers and watercourses. Use water to keep fire exposed containers cool and disperse vapors. Warn everybody of potential hazards and evacuate if necessary.
---	--

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation. Eliminate all sources of ignition.
-----------------------------	--

Environmental precautions

Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.
----------------------------------	---

Methods and material for containment and cleaning up

Methods for cleaning up	Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labeled with correct contents and hazard symbol.
--------------------------------	---

Reference to other sections	Wear protective clothing as described in Section 8 of this safety data sheet.
------------------------------------	---

7. Handling and storage

Precautions for safe handling

WEAR GUARD (HIGH TEMP 450) HARDENER

Usage precautions Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. Avoid contact with skin and eyes. Contaminated clothing and shoes must be discarded. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented.

Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10).

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Ingredient comments WEL = Workplace Exposure Limits

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles. Personal protective equipment for eye and face protection should comply with OSHA 1910.133.

Hand protection

Use protective gloves. It is recommended that gloves are made of the following material: Rubber (natural, latex). It is recommended that gloves are made of the following material: Butyl rubber. It is recommended that gloves are made of the following material: Polyvinyl chloride (PVC). It is recommended that gloves are made of the following material: Neoprene. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. The selected gloves should have a breakthrough time of at least 8 hours.

Other skin and body protection

Wear apron or protective clothing in case of contact.

Hygiene measures

Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Check that the respirator fits tightly and the filter is changed regularly. Wear a respirator fitted with the following cartridge: Gas filter, type A2. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Liquid.

WEAR GUARD (HIGH TEMP 450) HARDENER

Color	Black.
Odor	Amine.
pH	pH (diluted solution): 11.5 5%
Melting point	N/D°C
Initial boiling point and range	249°C @
Flash point	110°C TOC (Tag open cup).
Evaporation rate	<1 (butyl acetate =1)
Upper/lower flammability or explosive limits	Upper flammable/explosive limit: N/D Lower flammable/explosive limit: N/D
Vapor density	>1
Relative density	0.92 @ 20 °C°C
Solubility(ies)	Slightly soluble in water.
Other information	Not available.

10. Stability and reactivity

Reactivity	Acids. Strong oxidizing agents.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	Will not polymerize.
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time.
Materials to avoid	Avoid contact with the following materials: Acids. Oxidizing agents.
Hazardous decomposition products	Fire or high temperatures create: Nitrous gases (NOx). Oxides of the following substances: Carbon monoxide (CO). Carbon dioxide (CO2). Vapours/gases/fumes of: Ammonia or amines.

11. Toxicological information**Information on toxicological effects****Acute toxicity - oral**

ATE oral (mg/kg) 520.83

Acute toxicity - dermal

ATE dermal (mg/kg) 1,145.83

Inhalation	High concentrations may cause severe lung damage. Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapor concentrations. May cause discomfort. Symptoms following overexposure may include the following: Headache. Dizziness. Nausea, vomiting. Delayed, often serious, breathing problems.
Ingestion	Ingestion may cause severe irritation of the mouth, the esophagus and the gastrointestinal tract. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

WEAR GUARD (HIGH TEMP 450) HARDENER

Skin Contact	Causes burns. Corrosive. Prolonged contact causes serious tissue damage. May cause sensitisation by skin contact.
Eye contact	Risk of serious damage to eyes. Causes burns. Irritation, burning, lachrymation, blurred vision after liquid splash.
Acute and chronic health hazards	This product is corrosive. This product is corrosive. This product may cause skin and eye irritation. Prolonged contact may cause burns.
Route of entry	Inhalation Skin absorption Ingestion. Skin and/or eye contact

12. Ecological Information

Ecotoxicity	Avoid releasing into the environment. The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
Toxicity	Not considered toxic to fish.
<u>Persistence and degradability</u>	
Persistence and degradability	There are no data on the degradability of this product.
<u>Bioaccumulative potential</u>	
Bio-Accumulative Potential	No data available on bioaccumulation.
<u>Mobility in soil</u>	
Mobility	Do not discharge into drains or watercourses or onto the ground.
<u>Other adverse effects</u>	
Other adverse effects	Not available.

13. Disposal considerations

Waste treatment methods

General information	When handling waste, the safety precautions applying to handling of the product should be considered.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	08 04 99

14. Transport information

General	No other information known.
<u>UN Number</u>	
UN No. (TDG)	2289
UN No. (IMDG)	2289
UN No. (ICAO)	2289
UN No. (DOT)	2289
<u>UN proper shipping name</u>	
Proper shipping name (TDG)	ISOPHORONEDIAMINE
Proper shipping name (IMDG)	ISOPHORONEDIAMINE

WEAR GUARD (HIGH TEMP 450) HARDENER

Proper shipping name (ICAO) ISOPHORONEDIAMINE

Proper shipping name (DOT) ISOPHORONEDIAMINE

Transport hazard class(es)

TDG class 8

TDG label(s) 8

IMDG Class 8

ICAO class/division 8

Transport labels**Packing group**

TDG Packing Group III

IMDG packing group III

ICAO packing group III

DOT packing group III

Environmental hazards**Environmentally Hazardous Substance**

No.

Special precautions for user

EmS F-A, S-B

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information required.

15. Regulatory information**16. Other information**

General information	Only trained personnel should use this material.
Revision date	4/4/2018
Revision	5
Supersedes date	4/28/2016
Hazard statements in full	H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.