



SAFETY DATA SHEET
MA8110 Gray Activator

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name MA8110 Gray Activator

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Activator.

1.3. Details of the supplier of the safety data sheet

Supplier

ITW Performance Polymers
Bay 150
Shannon Industrial Estate
Co. Clare
Ireland
V14 DF82
353(61)771500
353(61)471285
mail@itwpp.com

1.4. Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H335

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

MA8110 Gray Activator

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p>
Contains	METHYL METHACRYLATE, Poly(oxy-1,2-ethanediyl), α, α' -[[1-methylethylidene]di-4,1-phenylene]bis[ω -[(2-methyl-1-oxo-2-propen-1-yl)oxy]
Supplementary precautionary statements	<p>P240 Ground/ bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use only non-sparking tools.</p> <p>P243 Take precautionary measures against static discharge.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P312 Call a POISON CENTER/ doctor if you feel unwell.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

METHYL METHACRYLATE		60-100%
CAS number: 80-62-6	EC number: 201-297-1	REACH registration number: 01-2119452498-28-0000
Classification		
Flam. Liq. 2 - H225		
Skin Irrit. 2 - H315		
Skin Sens. 1 - H317		
STOT SE 3 - H335		

MA8110 Gray Activator

3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine 1-5% CAS number: 34562-31-7
Classification Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319
Poly(oxy-1,2-ethanediyl), α,α'-[(1-methylethylidene)di-4,1-phenylene]bis[ω-[(2-methyl-1-oxo-2-propen-1-yl)oxy] 1-5% CAS number: 41637-38-1
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H335 Aquatic Chronic 4 - H413

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	IF INHALED: Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if symptoms are severe or persist.
Ingestion	IF SWALLOWED: Do not induce vomiting. Call a physician or poison control centre immediately. Never give anything by mouth to an unconscious person.
Skin contact	IF ON SKIN: Remove contaminated clothing immediately and wash skin with soap and water. Continue to rinse for at least 15 minutes and get medical attention.
Eye contact	IF IN EYES: Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Continue flushing during transport to hospital. Bring these instructions.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause respiratory irritation. Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: May cause nausea, headache, dizziness and intoxication.
Skin contact	This product is strongly irritating. May cause an allergic skin reaction.
Eye contact	Severe irritation, burning, tearing and blurred vision. Overexposure may cause the following adverse effects: Corneal damage.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use foam, carbon dioxide or dry powder to extinguish.
Unsuitable extinguishing media	Do not use water, if avoidable.

MA8110 Gray Activator

5.2. Special hazards arising from the substance or mixture

Specific hazards Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

5.3. Advice for firefighters

Protective actions during firefighting In case of fire: Evacuate area. Use cold water spray to cool fire exposed containers to minimise risk of rupture. Do not enter storage areas or confined spaces unless adequately ventilated. Control run-off water by containing and keeping it out of sewers and watercourses. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate area. Keep unnecessary and unprotected personnel away from the spillage.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Eliminate all sources of ignition. Use non sparking handtools and explosion-proof electric equipment. Ventilate area. Wear chemical gloves and protective gear to avoid skin contact. Wipe spills with cloth. Incinerate or dispose wastes according to local regulations.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Provide adequate ventilation. Avoid breathing gas, fume, vapours or spray. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures. Do not reuse containers without proper cleaning or reconditioning.

Advice on general occupational hygiene Wash skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Do not store near heat sources or expose to high temperatures. Store away from incompatible materials (see Section 10).

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

METHYL METHACRYLATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 208 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 416 mg/m³

MA8110 Gray Activator

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Eye/face protection

Wear eye protection. Wear tight-fitting, dust-resistant, chemical splash goggles if airborne dust is generated. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Wear protective gloves. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 8 hours.

Other skin and body protection

Wear apron or protective clothing in case of contact.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Wear a suitable dust mask. Gas filter, type A2. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Paste.
Colour	Grey.
Flash point	10°C TCC (Tag closed cup).
Upper/lower flammability or explosive limits	: 2.1% and 12.5%

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity See Section 10.3 (Possibility of hazardous reactions) for further information.

10.2. Chemical stability

Stability Unstable.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions May polymerise.

10.4. Conditions to avoid

Conditions to avoid Extreme heat, sparks and open flame. Incompatible materials, oxidisers and oxidising conditions

10.5. Incompatible materials

MA8110 Gray Activator

Materials to avoid Oxidising agents (such as peroxides), reducing agents, acids, bases, azo-compounds, catalytic metals (such as copper, iron), halogens. Free radical initiators. Oxygen scavengers.

10.6. Hazardous decomposition products

Hazardous decomposition products Vapours may be ignited by a spark, a hot surface or an ember.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 200,000.0

Acute toxicity - dermal

ATE dermal (mg/kg) 440,000.0

Inhalation This product is moderately irritating. Gas or vapour is harmful on prolonged exposure or in high concentrations. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin contact Prolonged or repeated exposure may cause severe irritation. May cause an allergic skin reaction.

Eye contact Causes severe skin burns and eye damage.

Route of entry Inhalation Ingestion Skin and/or eye contact

SECTION 12: Ecological Information

Ecotoxicity No information available.

12.1. Toxicity

Toxicity No data available.

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential No information available.

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment No data available.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

MA8110 Gray Activator

General information	The generation of waste should be minimised or avoided wherever possible. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Dispose of waste product or used containers in accordance with local regulations
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	08 04 09

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1133
UN No. (IMDG)	1133
UN No. (ICAO)	1133
UN No. (ADN)	1133

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	ADHESIVES
Proper shipping name (IMDG)	ADHESIVES
Proper shipping name (ICAO)	ADHESIVES
Proper shipping name (ADN)	ADHESIVES

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ADN packing group	II
ICAO packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

MA8110 Gray Activator

14.6. Special precautions for user

EmS	F-E, S-D
ADR transport category	2
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
----------------	--

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date	05/04/2018
Revision	1
Supersedes date	26/08/2016
SDS number	20771
Hazard statements in full	H225 Highly flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H413 May cause long lasting harmful effects to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.