SAFETY DATA SHEET

Version # 10

Issue date: 05-29-2019 Revision date: 07-28-2023 Supersedes date: 07-15-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

DEVCON® Wear Guard™ Fine Load Resin

Registration number

None. Synonyms SKU# 0139

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Not available. Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

ITW Performance Polymers Company Name

Bay 150 Address

Shannon Industrial Estate

Co. Clare Ireland V14 DF82

Contact Person Customer Service Telephone Number 353(61)771500

353(61)471285

customerservice.shannon@itwpp.com **Fmail**

Emergency Phone Number 44(0) 1235 239 670 (24 hours)

1.4. Emergency telephone number

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons

Information Center

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Belgium National Poisons

Control Center

070 245 245 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Bulgaria National

Toxicological Information

Center

+359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Croatia Poisons Information Center +385 1 2348 342 (Hours of operation not provided. SDS/Product information may

not be available for the Emergency Service.)

Cyprus Poison Center

1401 (Available 24 hours a day. SDS/Product information may not be available

for the Emergency Service.)

Czech Republic National Poisons Information

Center

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons

Control Center

+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Estonia National Poisons Information Center

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be

available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

1.4. Emergency telephone number

Greece Poison Information Centre

(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Hungary National Emergency Phone Number +36-80-201-199 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Iceland Poison Center

(+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Latvia Emergency medical

aid

+371 67042473 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.) Information Center

113

Lithuania Neatidėliotina informacija apsinuodijus

Latvia Poison and Drug

+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and **Emergency Department**

2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Netherlands National Poisons Information Center (NVIC)

NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel in cases of acute intoxications)

Norway Norwegian Poison Information Center

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Portugal Poison Center

800 250 250 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Romania Biroul RSI si Informare Toxicologica 021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be

available for the Emergency Service.)

Slovakia National Toxicological Information Center

+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Spain Toxicology Information Service + 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Sweden National Poison Information Center

112 - and ask for Poison Information (Available 24 hours a day. SDS/Product

information may not be available for the Emergency Service.)

Switzerland Tox Info Suisse

145 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Skin sensitization

Skin corrosion/irritation Category 2 H315 - Causes skin irritation. Serious eye damage/eye irritation Category 2 H319 - Causes serious eye irritation.

> Category 1 H317 - May cause an allergic skin

reaction.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Austria: R080-X00F-100S-AH9P Belgium: R080-X00F-100S-AH9P Bulgaria: R080-X00F-100S-AH9P Croatia: R080-X00F-100S-AH9P Cyprus: R080-X00F-100S-AH9P

Czech Republic: R080-X00F-100S-AH9P Denmark: R080-X00F-100S-AH9P Estonia: R080-X00F-100S-AH9P EU: R080-X00F-100S-AH9P Finland: R080-X00F-100S-AH9P France: R080-X00F-100S-AH9P Germany: R080-X00F-100S-AH9P Greece: R080-X00F-100S-AH9P Hungary: R080-X00F-100S-AH9P Iceland: R080-X00F-100S-AH9P Ireland: R080-X00F-100S-AH9P Italy: R080-X00F-100S-AH9P Latvia: R080-X00F-100S-AH9P Lithuania: R080-X00F-100S-AH9P Luxembourg: R080-X00F-100S-AH9P Malta: R080-X00F-100S-AH9P Netherlands: R080-X00F-100S-AH9P

Norway: R080-X00F-100S-AH9P Poland: R080-X00F-100S-AH9P Portugal: R080-X00F-100S-AH9P Romania: R080-X00F-100S-AH9P Slovakia: R080-X00F-100S-AH9P Slovenia: R080-X00F-100S-AH9P

Spain: R080-X00F-100S-AH9P Sweden: R080-X00F-100S-AH9P

Contains: Aluminium Oxide, Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers, reaction product:

bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

Hazard pictograms



Signal word Warning

Hazard statements

Causes skin irritation.

May cause an allergic skin reaction. H317 Causes serious eye irritation. H319

Precautionary statements

Prevention

Avoid breathing mist/vapors. P261 Wash thoroughly after handling. P264

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear eye protection/face protection.

P280 Wear protective gloves.

Response

IF ON SKIN: Wash with plenty of water. P302 + P352

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present P305 + P351 + P338

and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/attention. P333 + P313 If eye irritation persists: Get medical advice/attention. P337 + P313 Take off contaminated clothing and wash it before reuse. P362 + P364

Storage Not available.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Supplemental label information

85,6% of the mixture consists of component(s) of unknown acute inhalation toxicity.

2.3. Other hazards This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a

concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

| Chemical name | % | CAS-No. / EC No. | REACH Registration No. | Index No. | Notes |
|---|------------------------------|-------------------------|-----------------------------|--------------|-------|
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) | 60 - < 70 | 409-21-2 206-991-8 | - | 014-048-00-5 | |
| Classification: | Water-Rea | ct. 3;H261, Carc. 1B | ;H350i | | |
| Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers | 20 - < 30 | 25085-99-8 - | - | - | |
| Classification: | Skin Irrit. 2 | ;H315, Eye Irrit. 2;H3 | 319, Skin Sens. 1;H317 | | |
| Aluminium Oxide | 10 - < 20 | 1344-28-1 215-691-6 | - | - | |
| Classification: | - | | | | |
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) | < 0,3 | 25068-38-6 500-033-5 | 01-2119456619-26-0000 | 603-074-00-8 | |
| | Skin Irrit. 2 Chronic 2;I | | 319, Skin Sens. 1;H317, Aqu | ıatic | |
| Specific Concentration Limits: | Skin Irrit. 2 | ;H315: C ≥ 5 %, Eye | Irrit. 2;H319: C ≥ 5 % | | |

Other components below reportable

levels

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance. PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

3 - 7

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and

delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Special fire fighting procedures

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

For emergency responders

Keep unnecessary personnel away. Ensure adequate ventilation. Avoid breathing mist/vapors. Local authorities should be advised if significant spillages cannot be contained. Use personal

protection recommended in Section 8 of the SDS.

Avoid discharge into drains, water courses or onto the ground.

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product

recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the

SDS).

7.3. Specific end use(s)

Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

| Austria. MAK List, OEL Ordinance (Gv | wV), BGBI, II, no. 184/2001, as amend | led |
|--------------------------------------|---------------------------------------|-----|
|--------------------------------------|---------------------------------------|-----|

| Components | Туре | Value | Form |
|--|------|----------|----------------------|
| Aluminium Oxide (CAS 1344-28-1) | MAK | 5 mg/m3 | Respirable fraction. |
| | | 5 mg/m3 | Respirable fume. |
| | | 10 mg/m3 | Inhalable fraction. |
| | STEL | 20 mg/m3 | Inhalable fraction. |
| | | 10 mg/m3 | Respirable fume. |
| | | 10 mg/m3 | Respirable fraction. |
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | MAK | 5 mg/m3 | Respirable fraction. |
| | STEL | 10 mg/m3 | Respirable fraction. |

Belgium. OEL. Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1 -Chemical agents, as amended

| Components | Туре | Value | Form |
|--|------|----------|----------------------|
| Aluminium Oxide (CAS 1344-28-1) | TWA | 1 mg/m3 | Respirable fraction. |
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | TWA | 10 mg/m3 | |

Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as amended

| Components | Туре | Value | Form |
|--|------|-----------|----------------------|
| Aluminium Oxide (CAS 1344-28-1) | TWA | 10 mg/m3 | Inhalable fraction. |
| | | 1,5 mg/m3 | Respirable fraction. |
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | TWA | 5 mg/m3 | Inhalable fraction. |

Croatia. OELs (GVI). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and Biological Limit Values, Annex I (NN 91/2018), as amended

| Components | Type | Value | Form |
|--|------|----------|------------------|
| Aluminium Oxide (CAS 1344-28-1) | MAC | 4 mg/m3 | Respirable dust. |
| | | 10 mg/m3 | Total dust. |
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | MAC | 4 mg/m3 | Respirable dust. |
| | | 10 mg/m3 | Total dust. |

Czech Republic. Occupational exposure limit values of chemicals at work (Decree on protection of health at work, 361/2007, Annex 2, Part A & Annex 3, Part A, as amended)

| Components | Туре | Value | Form |
|---------------------------------|------|-----------|------------------|
| Aluminium Oxide (CAS 1344-28-1) | TWA | 0,1 mg/m3 | Respirable dust. |

Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, Annex 2

| Components | Туре | Value | Form |
|--|------|-----------|-----------------------------|
| Aluminium Oxide (CAS 1344-28-1) | TLV | 5 mg/m3 | Total |
| | | 2 mg/m3 | Respirable. |
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | TLV | 5 mg/m3 | Respirable dust. |
| | | 10 mg/m3 | Dust. |
| | | 0,5 mg/m3 | Respirable quartz fraction. |

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended Components Type Value Form

| Components | туре | value | Form |
|--|------|----------|---------------------------------|
| Aluminium Oxide (CAS 1344-28-1) | TWA | 4 mg/m3 | Fine dust, respiratory fraction |
| | | 10 mg/m3 | Total dust. |
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | TWA | 5 mg/m3 | Fine dust, respiratory fraction |
| | | 10 mg/m3 | Respirable fraction. |

Finland. HTP-arvot, App 3., Binding Limit Values, Social Affairs and Ministry of Health Components Type Value

silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2)

TWA 0,1 fibers/cm3

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value

Aluminium Oxide (CAS VME 10 mg/m3 1344-28-1)

Regulatory status: Indicative limit (VL)

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value

VME

silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2)

10 mg/m3

1,25 mg/m3

Respirable fraction.

Regulatory status: Indicative limit (VL)

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG), as updated

| Components | Туре | Value | Form |
|--|------|-----------|------------------|
| Aluminium Oxide (CAS 1344-28-1) | TWA | 4 mg/m3 | Inhalable dust. |
| | | 1,5 mg/m3 | Respirable dust. |
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | TWA | 4 mg/m3 | Inhalable dust. |

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

| Components | Туре | Value | Form |
|--|------|------------|----------------------|
| Aluminium Oxide (CAS 1344-28-1) | AGW | 10 mg/m3 | Inhalable fraction. |
| | | 1,25 mg/m3 | Respirable fraction. |
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | AGW | 10 mg/m3 | Inhalable fraction. |

Greece. OELs, Presidential Decree No. 307/1986, as amended

| Components | Туре | Value | Form | |
|--|------|----------|-------------|--|
| Aluminium Oxide (CAS 1344-28-1) | TWA | 5 mg/m3 | Respirable. | |
| | | 10 mg/m3 | Inhalable | |
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | TWA | 5 mg/m3 | Respirable. | |
| | | 10 mg/m3 | Inhalable | |

Hungary. OELs. Decree on protection of workers exposed to chemical agents (5/2020. (II.6)), Annex 1&2, as amended Components Type Value Form

Aluminium Oxide (CAS TWA 5 mg/m3 1344-28-1) 2 mg/m3 Respirable.

Iceland. OELs. Regulation 390/2009 on Pollution Limits and Measures to Reduce Pollution at the Workplace, as amended Components

Type

Value

Aluminium Oxide (CAS TWA 10 mg/m3 1344-28-1)

Ireland. OELVs, Schedules 1 & 2, Code of Practice for Chemical Agents and Carcinogens Regulations

| Components | Type | Value | Form |
|--|------|----------------|-----------------------|
| Aluminium Oxide (CAS 1344-28-1) | TWA | 4 mg/m3 | Respirable dust. |
| | | 10 mg/m3 | Total inhalable dust. |
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | TWA | 0,1 fibers/cm3 | Fiber. |
| | | 3 mg/m3 | Respirable dust. |
| | | 10 mg/m3 | Total inhalable dust. |

| Components | 1, 9 April 2008), as amended Type | Value | Form |
|--|---|---|---|
| ilicon carbide fibres (with liameter < 3 .mu.m, length • 5 .mu.m and aspect ratio • 3:1) (CAS 409-21-2) | TWA | 0,1 fibers/cm3 | Fiber. |
| | | 3 mg/m3 | Respirable fraction. |
| | | 10 mg/m3 | Inhalable fraction. |
| .atvia. OELs. Occupational Expos), as amended | ure Limits of Chemical Substa | ances at Workplace (Reg. No. 3 | 325/ 2007, L.V. 80, Annex |
| Components | Туре | Value | Form |
| Aluminium Oxide (CAS 344-28-1) | TWA | 6 mg/m3 | Decomposition aerosol. |
| | | 4 mg/m3 | |
| ilicon carbide fibres (with liameter < 3 .mu.m, length 5 .mu.m and aspect ratio 2 3:1) (CAS 409-21-2) | TWA | 6 mg/m3 | |
| Lithuania. OELs. Occupational Exp 7-824/A1-389), as amended Components | oosure Limit Values for Chemi Type | ical Substances (Hygiene Nori Value | m HN 23:2011; Order No. |
| <u> </u> | TWA | | |
| silicon carbide fibres (with liameter < 3 .mu.m, length ► 5 .mu.m and aspect ratio ≿ 3:1) (CAS 409-21-2) | TWA | 5 mg/m3 | Respirable fraction. |
| | | 10 mg/m3 | Inhalable fraction. |
| Norway. Regulation No. 1358 on M | easures and Limit Values for | Physical and Chemical Factor | s in Work Environment ar |
| nfection Groups for Biological Fac Components | ctors, as amended Type | Value | Form |
| Aluminium Oxide (CAS 1344-28-1) | TLV | 10 mg/m3 | |
| silicon carbide fibres (with liameter < 3 .mu.m, length - 5 .mu.m and aspect ratio - 3:1) (CAS 409-21-2) | TLV | 0,1 fibers/cm3 | Fiber. |
| , , | | 0,5 mg/m3 | Dognirable dust |
| | | 0,5 mg/m5 | Respirable dust. |
| | centrations and intensities of | | • |
| 286/2018, Annex 1) | centrations and intensities of | | • |
| 1286/2018, Annex 1) Components Aluminium Oxide (CAS | | harmful factors in the work e | nvironment (Dz.U.Poz. |
| 286/2018, Annex 1) Components Aluminium Oxide (CAS | Туре | harmful factors in the work e | nvironment (Dz.U.Poz. |
| Aluminium Oxide (CAS 1344-28-1) Silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio | Туре | Value 2,5 mg/m3 | Form Inhalable fraction. |
| Aluminium Oxide (CAS 344-28-1) silicon carbide fibres (with diameter < 3 .mu.m, length 5 .mu.m and aspect ratio 3:1) (CAS 409-21-2) Portugal. VLEs. Norm on occupation | Type TWA | Value 2,5 mg/m3 1,2 mg/m3 10 mg/m3 | Form Inhalable fraction. Respirable fraction. |
| 286/2018, Annex 1) Components Aluminium Oxide (CAS 344-28-1) illicon carbide fibres (with liameter < 3 .mu.m, length 5 .mu.m and aspect ratio 3:1) (CAS 409-21-2) Portugal. VLEs. Norm on occupation Components Aluminium Oxide (CAS | Type TWA TWA onal exposure to chemical ago | Value 2,5 mg/m3 1,2 mg/m3 10 mg/m3 ents (NP 1796-2014) | Form Inhalable fraction. Respirable fraction. Inhalable fraction. |
| Components Aluminium Oxide (CAS 344-28-1) Idilicon carbide fibres (with liameter < 3 .mu.m, length | Type TWA TWA onal exposure to chemical agony | Value 2,5 mg/m3 1,2 mg/m3 10 mg/m3 ents (NP 1796-2014) Value | Form Inhalable fraction. Respirable fraction. Inhalable fraction. Form |
| Poland. Maximum permissible con 1286/2018, Annex 1) Components Aluminium Oxide (CAS 1344-28-1) Silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) Portugal. VLEs. Norm on occupation occup | Type TWA TWA onal exposure to chemical ago Type TWA | Value 2,5 mg/m3 1,2 mg/m3 10 mg/m3 ents (NP 1796-2014) Value 1 mg/m3 | Form Inhalable fraction. Respirable fraction. Inhalable fraction. Form Respirable fraction. |

Romania. OELs. Limit Values of Chemical Agents at Workplace (Regulation 1.218/2006, M.O 845, Annex 1, 3&4, as amended)

| Components | Type | Value | Form |
|--|------|----------|---------------------|
| Aluminium Oxide (CAS 1344-28-1) | STEL | 5 mg/m3 | Aerosol. |
| | TWA | 2 mg/m3 | Aerosol. |
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | TWA | 10 mg/m3 | Inhalable fraction. |

Slovakia. OELs. Maximum permissible exposure limits for chemical factors in workplace air (Regulation No 355/2006, Annex 1, Table 1, as amended)

| Components | Туре | Value | Form |
|--|------|-----------|----------------------|
| Aluminium Oxide (CAS 1344-28-1) | TWA | 4 mg/m3 | Inhalable fraction. |
| | | 0,1 mg/m3 | Respirable fraction. |
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | TWA | 4 mg/m3 | Inhalable fraction. |
| | | 1,5 mg/m3 | Respirable fraction. |

Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Annex I), as amended

| Components | Туре | Value | Form |
|--|------|------------|----------------------|
| Aluminium Oxide (CAS 1344-28-1) | TWA | 10 mg/m3 | Inhalable fraction. |
| | | 1,25 mg/m3 | Respirable fraction. |
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | TWA | 10 mg/m3 | Inhalable fraction. |
| | | 1.25 mg/m3 | Respirable fraction |

Spain. OELs. INSST, Límites de Exposición Profesional Para Agentes Químicos, Table 1-Valores Límites Ambientales (VLAs)

| Components | Type | Value | Form |
|--|------|----------|----------------------|
| Aluminium Oxide (CAS 1344-28-1) | TWA | 10 mg/m3 | |
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | TWA | 3 mg/m3 | Respirable fraction. |
| | | 10 mg/m3 | Inhalable fraction. |

Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended

| Components | Туре | Value | Form |
|--|------|---------------|------------------|
| Aluminium Oxide (CAS 1344-28-1) | TWA | 5 mg/m3 | Total dust. |
| | | 2 mg/m3 | Respirable dust. |
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | TWA | 0,2 fibers/ml | |

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte

| Components | Туре | Value | Form |
|------------------------------------|------|----------|------------------------------|
| Aluminium Oxide (CAS 1344-28-1) | STEL | 24 mg/m3 | Respirable dust and/or fume. |
| | TWA | 3 mg/m3 | Respirable dust. |
| | | 3 mg/m3 | Respirable dust and/or fume. |

| | Туре | | Va | lue | Form |
|--|---|--|---|---|---|
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | TWA | | 3 r | ng/m3 | Respirable dust. |
| | | | 10 | mg/m3 | Inhalable dust. |
| UK. OELs. Workplace Expo | osure Limits (WELs) (I Type | EH40/2005 (Fourth | | , Table 1 lue | Form |
| Aluminium Oxide (CAS 1344-28-1) | TWA | | | ng/m3 | Respirable dust. |
| silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2) | TWA | | | mg/m3 ng/m3 | Inhalable dust. Respirable. |
| | | | 10 | mg/m3 | Inhalable |
| logical limit values Hungary. BELs. Decree on Components | protection of workers Value | s exposed to chem Determinant | nical agents (5/ Specimen | 2020. (II.6)), <i>I</i> Sampling | |
| Aluminium Oxide (CAS 1344-28-1) | 0,25 µmol/mmol | Aluminum | Creatinine in urine | * | |
| (| 0,06 mg/g | Aluminum | Creatinine in urine | * | |
| * - For sampling details, pleas | | | | | |
| Switzerland. SUVA Grenzw Components | erte am Arbeitsplatz: Value | Aktuelle BAT-Wer Determinant | rte Specimen | Sampling | Time |
| AL :: 0:1 (0A0 | FO / | | | | |
| 1344-28-1) | 50 μg/g | Aluminium | Creatinine in urine | * | |
| 1344-28-1) * - For sampling details, plea | se see the source docu | ıment. | urine | * | |
| 1344-28-1) * - For sampling details, please commended monitoring cedures | se see the source docu Follow standard mod | ıment. | urine | * | |
| 1344-28-1) * - For sampling details, pleasemended monitoring | se see the source docu | ıment. | urine | * | |
| 1344-28-1) * - For sampling details, please commended monitoring cedures ived no effect levels | se see the source docu Follow standard mod | ıment. | urine | * | |
| 1344-28-1) * - For sampling details, please commended monitoring cedures ived no effect levels ELs) dicted no effect | se see the source docu Follow standard mod Not available. Not available. | ıment. nitoring procedures | urine | | |
| 1344-28-1) * - For sampling details, please commended monitoring cedures ived no effect levels ELs) dicted no effect centrations (PNECs) | se see the source docu Follow standard mon Not available. Not available. Good general ventila applicable, use procu maintain airborne le | iment. nitoring procedures ation should be use ess enclosures, loc vels below recomm | urine ed. Ventilation ra cal exhaust venti | tes should be ilation, or othe e limits. If expo | matched to conditions. If er engineering controls to osure limits have not been eyewash station and safe |
| 1344-28-1) * - For sampling details, please commended monitoring cedures ived no effect levels ELs) dicted no effect centrations (PNECs) Exposure controls propriate engineering trols | se see the source docu Follow standard mon Not available. Not available. Good general ventila applicable, use proc maintain airborne le established, maintai shower. | iment. nitoring procedures ation should be use ess enclosures, loc vels below recomm n airborne levels to | urine d. Ventilation ra cal exhaust venti ended exposure an acceptable l | tes should be ilation, or othe e limits. If expo evel. Provide | er engineering controls to osure limits have not beer eyewash station and safe |
| 1344-28-1) * - For sampling details, please commended monitoring cedures lived no effect levels ELs) dicted no effect centrations (PNECs) Exposure controls propriate engineering trols | se see the source docu Follow standard mon Not available. Not available. Good general ventila applicable, use procumaintain airborne levestablished, maintain shower. such as personal procuments of the personal process | ation should be use ess enclosures, loc vels below recomm n airborne levels to otective equipmer tive equipment as i | urine d. Ventilation ra cal exhaust venti ended exposure an acceptable l nt required. Persor | tes should be ilation, or othe e limits. If exp evel. Provide nal protection | er engineering controls to osure limits have not beer |
| 1344-28-1) * - For sampling details, please commended monitoring cedures ived no effect levels ELs) dicted no effect centrations (PNECs) Exposure controls propriate engineering trols | se see the source docu Follow standard mon Not available. Not available. Good general ventila applicable, use procumaintain airborne levestablished, maintain shower. such as personal protect according to the CE | ation should be use ess enclosures, loc vels below recomm n airborne levels to otective equipmer as in N standards and in | ed. Ventilation racal exhaust ventilended exposure an acceptable of trequired. Persor discussion with | tes should be ilation, or othe e limits. If expo evel. Provide nal protection the supplier o | er engineering controls to osure limits have not been eyewash station and safe equipment should be cho of the personal protective |
| 1344-28-1) * - For sampling details, please commended monitoring cedures ived no effect levels ELs) dicted no effect centrations (PNECs) Exposure controls propriate engineering trols vidual protection measures General information | se see the source docu Follow standard mon Not available. Not available. Good general ventila applicable, use procumaintain airborne leestablished, maintain shower. such as personal procuments of the CE equipment. | ation should be use ess enclosures, locular below recomm airborne levels to otective equipment as in N standards and in swith side shields (and the standards). | ed. Ventilation racal exhaust ventilended exposure an acceptable of a required. Persor discussion with or goggles). Face | tes should be ilation, or othe e limits. If expo evel. Provide nal protection the supplier o | er engineering controls to osure limits have not been eyewash station and safe equipment should be cho of the personal protective |
| 1344-28-1) * - For sampling details, please commended monitoring cedures ived no effect levels ELs) dicted no effect centrations (PNECs) Exposure controls propriate engineering trols vidual protection measures General information Eye/face protection Skin protection | se see the source docu Follow standard mon Not available. Not available. Good general ventila applicable, use procumaintain airborne levestablished, maintain shower. such as personal procuments of the CE equipment. Wear safety glasses Wear appropriate ch | ation should be use ess enclosures, loc vels below recomm n airborne levels to otective equipment as in N standards and in with side shields (another emical resistant global memical resistant global entition in the side shields (another equipment as in the side shields (another equ | ed. Ventilation racal exhaust ventilended exposure an acceptable lacquired. Person discussion with or goggles). Fac | tes should be ilation, or othe e limits. If expo evel. Provide nal protection the supplier o | er engineering controls to osure limits have not been eyewash station and safe equipment should be cho of the personal protective |
| 1344-28-1) * - For sampling details, please commended monitoring cedures ived no effect levels ELs) dicted no effect centrations (PNECs) Exposure controls propriate engineering trols vidual protection measures General information Eye/face protection Skin protection - Hand protection | se see the source docu Follow standard mon Not available. Not available. Good general ventila applicable, use procumaintain airborne levestablished, maintain shower. such as personal procuments of the CE equipment. Wear safety glasses Wear appropriate ch | ation should be use ess enclosures, loc vels below recomm n airborne levels to otective equipment as in N standards and in swith side shields (in memical resistant glonemical resistant clonet ventilation, wear standards and standards and standards and standards and sin memical resistant clonet ventilation, wear standards and standards a | urine d. Ventilation ra cal exhaust venti- lended exposure o an acceptable lent required. Persor discussion with or goggles). Fac- oves. othing. Use of an | tes should be ilation, or othe limits. If experience. Provide the supplier of | er engineering controls to be sure limits have not been eyewash station and safe equipment should be chost the personal protective commended. |

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or

engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid.

Form Liquid. Viscous. Color Not available. Slight. Odor

Melting point/freezing point Not available.

Boiling point or initial boiling point and boiling range

608 °F (320 °C) estimated

Flammability Not applicable.

265,0 °F (129,4 °C) estimated Flash point

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. Kinematic viscosity Not available.

Solubility

Solubility (water) Not available. Partition coefficient Not available.

(n-octanol/water) (log value)

Vapor pressure Not available.

Density and/or relative density

2,20 g/cm3 Mixed material Density

Not available Vapor density Not available. Particle characteristics

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No relevant additional information available.

9.2.2. Other safety characteristics

2.2 Mixed material Specific gravity 100 % Solids VOC

SECTION 10: Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. 10.1. Reactivity

Material is stable under normal conditions. 10.2. Chemical stability

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Contact with incompatible materials. 10.4. Conditions to avoid

Strong oxidizing agents. 10.5. Incompatible materials

No hazardous decomposition products are known. 10.6. Hazardous

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis, Rash.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not known.

Test Results Components **Species**

Aluminium Oxide (CAS 1344-28-1)

Acute Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Due to partial or complete lack of data the classification is not possible. Respiratory sensitization

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible. Carcinogenicity

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2)

IARC Monographs. Overall Evaluation of Carcinogenicity

silicon carbide fibres (with diameter < 3 .mu.m, length > 5 2A Probably carcinogenic to humans. .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2)

Reproductive toxicity

Specific target organ toxicity single exposure

Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard

No information available.

Mixture versus substance

information

11.2. Information on other hazards

Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity Based on available data, the classification criteria are not met for hazardous to the aquatic

environment.

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential No data available. Not available

Partition coefficient

n-octanol/water (log Kow)

Not available. **Bioconcentration factor (BCF)** 12.4. Mobility in soil No data available

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

12.7. Other adverse effects

The product contains volatile organic compounds which have a photochemical ozone creation potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of Disposal methods/information

contents/container in accordance with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

UN3082 14.1. UN number

14.2. UN proper shipping

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

name

14.3. Transport hazard class(es)

Class 9 Subsidiary risk 9 Label(s) Hazard No. (ADR) 90 **Tunnel restriction code** Ε Ш 14.4. Packing group 14.5. Environmental hazards No.

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

RID

14.1. UN number UN3082

14.2. UN proper shipping ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

name

14.3. Transport hazard class(es)

Class 9 Subsidiary risk 9 Label(s) Ш 14.4. Packing group 14.5. Environmental hazards No.

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

ADN

14.1. UN number UN3082

14.2. UN proper shipping ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

name

14.3. Transport hazard class(es)

Class 9 Subsidiary risk 9 Label(s) Ш 14.4. Packing group 14.5. Environmental hazards No.

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user IATA

14.1. UN number

Not regulated as dangerous goods. Not regulated as dangerous goods. 14.2. UN proper shipping

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk 14.4. Packing group 14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

IMDG

Not regulated as dangerous goods. 14.1. UN number Not regulated as dangerous goods. 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

Class Not assigned. Subsidiary risk
14.4. Packing group

14.5. Environmental hazards


Marine pollutant No.

EmS Not assigned. 14.6. Special precautions Not assigned.

for user

14.7. Maritime transport in bulk Not established according to IMO instruments

ADN; ADR; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Aluminium Oxide (CAS 1344-28-1)

silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

UFI:

Austria: R080-X00F-100S-AH9P Belgium: R080-X00F-100S-AH9P Bulgaria: R080-X00F-100S-AH9P Croatia: R080-X00F-100S-AH9P Cyprus: R080-X00F-100S-AH9P

Czech Republic: R080-X00F-100S-AH9P Denmark: R080-X00F-100S-AH9P Estonia: R080-X00F-100S-AH9P EU: R080-X00F-100S-AH9P Finland: R080-X00F-100S-AH9P France: R080-X00F-100S-AH9P Germany: R080-X00F-100S-AH9P Greece: R080-X00F-100S-AH9P Hungary: R080-X00F-100S-AH9P Iceland: R080-X00F-100S-AH9P Ireland: R080-X00F-100S-AH9P Italy: R080-X00F-100S-AH9P Latvia: R080-X00F-100S-AH9P Lithuania: R080-X00F-100S-AH9P Luxembourg: R080-X00F-100S-AH9P Malta: R080-X00F-100S-AH9P Netherlands: R080-X00F-100S-AH9P Norway: R080-X00F-100S-AH9P Poland: R080-X00F-100S-AH9P Portugal: R080-X00F-100S-AH9P Romania: R080-X00F-100S-AH9P Slovakia: R080-X00F-100S-AH9P Slovenia: R080-X00F-100S-AH9P

Spain: R080-X00F-100S-AH9P Sweden: R080-X00F-100S-AH9P

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

silicon carbide fibres (with diameter < 3 .mu.m, length > 5 .mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

époxydiques et leurs constituants 51

Contains a substance which is included on the TRGS 905 list of carcinogenic, germ cell mutagenic and reproductive toxic substances

Aluminium Oxide (CAS 1344-28-1)

Faserstäube, anorganische (außer Asbest), Künstlich hergestellte anorganische einkristalline Fasern (Whisker) aus Aluminoxid

.mu.m and aspect ratio \geq 3:1) (CAS 409-21-2)

silicon carbide fibres (with diameter < 3 .mu.m, length > 5 Faserstäube, anorganische (außer Asbest), Künstlich hergestellte anorganische einkristalline Fasern (Whisker) aus Siliziumkarbid

France regulations

France INRS Table of Occupational Diseases

Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers Maladies professionnelles provoquées par les résines

(CAS 25085-99-8)

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

(CAS 25068-38-6)

.mu.m and aspect ratio ≥ 3:1) (CAS 409-21-2)

époxydiques et leurs constituants 51 silicon carbide fibres (with diameter < 3 .mu.m, length > 5 Affections respiratoires dues aux poussières de carbures métalliques frittés ou fondus contenant du cobalt 70 bis

Maladies professionnelles provoquées par les résines

Product registration number

Austria UFI: R080-X00F-100S-AH9P UFI: R080-X00F-100S-AH9P **Belgium** UFI: R080-X00F-100S-AH9P **Czech Republic Denmark** UFI: R080-X00F-100S-AH9P UFI: R080-X00F-100S-AH9P **European Union**

UFI: R080-X00F-100S-AH9P **Finland France** UFI: R080-X00F-100S-AH9P UFI: R080-X00F-100S-AH9P Germany UFI: R080-X00F-100S-AH9P Greece Hungary UFI: R080-X00F-100S-AH9P Italy UFI: R080-X00F-100S-AH9P **Netherlands** UFI: R080-X00F-100S-AH9P UFI: R080-X00F-100S-AH9P **Norway Poland** UFI: R080-X00F-100S-AH9P UFI: R080-X00F-100S-AH9P **Portugal** UFI: R080-X00F-100S-AH9P Slovakia Slovenia UFI: R080-X00F-100S-AH9P UFI: R080-X00F-100S-AH9P Spain UFI: R080-X00F-100S-AH9P Sweden UFI: R080-X00F-100S-AH9P **Switzerland**

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

References

Information on evaluation method leading to the classification of mixture

Not available

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H261 In contact with water releases flammable gas.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H350i May cause cancer by inhalation.

H411 Toxic to aquatic life with long lasting effects. Physical & Chemical Properties: Multiple Properties

Revision information Training information

Follow training instructions when handling this material.

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Material name: DEVCON® Wear Guard™ Fine Load Resin

0139 Version #: 10 Revision date: 07-28-2023 Issue date: 05-29-2019