## **SAFETY DATA SHEET**

1. Identification

Product identifier DEVCON® Brushable Ceramic Blue Resin

Other means of identification

SKU# 0144

**Recommended use** Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact person Customer Service
Telephone number 978-777-1100

Fax E-mail

**Emergency telephone** 

800-424-9300

number

**Supplier** Not available.

## 2. Hazard identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2
Sensitization, skin Category 1
Hazardous to the aquatic environment, acute Category 2

Environmental hazards Hazardous to the aquatic environment, acute Ca

hazard

Label elements



Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to

aquatic life.

**Precautionary statement** 

Prevention Avoid breathing mist/vapours. Wash thoroughly after handling. Contaminated work clothing

should not be allowed out of the workplace. Avoid release to the environment. Wear eye

protection/face protection. Wear protective gloves.

**Response** IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Storage Not available.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information

tion None.

Other hazards None known.

Material name: DEVCON® Brushable Ceramic Blue Resin
0144 Version #: 07 Revision date: 26-July-2023 Issue date: 29-May-2019

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name Common name and synonyms		CAS number	%	
Aluminium oxide		1344-28-1	40 - < 50	
Epoxy Resin: reaction product of Bisphenol A and epichlorohydrin (refer to epichlorohydrin)		25068-38-6	40 - < 50	
Xylene	XYLENE	1330-20-7	< 1	
Other components below reportable	e levels		10 - < 20	

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and

delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment

and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Specific methods

Move containers from fire area if you can do so without risk.

General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Prevent product from entering drains.

drains, water courses or onto the ground.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

## **Environmental precautions**

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into

Material name: DEVCON® Brushable Ceramic Blue Resin

SDS CANADA

## 7. Handling and storage

Precautions for safe handling Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged

exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid

release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

## Occupational exposure limits

Components	Туре	Value
Xylene (CAS 1330-20-7)	TWA	20 ppm

## Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended

Components	Туре	Value
Aluminium oxide (CAS 1344-28-1)	TWA	10 mg/m3
Xylene (CAS 1330-20-7)	STEL	651 mg/m3
		150 ppm
	TWA	434 mg/m3
		100 ppm

## Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

## Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended

Components	Туре	Value	
Xvlene (CAS 1330-20-7)	TWA	20 ppm	

# Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191)

Components	Туре	Value	
Aluminium oxide (CAS 1344-28-1)	TWA	10 mg/m3	
Xylene (CAS 1330-20-7)	STEL	651 mg/m3	
		150 ppm	
	TWA	434 mg/m3	
		100 ppm	

# Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended Components Type Value

	- 71	
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

## Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended

Components	туре	Value	Form
Aluminium oxide (CAS 1344-28-1)	TWA	10 mg/m3	Total dust.
Xylene (CAS 1330-20-7)	STEL	651 mg/m3	
		150 ppm	
	TWA	434 mg/m3	
		100 ppm	

SDS CANADA

#### Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended Components Value **Type** 15 minute

Aluminium oxide (CAS

1344-28-1)

20 mg/m3

Xylene (CAS 1330-20-7) 15 minute 150 ppm 100 ppm 8 hour

## **Biological limit values**

**ACGIH Biological Exposure Indices (BEI)** 

Components	Value	Determinant	Specimen	Sampling Time
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

<sup>\* -</sup> For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

### Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

Viscous. Liquid. **Appearance** 

Physical state Liquid.

Viscous. Liquid. **Form** 

Colour Blue. Slight. Odour Not available. **Odour threshold** Not available. pН

Not available. Melting point/freezing point Initial boiling point and boiling

320 °C (608 °F) estimated

range

129.4 °C (265.0 °F) estimated Flash point

Not available. **Evaporation rate** Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available. Explosive limit - upper

(%)

Not available.

Not available. Vapour pressure Vapour density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Material name: DEVCON® Brushable Ceramic Blue Resin

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

**Density** 1.20 g/cm3 estimated

**Explosive properties** Not explosive.

Flammability class Combustible IIIB estimated

Oxidising properties Not oxidising.

Specific gravity 1.2 estimated

**VOC** 0 g/l

## 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidising agents.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact** Causes skin irritation. May cause an allergic skin reaction.

**Eye contact** Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

Aluminium oxide (CAS 1344-28-1)

Acute Oral

. . . . .

LD50 Rat > 5000 mg/kg

Xylene (CAS 1330-20-7)

<u>Acute</u>

**Dermal** 

LD50 Rabbit > 43 g/kg

Oral

LD50 Rat 3523 - 8600 mg/kg

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye Causes serious eye irritation.

irritation

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant

Aluminium oxide (CAS 1344-28-1) Irritant

**Respiratory sensitisation** Not a respiratory sensitiser.

Material name: DEVCON® Brushable Ceramic Blue Resin
0144 Version #: 07 Revision date: 26-July-2023 Issue date: 29-May-2019

**Skin sensitisation** May cause an allergic skin reaction.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

**ACGIH Carcinogens** 

Aluminium oxide (CAS 1344-28-1)

A4 Not classifiable as a human carcinogen.

Xylene (CAS 1330-20-7)

A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Aluminium oxide (CAS 1344-28-1)

Xylene (CAS 1330-20-7)

Not classifiable as a human carcinogen.

Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Xylene (CAS 1330-20-7) 3 Not classifiable as to carcinogenicity to humans.

Specific target ergen toxicity

Specific target organ toxicity - single exposure

Not classified.

Charific toward owner toylaity

Reproductive toxicity

**Aspiration hazard** 

Specific target organ toxicity -

Not classified.

repeated exposure

Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

**Ecotoxicity** Toxic to aquatic life.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

This product is not expected to cause reproductive or developmental effects.

**Bioaccumulative potential** 

Partition coefficient n-octanol / water (log Kow)

Xylene 3.12 - 3.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

**TDG** 

Not regulated as dangerous goods.

**IATA** 

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

Material name: DEVCON® Brushable Ceramic Blue Resin
0144 Version #: 07 Revision date: 26-July-2023 Issue date: 29-May-2019

## 15. Regulatory information

#### Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

## **Controlled Drugs and Substances Act**

Not regulated.

#### Export Control List (CEPA 1999, Schedule 3)

Not listed.

#### **Greenhouse Gases**

Not listed.

## Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)

Xylene (CAS 1330-20-7)

## **Precursor Control Regulations**

Not regulated.

## International regulations

#### Stockholm Convention

Not applicable.

#### **Rotterdam Convention**

Not applicable.

#### **Kyoto Protocol**

Not applicable.

#### **Montreal Protocol**

Not applicable.

#### **Basel Convention**

Not applicable.

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information

Issue date 29-May-2019 **Revision date** 26-July-2023

Version No.

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: DEVCON® Brushable Ceramic Blue Resin

0144 Version #: 07 Revision date: 26-July-2023 Issue date: 29-May-2019

SDS CANADA