SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® Floor Patch™ Resin

Other means of identification

SKU# 0182

Recommended use Not available.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number978-777-1100

Fax E-mail

Emergency telephone

number

800-424-9300

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2
Sensitization, skin Category 1

Environmental hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statement

Prevention Avoid breathing mist/vapours. Wash thoroughly after handling. Contaminated work clothing

should not be allowed out of the workplace. Wear eye protection/face protection. Wear protective

gloves.

Response IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Storage Not available.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental informationNone.Other hazardsNone known.

3. Composition/information on ingredients

Mixtures

Material name: DEVCON® Floor Patch™ Resin
0182 Version #: 06 Revision date: 31-July-2023 Issue date: 28-May-2019

Chemical name	Common name and synonyms	CAS number	%
Epoxy Resin: reaction product of Bisphenol A and epichlorohydrin (refer to epichlorohydrin)		25068-38-6	70 - < 80
Alky Glycidyl Ether (oxirane) (as Polymer), Particulate		68609-97-2	10 - < 20
Titanium dioxide	Titanium dioxide	13463-67-7	3 - < 5
Epoxy Resin:reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)	Epoxy resin	25068-38-6	<1
FORMALDEHYDE POLYMER WITH (CHLOROMETHYL) OXIRANE AND 4,4'-(1-METHYLETHYLIDENE) BIS[PHENOL]		28906-96-9	<1
Propanol, (n)		71-23-8	< 0.3
Silica, amorphous		7631-86-9	< 0.3
Other components below reportable	levels		3 - < 5

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4.	First-aid	d measures
	I II OL GIO	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders. Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Specific hazards arising from

Unsuitable extinguishing

media

the chemical

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

110	ACCILL '	Thresho	14 1500:4	Maluas	/TI \/\
US.	ACGIH	inresno	ıa ı ımı ı	vallies	(11 V)

Components	Туре	Value	Form
Propanol, (n) (CAS 71-23-8)	TWA	100 ppm	
Titanium dioxide (CAS 13463-67-7)	TWA	2.5 mg/m3	Respirable finescale particles
		0.2 mg/m3	Respirable nanoscale particles

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended

Components	Туре	Value	Form
Propanol, (n) (CAS 71-23-8)	STEL	984 mg/m3	
		400 ppm	
	TWA	492 mg/m3	
		200 ppm	
Silica, amorphous (CAS 7631-86-9)	TWA	3 mg/m3	Respirable particles.
		10 mg/m3	Total
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
Propanol, (n) (CAS 71-23-8)	TWA	100 ppm	
Silica, amorphous (CAS 7631-86-9)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Titanium dioxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended

Components	Туре	Value	Form
Propanol, (n) (CAS 71-23-8)	TWA	100 ppm	
Titanium dioxide (CAS 13463-67-7)	TWA	2.5 mg/m3	Respirable finescale particles
		0.2 mg/m3	Respirable nanoscale particles

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs **Publication (New Brunswick Regulation 91-191)**

Components	Туре	Value	Form
Propanol, (n) (CAS 71-23-8)	STEL	614 mg/m3	
		250 ppm	
	TWA	492 mg/m3	
		200 ppm	
Silica, amorphous (CAS 7631-86-9)	TWA	3 mg/m3	Respirable.
		10 mg/m3	Inhalable
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
	ntrol of Exposure to Biological or Chemica		
Components	Туре	Value	
Propanol, (n) (CAS 71-23-8)	TWA	100 ppm	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. Quebec OELs. (Min Components	istry of Labor - Regulation respecting occ Type	cupational health and s Value	afety), as amended Form
Propanol, (n) (CAS 71-23-8)	TWA	100 ppm	
Silica, amorphous (CAS 7631-86-9)	TWA	10 mg/m3	Total dust.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Total dust.
Canada. Saskatchewan OEL Components	s (Occupational Health and Safety Regula Type	ations, 1996, Table 21), Value	as amended Form
Propanol, (n) (CAS 71-23-8)	15 minute	400 ppm	
	8 hour	200 ppm	
Silica, amorphous (CAS 7631-86-9)	15 minute	6 mg/m3	Respirable fraction.
		20 mg/m3	Inhalable fraction.
T:(: !: : 1 (OAO		_0g,	
Titanium dioxide (CAS 13463-67-7)	15 minute	20 mg/m3	
	15 minute No biological exposure limits noted for the	20 mg/m3	
13463-67-7)	•	20 mg/m3 ingredient(s). Ventilation rates should be exhaust ventilation, or oth ded exposure limits. If exp	er engineering controls to posure limits have not been
13463-67-7) logical limit values propriate engineering trols	No biological exposure limits noted for the Good general ventilation should be used. \applicable, use process enclosures, local emaintain airborne levels below recommend established, maintain airborne levels to an	20 mg/m3 ingredient(s). Ventilation rates should be exhaust ventilation, or oth ded exposure limits. If expanded acceptable level. Provided	er engineering controls to posure limits have not been e eyewash station and safety
13463-67-7) logical limit values propriate engineering trols	No biological exposure limits noted for the Good general ventilation should be used. \ applicable, use process enclosures, local e maintain airborne levels below recommend established, maintain airborne levels to an shower. such as personal protective equipment	20 mg/m3 ingredient(s). Ventilation rates should be exhaust ventilation, or oth ded exposure limits. If expanded exposure level. Provided exposure level. Provided exposure shield is responsible to the exposure shield in the exposure shield is responsible to the exposure shield in the exposure shield in the exposure shield in the exposure shield is responsible to the exposure shield in the exposure	er engineering controls to posure limits have not been e eyewash station and safety
13463-67-7) logical limit values propriate engineering trols vidual protection measures, Eye/face protection Skin protection	No biological exposure limits noted for the Good general ventilation should be used. A applicable, use process enclosures, local emaintain airborne levels below recommence established, maintain airborne levels to an shower. such as personal protective equipment Wear safety glasses with side shields (or g	20 mg/m3 ingredient(s). Ventilation rates should be exhaust ventilation, or oth ded exposure limits. If expacceptable level. Provide goggles). Face shield is researched.	er engineering controls to posure limits have not been e eyewash station and safety ecommended.
13463-67-7) logical limit values propriate engineering trols vidual protection measures, Eye/face protection Skin protection Hand protection Other	No biological exposure limits noted for the Good general ventilation should be used. A applicable, use process enclosures, local emaintain airborne levels below recommence established, maintain airborne levels to an shower. such as personal protective equipment. Wear safety glasses with side shields (or good wear appropriate chemical resistant gloves wear appropriate chemical resistant clothing.	20 mg/m3 ingredient(s). Ventilation rates should be exhaust ventilation, or oth ded exposure limits. If expacceptable level. Provide goggles). Face shield is researched.	er engineering controls to cosure limits have not been e eyewash station and safety ecommended.
13463-67-7) logical limit values propriate engineering trols vidual protection measures, Eye/face protection Skin protection Hand protection	No biological exposure limits noted for the Good general ventilation should be used. No applicable, use process enclosures, local emaintain airborne levels below recommend established, maintain airborne levels to an shower. such as personal protective equipment Wear safety glasses with side shields (or good wear appropriate chemical resistant gloves)	20 mg/m3 ingredient(s). Ventilation rates should be exhaust ventilation, or othe ded exposure limits. If expacceptable level. Provide goggles). Face shield is respondent to the control of the control o	er engineering controls to cosure limits have not been e eyewash station and safety ecommended.

General hygiene

considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

9. Physical and chemical properties

Appearance Viscous. Liquid. Physical state Liquid.

Form Viscous. Liquid.
Colour Not available.

Odour Slight.

Odour threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

range

320 °C (608 °F) estimated

Flash point 129.4 °C (265.0 °F) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper

r

Not available.

(%) .

Vapour pressure 0.001 hPa estimated

Vapour density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 1.23 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Combustible IIIB estimated

Oxidising properties Not oxidising.

Specific gravity 1.23 estimated

VOC 0 a/l

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Strong oxidising agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Material name: DEVCON® Floor Patch™ Resin
0182 Version #: 06 Revision date: 31-July-2023 Issue date: 28-May-2019

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

Silica, amorphous (CAS 7631-86-9)

Acute Oral

LD50 Rat > 22500 mg/kg

Titanium dioxide (CAS 13463-67-7)

Acute Dermal

LD50 Hamster >= 10000 mg/kg

Oral

LD50 Rat > 10000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant

Propanol, (n) (CAS 71-23-8) Irritant Silica, amorphous (CAS 7631-86-9) Irritant Titanium dioxide (CAS 13463-67-7) Irritant

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

Propanol, (n) (CAS 71-23-8)

A4 Not classifiable as a human carcinogen.

Titanium dioxide (CAS 13463-67-7)

A3 Confirmed animal carcinogen with unknown relevance to

humans.

Canada - Manitoba OELs: carcinogenicity

Propanol, (n) (CAS 71-23-8)

Not classifiable as a human carcinogen.

Titanium dioxide (CAS 13463-67-7)

Confirmed animal carcinogen with unknown relevance to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Silica, amorphous (CAS 7631-86-9)

3 Not classifiable as to carcinogenicity to humans.

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity - N

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Propanol, (n) 0.25

Material name: DEVCON® Floor Patch™ Resin
0182 Version #: 06 Revision date: 31-July-2023 Issue date: 28-May-2019

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulationsDispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No

Material name: DEVCON® Floor Patch™ Resin

0182 Version #: 06 Revision date: 31-July-2023 Issue date: 28-May-2019

Country(s) or regionInventory nameOn inventory (yes/no)*EuropeEuropean Inventory of Existing Commercial ChemicalNo

Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS) No
Japan Inventory of Existing and New Chemical Substances (ENCS) No
Korea Existing Chemicals List (ECL) Yes
New Zealand New Zealand Inventory Yes
Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

16. Other information

Issue date28-May-2019Revision date31-July-2023

Version No. 06

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information Physical & Chemical Properties: Multiple Properties

Material name: DEVCON® Floor Patch™ Resin

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).