SAFETY DATA SHEET

Version #: 05

Issue date: 10-31-2021 Revision date: 07-31-2023 Supersedes date: 06-25-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

DEVCON® Flexane® 80 Liquid Resin

Registration number

Synonyms None. SKU# 0318N

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified usesNot available.Uses advised againstNone known.

1.3. Details of the supplier of the safety data sheet

Company Name ITW Performance Polymers

Address Bay 150

Shannon Industrial Estate

Co. Clare Ireland V14 DF82

Contact Person Customer Service
Telephone Number 353(61)771500

353(61)471285

Email customerservice.shannon@itwpp.com

Emergency Phone Number 44(0) 1235 239 670 (24 hours)

1.4. Emergency telephone number

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons

Information Center

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Belgium National Poisons

Control Center

070 245 245 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Bulgaria National

Toxicological Information

Center

+359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Croatia Poisons Information Center

+385 1 2348 342 (Hours of operation not provided. SDS/Product information may

not be available for the Emergency Service.)

Cyprus Poison Center 1401 (Available 24 hours a day. SDS/Product information may not be available

for the Emergency Service.)

Czech Republic National Poisons Information

Center

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons

Control Center

+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Estonia National Poisons 16662

Information Center

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be

available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Material name: DEVCON® Flexane® 80 Liquid Resin

1.4. Emergency telephone number

Greece Poison Information Centre

(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Hungary National Emergency Phone Number +36-80-201-199 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Iceland Poison Center

(+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Latvia Emergency medical

aid

113

Latvia Poison and Drug Information Center

+371 67042473 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Lithuania Neatidėliotina informacija apsinuodijus +370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and Emergency Department 2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Netherlands National Poisons Information Center (NVIC)

NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel

in cases of acute intoxications)

Norway Norwegian Poison Information Center

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Portugal Poison Center 800 2

800 250 250 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Romania Biroul RSI si Informare Toxicologica 021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be

available for the Emergency Service.)

Slovakia National Toxicological Information Center +421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Spain Toxicology Information Service

+ 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Sweden National Poison Information Center

112 - and ask for Poison Information (Available 24 hours a day. SDS/Product

information may not be available for the Emergency Service.)

Switzerland Tox Info Suisse

145 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Acute toxicity, inhalation

Category 4

Skin corrosion/irritation

Category 2

H315 - Causes skin irritation.

Serious eye damage/eye irritation

Category 2

H319 - Causes serious eye

irritation.

Respiratory sensitization Category 1

H334 - May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Skin sensitization Category 1

H317 - May cause an allergic skin

reaction.

Specific target organ toxicity - single

exposure

Category 3 respiratory tract irritation

H335 - May cause respiratory

irritation.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard

Category 3

H412 - Harmful to aquatic life with long lasting effects.

2.2. Label elements

Material name: DEVCON® Flexane® 80 Liquid Resin

Label according to Regulation (EC) No. 1272/2008 as amended

UFI:

Austria: DJ40-P0DJ-S00Y-VV03 Belgium: DJ40-P0DJ-S00Y-VV03 Bulgaria: DJ40-P0DJ-S00Y-VV03 Croatia: DJ40-P0DJ-S00Y-VV03 Cyprus: DJ40-P0DJ-S00Y-VV03

Czech Republic: DJ40-P0DJ-S00Y-VV03 Denmark: DJ40-P0DJ-S00Y-VV03 Estonia: DJ40-P0DJ-S00Y-VV03 EU: DJ40-P0DJ-S00Y-VV03 Finland: DJ40-P0DJ-S00Y-VV03 France: DJ40-P0DJ-S00Y-VV03 Germany: DJ40-P0DJ-S00Y-VV03 Greece: DJ40-P0DJ-S00Y-VV03 Hungary: DJ40-P0DJ-S00Y-VV03 Iceland: DJ40-P0DJ-S00Y-VV03 Ireland: DJ40-P0DJ-S00Y-VV03 Italy: DJ40-P0DJ-S00Y-VV03 Latvia: DJ40-P0DJ-S00Y-VV03 Lithuania: DJ40-P0DJ-S00Y-VV03 Luxembourg: DJ40-P0DJ-S00Y-VV03 Malta: DJ40-P0DJ-S00Y-VV03 Netherlands: DJ40-P0DJ-S00Y-VV03

Malta: DJ40-P0DJ-S00Y-VV03
Netherlands: DJ40-P0DJ-S00Y-VV03
Norway: DJ40-P0DJ-S00Y-VV03
Poland: DJ40-P0DJ-S00Y-VV03
Portugal: DJ40-P0DJ-S00Y-VV03
Romania: DJ40-P0DJ-S00Y-VV03
Slovakia: DJ40-P0DJ-S00Y-VV03
Slovenia: DJ40-P0DJ-S00Y-VV03
Spain: DJ40-P0DJ-S00Y-VV03

Sweden: DJ40-P0DJ-S00Y-VV03

Contains: 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate

Hazard pictograms



Signal word Danger

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P261	Avoid breathing mist/vapors.
P264	Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.
P280 Wear eye protection/face protection.

P280 Wear protective gloves. P284 Wear respiratory protection.

Response

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P312 Call a PÓISON CENTER/doctor if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice/attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Store locked up. P405

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Supplemental label information None.

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation 2.3. Other hazards

> (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a

concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name CAS-No. / EC No. **REACH Registration No.** Index No. **Notes** 3-isocyanatomethyl-3,5,5-trimethylcyc 20 - < 30 4098-71-9 615-008-00-5 lohexyl isocyanate; isophorone 223-861-6 di-isocyanate

Classification: Acute Tox. 4;H302;(ATE: 1000 mg/kg bw), Acute Tox. 4;H312;(ATE: 1060

mg/kg bw), Acute Tox. 3;H331;(ATE: 3 mg/l), Skin Irrit. 2;H315, Eye Irrit. 2;H319, Resp. Sens. 1;H334, Skin Sens. 1;H317, STOT SE 3;H335,

Aquatic Chronic 2;H411

Specific Concentration Limits: Resp. Sens. 1;H334: C ≥ 0.5 %, Skin Sens. 1;H317: C ≥ 0.5 %

70 - < 80 Other components below reportable

levels

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance. PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information If you feel unwell, seek medical advice (show the label where possible). Ensure that medical

personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash

contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

> artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a poison center or

doctor/physician.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

4.2. Most important symptoms and effects, both acute and

and special treatment needed

delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

4.3. Indication of any Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim immediate medical attention

under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

media

Foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Water. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed.

Material name: DEVCON® Flexane® 80 Liquid Resin

5.3. Advice for firefighters

Special protective equipment for firefighters

Special fire fighting procedures

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Ensure adequate ventilation. Avoid breathing mist/vapors. Local authorities should be advised if significant spillages cannot be contained. Use personal

protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into

drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

Value

Observe industrial sector guidance on best practices. 7.3. Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL	Ordinance (GwV), BGBI. II, no.	184/2001, as amended
Components	Type	

3-isocyanatomethyl-3,5,5-tri methylcyclohexyl isocyanate; isophorone	Ceiling	0,092 mg/m3
di-isocyanate (CAS 4098-71-9)		
•		0,01 ppm
	MAK	0,046 mg/m3
		maa 200.0

Belgium, OEL, Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1 -Chamical agents as amonded

Components	Туре	Value	
3-isocyanatomethyl-3,5,5-tri methylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	TWA	0,046 mg/m3	
		0,005 ppm	

Material name: DEVCON® Flexane® 80 Liquid Resin

Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as amended

Components	Туре	Value	
3-isocyanatomethyl-3,5,5-tri methylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	TWA	0,1 mg/m3	

Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, Annex 2 Components Type Value

TLV

3-isocyanatomethyl-3,5,5-tri methylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)

0,005 ppm

0,09 mg/m3

0,045 mg/m3

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended Components Type Value

3-isocyanatomethyl-3,5,5-tri methylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)

> 0,01 ppm 0,05 mg/m3

TWA

STEL

0,005 ppm

Finland. HTP-arvot, App 3., Binding Limit Values, Social Affairs and Ministry of Health Components Type Value

VLE

3-isocyanatomethyl-3,5,5-tri methylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9) STEL 0,035 mg/m3

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value

3-isocyanatomethyl-3,5,5-tri methylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)

Regulatory status:

Indicative limit (VL)

0,02 ppm

0,18 mg/m3

Regulatory status: Indicative limit (VL)

VME 0,09 mg/m3

Regulatory status: Indicative limit (VL)

0,01 ppm

Regulatory status: Indicative limit (VL)

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG), as updated

Components	Туре	Value	Form
3-isocyanatomethyl-3,5,5-tri methylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	TWA	0,046 mg/m3	Vapor and aerosol.
		0,005 ppm	Vapor and aerosol.

Germany. TRGS 900, Limit Values Components	Туре	Value	Form
3-isocyanatomethyl-3,5,5-tri methylcyclohexyl socyanate; isophorone di-isocyanate (CAS 4098-71-9)	AGW	0,046 mg/m3	Vapor and aerosol.
,		0,005 ppm	Vapor and aerosol.
Greece. OELs, Presidential Decree Components	No. 307/1986, as amended Type	Value	
B-isocyanatomethyl-3,5,5-tri methylcyclohexyl socyanate; isophorone di-isocyanate (CAS 1098-71-9)	STEL	0,18 mg/m3	
		0,02 ppm	
	TWA	0,09 mg/m3	
		0,01 ppm	
celand. OELs. Regulation 390/200 Components	9 on Pollution Limits and Mea Type	asures to Reduce Pollution at Value	the Workplace, as amende
3-isocyanatomethyl-3,5,5-tri methylcyclohexyl socyanate; isophorone di-isocyanate (CAS 4098-71-9)	STEL	0,09 mg/m3	
		0,01 ppm	
	TWA	0,05 mg/m3	
		0,005 ppm	
reland. OELVs, Schedules 1 & 2, 0 Components	code of Practice for Chemical Type	Agents and Carcinogens Reg Value	ulations
3-isocyanatomethyl-3,5,5-tri methylcyclohexyl socyanate; isophorone di-isocyanate (CAS 4098-71-9)	STEL	0,07 mg/m3	
	TWA	0,005 ppm	
taly. OELs (Legislative Decree n.8	1, 9 April 2008), as amended		
Components	Туре	Value	
3-isocyanatomethyl-3,5,5-tri methylcyclohexyl socyanate; isophorone di-isocyanate (CAS 4098-71-9)	TWA	0,005 ppm	
Lithuania. OELs. Occupational Exp V-824/A1-389), as amended		,	m HN 23:2011; Order No.
Components	Туре	Value	
3-isocyanatomethyl-3,5,5-tri nethylcyclohexyl socyanate; isophorone di-isocyanate (CAS 1098-71-9)	Ceiling	0,09 mg/m3	
		0,01 ppm	
	TWA	0,05 mg/m3	
	1 7 7 7	0,00 mg/mo	

Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended

Components	Туре	Value	
3-isocyanatomethyl-3,5,5-tri methylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	STEL	0,01 ppm	
	TLV	0,045 mg/m3	
		0,005 ppm	

Poland. Maximum permissible concentrations and intensities of harmful factors in the work environment (Dz.U.Poz. 1286/2018, Annex 1)

Components	Туре	Value
3-isocyanatomethyl-3,5,5-tri methylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	TWA	0,04 mg/m3

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796-2014) Components Type Value

TWA

3-isocyanatomethyl-3,5,5-tri methylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)

Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Annex I), as amended

Components	Туре	Value	
3-isocyanatomethyl-3,5,5-tri methylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	TWA	0,046 mg/m3	
		0.005	

0,005 ppm

Spain. OELs. INSST, Límites de Exposición Profesional Para Agentes Químicos, Table 1-Valores Límites Ambientales (VLAs)

Components	Туре	Value	
3-isocyanatomethyl-3,5,5-tri methylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	TWA	0,046 mg/m3	
		0.005	

0,005 ppm

0,005 ppm

Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended

amended			
Components	Туре	Value	
3-isocyanatomethyl-3,5,5-tri methylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	Ceiling	0,046 mg/m3	
		0,005 ppm	
	TWA	0,018 mg/m3	
		0,002 ppm	
Switzerland. SUVA Grenzwerte am	Arbeitsplatz: Aktuelle MAK-V	Verte	
Components	Туре	Value	
3-isocyanatomethyl-3,5,5-tri methylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	STEL	0,02 mg/m3	

Material name: DEVCON® Flexane® 80 Liquid Resin

Components Value Type **TWA** 0,02 mg/m3

UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1 Components Value Type

STEL 0,07 mg/m3 3-isocyanatomethyl-3,5,5-tri methylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)

> **TWA** 0,02 mg/m3

Biological limit values

UK. BELs. Biological Monitoring Guidance Values (BMGVs) (EH40/2005 (Fourth Edition 2020)), Table 2 **Determinant Specimen** Sampling Time Components Value 3-isocyanatomethyl-3,5,5-tri 1 umol/mol Isocyanate-deri Creatinine in methylcyclohexyl ved diamine urine isocyanate; isophorone di-isocyanate (CAS 4098-71-9)

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no effect levels

(DNELs)

Not available.

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines

Belgium OELs: Skin designation

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; Can be absorbed through the skin. isophorone di-isocyanate (CAS 4098-71-9)

Greece OEL: Skin designation

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; Can be absorbed through the skin. isophorone di-isocyanate (CAS 4098-71-9)

Iceland OELs: Skin designation

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; Can be absorbed through the skin. isophorone di-isocyanate (CAS 4098-71-9)

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally adequate. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Wear appropriate chemical resistant gloves. - Hand protection - Other Wear appropriate chemical resistant clothing.

Chemical respirator with organic vapor cartridge and full facepiece. Respiratory protection

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

Always observe good personal hygiene measures, such as washing after handling the material Hygiene measures

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

^{* -} For sampling details, please see the source document.

Environmental exposure controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Liquid. Physical state Liquid. **Form** Colorless. Color Odor Slight.

-76 °F (-60 °C) estimated Melting point/freezing point

Boiling point or initial boiling point and boiling range

Not available.

Flammability Not applicable.

311,0 °F (155,0 °C) estimated Flash point

Auto-ignition temperature Not available. **Decomposition temperature** Not available. 7 @ 5% solution pН Not available. Kinematic viscosity

Solubility

Not available Solubility (water) Not available. **Partition coefficient**

(n-octanol/water) (log value)

Vapor pressure 0,0004 hPa estimated

Density and/or relative density

Density 1,03 g/cm3 estimated

Not available. Vapor density **Particle characteristics** Not available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No relevant additional information available.

9.2.2. Other safety characteristics

1,03 estimated Specific gravity

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. 10.2. Chemical stability

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Contact with incompatible materials. 10.5. Incompatible materials Alcohols. Amides. Amines. Phenols.

10.6. Hazardous

No hazardous decomposition products are known.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Causes skin irritation. May cause an allergic skin reaction. Skin contact

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred **Symptoms**

vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness

and pain. May cause an allergic skin reaction. Dermatitis. Rash.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Material name: DEVCON® Flexane® 80 Liquid Resin

Harmful if inhaled. **Acute toxicity**

Components **Species Test Results**

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)

Dermal

LD50 Rat 1060 mg/kg

Oral

> 1000 mg/kg LD50 Rat

Skin corrosion/irritation

Serious eye damage/eye

irritation

Causes serious eye irritation.

Causes skin irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled. Respiratory sensitization

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible. Carcinogenicity Due to partial or complete lack of data the classification is not possible. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not applicable.

Due to partial or complete lack of data the classification is not possible. **Aspiration hazard**

Mixture versus substance

information

No information available.

11.2. Information on other hazards

Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.

Not available. Other information

SECTION 12: Ecological information

12.1. Toxicity Harmful to aquatic life with long lasting effects. Based on available data, the classification criteria

are not met for hazardous to the aquatic environment, acute hazard.

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; 4.75

isophorone di-isocyanate

Bioconcentration factor (BCF) Not available. 12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

12.7. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

Material name: DEVCON® Flexane® 80 Liquid Resin

EU waste codeThe Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Special precautionsDispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number Not regulated as dangerous goods.

14.2. UN proper shipping

Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk -

Hazard No. (ADR) Not assigned.
Tunnel restriction code Not assigned.

14.4. Packing group -

14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

RID

14.1. UN number Not regulated as dangerous goods.14.2. UN proper shipping Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk -14.4. Packing group -14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

ADN

14.1. UN numberNot regulated as dangerous goods. **14.2. UN proper shipping**Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk -14.4. Packing group -14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

IATA

14.1. UN number Not regulated as dangerous goods.14.2. UN proper shipping Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk 14.4. Packing group 14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

IMDG

14.1. UN number Not regulated as dangerous goods.14.2. UN proper shipping Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk 14.4. Packing group 14.5. Environmental hazards
Marine pollutant No.

EmS Not assigned. 14.6. Special precautions Not assigned.

for user

14.7. Maritime transport in bulk Not established.

according to IMO instruments

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

UFI:

Austria: DJ40-P0DJ-S00Y-VV03 Belgium: DJ40-P0DJ-S00Y-VV03 Bulgaria: DJ40-P0DJ-S00Y-VV03 Croatia: DJ40-P0DJ-S00Y-VV03 Cyprus: DJ40-P0DJ-S00Y-VV03

Czech Republic: DJ40-P0DJ-S00Y-VV03 Denmark: DJ40-P0DJ-S00Y-VV03 Estonia: DJ40-P0DJ-S00Y-VV03 EU: DJ40-P0DJ-S00Y-VV03 Finland: DJ40-P0DJ-S00Y-VV03 France: DJ40-P0DJ-S00Y-VV03 Germany: DJ40-P0DJ-S00Y-VV03 Greece: DJ40-P0DJ-S00Y-VV03 Hungary: DJ40-P0DJ-S00Y-VV03 Iceland: DJ40-P0DJ-S00Y-VV03 Ireland: DJ40-P0DJ-S00Y-VV03 Italy: DJ40-P0DJ-S00Y-VV03 Latvia: DJ40-P0DJ-S00Y-VV03 Lithuania: DJ40-P0DJ-S00Y-VV03 Luxembourg: DJ40-P0DJ-S00Y-VV03 Malta: DJ40-P0DJ-S00Y-VV03 Netherlands: DJ40-P0DJ-S00Y-VV03

Netherlands: DJ40-P0DJ-S00Y-VV Norway: DJ40-P0DJ-S00Y-VV03 Poland: DJ40-P0DJ-S00Y-VV03 Portugal: DJ40-P0DJ-S00Y-VV03 Romania: DJ40-P0DJ-S00Y-VV03 Slovakia: DJ40-P0DJ-S00Y-VV03 Slovenia: DJ40-P0DJ-S00Y-VV03 Spain: DJ40-P0DJ-S00Y-VV03 Sweden: DJ40-P0DJ-S00Y-VV03

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Not listed.

Material name: DEVCON® Flexane® 80 Liquid Resin

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Young people under 18 years old are not allowed to work with this product according to EU

Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

France regulations

France INRS Table of Occupational Diseases

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; Affections professionnelles provoquées par les isocyanates isophorone di-isocyanate (CAS 4098-71-9) organiques 62

Product registration number

Austria UFI: DJ40-P0DJ-S00Y-VV03 UFI: DJ40-P0DJ-S00Y-VV03 Belgium Czech Republic UFI: DJ40-P0DJ-S00Y-VV03 **Denmark** UFI: DJ40-P0DJ-S00Y-VV03 UFI: DJ40-P0DJ-S00Y-VV03 **European Union** UFI: DJ40-P0DJ-S00Y-VV03 **Finland** UFI: DJ40-P0DJ-S00Y-VV03 France UFI: DJ40-P0DJ-S00Y-VV03 Germany Greece UFI: DJ40-P0DJ-S00Y-VV03 Hungary UFI: DJ40-P0DJ-S00Y-VV03 Italy UFI: DJ40-P0DJ-S00Y-VV03 **Netherlands** UFI: DJ40-P0DJ-S00Y-VV03 Norway UFI: DJ40-P0DJ-S00Y-VV03 UFI: DJ40-P0DJ-S00Y-VV03 Poland UFI: DJ40-P0DJ-S00Y-VV03 **Portugal** UFI: DJ40-P0DJ-S00Y-VV03 Slovakia UFI: DJ40-P0DJ-S00Y-VV03 Slovenia UFI: DJ40-P0DJ-S00Y-VV03 Spain Sweden UFI: DJ40-P0DJ-S00Y-VV03 Switzerland UFI: DJ40-P0DJ-S00Y-VV03

15.2. Chemical safety No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert - Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

Not available.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full

under sections 2 to 15 H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

Revision information

Training information

Disclaimer

None.

Follow training instructions when handling this material.

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: DEVCON® Flexane® 80 Liquid Resin