SAFETY DATA SHEET

1. Identification

1. Identification		
Product identifier	Korrobond 65 Component A	
Other means of identification		
SKU#	0550-707A-X00F-H82J	
Recommended use	Not available.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier	r/Distributor information	
Manufacturer		
Company name	ITW Performance Polymers	
Address	Bay 150	
	Shannon Industrial Estate Co, Clare, Ireland	
Telephone	Phone 363(61)771500	
E-mail	customerservice.shannon@itwpp.com	
Emergency phone number	Emergency Number 44(0)1235 239 67	70
2. Hazard(s) identification	n	
Physical hazards	Not classified.	
Health hazards	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements	•	
	\mathbf{V}	
Signal word	Warning	
Hazard statement	Combustible liquid. Harmful if swallowed. Caus	ses skin irritation. May cause an allergic skin
	reaction. Causes serious eye irritation.	
Precautionary statement		
Prevention	Keep away from flames and hot surfaces No	
		smoke when using this product. Contaminated work ace. Wear protective gloves/protective clothing/eye
	protection/face protection.	ace. Wear protective gloves/protective clothing/eye
Response	If swallowed: Call a poison center/doctor if you	feel unwell. Rinse mouth. If on skin: Wash with
	plenty of water. If in eyes: Rinse cautiously with	h water for several minutes. Remove contact
		sing. If skin irritation or rash occurs: Get medical nedical advice/attention. Take off contaminated
	clothing and wash it before reuse. In case of fir	
Storage	Store in a well-ventilated place. Keep cool.	-
Disposal		/ith local/regional/national/international regulations.
Hazard(s) not otherwise	None known.	
classified (HNOC)		

69.29% of the mixture consists of component(s) of unknown acute oral toxicity. 91.76% of the mixture consists of component(s) of unknown acute inhalation toxicity. 95.92% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 95.92% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
Quartz		14808-60-7	30 - 60
Bisphenol A Diglycidyl Ether		25068-38-6	10 - 30
Dolomite		16389-88-1	2.5 - 10
1,4-butanediol Diglycidyl Ether		2425-79-8	1 - 5
Benzyl Alcohol		100-51-6	1 - 5
Titanium Dioxide	TITANIUM DIOXIDE	13463-67-7	0.1 - 1
4-MORPHOLINECARBALDEH	YDE	4394-85-8	< 1
Propylene Glycol Methyl Ether Acetate	1-Methoxy-2-propylacetate	108-65-6	< 1
Other components below report	able levels		0.1 - 1
4. First-aid measures			
nhalation	Move to fresh air. Call a physician if sympton	ns develop or persist.	
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Was contaminated clothing before reuse.		
Eye contact	Immediately flush eyes with plenty of water for present and easy to do. Continue rinsing. Get		
ngestion	Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs Get medical advice/attention if you feel unwell.		
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis Rash.		
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.		
General information	Ensure that medical personnel are aware of the protect themselves. Show this safety data she clothing before reuse.		
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Car	oon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.		
Specific hazards arising from the chemical	The product is combustible, and heating may generate vapors which may form explosive vapor/a mixtures. During fire, gases hazardous to health may be formed.		
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full p	protective clothing must be wor	n in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breath so without risk.	e fumes. Move containers fron	n fire area if you can d
Specific methods	Use standard firefighting procedures and cor	nsider the hazards of other invo	olved materials.
General fire hazards	Combustible liquid.		
6. Accidental release mea	sures		
Personal precautions, protective equipment and emergency procedures	cautions, Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate a ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate		

damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be

contained. For personal protection, see section 8 of the SDS.

the sale is an allow standards from			
thods and materials for ntainment and cleaning up	Eliminate all ignition sources (no smo combustibles (wood, paper, oil, etc.)		n immediate area). Keep
	Large Spills: Stop the flow of materia possible. Use a non-combustible ma and place into a container for later di	terial like vermiculite, sand or ea	arth to soak up the product
	Small Spills: Absorb with earth, sand for later disposal. Wipe up with abso remove residual contamination.		
	Never return spills to original contain	ers for re-use. For waste dispos	al, see section 13 of the SE
vironmental precautions	Avoid discharge into drains, water co	ourses or onto the ground.	
Handling and storage			
ecautions for safe handling	Keep away from open flames, hot su breathing mist/vapors. Avoid contact When using, do not eat, drink or smo protective equipment. Wash hands th practices.	t with eyes, skin, and clothing. Av oke. Provide adequate ventilation	void prolonged exposure. n. Wear appropriate person
nditions for safe storage, luding any incompatibilities	Keep away from heat, sparks and op Store in tightly closed container. Stor sprinklers. Store away from incompa	re in a well-ventilated place. Kee	p in an area equipped with
Exposure controls/pers	onal protection		
cupational exposure limits			
The following constituents are	the only constituents of the product w	hich have a PEL, TLV or other re	ecommended exposure limi
At this time, the other constitue	ents have no known exposure limits.		
At this time, the other constitue	ents have no known exposure limits. sible Exposure Limits (PEL) for Air (Type	Contaminants (29 CFR 1910.10 Value	000) Form
At this time, the other constitue US. OSHA Table Z-1 Permiss	sible Exposure Limits (PEL) for Air (-
At this time, the other constitu- US. OSHA Table Z-1 Permiss Components	sible Exposure Limits (PEL) for Air (Type	Value	Form
At this time, the other constitu- US. OSHA Table Z-1 Permiss Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7)	sible Exposure Limits (PEL) for Air (Type PEL	Value 0.05 mg/m3 15 mg/m3	Form Respirable dust. Total dust.
At this time, the other constitu- US. OSHA Table Z-1 Permiss Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. OSHA Table Z-3 Permiss	sible Exposure Limits (PEL) for Air (Type PEL PEL sible Exposure Limits (PEL) for Mine	Value 0.05 mg/m3 15 mg/m3 eral Dusts (29 CFR 1910.1000)	Form Respirable dust. Total dust.
At this time, the other constitu- US. OSHA Table Z-1 Permiss Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. OSHA Table Z-3 Permiss Components	sible Exposure Limits (PEL) for Air (Type PEL PEL sible Exposure Limits (PEL) for Mine Type	Value 0.05 mg/m3 15 mg/m3 eral Dusts (29 CFR 1910.1000) Value	Form Respirable dust. Total dust. Form
At this time, the other constitu- US. OSHA Table Z-1 Permiss Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. OSHA Table Z-3 Permiss Components	sible Exposure Limits (PEL) for Air (Type PEL PEL sible Exposure Limits (PEL) for Mine Type	Value 0.05 mg/m3 15 mg/m3 eral Dusts (29 CFR 1910.1000) Value 5 mg/m3	Form Respirable dust. Total dust. Form Respirable fraction.
At this time, the other constitu- US. OSHA Table Z-1 Permiss Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. OSHA Table Z-3 Permiss Components	sible Exposure Limits (PEL) for Air (Type PEL PEL sible Exposure Limits (PEL) for Mine Type	Value 0.05 mg/m3 15 mg/m3 eral Dusts (29 CFR 1910.1000) Value 5 mg/m3 15 mg/m3	Form Respirable dust. Total dust. Form Respirable fraction. Total dust.
At this time, the other constitu- US. OSHA Table Z-1 Permiss Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. OSHA Table Z-3 Permiss Components	sible Exposure Limits (PEL) for Air (Type PEL PEL sible Exposure Limits (PEL) for Mine Type	Value 0.05 mg/m3 15 mg/m3 eral Dusts (29 CFR 1910.1000) Value 5 mg/m3 15 mg/m3 50 mppcf	Form Respirable dust. Total dust. Form Respirable fraction. Total dust. Total dust. Total dust.
At this time, the other constitu- US. OSHA Table Z-1 Permiss Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. OSHA Table Z-3 Permiss Components Dolomite (CAS 16389-88-1)	sible Exposure Limits (PEL) for Air of Type PEL PEL sible Exposure Limits (PEL) for Mino Type TWA	Value 0.05 mg/m3 15 mg/m3 eral Dusts (29 CFR 1910.1000) Value 5 mg/m3 15 mg/m3 50 mppcf 15 mppcf	Form Respirable dust. Total dust. Form Respirable fraction. Total dust. Total dust. Respirable fraction.
At this time, the other constitu- US. OSHA Table Z-1 Permiss Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. OSHA Table Z-3 Permiss Components Dolomite (CAS 16389-88-1)	sible Exposure Limits (PEL) for Air of Type PEL PEL sible Exposure Limits (PEL) for Mino Type TWA	Value 0.05 mg/m3 15 mg/m3 eral Dusts (29 CFR 1910.1000) Value 5 mg/m3 15 mg/m3 50 mppcf 15 mg/m3 0.0 mppcf 0.1 mg/m3	Form Respirable dust. Total dust. Form Respirable fraction. Total dust. Total dust. Respirable fraction. Respirable fraction. Respirable fraction.
At this time, the other constitu- US. OSHA Table Z-1 Permiss Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. OSHA Table Z-3 Permiss Components Dolomite (CAS 16389-88-1) Quartz (CAS 14808-60-7) Titanium Dioxide (CAS	sible Exposure Limits (PEL) for Air of Type PEL PEL sible Exposure Limits (PEL) for Mino Type TWA	Value 0.05 mg/m3 15 mg/m3 eral Dusts (29 CFR 1910.1000) Value 5 mg/m3 15 mg/m3 50 mppcf 15 mppcf 0.1 mg/m3 2.4 mppcf	Form Respirable dust. Total dust. Form Respirable fraction. Total dust. Total dust. Respirable fraction. Respirable. Respirable.
At this time, the other constitu- US. OSHA Table Z-1 Permiss Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. OSHA Table Z-3 Permiss Components Dolomite (CAS 16389-88-1) Quartz (CAS 14808-60-7) Titanium Dioxide (CAS	sible Exposure Limits (PEL) for Air of Type PEL PEL sible Exposure Limits (PEL) for Mino Type TWA	Value 0.05 mg/m3 15 mg/m3 eral Dusts (29 CFR 1910.1000) Value 5 mg/m3 15 mg/m3 50 mppcf 15 mp/m3 2.4 mppcf 5 mg/m3	FormRespirable dust.Total dust.FormRespirable fraction.Total dust.Total dust.Respirable fraction.Respirable fraction.Respirable fraction.Respirable.Respirable.Respirable.Respirable fraction.
At this time, the other constitu- US. OSHA Table Z-1 Permiss Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. OSHA Table Z-3 Permiss Components Dolomite (CAS 16389-88-1) Quartz (CAS 14808-60-7) Titanium Dioxide (CAS	sible Exposure Limits (PEL) for Air of Type PEL PEL sible Exposure Limits (PEL) for Mino Type TWA	Value 0.05 mg/m3 15 mg/m3 eral Dusts (29 CFR 1910.1000) Value 5 mg/m3 15 mg/m3 50 mppcf 15 mg/m3 2.4 mppcf 5 mg/m3 15 mg/m3 15 mg/m3	Form Respirable dust. Total dust. Form Respirable fraction. Total dust. Total dust. Respirable fraction. Respirable. Respirable. Respirable fraction. Total dust.
At this time, the other constitu- US. OSHA Table Z-1 Permiss Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. OSHA Table Z-3 Permiss Components Dolomite (CAS 16389-88-1) Quartz (CAS 14808-60-7) Titanium Dioxide (CAS	sible Exposure Limits (PEL) for Air of Type PEL PEL sible Exposure Limits (PEL) for Mine Type TWA TWA TWA	Value 0.05 mg/m3 15 mg/m3 eral Dusts (29 CFR 1910.1000) Value 5 mg/m3 15 mg/m3 50 mppcf 15 mg/m3 2.4 mppcf 5 mg/m3 15 mg/m3 5.0 mppcf 5 mg/m3 5.5 mg/m3 5.5 mg/m3 5.5 mg/m3 5.5 mg/m3 15 mg/m3 5.5 mg/m3 15 mg/m3 5.5 mg/m3 15 mg/m3 5.5 mppcf	FormRespirable dust.Total dust.FormRespirable fraction.Total dust.Total dust.Respirable fraction.Respirable fraction.Respirable.Respirable.Respirable.Respirable.Total dust.Total dust.Total dust.Total dust.Total dust.Total dust.Total dust.Total dust.Total dust.
At this time, the other constitu- US. OSHA Table Z-1 Permiss Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. OSHA Table Z-3 Permiss Components Dolomite (CAS 16389-88-1) Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. ACGIH Threshold Limit Components	sible Exposure Limits (PEL) for Air of Type PEL PEL sible Exposure Limits (PEL) for Mine Type TWA TWA TWA	Value 0.05 mg/m3 15 mg/m3 eral Dusts (29 CFR 1910.1000) Value 5 mg/m3 15 mg/m3 50 mppcf 15 mg/m3 2.4 mppcf 5 mg/m3 15 mg/m3 2.4 mppcf 5 mg/m3 15 mg/m3 50 mppcf 15 mg/m3 50 mppcf 15 mg/m3 50 mppcf 15 mg/m3 50 mppcf	FormRespirable dust.Total dust.FormRespirable fraction.Total dust.Total dust.Respirable fraction.Respirable.Respirable.Respirable.Respirable fraction.Total dust.Total dust.Respirable fraction.Total dust.Respirable fraction.Total dust.Total dust.Respirable fraction.Form
At this time, the other constitu- US. OSHA Table Z-1 Permiss Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. OSHA Table Z-3 Permiss Components Dolomite (CAS 16389-88-1) Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. ACGIH Threshold Limit	sible Exposure Limits (PEL) for Air of Type PEL PEL sible Exposure Limits (PEL) for Mino Type TWA TWA TWA TWA TWA	Value 0.05 mg/m3 15 mg/m3 eral Dusts (29 CFR 1910.1000) Value 5 mg/m3 15 mg/m3 50 mppcf 15 mg/m3 2.4 mppcf 5 mg/m3 15 mg/m3 2.4 mppcf 5 mg/m3 15 mppcf 15 mg/m3 15 mppcf 15 mppcf 15 mppcf 15 mg/m3 15 mppcf 15 mppcf 15 mppcf	FormRespirable dust.Total dust.FormRespirable fraction.Total dust.Total dust.Respirable fraction.Respirable.Respirable.Respirable.Respirable fraction.Total dust.Total dust.Respirable fraction.Respirable fraction.Respirable fraction.Respirable fraction.Respirable fraction.Total dust.Total dust.Respirable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Туре	Value
Quartz (CAS 14808-60-7)	IDLH	50 mg/m3

Components	Туре	Value	
Titanium Dioxide (CAS 13463-67-7)	IDLH	5000 mg/m3	
US. NIOSH: Pocket Guide	to Chemical Hazards Recommended Ex	posure Limits (REL)	
Components	Туре	Value	Form
Quartz (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
US. OARS. Workplace Env	rironmental Exposure Level (WEEL) Gui	de	
Components	Туре	Value	
Benzyl Alcohol (CAS 100-51-6)	TWA	44.2 mg/m3	
		10 ppm	
Propylene Glycol Methyl Ether Acetate (CAS 108-65-6)	TWA	50 ppm	
Biological limit values	No biological exposure limits noted for	the ingredient(s).	
xposure guidelines			
US - California OELs: Skir	designation		
Propylene Glycol Methy	ا Ether Acetate (CAS 108-65-6) Can be	e absorbed through the skin.	
ontrols	Good general ventilation should be use applicable, use process enclosures, lo maintain airborne levels below recomn established, maintain airborne levels to shower.	cal exhaust ventilation, or othe nended exposure limits. If exp	er engineering controls to osure limits have not been
ndividual protection measure	s, such as personal protective equipme	nt	
Eye/face protection	Wear safety glasses with side shields	(or goggles). Face shield is re	commended.
Skin protection			
Hand protection	Wear appropriate chemical resistant gl	oves.	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.		apron is recommended.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.		
Thermal hazards	Wear appropriate thermal protective cl	othing, when necessary.	
General hygiene onsiderations	When using do not smoke. Keep away hygiene measures, such as washing a smoking. Routinely wash work clothin Contaminated work clothing should no	fter handling the material and g and protective equipment to	before eating, drinking, and/o remove contaminants.
9. Physical and chemica	l properties		
	Viscous Liquid		

Appearance	Viscous. Liquid.
Physical state	Liquid.
Form	Liquid.
Color	Light grey
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	46.4 °F (8 °C) estimated
Initial boiling point and boiling range	Not available.
Flash point	>392.0 °F (>200.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Explosive limit - lower (%)	Not available.

Explosive limit - upper (%)	Not available.
Vapor pressure	-0.01 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	1.81 g/cm3
Explosive properties	Not explosive.
Flammability class	Combustible IIIB estimated
Oxidizing properties	Not oxidizing.
Specific gravity	1.81
10. Stability and reactivity	/

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on	likely rout	es of exposure
----------------	-------------	----------------

·····,	-F
Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Harmful if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

lts
3
99999999999 mg/l, 4 Hours
0 mg/kg
,

Components	Species	Test Results
Oral LD50	Rat	> 1000 mg/kg
itanium Dioxide (CAS 13463-67-	7)	
Acute		
Dermal		
LD50	Hamster	>= 10000 mg/kg
Oral		
LD50	Rat	> 10000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye rritation	Causes serious eye irritation.	
Respiratory or skin sensitizatior	n	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin rea	action.
Germ cell mutagenicity	No data available to indicate p mutagenic or genotoxic.	product or any components present at greater than 0.1% are
Carcinogenicity	Not classifiable as to carcinog	enicity to humans.
IARC Monographs. Overall	Evaluation of Carcinogenicity	
Bisphenol A Diglycidyl Et Quartz (CAS 14808-60-7 Titanium Dioxide (CAS 13 OSHA Specifically Regulate	her (CAS 25068-38-6)) 3463-67-7) d Substances (29 CFR 1910.1	 3 Not classifiable as to carcinogenicity to humans. 1 Carcinogenic to humans. 2B Possibly carcinogenic to humans. 001-1053)
Quartz (CAS 14808-60-7) ogram (NTP) Report on Carcin	Cancer
Quartz (CAS 14808-60-7	• • • •	Known To Be Human Carcinogen.
Reproductive toxicity	,	o cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be	harmful.
12. Ecological information	n	
Ecotoxicity	possibility that large or freque	is environmentally hazardous. However, this does not exclude the nt spills can have a harmful or damaging effect on the environment
Persistence and degradability	No data is available on the de	gradability of any ingredients in the mixture.
Bioaccumulative potential		
Partition coefficient n-octan	ol / water (log Kow)	4.4
		1.1
Benzyl Alcohol Bisphenol A Diglycidyl Ether		3.84
Bisphenol A Diglycidyl Ether	No data available.	3.84
Bisphenol A Diglycidyl Ether Mobility in soil	No other adverse environmen	3.84 tal effects (e.g. ozone depletion, photochemical ozone creation n, global warming potential) are expected from this component.
Bisphenol A Diglycidyl Ether Mobility in soil Other adverse effects	No other adverse environmen potential, endocrine disruption	tal effects (e.g. ozone depletion, photochemical ozone creation
Bisphenol A Diglycidyl Ether Mobility in soil Other adverse effects 13. Disposal consideratio	No other adverse environmen potential, endocrine disruption ns Collect and reclaim or dispose	tal effects (e.g. ozone depletion, photochemical ozone creation
Bisphenol A Diglycidyl Ether Mobility in soil Other adverse effects 13. Disposal consideratio Disposal instructions	No other adverse environmen potential, endocrine disruption ns Collect and reclaim or dispose	tal effects (e.g. ozone depletion, photochemical ozone creation n, global warming potential) are expected from this component. e in sealed containers at licensed waste disposal site. Dispose of nce with local/regional/national/international regulations.
Bisphenol A Diglycidyl Ether Mobility in soil Other adverse effects	No other adverse environmen potential, endocrine disruption ns Collect and reclaim or dispose contents/container in accorda Dispose in accordance with a	tal effects (e.g. ozone depletion, photochemical ozone creation n, global warming potential) are expected from this component. e in sealed containers at licensed waste disposal site. Dispose of nce with local/regional/national/international regulations.

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (CAS 14808-60-7)

Cancer lung effects immune system effects kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.SARA 311/312 Hazardous
chemicalYesClassified hazard
categoriesAcute toxicity (any route of exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitization

SARA 313 (TRI reporting) Not regulated.

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7)

California Proposition 65



WARNING: This product can expose you to chemicals including Quartz, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (CAS 14808-60-7)	Listed: October 1, 1988
Titanium Dioxide (CAS 13463-67-7)	Listed: September 2, 2011

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	03-24-2022
Revision date	08-11-2023
Version #	04
HMIS® ratings	Health: 2 Flammability: 0 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 0 Instability: 0
Disclaimer	ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.