# SAFETY DATA SHEET

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

PLEXUS® MA8110 Activator

Registration number

**Product registration number** UFI: 40C0-N05A-S003-GFPX

None. **Synonyms** SKU# 0810

16-July-2023 Issue date

Version number 03

**Revision date** 22-August-2024 Supersedes date 03-August-2023

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified** uses Not available. Uses advised against None known 1.3. Details of the supplier of the safety data sheet

Company name **ITW Performance Polymers** 

**Address** Bay 150

Shannon Industrial Estate

Co Clare Ireland V14 DF82

Contact person **Customer Service** 353(61)771500 Telephone number

353(61)471285

**Email** customerservice.shannon@itwpp.com

44(0) 1235 239 670 (24 hours) **Emergency phone number** 

1.4. Emergency telephone number

112 or 999 SDS/Product information may not be available for the Emergency **General emergency** 

Non-emergency medical

helpline

111 SDS/Product information may not be available for the Emergency Service.

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

## Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids Category 2 H225 - Highly flammable liquid and

vapour.

**Health hazards** 

Skin corrosion/irritation H315 - Causes skin irritation. Category 2 Skin sensitisation

Category 1 H317 - May cause an allergic skin

reaction.

Specific target organ toxicity - single Category 3 respiratory tract irritation H335 - May cause respiratory

exposure

irritation.

#### 2.2. Label elements

# Label according to Regulation (EC) No. 1272/2008 as amended

Contains: methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate, Ethoxylated

bisphenol A dimethacrylate, PYRIDINE, 3,5-DIETHYL-1,2-DIHYDRO-1-PHENYL-2-P ROPYL-

Material name: PLEXUS® MA8110 Activator SDS GREAT BRITAIN

#### **Hazard pictograms**



Signal word Danger

**Hazard statements** 

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

#### **Precautionary statements**

#### Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist/vapours.
P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Response

P302 + P352 IF ON SKIN: Wash with plenty of water.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTRE/doctor if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use appropriate media to extinguish.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

**Disposal** 

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Supplemental label information None.

#### 2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

## **General information**

Paraffin wax

Chemical name	%	CAS-No. / EC No.	<b>REACH Registration No.</b>	Index No.	Notes
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	70 - < 80	80-62-6 201-297-1	01-2119452498-28-0000	607-035-00-6	#
Classification:		2;H225, Acute Tox. 4 ГОТ SE 3;H335	;H332, Skin Irrit. 2;H315, Sk	kin Sens.	D
Specific Concentration Limits:	STOT SE	3;H335: C ≥ 10 %			
Ethoxylated bisphenol A dimethacrylate	1 - < 3	41637-38-1 -	-	-	
Classification:	-				

8002-74-2 232-315-6

Classification: -

1 - < 3

Material name: PLEXUS® MA8110 Activator SDS GREAT BRITAIN

Chemical name CAS-No. / EC No. REACH Registration No. **Notes** Index No. # Phenol 1 - < 3128-37-0 204-881-4 2,6-bis(1,1-dimethylethyl)-4-methyl-Classification: Acute Tox. 4;H302, Aquatic Acute 1;H400, Aquatic Chronic 2;H411 34562-31-7 **PYRIDINE** 1 - < 33,5-DIETHYL-1,2-DIHYDRO-1-PHEN 252-091-3 YL-2-P ROPYL-Classification: -

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

Other components below reportable

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

20 - < 30

#### **SECTION 4: First aid measures**

General information

Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the

label where possible). Ensure that medical personnel are aware of the material(s) involved, and

take precautions to protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

centre or doctor/physician if you feel unwell.

**Skin contact** Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and

delayed

Direct contact with eyes may cause temporary irritation. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

# **SECTION 5: Firefighting measures**

General fire hazards Highly flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

source of ignition and flash back. During fire, gases hazardous to health may be formed.

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a

Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

so without risk.

**Specific methods**Use standard firefighting procedures and consider the hazards of other involved materials.

#### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

Material name: PLEXUS® MA8110 Activator SDS GREAT BRITAIN

#### For emergency responders

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ventilate closed spaces before entering them. Avoid breathing mist/vapours. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

#### 6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

## 6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

#### 6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

### 7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P5a, b or c FLAMMABLE LIQUIDS (Lower-tier requirements = 50 tonnes; Upper-tier requirements = 200 tonnes)

## 7.3. Specific end use(s)

Observe industrial sector guidance on best practices.

#### SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

#### Occupational exposure limits

Components	Туре	Value	Form		
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	416 mg/m3			
		100 ppm			
	TWA	208 mg/m3			
		50 ppm			
Paraffin wax (CAS 8002-74-2)	STEL	6 mg/m3	Fume.		
	TWA	2 mg/m3	Fume.		
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- (CAS 128-37-0)	TWA	10 mg/m3			
logical limit values	No biological exposure limits noted for the ingredient(s).				
commended monitoring cedures	Follow standard monitoring procedures.				
rived no effect levels IELs)	Not available.				

Material name: PLEXUS® MA8110 Activator

SDS GREAT BRITAIN

Predicted no effect concentrations (PNECs) Not available.

8.2. Exposure controls

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an

acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

**General information** Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves. - Other Wear appropriate chemical resistant clothing.

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not

be allowed out of the workplace.

**Environmental exposure** 

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or

engineering modifications to the process equipment may be necessary to reduce emissions to

acceptable levels.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

**Appearance** Paste **Physical state** Liquid. **Form** Paste. Colour Grey

Not available. Odour **Odour threshold** Not available. pН Not available.

Melting point/freezing point -48 °C (-54.4 °F) estimated Initial boiling point and boiling 100.5 °C (212.9 °F) estimated

range

10.0 °C (50.0 °F) estimated Flash point

Not available. **Evaporation rate** Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits Explosive limit - lower (%) 2.1 % estimated

Explosive limit - upper 8.2 % estimated

(%)

51.33 hPa estimated Vapour pressure

Not available. Vapour density Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

435 °C (815 °F) estimated **Auto-ignition temperature** 

**Decomposition temperature** Not available. **Viscosity** Not available.

Material name: PLEXUS® MA8110 Activator

SDS GREAT BRITAIN

**Explosive properties** Not explosive. **Oxidising properties** Not oxidising.

9.2. Other information

Density 0.94 g/cm3 estimated
Specific gravity 0.94 estimated

## **SECTION 10: Stability and reactivity**

**10.1. Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**10.2. Chemical stability** Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**10.4. Conditions to avoid**Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

**10.5.** Incompatible materials Strong oxidising agents. Nitrates. Peroxides.

**10.6. Hazardous** No hazardous decomposition products are known.

decomposition products

# **SECTION 11: Toxicological information**

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

**Inhalation** May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact

Causes skin irritation. May cause an allergic skin reaction.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an

allergic skin reaction. Dermatitis. Rash.

11.1. Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)

<u>Acute</u>

Oral

LD50 Rat 7800 mg/kg

Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- (CAS 128-37-0)

<u>Acute</u>

Dermal

LD50 Rat > 2000 mg/kg

Oral

LD50 Rat 890 mg/kg

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

**Respiratory sensitisation** Due to partial or complete lack of data the classification is not possible.

**Skin sensitisation** May cause an allergic skin reaction.

Germ cell mutagenicity

Due to partial or complete lack of data the classification is not possible.

Carcinogenicity

Due to partial or complete lack of data the classification is not possible.

IARC Monographs. Overall Evaluation of Carcinogenicity

methyl methacrylate; methyl 2-methylprop-2-enoate;

methyl 2-methylpropenoate (CAS 80-62-6)

3 Not classifiable as to carcinogenicity to humans.

Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-

3 Not classifiable as to carcinogenicity to humans.

(CAS 128-37-0)

**Reproductive toxicity**Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - M

single exposure

May cause respiratory irritation.

Material name: PLEXUS® MA8110 Activator SDS GREAT BRITAIN

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

**Aspiration hazard** 

Due to partial or complete lack of data the classification is not possible. No information available.

Mixture versus substance

information

## **SECTION 12: Ecological information**

12.1. Toxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

> methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 1.38

2-methylpropenoate

Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-5.1

**Bioconcentration factor (BCF)** Not available 12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

# **SECTION 13: Disposal considerations**

13.1. Waste treatment methods

Dispose of in accordance with local regulations. Empty containers or liners may retain some Residual waste

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

The Waste code should be assigned in discussion between the user, the producer and the waste EU waste code

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Discourage

sewage disposal. Waste should not be disposed of by release to sewers. Dispose of contents/container in accordance with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

# **SECTION 14: Transport information**

**ADR** 

UN1133 14.1. UN number

ADHESIVES containing flammable liquid (vapour pressure at 50 °C more than 14.2. UN proper shipping

110 kPa), Limited Quantity name

14.3. Transport hazard class(es)

Class 3 **Subsidiary hazard** 3 Label(s) 33 Hazard No. (ADR) D/F Tunnel restriction code 14.4. Packing group 14.5. Environmental hazards No.

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

RID

14.1. UN number UN1133

ADHESIVES containing flammable liquid (vapour pressure at 50 °C not more than 110 kPa) 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

3 Class **Subsidiary hazard** 3 Label(s) Ш 14.4. Packing group 14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. UN number **UN1133** 

ADHESIVES containing flammable liquid 14.2. UN proper shipping

14.3. Transport hazard class(es)

Class 3 **Subsidiary hazard** 3 Label(s) 14.4. Packing group Ш 14.5. Environmental hazards No.

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

**IATA** 

UN1133 14.1. UN number

14.2. UN proper shipping Adhesives containing flammable liquid, Limited Quantity

name

14.3. Transport hazard class(es)

3 Class Subsidiary hazard Ш 14.4. Packing group 14.5. Environmental hazards No. **ERG Code** 

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

**IMDG** 

14.1. UN number UN1133

ADHESIVES containing flammable liquid, Limited Quantity 14.2. UN proper shipping

Not established.

name

14.3. Transport hazard class(es)

3 Subsidiary hazard Ш 14.4. Packing group 14.5. Environmental hazards

Marine pollutant No. **EmS** 

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC

Code


ADN; RID



Material name: PLEXUS® MA8110 Activator

SDS GREAT BRITAIN

## ADR; IMDG



# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

#### **Authorisations**

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

#### Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P5a, b or c FLAMMABLE LIQUIDS

## Other regulations

This product is classified and labelled in accordance with the retained CLP Regulation (EC) No 1272/2008, as amended for Great Britain. This Safety Data Sheet is compiled in accordance with REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758.

Follow the requirements of the Control of Substances Hazardous to Health Regulations 2002 [SI 2002/2677], as amended, when using this material.

15.2. Chemical safety

No Chemical Safety Assessment has been carried out.

assessment

Material name: PLEXUS® MA8110 Activator SDS GREAT BRITAIN

## **SECTION 16: Other information**

#### List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TWA: Time Weighted Average.

vPvB: Very persistent and very bioaccumulative.

#### References

Information on evaluation method leading to the classification of mixture

Full text of any statements, which are not written out in full under sections 2 to 15

Not available.

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H335 May cause respiratory irritation. H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

#### **Revision information**

SECTION 2: Hazards identification: Prevention SECTION 2: Hazards identification: Response

SECTION 6: Accidental release measures: For emergency responders SECTION 8: Exposure controls/personal protection: Eye/face protection SECTION 8: Exposure controls/personal protection: Respiratory protection SECTION 8: Exposure controls/personal protection: PPE Symbols SECTION 12: Ecological information: 12.6. Other adverse effects SECTION 13: Disposal considerations: Disposal methods/information

## **Training information**

Disclaimer

Follow training instructions when handling this material.

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: PLEXUS® MA8110 Activator