

SAFETY DATA SHEET

Version #: 05

Issue date: 06-19-2019

Revision date: 07-30-2023

Supersedes date: 06-28-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture PLEXUS® AO420FS Adhesive

Registration number -

Synonyms None.

SKU# 0934

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Not available.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name ITW Performance Polymers

Address
Bay 150
Shannon Industrial Estate
Co. Clare
Ireland
V14 DF82

Contact Person Customer Service

Telephone Number
353(61)771500
353(61)471285

Email customerservice.shannon@itwpp.com

Emergency Phone Number 44(0) 1235 239 670 (24 hours)

1.4. Emergency telephone number

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Austria National Poisons Information Center +431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Belgium National Poisons Control Center 070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Bulgaria National Toxicological Information Center +359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Croatia Poisons Information Center +385 1 2348 342 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Cyprus Poison Center 1401 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Czech Republic National Poisons Information Center +420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons Control Center +45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Estonia National Poisons Information Center 16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)

Finland National Poison Information Center (09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Center ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

1.4. Emergency telephone number

Greece Poison Information Centre	(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Hungary National Emergency Phone Number	+36-80-201-199 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Iceland Poison Center	(+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Latvia Emergency medical aid	113
Latvia Poison and Drug Information Center	+371 67042473 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Lithuania Neatidėliotina informacija apsinuodijus	+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Malta Accident and Emergency Department	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Netherlands National Poisons Information Center (NVIC)	NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel in cases of acute intoxications)
Norway Norwegian Poison Information Center	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Portugal Poison Center	800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Romania Biroul RSI si Informare Toxicologica	021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be available for the Emergency Service.)
Slovakia National Toxicological Information Center	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Spain Toxicology Information Service	+ 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Sweden National Poison Information Center	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Switzerland Tox Info Suisse	145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 2	H225 - Highly flammable liquid and vapor.
-------------------	------------	---

Health hazards

Acute toxicity, dermal	Category 4	H312 - Harmful in contact with skin.
Acute toxicity, inhalation	Category 4	H332 - Harmful if inhaled.
Skin corrosion/irritation	Category 1A	H314 - Causes severe skin burns and eye damage.
Serious eye damage/eye irritation	Category 1	H318 - Causes serious eye damage.
Skin sensitization	Category 1	H317 - May cause an allergic skin reaction.
Carcinogenicity	Category 2	H351 - Suspected of causing cancer.
Specific target organ toxicity - single exposure	Category 3 respiratory tract irritation	H335 - May cause respiratory irritation.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

UFI:

Austria: G690-00P0-A00Q-M9FK
Belgium: G690-00P0-A00Q-M9FK
Bulgaria: G690-00P0-A00Q-M9FK
Croatia: G690-00P0-A00Q-M9FK
Cyprus: G690-00P0-A00Q-M9FK
Czech Republic: G690-00P0-A00Q-M9FK
Denmark: G690-00P0-A00Q-M9FK
Estonia: G690-00P0-A00Q-M9FK
EU: G690-00P0-A00Q-M9FK
Finland: G690-00P0-A00Q-M9FK
France: G690-00P0-A00Q-M9FK
Germany: G690-00P0-A00Q-M9FK
Greece: G690-00P0-A00Q-M9FK
Hungary: G690-00P0-A00Q-M9FK
Iceland: G690-00P0-A00Q-M9FK
Ireland: G690-00P0-A00Q-M9FK
Italy: G690-00P0-A00Q-M9FK
Latvia: G690-00P0-A00Q-M9FK
Lithuania: G690-00P0-A00Q-M9FK
Luxembourg: G690-00P0-A00Q-M9FK
Malta: G690-00P0-A00Q-M9FK
Netherlands: G690-00P0-A00Q-M9FK
Norway: G690-00P0-A00Q-M9FK
Poland: G690-00P0-A00Q-M9FK
Portugal: G690-00P0-A00Q-M9FK
Romania: G690-00P0-A00Q-M9FK
Slovakia: G690-00P0-A00Q-M9FK
Slovenia: G690-00P0-A00Q-M9FK
Spain: G690-00P0-A00Q-M9FK
Sweden: G690-00P0-A00Q-M9FK

Contains:

DIISODECYL ADIPATE, methacrylic acid; 2-methylpropenoic acid, methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate, N,N-dimethyl-p-toluidine; [1] N,N-dimethyl-m-toluidine; [2] N,N-dimethyl-o-toluidine [3], Styrene/butadiene Copolymer, TRIMETHYLOLPROPANE TRIMETHACRYLATE

Hazard pictograms



Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapor.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.

Precautionary statements

Prevention

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P235 Keep cool.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist/vapors.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Response

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use appropriate media to extinguish.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None.

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	50 - < 60	80-62-6 201-297-1	-	607-035-00-6	#
Classification: Flam. Liq. 2;H225, Skin Irrit. 2;H315, Skin Sens. 1;H317, STOT SE 3;H335					
Specific Concentration Limits: STOT SE 3;H335: C ≥ 10 %					
Styrene/butadiene Copolymer	10 - < 20	9003-55-8 -	-	-	
Classification: -					
methacrylic acid; 2-methylpropenoic acid	5 - < 10	79-41-4 201-204-4	-	607-088-00-5	
Classification: Acute Tox. 4;H302;(ATE: 500 mg/kg bw), Acute Tox. 4;H312;(ATE: 1100 mg/kg bw), Acute Tox. 3;H331;(ATE: 7,1000000000000005 mg/l), Skin Corr. 1A;H314, Eye Dam. 1;H318, STOT SE 3;H335					
Specific Concentration Limits: STOT SE 3;H335: C ≥ 1 %					
DIISODECYL ADIPATE	3 - < 5	27178-16-1 248-299-9	-	-	
Classification: -					
TRIMETHYLOLPROPANE TRIMETHACRYLATE	3 - < 5	3290-92-4 221-950-4	-	-	
Classification: -					
N,N-dimethyl-p-toluidine; [1] N,N-dimethyl-m-toluidine; [2] N,N-dimethyl-o-toluidine [3]	1 - < 3	99-97-8 202-805-4	-	612-056-00-9	
Classification: Acute Tox. 3;H301;(ATE: 100 mg/kg bw), Acute Tox. 3;H311;(ATE: 300 mg/kg bw), Acute Tox. 3;H331;(ATE: 3 mg/l), Carc. 2;H351, STOT RE 2;H373, Aquatic Chronic 3;H412					
Other components below reportable levels	10 - < 20				

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.
M: M-factor
vPvB: very persistent and very bioaccumulative substance.
PBT: persistent, bioaccumulative and toxic substance.
#: This substance has been assigned Union workplace exposure limit(s).
All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
4.1. Description of first aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
4.2. Most important symptoms and effects, both acute and delayed	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards	Highly flammable liquid and vapor.
5.1. Extinguishing media	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special fire fighting procedures	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
For emergency responders	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ventilate closed spaces before entering them. Avoid breathing mist/vapors. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
6.2. Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P5a, b or c FLAMMABLE LIQUIDS (Lower-tier requirements = 50 tons; Upper-tier requirements = 200 tons)

7.3. Specific end use(s)

Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits****Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001, as amended**

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	MAK	70 mg/m ³
		20 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	Ceiling	420 mg/m ³
		100 ppm
	MAK	210 mg/m ³
		50 ppm

Belgium. OEL. Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1 - Chemical agents, as amended

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	71 mg/m ³
		20 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	416 mg/m ³
		100 ppm
	TWA	208 mg/m ³
		50 ppm

Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as amended

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	70 mg/m ³

Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as amended

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm

Croatia. OELs (GVI). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and Biological Limit Values, Annex I (NN 91/2018), as amended

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	MAC	72 mg/m ³
		20 ppm
	STEL	143 mg/m ³
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)		40 ppm
	MAC	50 ppm
	STEL	100 ppm

Cyprus. OELs. Occupational Exposure Limit Values of Chemicals at Work (Safety and Health at Work (Chem. Agents) Reg., Ann. 1, R.A.A. 268/2001, as amended)

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm

Czech Republic. Occupational exposure limit values of chemicals at work (Decree on protection of health at work, 361/2007, Annex 2, Part A & Annex 3, Part A, as amended)

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	Ceiling	150 mg/m ³
	TWA	50 mg/m ³
N,N-dimethyl-p-toluidine; [1] N,N-dimethyl-m-toluidine; [2] N,N-dimethyl-o-toluidine [3] (CAS 99-97-8)	Ceiling	10 mg/m ³
	TWA	5 mg/m ³

Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, Annex 2

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TLV	70 mg/m ³
		20 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	TLV	102 mg/m ³
		25 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	100 mg/m ³
		30 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	TWA	70 mg/m3
		20 ppm
	STEL	100 ppm
	TWA	50 ppm

Finland. HTP-arvot, App 3., Binding Limit Values, Social Affairs and Ministry of Health

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	71 mg/m3
		20 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	210 mg/m3
		50 ppm
	TWA	42 mg/m3
		10 ppm

France. OELs. Occupational Exposure Limits as Prescribed by Art. R.4412-149 of Labor Code, as amended

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	VLE	410 mg/m3
		100 ppm
	VME	205 mg/m3
		50 ppm

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	VME	70 mg/m3
	Regulatory status: Indicative limit (VL)	20 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	VLE	410 mg/m3
	Regulatory status: Regulatory binding (VRC)	100 ppm
	Regulatory status: Regulatory binding (VRC)	205 mg/m3
	VME	205 mg/m3
	Regulatory status: Regulatory binding (VRC)	50 ppm
	Regulatory status: Regulatory binding (VRC)	

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG), as updated

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	180 mg/m3
		50 ppm

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG), as updated

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	TWA	210 mg/m ³
		50 ppm

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	AGW	180 mg/m ³
		50 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	AGW	210 mg/m ³
		50 ppm

Greece. OELs, Presidential Decree No. 307/1986, as amended

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	140 mg/m ³
		40 ppm
	TWA	70 mg/m ³ 20 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm

Hungary. OELs. Decree on protection of workers exposed to chemical agents (5/2020. (II.6)), Annex 1&2, as amended

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	415 mg/m ³
	TWA	208 mg/m ³

Iceland. OELs. Regulation 390/2009 on Pollution Limits and Measures to Reduce Pollution at the Workplace, as amended

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	70 mg/m ³
		20 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm

Ireland. OELVs, Schedules 1 & 2, Code of Practice for Chemical Agents and Carcinogens Regulations

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	140 mg/m ³
		40 ppm
	TWA	70 mg/m ³ 20 ppm

Ireland. OELVs, Schedules 1 & 2, Code of Practice for Chemical Agents and Carcinogens Regulations

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm

Italy. OELs (Legislative Decree n.81, 9 April 2008), as amended

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	20 ppm
	STEL	100 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	TWA	50 ppm

Latvia. OELs. Occupational Exposure Limits of Chemical Substances at Workplace (Reg. No. 325/ 2007, L.V. 80, Annex 1), as amended

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	10 mg/m3
	TWA	10 mg/m3
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	TWA	10 mg/m3

Lithuania. OELs. Occupational Exposure Limit Values for Chemical Substances (Hygiene Norm HN 23:2011; Order No. V-824/A1-389), as amended

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	100 mg/m3
	TWA	30 ppm
	TWA	70 mg/m3
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	20 ppm
	STEL	416 mg/m3
	TWA	100 ppm
	TWA	208 mg/m3
	TWA	50 ppm

Luxembourg. OELs. Binding Occupational Exposure Limit Values (Annex I), G.D.R. of 14 November 2016, OJ Memorial A, n ° 235/2016, as amended

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm

Malta. OELs. Protection of Health and Safety of Workers from Risks related to Chemical Agents at Work (L.N 227/2003 Schedules I and V), as amended

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm

Netherlands. OELs per Annex XIII of Working Conditions Regulation (Staatscourant no. 252, 29 December 2006), as amended

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	410 mg/m ³
	TWA	205 mg/m ³

Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TLV	70 mg/m ³
		20 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	400 mg/m ³
		100 ppm
	TLV	100 mg/m ³ 25 ppm

Poland. Maximum permissible concentrations and intensities of harmful factors in the work environment (Dz.U.Poz. 1286/2018, Annex 1)

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	300 mg/m ³
	TWA	100 mg/m ³

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796-2014)

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	20 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm

Romania. OELs. Limit Values of Chemical Agents at Workplace (Regulation 1.218/2006, M.O 845, Annex 1, 3&4, as amended)

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	45 mg/m ³
		13 ppm
	TWA	30 mg/m ³ 8,5 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	410 mg/m ³
		100 ppm
	TWA	205 mg/m ³ 50 ppm

Slovakia. OELs. Maximum permissible exposure limits for chemical factors in workplace air (Regulation No 355/2006, Annex 1, Table 1, as amended)

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm

Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Annex I), as amended

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	180 mg/m ³
		50 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	TWA	210 mg/m ³
		50 ppm

Spain. OELs. INSST, Límites de Exposición Profesional Para Agentes Químicos, Table 1-Valores Límites Ambientales (VLAs)

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	TWA	72 mg/m ³
		20 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm

Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	100 mg/m ³
		30 ppm
	TWA	70 mg/m ³ 20 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	Ceiling	400 mg/m ³
		100 ppm
	TWA	200 mg/m ³ 50 ppm

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	360 mg/m ³
		100 ppm
	TWA	180 mg/m ³ 50 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	420 mg/m ³

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte

Components	Type	Value
		100 ppm
	TWA	210 mg/m ³
		50 ppm

UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1

Components	Type	Value
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	143 mg/m ³
		40 ppm
	TWA	72 mg/m ³
		20 ppm
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	416 mg/m ³
		100 ppm
	TWA	208 mg/m ³
		50 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs) Not available.

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines
Croatia ELVs: Skin designation

methyl methacrylate; methyl 2-methylprop-2-enoate;
methyl 2-methylpropenoate (CAS 80-62-6) Can be absorbed through the skin.

Denmark GV: Skin designation

methyl methacrylate; methyl 2-methylprop-2-enoate;
methyl 2-methylpropenoate (CAS 80-62-6) Can be absorbed through the skin.

Germany DFG MAK (advisory): Skin designation

N,N-dimethyl-p-toluidine; [1] N,N-dimethyl-m-toluidine; [2] N,N-dimethyl-o-toluidine [3] (CAS 99-97-8) Can be absorbed through the skin.

Hungary OELs: Skin designation

methyl methacrylate; methyl 2-methylprop-2-enoate;
methyl 2-methylpropenoate (CAS 80-62-6) Can be absorbed through the skin.

Iceland OELs: Skin designation

methyl methacrylate; methyl 2-methylprop-2-enoate;
methyl 2-methylpropenoate (CAS 80-62-6) Can be absorbed through the skin.

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.
Individual protection measures, such as personal protective equipment	
General information	Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Eye/face protection	Chemical respirator with organic vapor cartridge and full facepiece.
Skin protection	
- Hand protection	Wear appropriate chemical resistant gloves.
- Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	Chemical respirator with organic vapor cartridge and full facepiece.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Paste.
Color	Off-white
Odor	Fragrant
Melting point/freezing point	-54,4 °F (-48 °C) estimated
Boiling point or initial boiling point and boiling range	212,9 °F (100,5 °C) estimated
Flammability	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	2,1 % estimated
Explosive limit - upper (%)	8,2 % estimated
Flash point	50,0 °F (10,0 °C) estimated
Auto-ignition temperature	752 °F (400 °C) estimated
Decomposition temperature	Not available.
pH	Not available.
Kinematic viscosity	Not available.
Solubility	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water) (log value)	Not available.
Vapor pressure	28 mm Hg @ 68 F
Density and/or relative density	
Density	0,95 g/cm ³ estimated
Vapor density	Not available.
Particle characteristics	Not available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes No relevant additional information available.

9.2.2. Other safety characteristics

Specific gravity 0,95 estimated

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidizing agents. Nitrates. Peroxides.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	Harmful if inhaled.
Skin contact	Causes severe skin burns. Harmful in contact with skin. May cause an allergic skin reaction.
Eye contact	Causes serious eye damage.
Ingestion	Causes digestive tract burns.

Symptoms Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Harmful if inhaled. Harmful in contact with skin.

Components	Species	Test Results
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)		

Acute

Inhalation

LC50	Rat	7,1000000000000005 mg/l, 4 Hours
------	-----	----------------------------------

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)

Acute

Oral

LD50	Rat	7800 mg/kg
------	-----	------------

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory sensitization Due to partial or complete lack of data the classification is not possible.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6) 3 Not classifiable as to carcinogenicity to humans.

N,N-dimethyl-p-toluidine; [1] N,N-dimethyl-m-toluidine; [2] N,N-dimethyl-o-toluidine [3] (CAS 99-97-8) 2B Possibly carcinogenic to humans.

Styrene/butadiene Copolymer (CAS 9003-55-8) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - single exposure May cause respiratory irritation.

Specific target organ toxicity - repeated exposure Not applicable.

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Mixture versus substance information No information available.

11.2. Information on other hazards

Endocrine disrupting properties	This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.
Other information	Not available.

SECTION 12: Ecological information

12.1. Toxicity	Based on available data, the classification criteria are not met for hazardous to the aquatic environment.
12.2. Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.
12.3. Bioaccumulative potential	
Partition coefficient n-octanol/water (log Kow)	
methacrylic acid; 2-methylpropenoic acid	0,93
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	1,38
Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	No data available.
12.5. Results of PBT and vPvB assessment	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.
12.6. Endocrine disrupting properties	This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.
12.7. Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1133
14.2. UN proper shipping name	ADHESIVES containing flammable liquid, Limited Quantity
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Hazard No. (ADR)	30
Tunnel restriction code	D/E
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number	UN1133
14.2. UN proper shipping name	ADHESIVES containing flammable liquid
14.3. Transport hazard class(es)	
Class	3

Subsidiary risk -
Label(s) 3
14.4. Packing group III
14.5. Environmental hazards No.
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number UN1133
14.2. UN proper shipping name ADHESIVES containing flammable liquid
14.3. Transport hazard class(es)
Class 3
Subsidiary risk -
Label(s) 3
14.4. Packing group III
14.5. Environmental hazards No.
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number UN1133
14.2. UN proper shipping name Adhesives containing flammable liquid, Limited Quantity
14.3. Transport hazard class(es)
Class 3
Subsidiary risk -
14.4. Packing group III
14.5. Environmental hazards No.
ERG Code 3L
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed with restrictions.
Cargo aircraft only Allowed with restrictions.

IMDG


14.1. UN number UN1133
14.2. UN proper shipping name ADHESIVES containing flammable liquid, Limited Quantity
14.3. Transport hazard class(es)
Class 3
Subsidiary risk -
14.4. Packing group III
14.5. Environmental hazards
Marine pollutant No.
EmS F-E, S-D
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

14.7. Maritime transport in bulk according to IMO instruments Not established.


ADN; RID



ADR; IMDG



IATA



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

UFI:

Austria: G690-00P0-A00Q-M9FK
Belgium: G690-00P0-A00Q-M9FK
Bulgaria: G690-00P0-A00Q-M9FK
Croatia: G690-00P0-A00Q-M9FK
Cyprus: G690-00P0-A00Q-M9FK
Czech Republic: G690-00P0-A00Q-M9FK
Denmark: G690-00P0-A00Q-M9FK
Estonia: G690-00P0-A00Q-M9FK
EU: G690-00P0-A00Q-M9FK
Finland: G690-00P0-A00Q-M9FK
France: G690-00P0-A00Q-M9FK
Germany: G690-00P0-A00Q-M9FK
Greece: G690-00P0-A00Q-M9FK
Hungary: G690-00P0-A00Q-M9FK
Iceland: G690-00P0-A00Q-M9FK
Ireland: G690-00P0-A00Q-M9FK
Italy: G690-00P0-A00Q-M9FK
Latvia: G690-00P0-A00Q-M9FK
Lithuania: G690-00P0-A00Q-M9FK
Luxembourg: G690-00P0-A00Q-M9FK
Malta: G690-00P0-A00Q-M9FK
Netherlands: G690-00P0-A00Q-M9FK
Norway: G690-00P0-A00Q-M9FK
Poland: G690-00P0-A00Q-M9FK
Portugal: G690-00P0-A00Q-M9FK
Romania: G690-00P0-A00Q-M9FK
Slovakia: G690-00P0-A00Q-M9FK
Slovenia: G690-00P0-A00Q-M9FK
Spain: G690-00P0-A00Q-M9FK
Sweden: G690-00P0-A00Q-M9FK

Authorizations**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

Restrictions on use**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered**

methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4) 75

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances
Hazard categories in accordance with Regulation (EC) No 1272/2008
- P5a, b or c FLAMMABLE LIQUIDS

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

According to Directive 92/85/EEC as amended, pregnant women should not work with the product, if there is the least risk of exposure.

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

France regulations**France INRS Table of Occupational Diseases**

methacrylate; methyl 2-methylprop-2-enoate; Affections provoquées par le méthacrylate de méthyle 82
methyl 2-methylpropenoate (CAS 80-62-6)

Product registration number

Austria	UFI: G690-00P0-A00Q-M9FK
Belgium	UFI: G690-00P0-A00Q-M9FK
Czech Republic	UFI: G690-00P0-A00Q-M9FK
Denmark	UFI: G690-00P0-A00Q-M9FK
European Union	UFI: G690-00P0-A00Q-M9FK
Finland	UFI: G690-00P0-A00Q-M9FK
France	UFI: G690-00P0-A00Q-M9FK
Germany	UFI: G690-00P0-A00Q-M9FK

Greece	UFI: G690-00P0-A00Q-M9FK
Hungary	UFI: G690-00P0-A00Q-M9FK
Italy	UFI: G690-00P0-A00Q-M9FK
Netherlands	UFI: G690-00P0-A00Q-M9FK
Norway	UFI: G690-00P0-A00Q-M9FK
Poland	UFI: G690-00P0-A00Q-M9FK
Portugal	UFI: G690-00P0-A00Q-M9FK
Slovakia	UFI: G690-00P0-A00Q-M9FK
Slovenia	UFI: G690-00P0-A00Q-M9FK
Spain	UFI: G690-00P0-A00Q-M9FK
Sweden	UFI: G690-00P0-A00Q-M9FK
Switzerland	UFI: G690-00P0-A00Q-M9FK

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
 ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.
 AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).
 CAS: Chemical Abstract Service.
 CEN: European Committee for Standardization.
 IATA: International Air Transport Association.
 IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
 IMDG: International Maritime Dangerous Goods.
 MAC: Maximum Allowed Concentration.
 MARPOL: International Convention for the Prevention of Pollution from Ships.
 PBT: Persistent, bioaccumulative and toxic.
 RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
 STEL: Short term exposure limit.
 TLV: Threshold Limit Value.
 TWA: Time Weighted Average.
 VLE: Exposure Limit Value.
 VME: Exposure Average Value.
 vPvB: Very persistent and very bioaccumulative.
 Not available.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H225 Highly flammable liquid and vapor.
 H301 Toxic if swallowed.
 H302 Harmful if swallowed.
 H311 Toxic in contact with skin.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H331 Toxic if inhaled.
 H335 May cause respiratory irritation.
 H351 Suspected of causing cancer.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.

Revision information

None.

Training information

Follow training instructions when handling this material.

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.