# SAFETY DATA SHEET

### 1. Identification

Product identifier DEVCON® Wear Resistant Putty (WR-2) Resin

Other means of identification

**SKU#** 0106

**Recommended use**Not available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers

Address 30 Endicott Street

Danvers, MA 01923 United States

**Telephone** Customer Service 978-777-1100

Website www.itwperformancepolymers.com

E-mail Not available.

Contact person EHS Department

Emergency phone number Chemtrec 800-424-9300

International 703-527-3887

### 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2
Sensitization, skin Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

**Precautionary statement** 

Prevention Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated

work clothing must not be allowed out of the workplace. Wear eye protection/face protection.

Wear protective gloves.

**Response** If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take

off contaminated clothing and wash it before reuse.

Storage Not available.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Aluminium Oxide		1344-28-1	40 - 70
Graphite		7782-42-5	1 - 5
Other components below re	eportable levels		1 - < 3

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

Indication of immediate medical attention and special

treatment needed **General information**  Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Use water spray to cool unopened containers.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Following product recovery, flush area with water.

Small Spills: Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid discharge into drains, water courses or onto the ground. **Environmental precautions** 

### 7. Handling and storage

Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Material name: DEVCON® Wear Resistant Putty (WR-2) Resin 0106 Version #: 06 Revision date: 07-31-2023 Issue date: 05-29-2019

# 8. Exposure controls/personal protection

### Occupational exposure limits

Components	Туре	Value	Form
Aluminium Oxide (CAS 1344-28-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
	ssible Exposure Limits (PEL) for Min		)) Form
Components	Type	Value	FOIII
Aluminium Oxide (CAS 1344-28-1)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Graphite (CAS 7782-42-5)	TWA	15 mppcf	
US. ACGIH Threshold Limi	t Values (TLV)		_
Components	Туре	Value	Form
Graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.
NIOSH. Immediately Dange	erous to Life or Health (IDLH) Values,	as amended	
Components	Туре	Value	
Graphite (CAS 7782-42-5)	IDLH	1250 mg/m3	
	o Chemical Hazards Recommended		_
Components	Туре	Value	Form
Graphite (CAS 7782-42-5)	TWA	2.5 mg/m3	Respirable.
logical limit values	No biological exposure limits noted	for the ingredient(s).	
propriate engineering trols	Good general ventilation should be applicable, use process enclosures, maintain airborne levels below record established, maintain airborne levels shower.	local exhaust ventilation, or other mmended exposure limits. If ex	ner engineering controls to posure limits have not been
vidual protection measures	, such as personal protective equipr	ment	
Eye/face protection	Wear safety glasses with side shield	ls (or goggles). Face shield is re	ecommended.
Skin protection Hand protection	Wear appropriate chemical resistant	t gloves.	
- -	Wear appropriate chemical resistant	t clothing. Use of an impervious	apron is recommended.
Other	In case of insufficient ventilation, wear suitable respiratory equipment.		
	In case of insufficient ventilation. we	ar suitable respiratory equipme	nt.
Other  Respiratory protection  Thermal hazards	In case of insufficient ventilation, we Wear appropriate thermal protective	. ,	nt.

# 9. Physical and chemical properties

considerations

**Appearance** Paste. Solid. **Physical state** Solid. Paste. **Form** Grey. Color Odor Slight. Not available. **Odor threshold** Not available. pН Not available. Melting point/freezing point

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

Initial boiling point and boiling 608

range

608 °F (320 °C) estimated

Flash point 265.0 °F (129.4 °C) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

**Density** 1.17 g/cm3 estimated

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 1.17 estimated

**VOC** 0 g/l

### 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

### 11. Toxicological information

### Information on likely routes of exposure

**Inhalation** No adverse effects due to inhalation are expected.

**Skin contact** Causes skin irritation. May cause an allergic skin reaction.

**Eye contact** Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

Aluminium Oxide (CAS 1344-28-1)

Acute Oral

LD50 Rat > 5000 mg/kg

Material name: DEVCON® Wear Resistant Putty (WR-2) Resin
0106 Version #: 06 Revision date: 07-31-2023 Issue date: 05-29-2019

Components Species Test Results

Graphite (CAS 7782-42-5)

Acute Oral

LD50 Rat > 10000 mg/kg

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

### 12. Ecological information

**Ecotoxicity**The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations**Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Not applicable.

### 15. Regulatory information

**US** federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Aluminium Oxide (CAS 1344-28-1)

% 1.0

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Aluminium Oxide (CAS 1344-28-1) Listed.

**Toxic Substances Control Act (TSCA)** 

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard

Skin corrosion or irritation

categories

Serious eye damage or eye irritation Respiratory or skin sensitization

na)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Aluminium Oxide	1344-28-1	40 - 70	

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

**US state regulations** 

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No

Material name: DEVCON® Wear Resistant Putty (WR-2) Resin

Country(s) or region Inventory name On inventory (yes/no)\*

New Zealand Inventory Yes

Philippines Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

 Issue date
 05-29-2019

 Revision date
 07-31-2023

Version # 06

HMIS® ratings Health: 2

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 1 Instability: 0

**Disclaimer** ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or

in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information Physical & Chemical Properties: Multiple Properties

Material name: DEVCON® Wear Resistant Putty (WR-2) Resin 0106 Version #: 06 Revision date: 07-31-2023 Issue date: 05-29-2019

# SAFETY DATA SHEET

### 1. Identification

Product identifier Putty Hardener

Other means of identification

**SKU#** 0200C

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers

Address 30 Endicott Street

Danvers, MA 01923

United States

**Telephone** Customer Service 978-777-1100

Website www.itwperformancepolymers.com

E-mail Not available.

Contact person EHS Department

Emergency phone number Chemtrec 800-424-9300

International 703-527-3887

## 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, dermal Category 4

Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes

serious eye damage.

Precautionary statement

**Prevention** Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated

work clothing must not be allowed out of the workplace. Wear eye protection/face protection.

Wear protective gloves/protective clothing.

**Response** If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated

clothing and wash it before reuse.

Storage Not available.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Material name: Putty Hardener sps us

### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Aliphatic Amines		N/A	40 - 60
Benzyl Alcohol		100-51-6	20 - 40
TRIETHYLENETETRAMINE	TETA	112-24-3	20 - 40
Silicon Dioxide	Silica, amorphous, fumed, crystfree	112945-52-5	2.5 - 10
Titanium Dioxide	TITANIUM DIOXIDE	13463-67-7	0.1 - 1
Other components below reporta	ble levels		0.1 - 1

### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. Get medical Skin contact advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical

attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention immediately.

Rinse mouth. Get medical advice/attention if you feel unwell. Ingestion

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

**General information** 

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters Fire fighting

equipment/instructions

Specific methods General fire hazards Water spray. Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Use water spray to cool unopened containers.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Following product recovery, flush area with water.

Small Spills: Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** Avoid discharge into drains, water courses or onto the ground.

Material name: Putty Hardener SDS US

### 7. Handling and storage

Precautions for safe handling

Do not get this material in contact with eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

### 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
JS. OSHA Table Z-3 Permissible E			
Components	Туре	Value	Form
Silicon Dioxide (CAS 112945-52-5)	TWA	0.8 mg/m3	
		20 mppcf	
Гitanium Dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
JS. ACGIH Threshold Limit Value	s (TLV)		
Components	Type	Value	Form
Titanium Dioxide (CAS 13463-67-7)	TWA	2.5 mg/m3	Respirable finescale
13463-67-7)			particles
13463-67-7)		0.2 mg/m3	particles Respirable nanoscale particles
13463-67-7) NIOSH. Immediately Dangerous to	b Life or Health (IDLH) Values,	-	Respirable nanoscale
·	o Life or Health (IDLH) Values, Type	-	Respirable nanoscale
NIOSH. Immediately Dangerous to		as amended	Respirable nanoscale
NIOSH. Immediately Dangerous to Components Fitanium Dioxide (CAS 13463-67-7) JS. NIOSH: Pocket Guide to Chen	Type  IDLH  nical Hazards Recommended	as amended Value 5000 mg/m3 Exposure Limits (REL)	Respirable nanoscale
NIOSH. Immediately Dangerous to Components Fitanium Dioxide (CAS 13463-67-7)	Type IDLH	as amended Value 5000 mg/m3	Respirable nanoscale
NIOSH. Immediately Dangerous to Components Fitanium Dioxide (CAS 13463-67-7) JS. NIOSH: Pocket Guide to Chen	Type  IDLH  nical Hazards Recommended	as amended Value 5000 mg/m3 Exposure Limits (REL)	Respirable nanoscale
NIOSH. Immediately Dangerous to Components  Fitanium Dioxide (CAS 13463-67-7)  JS. NIOSH: Pocket Guide to Chen Components  Gilicon Dioxide (CAS 112945-52-5)  JS. OARS. Workplace Environments	Type  IDLH  nical Hazards Recommended Type  TWA  ntal Exposure Level (WEEL) G	as amended Value 5000 mg/m3  Exposure Limits (REL) Value 6 mg/m3	Respirable nanoscale
NIOSH. Immediately Dangerous to Components  Fitanium Dioxide (CAS 13463-67-7)  JS. NIOSH: Pocket Guide to Chen Components  Silicon Dioxide (CAS 112945-52-5)	Type  IDLH  nical Hazards Recommended Type  TWA	as amended Value 5000 mg/m3  Exposure Limits (REL) Value 6 mg/m3	Respirable nanoscale
NIOSH. Immediately Dangerous to Components  Fitanium Dioxide (CAS 13463-67-7)  JS. NIOSH: Pocket Guide to Chen Components  Gilicon Dioxide (CAS 112945-52-5)  JS. OARS. Workplace Environments	Type  IDLH  nical Hazards Recommended Type  TWA  ntal Exposure Level (WEEL) G	as amended Value 5000 mg/m3  Exposure Limits (REL) Value 6 mg/m3  Guide	Respirable nanoscale
NIOSH. Immediately Dangerous to Components  Fitanium Dioxide (CAS 13463-67-7)  JS. NIOSH: Pocket Guide to Chen Components  Silicon Dioxide (CAS 112945-52-5)  JS. OARS. Workplace Environme Components  Benzyl Alcohol (CAS	Type  IDLH  nical Hazards Recommended Type  TWA  ntal Exposure Level (WEEL) G	as amended Value 5000 mg/m3  Exposure Limits (REL) Value 6 mg/m3  Guide Value	Respirable nanoscale
NIOSH. Immediately Dangerous to Components  Fitanium Dioxide (CAS 13463-67-7)  JS. NIOSH: Pocket Guide to Chen Components  Silicon Dioxide (CAS 112945-52-5)  JS. OARS. Workplace Environme Components  Benzyl Alcohol (CAS	Type  IDLH  nical Hazards Recommended Type  TWA  ntal Exposure Level (WEEL) G	as amended Value 5000 mg/m3  Exposure Limits (REL) Value 6 mg/m3  Guide Value 44.2 mg/m3	Respirable nanoscale

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Exposure guidelines**Occupational Exposure Limits are not relevant to the current physical form of the product.

**US WEEL Guides: Skin designation** 

TRIETHYLENETETRAMINE (CAS 112-24-3)

Can be absorbed through the skin.

Material name: Putty Hardener sps us

# Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

#### Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles) and a face shield. Face shield is Eye/face protection

recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

### 9. Physical and chemical properties

Paste. Appearance Solid. Physical state Paste. **Form** Color White Ammoniacal.

Odor Not available. **Odor threshold** Not available.

Melting point/freezing point Initial boiling point and boiling

4.64 °F (-15.2 °C) estimated 420.8 °F (216 °C) estimated

range

Flash point

>199.9 °F (>93.3 °C)

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%)

Vapor pressure 5.73 hPa estimated

Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) Not available. Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** 640 °F (337.78 °C) estimated

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Density 1.00 g/cm3 estimated

**Explosive properties** Not explosive. Oxidizing properties Not oxidizing. Specific gravity 1 estimated

### 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material name: Putty Hardener SDS US 4/8 Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**Conditions to avoid** Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Peroxides. Phenols.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

# 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation** No adverse effects due to inhalation are expected.

**Skin contact** Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.

**Eye contact** Causes serious eye damage.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause

redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

#### Information on toxicological effects

Acute toxicity Harmful in contact with skin.

Components	Species	Test Results
------------	---------	--------------

Benzyl Alcohol (CAS 100-51-6)

Acute Dermal

LD50 Rabbit 2000 mg/kg

Inhalation

LC50 Rat > 4.17799999999999 mg/l, 4 Hours

Oral

LD50 Rat 1230 - 3100 mg/kg

Silicon Dioxide (CAS 112945-52-5)

<u>Acute</u>

Oral

LD50 Rat > 22500 mg/kg

Titanium Dioxide (CAS 13463-67-7)

Acute Dermal

LD50 Hamster >= 10000 mg/kg

Oral

LD50 Rat > 10000 mg/kg

TRIETHYLENETETRAMINE (CAS 112-24-3)

Acute Dermal

Liquid

LD50 Rat 1465 mg/kg

Oral

Liquid

LD50 Rat 1716 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

Material name: Putty Hardener

0200C Version #: 13 Revision date: 08-02-2023 Issue date: 07-03-2019

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Silicon Dioxide (CAS 112945-52-5)

3 Not classifiable as to carcinogenicity to humans.

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Benzyl Alcohol 1.1

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

**Toxic Substances Control Act (TSCA)** 

Material name: Putty Hardener SDS US

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

categories

SARA 311/312 Hazardous

Yes

chemical

**Classified hazard** 

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

#### SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### **US state regulations**

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Titanium Dioxide (CAS 13463-67-7)

#### **California Proposition 65**



WARNING: This product can expose you to Titanium Dioxide, which is known to the State of California to

cause cancer. For more information go to www.P65Warnings.ca.gov.

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

Inventory name

Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

#### **International Inventories**

Country(s) or region

Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

Material name: Putty Hardener sps us

On inventory (yes/no)\*

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

 Issue date
 07-03-2019

 Revision date
 08-02-2023

Version # 13

HMIS® ratings Health: 3

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 3

Flammability: 1 Instability: 0

**Disclaimer** ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Material name: Putty Hardener SDS US