SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® R-Flex® II Resin

Other means of identification

SKU# 0339B

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number978-777-1100

Fax E-mail

Emergency telephone

number

800-424-9300

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2
Sensitization, respiratory Category 1
Sensitization, skin Category 1A
Carcinogenicity Category 2
Reproductive toxicity Category 2

Specific target organ toxicity following single Category 3 respiratory tract irritation

exposure

Environmental hazards Hazardous to the aquatic environment, acute Category 2

hazard

Label elements



Signal word Danger

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May

cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Toxic

to aquatic life.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing mist/vapours. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye

protection/face protection. Wear respiratory protection.

Material name: DEVCON® R-Flex® II Resin

SDS CANADA

IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep Response

> comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a POISON

CENTRE/doctor. Take off contaminated clothing and wash it before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ISOPHORONE DIISOCYANATE		4098-71-9	15 - 40
Polytetramethylene Ether Glycol		25190-06-1	10 - 30
METHYL ETHYL KETONE		78-93-3	3 - 7
Polypropylene Glycols		25322-69-4	3 - 7
4,4'-DIPHENYLMETHANE DIISOCYANATE		101-68-8	0.1 - 1
Other components below reportable	levels		30 - 60

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

> artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a poison center or

doctor/physician.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

symptoms/effects, acute and delaved

vision. May cause respiratory irritation. Coughing. Difficulty in breathing. Skin irritation. May cause

redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice **General information** (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in

attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

and precautions for firefighters Fire fighting

Move containers from fire area if you can do so without risk.

equipment/instructions Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

Material name: DEVCON® R-Flex® II Resin

SDS CANADA

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Use water spray to reduce vapours or divert vapour cloud drift. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Value Components	s Type	Value	
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	TWA	0.005 ppm	
ISOPHORONE DIISOCYANATE (CAS 4098-71-9)	TWA	0.005 ppm	
METHYL ETHYL KETONE (CAS 78-93-3)	STEL	300 ppm	
	TWA	200 ppm	
Canada. Alberta OELs (Occupation	onal Health & Safety Code, Sc	hedule 1, Table 2)	
Components	Туре	Value	
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	TWA	0.05 mg/m3	
		0.005 ppm	
ISOPHORONE DIISOCYANATE (CAS 4098-71-9)	TWA	0.05 mg/m3	
		0.005 ppm	
METHYL ETHYL KETONE (CAS 78-93-3)	STEL	885 mg/m3	
		300 ppm	
	TWA	590 mg/m3	
		200 ppm	

Material name: DEVCON® R-Flex® II Resin

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97. as amended)

Safety Regulation 296/97, as amend Components	ded) Type	Value
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	Ceiling	0.01 ppm
101 00 0)	TWA	0.005 ppm
ISOPHORONE DIISOCYANATE (CAS 4098-71-9)	Ceiling	0.01 ppm
	TWA	0.005 ppm
METHYL ETHYL KETONE (CAS 78-93-3)	STEL	100 ppm
	TWA	50 ppm
Canada. Manitoba OELs (Reg. 217/Components	2006, The Workplace Safety Type	And Health Act) Value
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	TWA	0.005 ppm
ISOPHORONE DIISOCYANATE (CAS 4098-71-9)	TWA	0.005 ppm
METHYL ETHYL KETONE (CAS 78-93-3)	STEL	300 ppm
	TWA	200 ppm
Canada. Ontario OELs. (Control of Components	Exposure to Biological or Cl Type	hemical Agents) Value
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	Ceiling	0.02 ppm
,	TWA	0.005 ppm
ISOPHORONE DIISOCYANATE (CAS 4098-71-9)	Ceiling	0.02 ppm
,	TWA	0.005 ppm
METHYL ETHYL KETONE (CAS 78-93-3)	STEL	300 ppm
	TWA	200 ppm
Canada. Quebec OELs. (Ministry of Components	f Labor - Regulation respecti Type	ng occupational health and safety) Value
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	TWA	0.051 mg/m3
		0.005 ppm
ISOPHORONE DIISOCYANATE (CAS 4098-71-9)	TWA	0.045 mg/m3
		0.005 ppm
METHYL ETHYL KETONE (CAS 78-93-3)	STEL	300 mg/m3
		100 ppm
	TWA	150 mg/m3 50 ppm
		00 pp

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Value Type 4.4'-DIPHENYLMETHANE 15 minute 0.015 ppm DIISOCYANATE (CAS

15 minute

101-68-8)

8 hour 0.005 ppm

ISOPHORONE

DIISOCYANATE (CAS

4098-71-9)

8 hour 0.005 ppm

METHYL ETHYL KETONE

(CAS 78-93-3)

15 minute 300 ppm

8 hour 200 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
METHYL ETHYL KETON (CAS 78-93-3)	IE 2 mg/l	MEK	Urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

Canada - British Columbia OELs: Skin designation

4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)

Can be absorbed through the skin.

0.015 ppm

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally

adequate. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapour cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapour cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

range

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Liquid. Liquid. **Physical state Form** Liquid.

Colour Clear colorless or nearly colorless

Odour Slight.

Odour threshold Not available. 7 @ 5% solution рH

Melting point/freezing point 79.59 °C (175.26 °F) estimated Initial boiling point and boiling

-86.64 °C (-123.95 °F) estimated

204.4 °C (399.9 °F) Closed cup Flash point

Not available. **Evaporation rate** Flammability (solid, gas) Not applicable.

Material name: DEVCON® R-Flex® II Resin

SDS CANADA

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

1.8 % estimated

Flammability limit - upper

(%)

10 % estimated

Explosive limit - lower (%)

Explosive limit - upper

Not available. Not available.

(%)

20.01 hPa estimated Vapour pressure

Not available. Vapour density Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

404 °C (759.2 °F) estimated **Auto-ignition temperature**

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 1.01 g/cm3 estimated

Not explosive. **Explosive properties**

Flammability class Combustible IIIB estimated

Not oxidising. Oxidising properties Specific gravity 1.01 estimated

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the decomposition temperature. Contact with incompatible

materials.

Incompatible materials Strong oxidising agents. Alcohols. Amides. Amines. Ammonia. Caustics. Isocyanates. Phenols.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. May cause allergy or asthma symptoms or

breathing difficulties if inhaled. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Causes serious eye irritation. Eye contact

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Coughing. Difficulty in breathing. Skin irritation. May cause

redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Not known. **Acute toxicity**

Test Results Components **Species**

ISOPHORONE DIISOCYANATE (CAS 4098-71-9)

Acute Dermal

LD50 Rat 1060 mg/kg

Material name: DEVCON® R-Flex® II Resin

0339B Version #: 06 Revision date: 29-June-2022 Issue date: 22-May-2019

Components Species Test Results

Oral

LD50 Rat > 1000 mg/kg

METHYL ETHYL KETONE (CAS 78-93-3)

Acute Dermal

LD50 Rabbit > 8000 mg/kg

Oral

LD50 Rat 2300 - 3500 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye Causes serious eye irritation.

irritation

Respiratory or skin sensitisation

Canada - British Columbia OELs: Respiratory or skin sensitiser

4,4'-DIPHENYLMETHANE DIISOCYANATE Capable of causing sensitization

(CAS 101-68-8)

ISOPHORONE DIISOCYANATE (CAS 4098-71-9) Capable of causing sensitization

Canada - Quebec OELs: Sensitizer

4,4'-DIPHENYLMETHANE DIISOCYANATE Sensitiser.

(CAS 101-68-8)

ISOPHORONE DIISOCYANATE (CAS 4098-71-9) Sensitiser.

Respiratory sensitisation May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

4,4'-DIPHENYLMETHANE DIISOCYANATE 3 Not classifiable as to carcinogenicity to humans.

(CAS 101-68-8)

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Toxic to aquatic life.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

METHYL ETHYL KETONE 0.29

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

METHYL ETHYL KETONE (CAS 78-93-3)

Class B

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Material name: DEVCON® R-Flex® II Resin

SDS CANADA

0339B Version #: 06 Revision date: 29-June-2022 Issue date: 22-May-2019

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

16. Other information

country(s).

Issue date22-May-2019Revision date29-June-2022

Version No. 06

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: DEVCON® R-Flex® II Resin

SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® R-Flex® Hardener

Other means of identification

SKU# 6928

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number978-777-1100

Fax E-mail

Emergency telephone

number

800-424-9300

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Serious eye damage/eye irritation Category 2A Specific target organ toxicity following Category 2

repeated exposure

Environmental hazards Not classified.

Label elements



Signal word Warning

Hazard statement Harmful if swallowed. Causes serious eye irritation. May cause damage to organs through

prolonged or repeated exposure.

Precautionary statement

Prevention Do not breathe mist/vapours. Wash thoroughly after handling. Do not eat, drink or smoke when

using this product. Wear eye protection/face protection.

Response IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell. Rinse mouth. IF IN EYES:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention if you feel unwell. If eye irritation persists: Get

medical advice/attention.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Diethyltoluenediamine		68479-98-1	60 - 100
Oleic acid		112-80-1	10 - 30
Carbon Black		1333-86-4	0.1 - 1
Other components below reports	able levels		1 - 5

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Eve contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

> present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and delayed

Ingestion

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

General information

During fire, gases hazardous to health may be formed.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk.

Do not use water jet as an extinguisher, as this will spread the fire.

Specific methods General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Use water spray to reduce vapours or divert vapour cloud drift.

Large Spills: Stop the flow of material, if this is without risk, Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Do not breathe mist/vapours. Do not taste or swallow. Avoid contact with eyes. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occu	national	exposure	limite
Occu	pationai	exposure	111111111111111111111111111111111111111

110	ACCIL	Throc	hald I	imit \	Values
uə.	ACGIR	inres	noia L	_imit '	vaiues

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) Components Type Value

CARBON BLACK (CAS TWA 3.5 mg/m3

1333-86-4)

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

ComponentsTypeValueFormCARBON BLACK (CAS
1333-86-4)TWA3 mg/m3Inhalable

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

ComponentsTypeValueFormCARBON BLACK (CAS
1333-86-4)TWA3 mg/m3Inhalable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

ComponentsTypeValueFormCARBON BLACK (CAS
1333-86-4)TWA3 mg/m3Inhalable fraction.

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

 Components
 Type
 Value

 CARBON BLACK (CAS 1333-86-4)
 TWA 3.5 mg/m3

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

 Components
 Type
 Value

 CARBON BLACK (CAS 1333-86-4)
 15 minute
 7 mg/m3

 8 hour
 3.5 mg/m3

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapour cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapour cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygieneKeep away from food and drink. Always observe good personal hygiene measures, such as considerations
washing after handling the material and before eating, drinking, and/or smoking. Routinely wash

work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Liquid.
Physical state Liquid.
Form Liquid.

Material name: DEVCON® R-Flex® Hardener
6928 Version #: 04 Revision date: 27-January-2023 Issue date: 22-May-2019

Colour Black

Ammoniacal. Odour **Odour threshold** Not available.

7 - 8 @ 5% solution pН

16.3 °C (61.34 °F) estimated Melting point/freezing point

Initial boiling point and boiling

range

Not available.

156.0 °C (312.8 °F) estimated Flash point

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Flammability limit - upper

Not available.

Not available.

(%)

(%)

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper

(%)

Vapour pressure < 1 mm Hg @ 70 F Not available. Vapour density Relative density Not available.

Solubility(ies)

Solubility (water) Not available. Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature 362.78 °C (685 °F) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 1.00 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Combustible IIIB estimated

Oxidising properties Not oxidising. Specific gravity 1 estimated

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the decomposition temperature. Contact with incompatible

materials.

Incompatible materials Strong oxidising agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

No adverse effects due to inhalation are expected. Inhalation Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Harmful if swallowed. Ingestion

Material name: DEVCON® R-Flex® Hardener 6928 Version #: 04 Revision date: 27-January-2023 Issue date: 22-May-2019 Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Components Species Test Results

Carbon Black (CAS 1333-86-4)

Acute Oral

LD50 Rat > 8000 mg/kg

Oleic acid (CAS 112-80-1)

<u>Acute</u>

Dermal

LD50 Guinea pig > 3000 mg/kg

Oral

LD50 Rat 74 g/kg

Skin corrosion/irritation Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitisation

Respiratory sensitisation Not a respiratory sensitizer.

Skin sensitisation This product is not expected to cause skin sensitisation.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

Prolonged skin contact may cause temporary irritation.

mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

Carbon Black (CAS 1333-86-4)

A3 Confirmed animal carcinogen with unknown relevance to

humans.

Canada - Manitoba OELs: carcinogenicity

Carbon Black (CAS 1333-86-4) Confirmed animal carcinogen with unknown relevance to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Carbon Black (CAS 1333-86-4) Known To Be Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects May cause damage to organs through prolonged or repeated exposure.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Material name: DEVCON® R-Flex® Hardener
6928 Version #: 04 Revision date: 27-January-2023 Issue date: 22-May-2019

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Country(s) or region Inventory name On inventory (yes/no)*

Taiwan Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

16. Other information

Issue date22-May-2019Revision date27-January-2023

Version No. 04

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: DEVCON® R-Flex® Hardener

SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® R-Flex® Surface Conditioner Powder Premix

Other means of identification

SKU# 6934

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number978-777-1100

Fax E-mail

Emergency telephone

number

800-424-9300

Supplier Not available.

2. Hazard identification

Physical hazardsOxidising solidsCategory 2Health hazardsAcute toxicity, oralCategory 4Skin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2

Specific target organ toxicity following single Category 3 respiratory tract irritation

exposure

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement May intensify fire; oxidiser. Harmful if swallowed. Causes skin irritation. Causes serious eye

irritation. May cause respiratory irritation.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep away from clothing and other combustible materials. Avoid breathing

dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective

gloves/protective clothing/eye protection/face protection.

Response IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell. Rinse mouth. IF ON SKIN:

Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTRE/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use

appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal**

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Ingestion

Chemical name	Common name and synonyms	CAS number	%
TRICHLOROISOCYANURIC AC	CID	87-90-1	60 - 100
Other components below reports	able levels		15 - 40

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

centre or doctor/physician if you feel unwell.

Skin contact If on clothing: Rinse immediately contaminated clothing and skin with plenty of water before

removing clothes. Wash with plenty of soap and water. If skin irritation occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and

delayed

Indication of immediate

medical attention and special treatment needed

General information

vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Take off all contaminated clothing immediately. Contact with combustible material may cause fire. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods General fire hazards Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Greatly increases the burning rate of combustible materials. Containers may explode when heated. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers.

Cool containers exposed to flames with water until well after the fire is out. May intensify fire; oxidiser. Contact with combustible material may cause fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep away from clothing and other combustible materials. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: DEVCON® R-Flex® Surface Conditioner Powder Premix 6934 Version #: 04 Revision date: 27-January-2023 Issue date: 23-May-2019

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Ventilate the contaminated area. Minimise dust generation and accumulation. Wear appropriate protective equipment and clothing during clean-up. This product is miscible in water. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Minimise dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Keep away from heat. Take any precaution to avoid mixing with combustibles. Keep away from clothing and other combustible materials. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage. including any incompatibilities

Store locked up. Keep away from heat. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Do not store near combustible materials. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

No exposure limits noted for ingredient(s).

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Frequent change is advisable.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with Respiratory protection organic vapour cartridge.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Keep from contact with clothing and other combustible materials. Remove and wash contaminated clothing promptly. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Solid. Solid. Physical state

> **Form** Solid. Colour Amber.

Slight. Chlorine. Odour **Odour threshold** Not available. Not available. pН

Melting point/freezing point

246 °C (474.8 °F) estimated

Initial boiling point and boiling

range

Not available.

Not available. Flash point **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

(%)

Flammability limit - upper

Flammability limit - lower

(%)

Not available.

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper Not available.

(%)

Vapour pressure

0.00001 hPa estimated

Vapour densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) 1.2 % @ 25 C

Partition coefficient Not available. (n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 1.16 - 1.90 g/cm3 **Explosive properties** Not explosive.

Oxidising properties May intensify fire; oxidiser.

Specific gravity 1.16 - 1.9

10. Stability and reactivity

Reactivity Greatly increases the burning rate of combustible materials.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat. Avoid temperatures exceeding the decomposition temperature. Contact with incompatible

materials

Incompatible materials Combustible material. Reducing Agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity In high concentrations, vapours are anaesthetic and may cause headache, fatigue, dizziness and

central nervous system effects. Harmful if swallowed.

Components Species Test Results

TRICHLOROISOCYANURIC ACID (CAS 87-90-1)

Acute Dermal

LD50 Rabbit 20000 mg/kg

Material name: DEVCON® R-Flex® Surface Conditioner Powder Premix
6934 Version #: 04 Revision date: 27-January-2023 Issue date: 23-May-2019

Skin corrosion/irritation

Serious eye damage/eye

irritation

Causes skin irritation.

Causes serious eye irritation.

Respiratory or skin sensitisation

Respiratory sensitisation

Not a respiratory sensitizer.

Skin sensitisation

This product is not expected to cause skin sensitisation.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

Not available.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential Mobility in soil

No data available. No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Material name: DEVCON® R-Flex® Surface Conditioner Powder Premix 6934 Version #: 04 Revision date: 27-January-2023 Issue date: 23-May-2019

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

Country(s) or region

International Inventories

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes

Inventory name

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

16. Other information

Taiwan

Issue date23-May-2019Revision date27-January-2023

Version No. 04

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for set a bondling, use processing storage transportation disposal and release.

for safe handling, use, processing, storage, transportation, disposal and release.

Material name: DEVCON® R-Flex® Surface Conditioner Powder Premix
6934 Version #: 04 Revision date: 27-January-2023 Issue date: 23-May-2019

On inventory (yes/no)*

Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® R-Flex® Surface Conditioner

Other means of identification

SKU# 6936

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number978-777-1100

Fax E-mail

Emergency telephone

number

800-424-9300

Supplier Not available.

2. Hazard identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2A

Specific target organ toxicity following single Category 3 narcotic effects

exposure

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or

dizziness.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing mist/vapours. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye

protection/face protection.

Response IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF

INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTRE/doctor if you feel unwell. If eye irritation persists: Get

medical advice/attention. In case of fire: Use appropriate media to extinguish.

Storage Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards Static accumulating flammable liquid can become electrostatically charged even in bonded and

grounded equipment. Sparks may ignite liquid and vapour. May cause flash fire or explosion.

6936 Version #: 03 Revision date: 19-September-2022 Issue date: 23-May-2019

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ACETONE		67-64-1	60 - 100

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

centre or doctor/physician if you feel unwell.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapour.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: DEVCON® R-Flex® Surface Conditioner
6936 Version #: 03 Revision date: 19-September-2022 Issue date: 23-May-2019

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke, Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

250 ppm

8. Exposure controls/personal protection

O	ccu	pational	exposure	limits
_	OUG	pationa	OXPODUIO	

US. ACGIH Threshold Limit Value Components	Туре	Value
ACETONE (CAS 67-64-1)	STEL	500 ppm
(TWA	250 ppm
Canada. Alberta OELs (Occupatio Components	onal Health & Safety Code, Sch Type	nedule 1, Table 2) Value
ACETONE (CAS 67-64-1)	STEL	1800 mg/m3
		750 ppm
	TWA	1200 mg/m3
		500 ppm
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame	•	s for Chemical Substances, Occupational Health and
Components	Туре	Value
ACETONE (CAS 67-64-1)	STEL	500 ppm

TWA

Material name: DEVCON® R-Flex® Surface Conditioner

6936 Version #: 03 Revision date: 19-September-2022 Issue date: 23-May-2019

Components Type		Value	
ACETONE (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Canada. Ontario OELs. (Control o	of Exposure to Biological or C	nemical Agents)	
Components	Туре	Value	
ACETONE (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Canada Quebec OFLs (Ministry	of Labor - Regulation respecti	ng occupational health and safety)	
Gariada: Quoboo GEEG: (illiningi)		- -	
` -	Type	Value	
Components	Type STEL	Value 2380 mg/m3	
Components			
Components		2380 mg/m3	
Components	STEL	2380 mg/m3 1000 ppm	
Components ACETONE (CAS 67-64-1) Canada. Saskatchewan OELs (Oc	STEL	2380 mg/m3 1000 ppm 1190 mg/m3 500 ppm	

ACETONE (CAS 67-64-1) 15 minute 750 ppm 8 hour 500 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
ACETONE (CAS 67-64-1)	25 mg/l	Acetone	Urine	*

^{* -} For sampling details, please see the source document.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapour cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

Respiratory protection Chemical respirator with organic vapour cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Liquid. **Appearance** Liquid. Physical state **Form** Liquid.

Colour Nearly colorless

Odour Fruity.

Odour threshold Not available. Not available. pН

Melting point/freezing point -94.7 °C (-138.46 °F) estimated 56.05 °C (132.89 °F) estimated Initial boiling point and boiling

6936 Version #: 03 Revision date: 19-September-2022 Issue date: 23-May-2019

range

-20.0 °C (-4.0 °F) estimated Flash point

Material name: DEVCON® R-Flex® Surface Conditioner

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

2.6 % estimated

(%)

Flammability limit - upper

(%)

12.8 % estimated

Explosive limit - lower (%)
Explosive limit - upper

er (%) Not available.

er Not available.

(%)

Vapour pressure 309.3 hPa estimated

Vapour densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 465 °C (869 °F) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 0.79 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Flammable IB estimated

Oxidising properties

Percent volatile

Specific gravity

VOC

Not oxidising.

100 % estimated

0.79 estimated

100 % estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

Hazardous polymerisation does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

decomposition temperature. Avoid temperatures exceeding the flash point. Contact with

incompatible materials.

Incompatible materials Acids. Strong oxidising agents.

Hazardous decomposition No hazard

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity

Species Test Results Components

ACETONE (CAS 67-64-1)

Acute Dermal

LD50 Rabbit 20000 mg/kg

Inhalation

LC50 Rat 50.1 mg/l, 8 Hours

Oral

LD50 Rat 5800 mg/kg

Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Respiratory sensitisation Not a respiratory sensitizer.

This product is not expected to cause skin sensitisation. Skin sensitisation

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

ACETONE (CAS 67-64-1) A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

ACETONE (CAS 67-64-1) Not classifiable as a human carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

ACETONE -0.24

Mobility in soil No data available.

The product contains volatile organic compounds which have a photochemical ozone creation Other adverse effects

potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

SDS CANADA

14. Transport information

TDG

UN1090 **UN** number

UN proper shipping name Acetone "Dangerous goods in excepted quantities"

Transport hazard class(es)

3 Class Subsidiary risk П Packing group

Not available. **Environmental hazards**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number

UN proper shipping name Acetone "Dangerous goods in excepted quantities"

Transport hazard class(es)

3 Class Subsidiary risk Ш Packing group **Environmental hazards** Nο **ERG Code** 3H

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN number UN1090

Acetone "Dangerous goods in excepted quantities" **UN proper shipping name**

Transport hazard class(es)

3 **Class** Subsidiary risk Ш Packing group **Environmental hazards**

Marine pollutant No.

EmS F-E, S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code



15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada. Excluded VOCs. Guidelines for Volatile Organic Compounds in Consumer Products. CEPA 1999. Environment Canada, as amended

ACETONE (CAS 67-64-1)

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

6936 Version #: 03 Revision date: 19-September-2022 Issue date: 23-May-2019

Greenhouse Gases

Not listed.

Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)

ACETONE (CAS 67-64-1)

Precursor Control Regulations

ACETONE (CAS 67-64-1) Class B

Inventory name

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

Country(s) or region

International Inventories

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Taiwan Chemical Substance Inventory (TCSI)

16. Other information

Taiwan

Issue date23-May-2019Revision date19-September-2022

Version No. 03

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

6936 Version #: 03 Revision date: 19-September-2022 Issue date: 23-May-2019

On inventory (yes/no)*

Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).