# SAFETY DATA SHEET

## 1. Identification

Product identifier DEVCON® Flexane® 80 Liquid Resin

Other means of identification

**SKU#** 0318N

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers

Address 30 Endicott Street

Danvers, MA 01923

**United States** 

**Telephone** Customer Service 978-777-1100

Website www.itwperformancepolymers.com

E-mail Not available.

Contact person EHS Department

Emergency phone number Chemtrec 800-424-9300

International 703-527-3887

# 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, inhalation Category 4

Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2
Sensitization, respiratory Category 1
Sensitization, skin Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful

if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause

respiratory irritation.

**Precautionary statement** 

**Prevention** Avoid breathing mist/vapors. Wash thoroughly after handling. Use only outdoors or in a

well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves. In case of inadequate ventilation wear

respiratory protection.

Response If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable

for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Take off

contaminated clothing and wash it before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Material name: DEVCON® Flexane® 80 Liquid Resin

20 Liquid Doois

**Disposal** 

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
3-ISOCYANATOMETHYL-3,5,5 METHYLCYCLOHEXYL ISOCYANATE	5-TRI	4098-71-9	20 - 40
Other components below report	table levels		60 - 80

## 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

> artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a poison center or

doctor/physician.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eve contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim

vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

under observation. Symptoms may be delayed.

**General information** If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash

and pain. May cause an allergic skin reaction. Dermatitis. Rash.

contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Foam. Powder. Carbon dioxide (CO2).

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters During fire, gases hazardous to health may be formed.

Fire fighting

equipment/instructions

Specific methods General fire hazards Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

No unusual fire or explosion hazards noted.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: DEVCON® Flexane® 80 Liquid Resin

SDS US 0318N Version #: 02 Revision date: 11-24-2021 Issue date: 10-31-2021

# Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

## **Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

## Precautions for safe handling

Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### **US. ACGIH Threshold Limit Values**

Components	Туре	Value
3-ISOCYANATOMETHYL-3 ,5,5-TRIMETHYLCYCLOHE XYL ISOCYANATE (CAS 4098-71-9)	TWA	0.005 ppm
US. NIOSH: Pocket Guide to Chemical F	łazards	
Components	Туре	Value

3-ISOCYANATOMETHYL-3 ,5,5-TRIMETHYLCYCLOHE XYL ISOCYANATE (CAS 4098-71-9)

0.02 ppm
TWA 0.045 mg/m3
0.005 ppm

0.18 mg/m3

#### **Biological limit values**

No biological exposure limits noted for the ingredient(s).

## **Exposure guidelines**

#### US - California OELs: Skin designation

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEX Can be absorbed through the skin.

**STEL** 

YL ISOCYANATE (CAS 4098-71-9)

#### **US - Minnesota Haz Subs: Skin designation applies**

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEX Skin designation applies.

YL ISOCYANATE (CAS 4098-71-9)

## **US - Tennessee OELs: Skin designation**

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEX Can be absorbed through the skin.

YL ISOCYANATE (CAS 4098-71-9)

#### US NIOSH Pocket Guide to Chemical Hazards: Skin designation

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEX Can be absorbed through the skin.

YL ISOCYANATE (CAS 4098-71-9)

# Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally adequate. Provide eyewash station and safety shower.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Chemical respirator with organic vapor cartridge and full facepiece.

Material name: DEVCON® Flexane® 80 Liquid Resin

onomical respirator with erganic raper santiage and rain acceptage.

Skin protection

Wear appropriate chemical resistant gloves. Hand protection Wear appropriate chemical resistant clothing. Other

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

# 9. Physical and chemical properties

Liquid. **Appearance** Physical state Liquid. Liquid. **Form** Color Colorless. Odor Slight.

**Odor threshold** Not available. 7 @ 5% solution На

-76 °F (-60 °C) estimated Melting point/freezing point

Initial boiling point and boiling

range

Not available.

325.4 °F (163.0 °C) estimated Flash point

**Evaporation rate** Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

0.0004 hPa estimated Vapor pressure

Not available. Vapor density Not available. Relative density

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

806 °F (430 °C) estimated **Auto-ignition temperature** 

**Decomposition temperature** Not available. Not available. **Viscosity** 

Other information

1.02 g/cm3 estimated Density

**Explosive properties** Not explosive.

Flammability class Combustible IIIB estimated

Not oxidizing. **Oxidizing properties** Specific gravity 1.02 estimated

#### 10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous No dangerous reaction known under conditions of normal use.

reactions

Conditions to avoid Avoid temperatures exceeding the decomposition temperature. Contact with incompatible

materials.

Incompatible materials

Alcohols. Amides. Amines. Phenols.

Hazardous decomposition

products

No hazardous decomposition products are known.

# 11. Toxicological information

#### Information on likely routes of exposure

Inhalation Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Skin contact** Causes skin irritation. May cause an allergic skin reaction.

**Eye contact** Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness

and pain. May cause an allergic skin reaction. Dermatitis. Rash.

#### Information on toxicological effects

Acute toxicity Harmful if inhaled.

Components Species Test Results

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE (CAS 4098-71-9)

<u>Acute</u>

**Dermal** 

LD50 Rat 1060 mg/kg

Inhalation

LC50 Rat 0.123 mg/l, 4 Hours

Oral

LD50 Rat > 1000 mg/kg

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

**Respiratory sensitization** May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity - Not classified.

repeated exposure
Aspiration hazard

Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful.

# 12. Ecological information

**Ecotoxicity**The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Material name: DEVCON® Flexane® 80 Liquid Resin

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

Not established.

# 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLO % 1.0

HEXYL ISOCYANATE (CAS 4098-71-9)

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLO Listed.

HEXYL ISOCYANATE (CAS 4098-71-9)

**Toxic Substances Control Act (TSCA)** 

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

ISOPHORONE DIISOCYANATE (CAS 4098-71-9)

500 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name **CAS** number Reportable Threshold Threshold **Threshold** quantity planning quantity planning quantity, planning quantity, (pounds) (pounds) lower value upper value (pounds) (pounds)

3-ISOCYANATOMET HYL-3,5,5-TRIMETHY 4098-71-9

500

500

LCYCLOHEXYL **ISOCYANATE** 

SARA 311/312 Hazardous Yes

chemical

Material name: DEVCON® Flexane® 80 Liquid Resin

Classified hazard categories

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

## SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
3-ISOCYANATOMETHYL-3,5,5-TRIMETHYL	CYCL 4098-71-9	20 - 40	
OHEXYL ISOCYANATE			

## Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

## **US** state regulations

## **California Proposition 65**



WARNING: This product can expose you to chemicals including FURAN, which is known to the State of

California to cause cancer. For more information go to www.P65Warnings.ca.gov.

# California Proposition 65 - CRT: Listed date/Carcinogenic substance

Acetaldehyde (CAS 75-07-0) Listed: April 1, 1988 FURAN (CAS 110-00-9) Listed: October 1, 1993 Propylene Oxide (CAS 75-56-9) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE (CAS 4098-71-9)

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

## 16. Other information, including date of preparation or last revision

10-31-2021 Issue date 11-24-2021 **Revision date** 

Version # 02

**HMIS®** ratings Health: 3

Flammability: 1 Physical hazard: 0

0318N Version #: 02 Revision date: 11-24-2021 Issue date: 10-31-2021

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

NFPA ratings Health: 3

Flammability: 1 Instability: 0

**Disclaimer** ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information Hazard(s) identification: Hazard statement

Hazard(s) identification: Response Hazard(s) identification: GHS Symbols

First-aid measures: Inhalation

Toxicological information: Acute toxicity Toxicological information: Inhalation

**GHS: Classification** 

0318N Version #: 02 Revision date: 11-24-2021 Issue date: 10-31-2021 8 / 8

# SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® Flexane® 80 Liquid Curing Agent

Other means of identification

SKU# 6922N1

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers

Address 30 Endicott Street

Danvers, MA 01923 United States

**Telephone** Customer Service 978-777-1100

Website www.itwperformancepolymers.com

E-mail Not available.

Contact person EHS Department

Emergency phone number Chemtrec 800-424-9300

International 703-527-3887

# 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Serious eye damage/eye irritation Category 2A
Specific target organ toxicity, repeated
exposure
Category 2

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Harmful if swallowed. Causes serious eye irritation. May cause damage to organs through

prolonged or repeated exposure.

**Precautionary statement** 

**Prevention** Do not breathe mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when

using this product. Wear eye protection/face protection.

**Response** If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If in eyes: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention if you feel unwell. If eye irritation persists: Get

medical advice/attention.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

**Supplemental information**1.44% of the mixture consists of component(s) of unknown acute dermal toxicity. 49.67% of the mixture consists of component(s) of unknown acute inhalation toxicity. 1.44% of the mixture

consists of component(s) of unknown acute hazards to the aquatic environment. 1.44% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

# 3. Composition/information on ingredients

#### **Mixtures**

Ingestion

Chemical name	Common name and synonyms	CAS number	%
Diethyltoluenediamine		68479-98-1	40 - 60
Carbon Black		1333-86-4	1 - 2.5
Other components below re	portable levels		40 - 60

## 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

**General information** 

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from

the chemical Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling

Do not breathe mist/vapors. Do not taste or swallow. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

 Components
 Type
 Value

 Carbon Black (CAS 1333-86-4)
 PEL
 3.5 mg/m3

**US. ACGIH Threshold Limit Values** 

ComponentsTypeValueFormCarbon Black (CAS<br/>1333-86-4)TWA3 mg/m3Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

ComponentsTypeValueCarbon Black (CAS<br/>1333-86-4)TWA0.1 mg/m3

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

#### 9. Physical and chemical properties

Appearance Liquid.
Physical state Liquid.
Form Liquid.

Color Not available.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point 312.8 °F (156.0 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

------

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

0.00009 hPa estimated Vapor pressure

Vapor density Not available. Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. Not available. **Viscosity** 

Other information

1.03 g/cm3 estimated **Density** 

Not explosive. **Explosive properties** 

Flammability class Combustible IIIB estimated

Oxidizing properties Not oxidizing. Specific gravity 1.03 estimated

# 10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the decomposition temperature. Contact with incompatible

materials.

Incompatible materials Strong oxidizing agents.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

# 11. Toxicological information

## Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Causes serious eye irritation. Eye contact

Harmful if swallowed. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

#### Information on toxicological effects

Harmful if swallowed. **Acute toxicity** 

Components **Species Test Results** 

Carbon Black (CAS 1333-86-4)

**Acute** Oral

LD50 Rat > 8000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

6922N1 Version #: 01 Issue date: 11-24-2021

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Carbon Black (CAS 1333-86-4) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful. May cause damage to organs through prolonged or

repeated exposure.

12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available. Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication US federal regulations

Standard, 29 CFR 1910.1200.

**Toxic Substances Control Act (TSCA)** 

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Diethyltoluenediamine (CAS 68479-98-1) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Material name: DEVCON® Flexane® 80 Liquid Curing Agent

SDS US 5/7 6922N1 Version #: 01 Issue date: 11-24-2021

## SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

## SARA 302 Extremely hazardous substance

SARA 311/312 Hazardous

Yes

chemical

Classified hazard Acute toxicity (any route of exposure) Serious eye damage or eye irritation categories

Specific target organ toxicity (single or repeated exposure)

## SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### **US** state regulations

#### **California Proposition 65**



WARNING: This product can expose you to Carbon Black, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

## California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon Black (CAS 1333-86-4) Listed: February 21, 2003

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Carbon Black (CAS 1333-86-4)

Diethyltoluenediamine (CAS 68479-98-1)

#### **International Inventories**

Country(s) or region	Inventory name On inventor	y (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
•	ents of this product comply with the inventory requirements administered by the governing country(s components of the product are not listed or exempt from listing on the inventory administered by the	,

## 16. Other information, including date of preparation or last revision

11-24-2021 Issue date

Version # 01

country(s).

Material name: DEVCON® Flexane® 80 Liquid Curing Agent SDS US 6/7 HMIS® ratings Health: 2\*

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 1
Instability: 0

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: DEVCON® Flexane® 80 Liquid Curing Agent

6922N1 Version #: 01 Issue date: 11-24-2021 7 /