SAFETY DATA SHEET

1. Identification

Product identifier	DEVCON® Cleaner Bl	end 300	
Other means of identification			
SKU#	19510		
Recommended use	Not available.		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplie	er/Distributor information		
Manufacturer			
Company name	ITW Performance Polymers		
Address	30 Endicott Street		
	Danvers, MA 01923		
	United States		
Telephone	Customer Service	978-777-1100	
Website	www.itwperformancepo	ymers.com	
E-mail	Not available.		
Contact person	EHS Department		
Emergency phone number	Chemtrec	800-424-9300	
C F :	International	703-527-3887	

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
	Reproductive toxicity	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Flammable liquid and vapor. May cause an allergic skin reaction. Causes serious eye irritation. May damage fertility or the unborn child.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist/vapors. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

3. Composition/information on ingredients

None.

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Propylene glycol monomethyl ethe	r	107-98-2	40 - 60
1-methoxy-2-acetoxypropane	1-Methoxy-2-propylacetate	108-65-6	20 - 40
(D)-LIMONENE		5989-27-5	2.5 - 10
Other components below reportable levels			10 - 20

4. First-aid measures Inhalation Move to fresh air. Call a physician if symptoms develop or persist. Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact eczema or other skin disorders: Seek medical attention and take along these instructions. Immediately flush eves with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Ingestion Rinse mouth. Get medical attention if symptoms occur. Headache. Dizziness. Nausea, vomiting. Diarrhea. Severe eye irritation. Symptoms may include Most important symptoms/effects, acute and stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash. delayed Indication of immediate Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an medical attention and special ambulance. Continue flushing during transport to hospital. Keep victim under observation. treatment needed Symptoms may be delayed. Take off all contaminated clothing immediately. IF exposed or concerned: Get medical **General information** advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
	spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
	For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. ACGIH Threshold Limit Valu Components	es (TLV) Type	Value	
Propylene glycol monomethyl ether (CAS 107-98-2)	STEL	100 ppm	
	TWA	50 ppm	
US. NIOSH: Pocket Guide to Che Components	emical Hazards Recommended Type	Exposure Limits (REL) Value	
Propylene glycol	STEL	540 mg/m3	
monomethyl ether (CAS 107-98-2)			
		150 ppm	
monomethyl ether (CAS 107-98-2)	TWA	150 ppm 360 mg/m3	

Components	Туре	Value
(D)-LIMONENE (CAS 5989-27-5)	TWA	165.5 mg/m3
		30 ppm
1-methoxy-2-acetoxypropan e (CAS 108-65-6)	TWA	50 ppm
Biological limit values	No biological exposure limits n	oted for the ingredient(s).
Exposure guidelines		
US - California OELs: Skin c	lesignation	
1-methoxy-2-acetoxyprop Propylene glycol monome	oane (CAS 108-65-6) ethyl ether (CAS 107-98-2)	Can be absorbed through the skin. Can be absorbed through the skin.
Appropriate engineering controls	Ventilation rates should be ma exhaust ventilation, or other er	cal exhaust ventilation. Good general ventilation should be used. tched to conditions. If applicable, use process enclosures, local igineering controls to maintain airborne levels below recommended hits have not been established, maintain airborne levels to an vash station.
ndividual protection measures, Eye/face protection		quipment ic vapor cartridge and full facepiece.
Skin protection		
Hand protection	Wear appropriate chemical resistant gloves.	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.	
Respiratory protection	Chemical respirator with organ	ic vapor cartridge and full facepiece.
Thermal hazards	Wear appropriate thermal prot	ective clothing, when necessary.
General hygiene considerations	personal hygiene measures, s drinking, and/or smoking. Rou	nce requirements. When using do not smoke. Always observe good uch as washing after handling the material and before eating, tinely wash work clothing and protective equipment to remove vork clothing should not be allowed out of the workplace.

E.

Appearance	Liquid.	
Physical state	Liquid.	
Form	Liquid.	
Color	Amber	
Odor	Ether-like.	
Odor threshold	Not available.	
рН	Not available.	
Melting point/freezing point	-139.9 °F (-95.5 °C) estimated	
Initial boiling point and boiling range	246.2 °F (119 °C) estimated	
Flash point	89.6 °F (32.0 °C) estimated	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not applicable.	
Upper/lower flammability or exp	losive limits	
Explosive limit - lower (%)	Not available.	
Explosive limit - upper (%)	6.1 % estimated	
Vapor pressure	12 mm Hg @ 68 F 11.67 hPa estimated	
Vapor density	Not available.	
Relative density	Not available.	
Solubility(ies)		
Solubility (water)	Not available.	

Not available.
458.6 °F (237 °C) estimated
Not available.
Not available.
0.91 g/cm3 estimated
Not explosive.
Flammable IC estimated
Not oxidizing.
0.91 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure		
Inhalation	Prolonged inhalation may be harmful.	
Skin contact	May cause an allergic skin reaction.	
Eye contact	Causes serious eye irritation.	
Ingestion	Expected to be a low ingestion hazard.	
Symptoms related to the physical, chemical and toxicological characteristics	Headache. Dizziness. Nausea, vomiting. Diarrhea. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.	

Information on toxicological effects


Acute toxicity	Not known.	
Components	Species	Test Results
(D)-LIMONENE (CAS 5989-27-	-5)	
Acute		
Dermal		
LD50	Rabbit	> 5 g/kg
Oral		
LD50	Rat	5 g/kg
Propylene glycol monomethyl e	ther (CAS 107-98-2)	
Acute		
Dermal		
LD50	Rabbit	13 - 14 g/kg
Inhalation		
LC50	Rat	54.600000000000014 mg/l, 4 Hours
Oral		
LD50	Rat	5.71 g/kg
Skin corrosion/irritation	Prolonged skin contact may cause tempora	ry irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.	

UN proper shipping name	Flammable liquids, n.o.s. (Propylene glycol monomethyl ether), Limited Quantity			
UN number	UN1993			
DOT				
14. Transport information				
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.			
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).			
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F The waste code should be assigned in discussion between the user, the producer and the waste disposal company.			
Local disposal regulations	Dispose in accordance with all applicable regulations.			
Disposal instructions	Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.			
13. Disposal consideration	ns			
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.			
Mobility in soil	No data available.			
(D)-LIMONENE Propylene glycol monomethyl	4.57 ether -0.49			
Partition coefficient n-octan				
Bioaccumulative potential				
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.			
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.			
12. Ecological information	l			
Chronic effects	Prolonged inhalation may be harmful.			
Aspiration hazard	Not an aspiration hazard.			
Specific target organ toxicity - repeated exposure	Not classified.			
single exposure				
Reproductive toxicity Specific target organ toxicity -	May damage fertility or the unborn child. Not classified.			
Not listed.				
Not listed. US. National Toxicology Pro	gram (NTP) Report on Carcinogens			
(D)-LIMONENE (CAS 598 OSHA Specifically Regulated	39-27-5) 3 Not classifiable as to carcinogenicity to humans. d Substances (29 CFR 1910.1001-1053)			
IARC Monographs. Overall E	Evaluation of Carcinogenicity			
Carcinogenicity	Not classifiable as to carcinogenicity to humans.			
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.			
Skin sensitization	May cause an allergic skin reaction.			
				

UN1993
Flammable liquids, n.o.s. (Propylene glycol monomethyl ether), Limited Quantity
3
-
3
III

Environmental hazards Marine pollutant Special precautions for user Special provisions Packaging exceptions Packaging non bulk Packaging bulk	No. Read safety instructions, SDS and emergency procedures before handling. B1, B52, IB3, T4, TP1, TP29 150 203 242
UN number	UN1993
UN proper shipping name	Flammable liquid, n.o.s. (Propylene glycol monomethyl ether), Limited Quantity
Transport hazard class(es)	······································
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
ERG Code	3L
	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Propylene glycol monomethyl ether), Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, <u>S-E</u>
	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

the IBC Code



15. Regulatory information

15. Regulatory informatio	n
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
Toxic Substances Control A	Act (TSCA)
TSCA Section 12(b) Exp	port Notification (40 CFR 707, Subpt. D)
Not regulated.	
CERCLA Hazardous Substa	Ince List (40 CFR 302.4)
Propylene glycol monome SARA 304 Emergency relea	ethyl ether (CAS 107-98-2) Listed. se notification
Not regulated. OSHA Specifically Regulate	ed Substances (29 CFR 1910.1001-1053)
Not listed.	
Superfund Amendments and Re SARA 302 Extremely hazard	eauthorization Act of 1986 (SARA) dous substance
Not listed.	
SARA 311/312 Hazardous chemical	Yes
Classified hazard categories	Flammable (gases, aerosols, liquids, or solids) Serious eye damage or eye irritation Respiratory or skin sensitization Reproductive toxicity Hazard not otherwise classified (HNOC)
SARA 313 (TRI reporting) Not regulated.	
Other federal regulations	
Clean Air Act (CAA) Section	n 112 Hazardous Air Pollutants (HAPs) List
Not regulated. Clean Air Act (CAA) Section Not regulated.	112(r) Accidental Release Prevention (40 CFR 68.130)
Safe Drinking Water Act (SDWA)	Not regulated.
US state regulations	
US. California. Candidate C (a))	hemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.
Propylene glycol monome	ethyl ether (CAS 107-98-2)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Country(s) or region

United States & Puerto Rico

Inventory name

Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

06-04-2019 **Issue date** 07-28-2023 **Revision date** Version # 05 Health: 2* **HMIS®** ratings Flammability: 3 Physical hazard: 0 Health: 2 **NFPA** ratings Flammability: 3 Instability: 0 ITW Performance Polymers cannot anticipate all conditions under which this information and its Disclaimer product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

16. Other information, including date of preparation or last revision