# SAFETY DATA SHEET

1. Identification				
Product identifier	PLEXUS® MA2290 Adhesive	9		
Other means of identification				
SKU#	0658	0658		
Recommended use	Not available.			
Recommended restrictions	None known.			
Manufacturer/Importer/Suppli Manufacturer	er/Distributor information			
Company name Address	ITW Performance Polymers 30 Endicott Street Danvers, MA 01923 United States	30 Endicott Street Danvers, MA 01923		
Telephone	Customer Service	978-777-1100		
Website	www.itwperformancepolymers	s.com		
E-mail	Not available.			
Contact person	EHS Department			
Emergency phone number		800-424-9300 703-527-3887		
		103-321-3001		
2. Hazard(s) identificati	on			
Physical hazards	Flammable liquids		Category 2	
Health hazards	Skin corrosion/irritation		Category 2	
	Serious eye damage/eye irrita	ation	Category 1	
	Sensitization, skin		Category 1	
	Specific target organ toxicity,	single exposure	Category 3 respiratory tract irritation	
Environmental hazards	Not classified.			
OSHA defined hazards	Not classified.			
Label elements				
		!>		
Signal word	Danger	Danger		
Hazard statement		Highly flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation.		
Precautionary statement				
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face			

protection.

Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
Supplemental information	None.

# 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Methyl Methacrylate		80-62-6	40 - 60
Benzyl 3-isobutyryloxy-1-isopropyl-2,2-dim ethylpropyl Phthalate		16883-83-3	2.5 - 10
METHACRYLIC ACID		79-41-4	2.5 - 10
Paraffin Wax		8002-74-2	1 - 2.5
Other components below reportable	e levels		40 - 60

### 4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may

be used for small fires only.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

and precautions for firefightersFire fightingIn case of fire aequipment/instructionsdo so without r	
equipment/instructions do so without r	breathing apparatus and full protective clothing must be worn in case of fire.
	nd/or explosion do not breathe fumes. Move containers from fire area if you can sk.
Specific methods Use standard f	refighting procedures and consider the hazards of other involved materials.
General fire hazards Highly flammal	le liquid and vapor.
6. Accidental release measures	

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch
damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.
Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

# 7. Handling and storage

Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get this material in contact with eyes. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
	For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 P Components	ermissible Exposure	e Limits (PEL) for A Type	ir Contaminants	(29 CFR 1910.10) Value	00)
Methyl Methacrylate (C 80-62-6)	AS	PEL		410 mg/m3	
				100 ppm	
US. ACGIH Threshold	Limit Values (TLV)				_
Components		Туре		Value	Form
METHACRYLIC ACID ( 79-41-4)	CAS	TWA		20 ppm	
Methyl Methacrylate (C 80-62-6)	AS	STEL		100 ppm	
		TWA		50 ppm	
Paraffin Wax (CAS 8002-74-2)		TWA		2 mg/m3	Fume.
NIOSH. Immediately D	angerous to Life or	Health (IDLH) Value	es, as amended		
Components		Туре		Value	
Methyl Methacrylate (C 80-62-6)	AS	IDLH		1.7 %	
				1000 ppm	
US. NIOSH: Pocket G	uide to Chemical Ha		ed Exposure Lim	. ,	<b>F</b>
Components		Туре		Value	Form
METHACRYLIC ACID ( 79-41-4)	CAS	TWA		70 mg/m3	
				20 ppm	
Methyl Methacrylate (C 80-62-6)	AS	TWA		410 mg/m3	
				100 ppm	_
Paraffin Wax (CAS 8002-74-2)		TWA		2 mg/m3	Fume.
Biological limit values	No biological	exposure limits note	d for the ingredier	nt(s).	
Appropriate engineering controls	Ventilation ra exhaust vent recommende	tes should be matche ilation, or other engin	ed to conditions. I neering controls to exposure limits ha	f applicable, use p maintain airborne ive not been estab	lished, maintain airborne
Individual protection meas Eye/face protection		onal protective equi	•	d full facepiece.	
Skin protection Hand protection	Wear approp	riate chemical resista	ant gloves.		
Other	Wear approp	riate chemical resista	ant clothing.		
Respiratory protection		pirator with organic v	•	d full facepiece.	
Thermal hazards		riate thermal protecti			

General hygiene considerations When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical	properties
Appearance	Paste.
Physical state	Liquid.
Form	Paste.
Color	Tan.
Odor	Not available.
Odor threshold	Not available.
рН	> 5 - < 6
Melting point/freezing point	-54.4 °F (-48 °C) estimated
Initial boiling point and boiling range	212.9 °F (100.5 °C) estimated
Flash point	50.0 °F (10.0 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp Explosive limit - lower (%)	Iosive limits 2.1 % estimated
Explosive limit - upper (%)	8.2 % estimated
Vapor pressure	45.13 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies) Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	815 °F (435 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.94 g/cm3 estimated
Explosive properties	Not explosive.
Flammability class	Flammable IB estimated
Oxidizing properties	Not oxidizing.
Specific gravity	0.94 estimated

# 10. Stability and reactivity

-	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Peroxides.
Hazardous decomposition products	No hazardous decomposition products are known.

## 11. Toxicological information

#### Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye damage.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

#### Information on toxicological effects

Acute toxicity	Not known.	
Components	Species	Test Results
METHACRYLIC ACID (CAS	S 79-41-4)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	500 mg/kg
Inhalation		
LC50	Rat	7.1 mg/l, 4 Hours
Oral		
LD50	Rat	1060 mg/kg

Methyl Methacrylate (CAS 80-62-6)

Methyl Methacrylate (CAS 80-62-6	5)	
<u>Acute</u>		
Oral		
LD50	Rat	7800 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Respiratory or skin sensitizatior	1	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any compo mutagenic or genotoxic.	nents present at greater than 0.1% are
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
IARC Monographs. Overall I	Evaluation of Carcinogenicity	
Not listed.		
OSHA Specifically Regulate	d Substances (29 CFR 1910.1001-1053)	
Not listed.		
	gram (NTP) Report on Carcinogens	
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive	or developmental effects.
Specific target organ toxicity -	May cause respiratory irritation.	
single exposure		
single exposure Specific target organ toxicity - repeated exposure	Not classified.	
Specific target organ toxicity -	Not classified. Not an aspiration hazard.	

12. Ecological information			
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.		
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.		
Bioaccumulative potential			
Partition coefficient n-octanol / water (log Kow)			
METHACRYLIC ACID	0.93		
Methyl Methacrylate	1.38		
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
13. Disposal considerations			


Disposal instructions	Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerat sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.	
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.	

# 14. Transport information

DOT	
UN number	UN1133
UN proper shipping name	Adhesives, containing a flammable liquid, Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Label(s)	3
Packing group	Ш
Environmental hazards	
Marine pollutant	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	149, B52, IB2, T4, TP1, TP8
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242
ΙΑΤΑ	
UN number	UN1133
UN proper shipping name	Adhesives containing flammable liquid, Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Packing group	Ш
Environmental hazards	No.
ERG Code	3L
	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.

Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1133
UN proper shipping name	ADHESIVES containing flammable liquid, Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not established.
Annex II of MARPOL 73/78 and	
the IBC Code	

DOT; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### **Toxic Substances Control Act (TSCA)**

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

# SARA 311/312 Hazardous Yes chemical

Classified hazard categories	Flammable (gases, aerosols, liquids, or solids) Skin corrosion or irritation Serious eye damage or eye irritation Respiratory or skin sensitization Specific target organ toxicity (single or repeated exposure) Hazard not otherwise classified (HNOC)			
SARA 313 (TRI reporting) Chemical name		CAS number	% by wt.	
Ethylene Glycol Methyl Methacrylate		107-21-1 80-62-6	0.1 - 1 40 - 60	
Other federal regulations				
Clean Air Act (CAA) Sectior	n 112 Hazardous Ai	r Pollutants (HAPs) List		
Not regulated. Clean Air Act (CAA) Sectior Not regulated.	n 112(r) Accidental	Release Prevention (40 CF	FR 68.130)	
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations California Proposition 65				
		se you to Ethylene Glycol, v eproductive harm. For more		
International Inventories				
Country(s) or region	Inventory name			On inventory (yes/no)*
Australia	Australian Invento	ry of Industrial Chemicals ( <i>i</i>	AICIS)	No
Canada	Domestic Substances List (DSL) Yes			
Canada	Non-Domestic Substances List (NDSL) No			
China	Inventory of Existing Chemical Substances in China (IECSC) No			
Europe	European Invento Substances (EIN	ry of Existing Commercial C ECS)	Chemical	No
Europe	European List of I	Notified Chemical Substance	es (ELINCS)	No
Japan	Inventory of Exist	ng and New Chemical Subs	stances (ENCS)	No
Korea	Existing Chemica	s List (ECL)		No
New Zealand	New Zealand Inve	entory		No
Philippines	Philippine Invento (PICCS)	ry of Chemicals and Chemi	cal Substances	No
Taiwan	Taiwan Chemical	Substance Inventory (TCSI)	)	No
United States & Puerto Rico	Toxic Substances	Control Act (TSCA) Invento	ry	Yes
*A "Yes" indicates that all compo A "No" indicates that one or mor governing country(s).				

# 16. Other information, including date of preparation or last revision

Issue date	08-28-2020
Revision date	01-09-2025
Version #	05
HMIS® ratings	Health: 2 Flammability: 3 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 3 Instability: 0

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release. This document has undergone significant changes and should be reviewed in its entirety.

**Revision information** 

# SAFETY DATA SHEET

1. Identification			
Product identifier	PLEXUS® MA2230/2245/2290 EU Blu	e Activator	
Other means of identification SKU#	0691		
Recommended use	Not available.		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplie	/Distributor information		
Manufacturer			
Company name Address	ITW Performance Polymers 30 Endicott Street Danvers, MA 01923 United States		
Telephone	Customer Service 978-777-	1100	
Website	www.itwperformancepolymers.com		
E-mail Contact person	Not available. EHS Department		
Emergency phone number	Chemtrec 800-424-	9300	
- J / P	International 703-527-		
2. Hazard(s) identificatio	n		
Physical hazards	Not classified.		
Health hazards	Skin corrosion/irritation	Category 2	
	Serious eye damage/eye irritation	Category 2	
	Sensitization, skin	Category 1	
	Specific target organ toxicity, single exp	oosure Category 3 respiratory tract irritation	
Environmental hazards	Not classified.		
OSHA defined hazards	Not classified.		
Label elements			
Signal word	Warning		
Hazard statement	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation.		
Precautionary statement Prevention	Avoid breathing mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves.		
Response	If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.		
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up.		
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.		

Supplemental information

#### 3. Composition/information on ingredients

None.

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Benzyl 3-isobutyryloxy-1-isopropyl-2,2-dim ethylpropyl Phthalate		16883-83-3	20 - 40
DIBUTYL MALEATE		105-76-0	20 - 40
Dibenzoyl Peroxide		94-36-0	2.5 - 10
ISODECYL BENZOATE		131298-44-7	2.5 - 10
Oxirane, Methyl-, Polymer With Oxirane, Monobutyl Ether		9038-95-3	1 - 2.5
Other components below reportable	levels		10 - 20

#### 4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	

5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.			
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.			
	Never return spills to original containe SDS.	ers for re-use. For waste disposal, see section 13 of the		
Environmental precautions	Avoid discharge into drains, water co	urses or onto the ground.		
7. Handling and storage				
Precautions for safe handling	Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.			
Conditions for safe storage, including any incompatibilities	Store locked up. Store in tightly close Section 10 of the SDS).	d container. Store away from incompatible materials (see		
8. Exposure controls/pers	sonal protection			
	the only constituents of the product wh nstituents have no known exposure lim	nich have a PEL, TLV or other recommended exposure its.		
US. OSHA Table Z-1 Permiss Components	OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000) ponents Type Value			
Dibenzoyl Peroxide (CAS 94-36-0)	PEL	5 mg/m3		
US. ACGIH Threshold Limit	Values (TLV)			
Components	Туре	Value		
Dibenzoyl Peroxide (CAS 94-36-0)	TWA 5 mg/m3			
NIOSH. Immediately Danger Components	ous to Life or Health (IDLH) Values, a Type	as amended Value		
Dibenzoyl Peroxide (CAS 94-36-0)	IDLH	1500 mg/m3		
US. NIOSH: Pocket Guide to Components	US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)			
Dibenzoyl Peroxide (CAS 94-36-0)	TWA	5 mg/m3		
Biological limit values	No biological exposure limits noted for	or the ingredient(s).		
Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.			
Individual protection measures, Eye/face protection	such as personal protective equipm Chemical respirator with organic vapo			
Skin protection Hand protection	Wear appropriate chemical resistant	gloves.		
Other	Wear appropriate chemical resistant	clothing.		
Respiratory protection	Chemical respirator with organic vapor cartridge and full facepiece.			
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.			

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties	
Appearance	Liquid.
Physical state	Liquid.
Form	Liquid.
Color	Blue.
Odor	Mild.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	217.4 °F (103 °C) estimated
Initial boiling point and boiling range	Not available.
Flash point	285.8 °F (141.0 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp Explosive limit - lower (%)	losive limits Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.5 mm Hg @ 68 F -0.01 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies) Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	176 °F (80 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	1.17 g/cm3 estimated
Explosive properties	Not explosive.
Flammability class	Combustible IIIB estimated
Oxidizing properties	Not oxidizing.
Specific gravity	1.17 estimated

### 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Acids. Alcohols. Amines.
Hazardous decomposition products	No hazardous decomposition products are known.

# 11. Toxicological information

0			
Information on likely routes of e Inhalation	-	atory system. Prolonged inhalation may be harmful.	
Skin contact	Causes skin irritation. May cause an allergic skin reaction.		
Eye contact	Causes serious eye irritation.		
Ingestion	Expected to be a low ingestion hazard.		
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.		
Information on toxicological effe	ects		
Acute toxicity	Not known.		
Components	Species	Test Results	
Dibenzoyl Peroxide (CAS 94-36-0)	)		
<u>Acute</u>			
Oral			
LD50	Rat	7710 mg/kg	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye rritation	Causes serious eye irritation.		
Respiratory or skin sensitizatior Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	May cause an allergic skin react	ion.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	Not classifiable as to carcinogen	icity to humans.	
Not listed. OSHA Specifically Regulate	Evaluation of Carcinogenicity d Substances (29 CFR 1910.100 <sup>7</sup>	1-1053)	
Not listed. US. National Toxicology Pro Not listed.	gram (NTP) Report on Carcinog	ens	
Reproductive toxicity	This product is not expected to c	ause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	May cause respiratory irritation.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Prolonged inhalation may be har	mful.	
12. Ecological informatio	n		
Ecotoxicity		environmentally hazardous. However, this does not exclude the spills can have a harmful or damaging effect on the environment	
Persistence and degradability	No data is available on the degra	adability of any ingredients in the mixture.	
Bioaccumulative potential			
Partition coefficient n-octan Dibenzoyl Peroxide	ol / water (log Kow)	3.46	
Mobility in soil	No data available.		
Other adverse effects		effects (e.g. ozone depletion, photochemical ozone creation lobal warming potential) are expected from this component.	

13. Disposal considerations		
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.	
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.	

# 14. Transport information

#### DOT

Not regulated as dangerous goods.

#### IATA

Not regulated as dangerous goods.

#### IMDG

Not regulated as dangerous goods.

#### Transport in bulk according to Not established. Annex II of MARPOL 73/78 and the IBC Code

#### 15. Regulatory information

**US** federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### **Toxic Substances Control Act (TSCA)**

Not regulated.		
CERCLA Hazardous Substa	ance List (40 CFR 302.4)	
Not listed.		
SARA 304 Emergency relea	se notification	
Not regulated.		
	ed Substances (29 CFR 1910.1001-1053)	
Not listed.		
SARA 302 Extremely hazar	eauthorization Act of 1986 (SARA) dous substance	
Not listed.		
SARA 311/312 Hazardous chemical	Yes	
Classified hazard	Skin corrosion or irritation	
categories	Serious eye damage or eye irritation	
	Respiratory or skin sensitization	
	Specific target organ toxicity (single or repeated	ed exposure)
SARA 313 (TRI reporting)	010	o/ 1 /
Chemical name	CAS number	% by wt.
Dibenzoyl Peroxide	94-36-0	2.5 - 10
Other federal regulations		
Clean Air Act (CAA) Sectior	n 112 Hazardous Air Pollutants (HAPs) List	
Not regulated.		
Clean Air Act (CAA) Sectior	n 112(r) Accidental Release Prevention (40 CF	<sup>:</sup> R 68.130)
Not regulated.		
Safe Drinking Water Act (SDWA)	Not regulated.	
Material name: PLEXUS® MA2230/	2245/2290 EU Blue Activator	

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

#### US state regulations

#### California Proposition 65



**WARNING:** This product can expose you to 1,2-BENZENEDICARBOXYLIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10-RICH, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

Issue date	07-10-2023
Revision date	01-09-2025
Version #	02
HMIS® ratings	Health: 2 Flammability: 1 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 1 Instability: 0
Disclaimer	ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.