SAFETY DATA SHEET

1. Identification

Product identifier	PLEXUS® MA550 Adh	esive
Other means of identification		
SKU#	0927	
Recommended use	Not available.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplie	er/Distributor information	
Manufacturer		
Company name	ITW Performance Polyn	ners
Address	30 Endicott Street	
	Danvers, MA 01923	
	United States	
Telephone	Customer Service	978-777-1100
Website	www.itwperformancepo	lymers.com
E-mail	Not available.	
Contact person	EHS Department	
Emergency phone number	Chemtrec	800-424-9300
	International	703-527-3887

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1A
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Highly flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/eye protection/face protection.
Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep cool.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion. None.

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the

material(s) involved, and take precautions to protect themselves. Wash contaminated clothing

Supplemental information

3. Composition/information on ingredients

Mixtures

wixtures			
Chemical name	Common name and synonyms	CAS number	%
Methyl Methacrylate		80-62-6	60 - 80
Styrene/butadiene Copolymer		9003-55-8	10 - 20
METHACRYLIC ACID		79-41-4	1 - 10
Paraffin Wax		8002-74-2	1 - 2.5
Other components below repor	table levels		10 - 20
4. First-aid measures			
Inhalation	Remove victim to fresh air and keep at rest in artificial respiration if needed. Call a poison ce		
Skin contact	Remove contaminated clothing immediately a eczema or other skin disorders: Seek medica contaminated clothing before reuse.		
Eye contact	Immediately flush eyes with plenty of water for present and easy to do. Continue rinsing. Get		
Ingestion	Rinse mouth. Get medical attention if sympton	ms occur.	
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include vision. Skin irritation. May cause redness and Rash.		
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and tre immediately. While flushing, remove clothes v ambulance. Continue flushing during transpor observation. Symptoms may be delayed.	which do not adhere to affecte	d area. Call an

General information

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

before reuse.

6. Accidental release measures

6. Accidental release measures		
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.	
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.	
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.	
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.	
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.	
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.	
7. Handling and storage		
Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.	
	For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".	
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).	

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	
Methyl Methacrylate (CAS 80-62-6)	PEL	410 mg/m3	
		100 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
METHACRYLIC ACID (CAS 79-41-4)	TWA	20 ppm	

Components	Туре	Value	Form
Methyl Methacrylate (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
Paraffin Wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.
US. NIOSH: Pocket Guide Components	to Chemical Hazards Type	Value	Form
METHACRYLIC ACID (CAS 79-41-4)	5 TWA	70 mg/m3	
		20 ppm	
Methyl Methacrylate (CAS 80-62-6)	TWA	410 mg/m3	
		100 ppm	
Paraffin Wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.
ological limit values	No biological exposure limits noted f	or the ingredient(s).	
posure guidelines	Occupational Exposure Limits are no	ot relevant to the current physic	al form of the product.
	n designation CAS 79-41-4) Can o Chemical Hazards: Skin designation		
METHACRYLIC ACID (be absorbed through the skin.	
propriate engineering ntrols	Explosion-proof general and local ex Ventilation rates should be matched exhaust ventilation, or other enginee exposure limits. If exposure limits ha acceptable level. Provide eyewash s	to conditions. If applicable, use ring controls to maintain airborn ve not been established, mainta	e process enclosures, local ne levels below recommended
Eye/face protection	s, such as personal protective equipm Chemical respirator with organic vap		
Skin protection Hand protection	Wear appropriate chemical resistant	aloves	
Other	Wear appropriate chemical resistant	-	
Respiratory protection	Chemical respirator with organic vap	0	
Thermal hazards	Wear appropriate thermal protective	clothing, when necessary.	
eneral hygiene nsiderations	When using do not smoke. Always o after handling the material and befor clothing and protective equipment to be allowed out of the workplace.	e eating, drinking, and/or smok	ing. Routinely wash work
. Physical and chemica	l properties		
pearance	Paste.		
Physical state	Liquid.		
Form	Paste.		

Form	Paste.
Color	Off-white.
Odor	Fragrant
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	-54.4 °F (-48 °C) estimated
Initial boiling point and boiling range	212.9 °F (100.5 °C) estimated
Flash point	50.0 °F (10.0 °C) estimated

Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.7 %
Flammability limit - upper (%)	12.5 %
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	2.8 mm Hg @ 68 F
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.95 g/cm3 estimated
Explosive properties	Not explosive.
Flammability class	Flammable IB estimated
Oxidizing properties	Not oxidizing.
Specific gravity	0.95 estimated
10 Stability and reactivity	-

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the decomposition temperature. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Peroxides.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

5	I Contraction of the second
Inhalation	Harmful if inhaled.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Information on texteele standard of	

Information on toxicological effects

Acute toxicity


Harmful if inhaled.

Components	Species	Test Results
METHACRYLIC ACID (CAS 79-41	-4)	
<u>Acute</u>		
Dermal	5.11.1	
LD50	Rabbit	500 mg/kg
Inhalation	Det	7.4
LC50	Rat	7.1 mg/l, 4 Hours
Oral LD50	Rat	1060 malka
		1060 mg/kg
Methyl Methacrylate (CAS 80-62-6 Acute))	
Inhalation		
LC50	Mouse	18.5 mg/l, 2 Hours
Oral		
LD50	Rat	7800 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye	Causes serious eye irritation	
irritation		
Respiratory or skin sensitization	ı	
ACGIH sensitization		
METHYL METHACRYLA	TE (CAS 80-62-6)	Dermal sensitization
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin re	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcino	genicity to humans.
IARC Monographs. Overall I	Evaluation of Carcinogenicity	,
Methyl Methacrylate (CA Styrene/butadiene Copoly OSHA Specifically Regulate		3 Not classifiable as to carcinogenicity to humans. 3 Not classifiable as to carcinogenicity to humans. 1001-1053)
	ogram (NTP) Report on Carci	nogens
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
12. Ecological information	1	
Ecotoxicity		as environmentally hazardous. However, this does not exclude the ent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the d	egradability of any ingredients in the mixture.
Bioaccumulative potential		
Partition coefficient n-octan METHACRYLIC ACID	ol / water (log Kow)	0.03
Methyl Methacrylate		0.93 1.38
Mobility in soil	No data available.	
Other adverse effects	The product contains volatile	organic compounds which have a photochemical ozone creation

13. Disposal considerations		
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).	
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.	

14. Transport information

DOT	
UN number	UN1133
UN proper shipping name	Adhesives, containing a flammable liquid, Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	149, B52, IB2, T4, TP1, TP8
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242
ΙΑΤΑ	
UN number	UN1133
UN proper shipping name	Adhesives containing flammable liquid, Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	П
Environmental hazards	No.
ERG Code	3L
	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1133
UN proper shipping name	ADHESIVES containing flammable liquid, Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	Ш
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not established.
Annex II of MARPOL 73/78 and	
the IBC Code	



15. Regulatory information

JS federal regulations	This product is a "H Standard, 29 CFR		fined by the OSHA Hazard Commun	ication
US EPCRA (SARA Title	III) Section 313 - To	xic Chemical: De minimi	s concentration	
Methyl Methacrylate	· · · ·	% 1.0		
•		xic Chemical: Listed sub	stance	
Methyl Methacrylate	(CAS 80-62-6)	Listed.		
Toxic Substances Control A	Act (TSCA)			
TSCA Section 12(b) Exp Not regulated.	oort Notification (40	CFR 707, Subpt. D)		
CERCLA Hazardous Substa	ince List (40 CFR 30	2.4)		
Methyl Methacrylate (CA: SARA 304 Emergency relea		Listed.		
Not regulated. OSHA Specifically Regulate	ed Substances (29 C	FR 1910.1001-1053)		
Not listed.				
Superfund Amendments and Re SARA 302 Extremely hazard Not listed.		f 1986 (SARA)		
SARA 311/312 Hazardous chemical	Yes			
Classified hazard categories	Acute toxicity (any Skin corrosion or ir Serious eye damag Respiratory or skin	ritation ge or eye irritation	;) ;)	
SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
Methyl Methacrylate		80-62-6	60 - 80	
Other federal regulations				
Clean Air Act (CAA) Section	ו 112 Hazardous Air	Pollutants (HAPs) List		
Methyl Methacrylate (CA		· · · · ·		
	n 112(r) Accidental F			

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Methyl Methacrylate (CAS 80-62-6)

Low priority

US state regulations

California Proposition 65



WARNING: This product can expose you to Ethylene Glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Developmental toxin

Ethylene Glycol (CAS 107-21-1)

Listed: June 19, 2015

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Methyl Methacrylate (CAS 80-62-6)

International Inventories

Country(s) or region	Inventory name On inve	ntory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

04-09-2019
08-03-2021
03
Health: 2 Flammability: 3 Physical hazard: 0
Health: 2 Flammability: 3 Instability: 0
ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.
Ecological information: Other adverse effects Transport Information: Proper Shipping Name/Packing Group

SAFETY DATA SHEET

1. Identification

Product identifier	PLEXUS® MA320/550 EU White Activator	
Other means of identification		
SKU#	0638	
Recommended use	Not available.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplie	r/Distributor information	
Manufacturer		
Company name Address	ITW Performance Polymers 30 Endicott Street Danvers, MA 01923 United States	
Telephone	Customer Service 978-777-1100	
Website	www.itwperformancepolymers.com	
E-mail	Not available.	
Contact person	EHS Department Chemtrec 800-424-9300	
Emergency phone number	Chemtrec 800-424-9300 International 703-527-3887	
2. Hazard(s) identification	n	
Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation Category 2	
	Serious eye damage/eye irritation Category 2A	
	Sensitization, skin Category 1	
	Specific target organ toxicity, single exposure Category 3 respiratory tract irritation	
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Warning	
Hazard statement	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation.	
Precautionary statement		
Prevention	Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves.	
Response	If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.	
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	
-		

3. Composition/information on ingredients

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
DIBUTYL MALEATE		105-76-0	20 - 40
Titanium Dioxide		13463-67-7	20 - 40
Dibenzoyl Peroxide		94-36-0	2.5 - 10
Other components below reportable levels			40 - 60

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe
	good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
Dibenzoyl Peroxide (CAS 94-36-0)	PEL	5 mg/m3	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CF	R 1910.1000)		
Components	Туре	Value	Form
Titanium Dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limi	t Values		
Components	Туре	Value	
Dibenzoyl Peroxide (CAS 94-36-0)	TWA	5 mg/m3	
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide	o Chemical Hazards		
Components	Туре	Value	
Dibenzoyl Peroxide (CAS 94-36-0)	TWA	5 mg/m3	
logical limit values	No biological exposure limits noted	for the ingredient(s).	
propriate engineering htrols	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.		
ividual protection measures	s, such as personal protective equip	ment	
Eye/face protection	Chemical respirator with organic va	por cartridge and full facepiece.	
Skin protection Hand protection	Wear appropriate chemical resistant gloves.		
Other	Wear appropriate chemical resistan	nt clothing.	
Respiratory protection	Chemical respirator with organic va	por cartridge and full facepiece.	
Thermal hazards	Wear appropriate thermal protective	e clothing, when necessary.	
neral hygiene nsiderations	Always observe good personal hygi and before eating, drinking, and/or equipment to remove contaminants workplace.	smoking. Routinely wash work	clothing and protective
Physical and chemical	properties		
pearance	Paste.		

Physical state Liquid.

Form	Paste.
Color	White
Odor	Slight.
Odor threshold	Not available.
рН	6
Melting point/freezing point	217.4 °F (103 °C) estimated
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.0004 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	176 °F (80 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
10. Stability and reactivity	/
Beactivity	The product is stable and non-reactive under normal conditions of use, storage and transport

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Alcohols. Amines.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
The second s	

Information on toxicological effects

Acute toxicity	Not known.		
Components	Species	Test Results	
Dibenzoyl Peroxide (CAS 94-36-0)			
<u>Acute</u>			
Oral			
LD50	Rat	7710 mg/kg	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes serious eye irritation	·	
Respiratory or skin sensitizatior	I		
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	May cause an allergic skin re	action.	
Germ cell mutagenicity	No data available to indicate mutagenic or genotoxic.	product or any components present at greater than 0.1% are	
Carcinogenicity	Not classifiable as to carcino	genicity to humans.	
IARC Monographs. Overall I	Evaluation of Carcinogenicity	1	
Dibenzoyl Peroxide (CAS Titanium Dioxide (CAS 13 OSHA Specifically Regulate		3 Not classifiable as to carcinogenicity to humans. 2B Possibly carcinogenic to humans. 1001-1052)	
Not regulated. US. National Toxicology Pro	gram (NTP) Report on Carciı	nogens	
Not listed.	, .	-	
Reproductive toxicity	This product is not expected	to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	May cause respiratory irritation	אר.	
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not likely, due to the form of the product.		
Chronic effects	Prolonged inhalation may be harmful.		
12. Ecological information	1		
Ecotoxicity		as environmentally hazardous. However, this does not exclude the ent spills can have a harmful or damaging effect on the environment.	
Persistence and degradability	No data is available on the de	egradability of any ingredients in the mixture.	
Bioaccumulative potential			
Partition coefficient n-octan	ol / water (log Kow)		
Dibenzoyl Peroxide	No data available	3.46	
Mobility in soil	No data available.		
Other adverse effects		ntal effects (e.g. ozone depletion, photochemical ozone creation n, global warming potential) are expected from this component.	
13. Disposal consideratio	ns		
Disposal instructions		e in sealed containers at licensed waste disposal site. Dispose of ance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with a	all applicable regulations.	
Hazardous waste code	disposal company.	ssigned in discussion between the user, the producer and the waste	
Waste from residues / unused products	product residues. This mater Disposal instructions).	h local regulations. Empty containers or liners may retain some ial and its container must be disposed of in a safe manner (see:	
Contaminated packaging		ay retain product residue, follow label warnings even after container is hould be taken to an approved waste handling site for recycling or	

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and the IBC Code				
15. Regulatory information	n			
US federal regulations	This product is a ' Standard, 29 CFF		efined by the OSHA Hazard Con	nmunication
US EPCRA (SARA Title	III) Section 313 - Te	oxic Chemical: De minimis	s concentration	
Dibenzoyl Peroxide	· /	% 1.0		
•	•	oxic Chemical: Listed sub	stance	
Dibenzoyl Peroxide		Listed.		
Toxic Substances Control				
TSCA Section 12(b) Ex Not regulated.	port Notification (4	0 CFR 707, Subpt. D)		
CERCLA Hazardous Substa	ance List (40 CFR 3	02.4)		
Not listed.				
SARA 304 Emergency relea	se notification			
Not regulated.				
OSHA Specifically Regulate	ed Substances (29	CFR 1910.1001-1052)		
Not regulated.				
Superfund Amendments and Re		of 1986 (SARA)		
SARA 302 Extremely hazard Not listed.	dous substance			
	Vaa			
SARA 311/312 Hazardous chemical	Yes			
Classified hazard categories	Respiratory or ski	age or eye irritation	od ovposuro)	
	Specific larger org	gan toxicity (single of repeat	ed exposure)	
SARA 313 (TRI reporting) Chemical name		CAS number	% by wt.	
Dibenzoyl Peroxide		94-36-0	2.5 - 10	
Other federal regulations				
Clean Air Act (CAA) Sectior	n 112 Hazardous Ai	ir Pollutants (HAPs) List		
Not regulated.				
Clean Air Act (CAA) Sectior	n 112(r) Accidental	Release Prevention (40 Cl	FR 68.130)	
Not regulated.				
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations				
California Proposition 65				



WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer, and 1,2-BENZENEDICARBOXYLIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10-RICH, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

2-Propenenitrile; Acrylonitrile, Cyanoethylene	Listed: July 1, 1987
(CAS 107-13-1)	
STYRENE (CAS 100-42-5)	Listed: April 22, 2016

Titanium Dioxide (CAS 13463-67-7)	Listed: September 2, 2011	
California Proposition 65 - CRT: Listed date/Developmental toxin		

1,2-BENZENEDICARBOXYLIC ACID, Listed: April 20, 2007 DI-C9-11-BRANCHED ALKYL ESTERS, C10-RICH

(CAS 68515-49-1)

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Titanium Dioxide (CAS 13463-67-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	04-09-2019
Version #	01
HMIS® ratings	Health: 2 Flammability: 1 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 1 Instability: 0
Disclaimer	ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.