# SAFETY DATA SHEET

1. Identification

Product identifier PLEXUS® H4110 Activator

Other means of identification

**SKU#** 41104

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers

Address 30 Endicott Street

Danvers, MA 01923 United States

**Telephone** Customer Service 978-777-1100

Website www.itwperformancepolymers.com

E-mail Not available.

Contact person EHS Department

Emergency phone number Chemtrec 800-424-9300

International 703-527-3887

# 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A Sensitization, skin Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

**Hazard statement** Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

**Precautionary statement** 

**Prevention** Avoid breathing mist/vapors. Wash thoroughly after handling. Contaminated work clothing must

not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves.

**Response** If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take

off contaminated clothing and wash it before reuse.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

**Supplemental information** 52% of the mixture consists of component(s) of unknown acute oral toxicity. 52% of the mixture consists of component(s) of unknown acute dermal toxicity. 52% of the mixture consists of

consists of component(s) of unknown acute dermal toxicity. 52% of the mixture consists of component(s) of unknown acute inhalation toxicity. 52% of the mixture consists of component(s)

of unknown acute hazards to the aquatic environment. 2% of the mixture consists of

component(s) of unknown long-term hazards to the aquatic environment.

Material name: PLEXUS® H4110 Activator

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Epoxy Resin:reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)	EPOXY RESIN	25068-38-6	40 - 60
3-(trimethoxysilyl)propyl Glycidyl Ether		2530-83-8	1 - 2.5
DIBUTYLTIN DI(ACETATE)		1067-33-0	0.1 - 1
Other components below reportable	levels		40 - 60

### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

symptoms/effects, acute and delayed

Indication of immediate

medical attention and special treatment needed

Rash.

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods
General fire hazards

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

41104 Version #: 05 Revision date: 07-18-2021 Issue date: 01-24-2020

## 7. Handling and storage

Precautions for safe handling Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged

exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe

good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in tightly closed container. Store away from incompatible materials (see Section 10 of the

SDS).

## 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
DIBUTYLTIN DI(ACETATE)	PEL	0.1 mg/m3	
(CAS 1067-33-0)			

ACCILL There are a fall through Males a

US. ACGIH Inresnoid Limit Values					
Components	Туре	Value			
DIBUTYLTIN DI(ACETATE) (CAS 1067-33-0)	STEL	0.2 mg/m3			
	TWA	0.1 mg/m3			
US. NIOSH: Pocket Guide to Chem	nical Hazards				
Components	Туре	Value			
DIBUTYLTIN DI(ACETATE) (CAS 1067-33-0)	TWA	0.1 mg/m3			

No biological exposure limits noted for the ingredient(s). **Biological limit values** 

**Exposure guidelines** 

US - California OELs: Skin designation

DIBUTYLTIN DI(ACETATE) (CAS 1067-33-0) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

DIBUTYLTIN DI(ACETATE) (CAS 1067-33-0) Skin designation applies.

US - Tennessee OELs: Skin designation

DIBUTYLTIN DI(ACETATE) (CAS 1067-33-0) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation** 

DIBUTYLTIN DI(ACETATE) (CAS 1067-33-0) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

DIBUTYLTIN DI(ACETATE) (CAS 1067-33-0) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Face shield is recommended. Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

# 9. Physical and chemical properties

Liquid. Appearance

**Physical state** Liquid. Liquid. **Form** Color Dark grey Slight. Odor

**Odor threshold** Not available. Not available. Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

> 392.0 °F (> 200.0 °C) Flash point

**Evaporation rate** Not available. Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits Flammability limit - lower Not available.

(%)

Flammability limit - upper

(%)

Not available.

Not available. Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Vapor pressure Vapor density Not available. Relative density Not available.

Solubility(ies)

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

**Auto-ignition temperature** Not available. **Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**Density** 1.55 g/cm3 Not explosive. **Explosive properties** 

Flammability class Combustible IIIB estimated

**Oxidizing properties** Not oxidizing.

Specific gravity 1.55

# 10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the decomposition temperature. Contact with incompatible

materials.

Incompatible materials Strong oxidizing agents.

**Hazardous decomposition** No hazardous decomposition products are known.

products

## 11. Toxicological information

### Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Causes skin irritation. May cause an allergic skin reaction. Skin contact

Causes serious eye irritation. Eye contact

Ingestion Expected to be a low ingestion hazard.

Material name: PLEXUS® H4110 Activator

SDS US

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

DIBUTYLTIN DI(ACETATE) (CAS 1067-33-0)

Acute Oral

LD50 Rat 32 mg/kg

Causes serious eve irritation.

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

irritation

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful.

# 12. Ecological information

**Ecotoxicity**The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

No data is available on the degradability of any ingredients in the mixture.

Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

DIBUTYLTIN DI(ACETATE) 1.27

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

Material name: PLEXUS® H4110 Activator

SDS US

# 14. Transport information

#### DOT

Not regulated as dangerous goods.

#### **IATA**

**UN** number UN3082

**UN proper shipping name** Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin:--reaction Product Of

Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))

Transport hazard class(es)

Class 9 Subsidiary risk Ш Packing group **Environmental hazards** Yes 9L **ERG Code** 

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

**IMDG** 

UN3082 **UN** number

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:--reaction **UN** proper shipping name

Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)), MARINE POLLUTANT

Transport hazard class(es)

9 Class Subsidiary risk Packing group Ш **Environmental hazards** 

Yes Marine pollutant **EmS** F-A, S-F


Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

Not established.

## IATA; IMDG



### Marine pollutant



IMDG Regulated Marine Pollutant. **General information** 

# 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Material name: PLEXUS® H4110 Activator 41104 Version #: 05 Revision date: 07-18-2021 Issue date: 01-24-2020

Standard, 29 CFR 1910.1200.

#### **Toxic Substances Control Act (TSCA)**

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

## SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

## SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard Skin corrosion or irritation

categories Serious eye damage or eye irritation

Respiratory or skin sensitization

#### SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

Inventory name

(SDWA)

## **US** state regulations

#### California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

#### **International Inventories**

Country(s) or region

Country(s) or region	inventory name	On inventory (yes/no)
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

# 16. Other information, including date of preparation or last revision

 Issue date
 01-24-2020

 Revision date
 07-18-2021

Version # 05

Material name: PLEXUS® H4110 Activator

41104 Version #: 05 Revision date: 07-18-2021 Issue date: 01-24-2020

On inventory (yes/no)\*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**HMIS®** ratings Health: 2

Flammability: 1 Physical hazard: 0

**NFPA** ratings Health: 2

Flammability: 1 Instability: 0

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: PLEXUS® H4110 Activator