SAFETY DATA SHEET

1. Identification		
Product identifier	PLEXUS® MA420W Adhesive	
Other means of identification SKU#	0814	
Recommended use	Not available.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier	r/Distributor information	
Company name	ITW Performance Polymers	
Address	35 Brownridge Rd	
	Unit 1	
	Halton Hills, ON L7G 0C6	
Contact person	Customer Service	
Telephone number	978-777-1100	
Fax		
E-mail		
Emergency telephone number	800-424-9300	
Supplier	Not available.	
2. Hazard identification		
Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, dermal	Category 4
	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 1
	Sensitization, skin	Category 1A
Environmental hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement	Highly flammable liquid and vapour. Harn cause an allergic skin reaction. Causes s	nful in contact with skin. Causes skin irritation. May erious eye damage. Harmful if inhaled.
Precautionary statement		
Prevention	Keep container tightly closed. Ground an explosion-proof electrical/ventilating/lighti prevent static discharges. Avoid breathing only outdoors or in a well-ventilated area.	ks, open flames and other ignition sources. No smoking. d bond container and receiving equipment. Use ng equipment. Use non-sparking tools. Take action to g mist/vapours. Wash thoroughly after handling. Use Contaminated work clothing should not be allowed out protective clothing/eye protection/face protection.
Response	INHALED: Remove person to fresh air ar cautiously with water for several minutes. Continue rinsing. Immediately call a POIS medical advice/attention. Take off contan Use appropriate media to extinguish.	ly all contaminated clothing. Rinse skin with water. IF id keep comfortable for breathing. IF IN EYES: Rinse Remove contact lenses, if present and easy to do. SON CENTRE/doctor. If skin irritation or rash occurs: Get hinated clothing and wash it before reuse. In case of fire:
Storage	Store in a well-ventilated place. Keep coo	ı.

DisposalDispose of contents/container in accordance with local/regional/national/international regulations.Other hazardsStatic accumulating flammable liquid can become electrostatically charged even in bonded and
grounded equipment. Sparks may ignite liquid and vapour. May cause flash fire or explosion.Supplemental information11.86 % of the mixture consists of component(s) of unknown acute oral toxicity. 74.36 % of the
mixture consists of component(s) of unknown acute dermal toxicity. 11.86 % of the mixture
consists of component(s) of unknown acute inhalation toxicity. 81.26 % of the mixture
consists of component(s) of unknown acute hazards to the aquatic environment.

3. Composition/information on ingredients

lixtures			
Chemical name	Common name and synonyms	CAS number	%
Methyl methacrylate		80-62-6	40 - 70
Methacrylic acid		79-41-4	5 - 10
TRIMETHYLOLPROPANE TRIMETHACRYLATE		3290-92-4	0.5 - 1.5
Ethylene glycol		107-21-1	0.1 - 1
N,n-dimethyl-p-toluidine		99-97-8	0.1 - 1
Other components below reporta	able levels		15 - 40

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

1 First aid massing	
4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a poison centre or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Ingestion	Rinse mouth. Get medical advice/attention if you feel unwell.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods General fire hazards	Use standard firefighting procedures and consider the hazards of other involved materials. Highly flammable liquid and vapour.

6. Accidental release measures

6. Accidental release meas	Suies
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get this material in contact with eyes. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.
	For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

cupational exposure limits US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
ETHYLENE GLYCOL (CAS 107-21-1)	STEL	10 mg/m3	Aerosol, inhalable.
		50 ppm	Vapor fraction
	TWA	25 ppm	Vapor fraction
METHACRYLIC ACID (CAS 79-41-4)	TWA	20 ppm	

US. ACGIH Threshold Limit Values	,
Components	

Components	Туре	Value	Form
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value
ETHYLENE GLYCOL (CAS 107-21-1)	Ceiling	100 mg/m3
METHACRYLIC ACID (CAS 79-41-4)	TWA	70 mg/m3
		20 ppm
METHYL METHACRYLATE (CAS 80-62-6)	STEL	410 mg/m3
		100 ppm
	TWA	205 mg/m3
		50 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
ETHYLENE GLYCOL (CAS 107-21-1)	Ceiling	100 mg/m3	Aerosol
		50 ppm	Vapour.
	STEL	20 mg/m3	Particulate.
	TWA	10 mg/m3	Particulate.
METHACRYLIC ACID (CAS 79-41-4)	TWA	20 ppm	
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value	Form
ETHYLENE GLYCOL (CAS 107-21-1)	STEL	10 mg/m3	Aerosol, inhalable.
		50 ppm	Vapor fraction
	TWA	25 ppm	Vapor fraction
METHACRYLIC ACID (CAS 79-41-4)	TWA	20 ppm	
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	Form
ETHYLENE GLYCOL (CAS 107-21-1)	Ceiling	100 mg/m3	Aerosol
METHACRYLIC ACID (CAS 79-41-4)	TWA	20 ppm	
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	

Components	Туре	Value	Form
ETHYLENE GLYCOL (CAS 107-21-1)	Ceiling	127 mg/m3	Vapor and mist.
		50 ppm	Vapor and mist.
METHACRYLIC ACID (CAS 79-41-4)	TWA	70 mg/m3	
		20 ppm	
METHYL METHACRYLATE (CAS 80-62-6)	TWA	205 mg/m3	
		50 ppm	
Canada, Saakatabawan OEL a (Oor	cupational Health and Safety Re	egulations, 1996, Table 21)	
Gallaua. Saskalchewall OELS (Occ			
•	Туре	Value	Form
ETHYLENE GLYCOL (CAS 107-21-1)		Value 100 mg/m3	Form Aerosol
Components ETHYLENE GLYCOL (CAS	Туре		-

100 ppm

(CAS 80-62-6) 8 hour 50 ppm Biological limit values No biological exposure limits noted for the ingredient(s). Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower. Individual protection measures, such as personal protective equipment Wear safety glasses with side shields (or googles) and a face shield. Face shield is

15 minute

Eyenace protection	recommended.
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

METHYL METHACRYLATE

Appearance	Paste.
Physical state	Liquid.
Form	Liquid. Paste.
Colour	Not available.
Odour	Not available.
Odour threshold	Not available.
рН	Not available.
Melting point/freezing point	-48 °C (-54.4 °F) estimated
Initial boiling point and boiling range	100.5 °C (212.9 °F) estimated
Flash point	10.0 °C (50.0 °F) estimated
Evaporation rate	Not available.

Material name: PLEXUS® MA420W Adhesive

0814 Version #: 02 Revision date: 06-February-2022 Issue date: 25-October-2021

Flammability (solid, gas)	Not applicable.	
Upper/lower flammability or explosive limits		
Flammability limit - lower (%)	2.1 % estimated	
Flammability limit - upper (%)	12.5 % estimated	
Explosive limit - lower (%)	Not available.	
Explosive limit – upper (%)	Not available.	
Vapour pressure	46.36 hPa estimated	
Vapour density	Not available.	
Relative density	Not available.	
Solubility(ies)		
Solubility (water)	Not available.	
Partition coefficient (n-octanol/water)	Not available.	
Auto-ignition temperature	67.78 °C (154 °F) estimated	
Decomposition temperature	Not available.	
Viscosity	Not available.	
Other information		
Density	0.97 g/cm3	
Explosive properties	Not explosive.	
Flammability class	Flammable IB estimated	
Oxidising properties	Not oxidising.	
Specific gravity	0.97	
10. Stability and reactivity		

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport. **Chemical stability** Material is stable under normal conditions. Possibility of hazardous Hazardous polymerisation does not occur. reactions Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the decomposition temperature. Avoid temperatures exceeding the flash point. Contact with incompatible materials. Incompatible materials Strong oxidising agents. Nitrates. Peroxides. Hazardous decomposition No hazardous decomposition products are known. products

11. Toxicological information

Information on likely routes of exposure			
Inhalation	Harmful if inhaled.		
Skin contact	Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.		
Eye contact	Causes serious eye damage.		
Ingestion	Expected to be a low ingestion hazard.		
Symptoms related to the physical, chemical and toxicological characteristicsSevere eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurre vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.			
Information on toxicological effects			

Acute toxicity

Harmful if inhaled. Harmful in contact with skin.


Species	Test Results	
	<i>"</i>	
Rabbit	9530 mg/kg	
Mouse	18.5 mg/l, 2 Hours	
	7000 //	
Rat	7800 mg/kg	
Causes skin irritation.		
Causes serious eye damage.		
1		
	Dermal sensitisation	
	Irritant	
	Irritant	
	Demail constitution	
sitizer	Dermal sensitisation	
	Sensitiser.	
S 80-62-6)	Sensitiser.	
Not a respiratory sensitizer.		
May cause an allergic skin reaction.		
No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Risk of cancer cannot be exclu	uded with prolonged exposure.	
S 80-62-6)	A4 Not classifiable as a human carcinogen. A4 Not classifiable as a human carcinogen.	
	Not classifiable as a human carcinogen.	
6 80-62-6)	Not classifiable as a human carcinogen.	
S 80-62-6)	3 Not classifiable as to carcinogenicity to humans. 2B Possibly carcinogenic to humans.	
,	o cause reproductive or developmental effects.	
Not classified.		
Not classified.		
Not an aspiration hazard.		
Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.		
	s environmentally hazardous. However, this does not exclude the	
	possibility that large or frequent spills can have a harmful or damaging effect on the environment.	
possibility that large or frequer		
possibility that large or frequer	nt spills can have a harmful or damaging effect on the environment gradability of any ingredients in the mixture.	
possibility that large or frequer		
	Rabbit Mouse Rat Causes skin irritation. Causes serious eye damage. Causes serious eye damage. Causes serious eye damage. S 80-62-6) ant Causes serious eye damage. Causes serious eye damage. Causes serious eye damage. Causes serious eye damage. S 80-62-6) S 80-62-6) S 80-62-6) Ls Hazard Data: Sensitiser S 80-62-6) Not a respiratory sensitizer. May cause an allergic skin rea No data available to indicate p mutagenic or genotoxic. Risk of cancer cannot be exclu C-21-1) S 80-62-6) Cause and the exclusion of Carcinogenicity S 80-62-6) CAS 99-97-8) This product is not expected to Not classified. Not classified. Not an aspiration hazard.	

Partition coefficient n-octanol / water (log Kow)			
Methacrylic acid	0.93		
Methyl methacrylate	1.38		
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal considerations		
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).	
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.	

14. Transport information

TDG	
UN number	UN1133
UN proper shipping name	ADHESIVES containing flammable liquid, Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	Not available.
	Read safety instructions, SDS and emergency procedures before handling.
ΙΑΤΑ	
UN number	UN1133
UN proper shipping name	Adhesives containing flammable liquid, Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3L
	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1133
UN proper shipping name	ADHESIVES containing flammable liquid, Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not established.
Annex II of MARPOL 73/78 and	
the IBC Code	



15. Regulatory information

Canadian regulations	This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.	
Controlled Drugs and Su	bstances Act	
Not regulated.		
Export Control List (CEP	A 1999, Schedule 3)	
Not listed.		
Greenhouse Gases		
Not listed.	-41	
Precursor Control Regulated	ations	
Not regulated.		
nternational regulations		
Stockholm Convention		
Not applicable. Rotterdam Convention		
Not applicable.		
Kyoto Protocol		
Not applicable.		
Montreal Protocol		
Not applicable.		
Basel Convention		
Not applicable.		
nternational Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes

Country(s) or region	Inventory name On inventor	y (yes/no)*
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)		

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information	
Issue date	25-October-2021
Revision date	06-February-2022
Version No.	02
Disclaimer	ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.
Revision information	Ecological information: Other adverse effects

SAFETY DATA SHEET

1. Identification			
Product identifier	PLEXUS® AO420/MA920/420/1020/10	23 ACTIVATOR	
Other means of identification			
SKU#	0641		
Recommended use	Not available.		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplie	r/Distributor information		
Company name	ITW Performance Polymers		
Address	35 Brownridge Rd		
	Unit 1		
	Halton Hills, ON L7G 0C6		
Contact person	Customer Service		
Telephone number	978-777-1100		
Fax			
E-mail			
Emergency telephone number	800-424-9300	800-424-9300	
Supplier	Not available.		
2. Hazard identification			
Physical hazards	Organic peroxides	Туре F	
Health hazards	Skin corrosion/irritation	Category 2	
	Serious eye damage/eye irritation	Category 2A	
	Sensitization, skin	Category 1	
Environmental hazards	Not classified.		
Label elements			
Signal word	Warning		
Hazard statement	Heating may cause a fire. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.		
Precautionary statement			
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep only in original packaging. Keep cool. Ground and bond container and receiving equipment. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.		
Response	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.		
Storage	Store in a well-ventilated place. Protect from sunlight. Store at temperatures not exceeding $25^{\circ}C/77^{\circ}F$. Store separately.		
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.		
Other hazards	None known.		
Supplemental information	None.	None.	

3. Composition/information on ingredients

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
BENZOYL PEROXIDE		94-36-0	15 - 40
DIISODECYL ADIPATE		27178-16-1	15 - 40
Epoxy Resin:reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)	Epoxy resin	25068-38-6	15 - 40
Dipropylene glycol dibenzoate		27138-31-4	1 - 5
Magnesium Sulphate		7487-88-9	1 - 5
STYRENE BLOCK POLYMER WITH ISOPRENE, HYDROGENATED		68648-89-5	1 - 5
STYRENE-ETHYLENE/BUTYLENE -STYRENE BLOCK COPOLYMER		66070-58-4	1 - 5
Other components below reportable	e levels		10 - 30

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures	
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tanks due to fire.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Heating may cause a fire.
6. Accidental release meas	sures
Personal precautions,	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

lethods and materials for		
ontainment and cleaning up	Eliminate all ignition sources (no smo combustibles (wood, paper, oil etc) a	king, flares, sparks, or flames in immediate area). Keep way from spilled material.
	possible. Use a non-combustible mat	, if this is without risk. Dike the spilled material, where this is erial like vermiculite, sand or earth to soak up the product sposal. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent remove residual contamination.	material (e.g. cloth, fleece). Clean surface thoroughly to
	Never return spills to original contain	ers for re-use. For waste disposal, see section 13 of the SDS
nvironmental precautions	Avoid discharge into drains, water co	urses or onto the ground.
7. Handling and storage		
recautions for safe handling	clothing and other combustible mater	en flame. When using do not smoke. Keep away from ials. Avoid breathing mist/vapours. Avoid contact with eyes, xposure. Provide adequate ventilation. Wear appropriate rve good industrial hygiene practices.
conditions for safe storage, ncluding any incompatibilities		en flame. Store in a cool, dry place out of direct sunlight. o only in the original container. Store away from other
Exposure controls/pers	onal protection	
occupational exposure limits		
US. ACGIH Threshold Limit Components	Values Type	Value
BENZOYL PEROXIDE (CAS 94-36-0)	TWA	5 mg/m3
, , ,	upational Health & Safety Code, Sch	
Components	Type	Value
-		
Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. British Columbia O	Type TWA ELs. (Occupational Exposure Limits	Value
Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. British Columbia O Safety Regulation 296/97, as	Type TWA ELs. (Occupational Exposure Limits s amended)	Value 5 mg/m3 for Chemical Substances, Occupational Health and
Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. British Columbia O Safety Regulation 296/97, as Components BENZOYL PEROXIDE	Type TWA ELs. (Occupational Exposure Limits	Value 5 mg/m3
Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. British Columbia O Safety Regulation 296/97, as Components BENZOYL PEROXIDE (CAS 94-36-0)	Type TWA ELs. (Occupational Exposure Limits s amended) Type	Value 5 mg/m3 for Chemical Substances, Occupational Health and Value 5 mg/m3
Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. British Columbia O Safety Regulation 296/97, as Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. Manitoba OELs (Re	Type TWA ELs. (Occupational Exposure Limits s amended) Type TWA eg. 217/2006, The Workplace Safety A	Value 5 mg/m3 for Chemical Substances, Occupational Health and Value 5 mg/m3 and Health Act)
Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. British Columbia O Safety Regulation 296/97, as Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. Manitoba OELs (Re Components BENZOYL PEROXIDE (CAS 94-36-0)	Type TWA ELs. (Occupational Exposure Limits s amended) Type TWA eg. 217/2006, The Workplace Safety A Type	Value 5 mg/m3 for Chemical Substances, Occupational Health and Value 5 mg/m3 and Health Act) Value 5 mg/m3
Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. British Columbia O Safety Regulation 296/97, as Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. Manitoba OELs (Re Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. Ontario OELs. (Cor	Type TWA ELs. (Occupational Exposure Limits samended) Type TWA eg. 217/2006, The Workplace Safety A Type TWA trol of Exposure to Biological or Ch	Value 5 mg/m3 for Chemical Substances, Occupational Health and Value 5 mg/m3 and Health Act) Value 5 mg/m3 emical Agents)
Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. British Columbia O Safety Regulation 296/97, as Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. Manitoba OELs (Re Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. Ontario OELs. (Cor Components BENZOYL PEROXIDE (CAS 94-36-0)	Type TWA ELs. (Occupational Exposure Limits a amended) Type TWA eg. 217/2006, The Workplace Safety A Type TWA TWA trol of Exposure to Biological or Ch Type	Value 5 mg/m3 for Chemical Substances, Occupational Health and Value 5 mg/m3 and Health Act) Value 5 mg/m3 emical Agents) Value 5 mg/m3
Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. British Columbia O Safety Regulation 296/97, as Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. Manitoba OELs (Re Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. Ontario OELs. (Cor Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. Quebec OELs. (Mir	Type TWA ELs. (Occupational Exposure Limits samended) Type TWA eg. 217/2006, The Workplace Safety A Type TWA htrol of Exposure to Biological or Ch Type TWA htrol of Exposure to Biological or Ch Type TWA htrol of Exposure to Biological or Ch Type TWA htrol of Exposure to Biological or Ch Type TWA	Value 5 mg/m3 for Chemical Substances, Occupational Health and Value 5 mg/m3 and Health Act) Value 5 mg/m3 emical Agents) Value 5 mg/m3 g occupational health and safety)
Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. British Columbia O Safety Regulation 296/97, as Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. Manitoba OELs (Re Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. Ontario OELs. (Cor Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. Quebec OELs. (Mir Components BENZOYL PEROXIDE (CAS 94-36-0)	Type TWA ELs. (Occupational Exposure Limits samended) Type TWA eg. 217/2006, The Workplace Safety A Type TWA eg. 217/2006, The Workplace Safety A Type TWA htrol of Exposure to Biological or Ch Type TWA htrol of Exposure to Biological or Ch Type TWA htrol of Exposure to Biological or Ch Type TWA htrol of Exposure to Biological or Ch Type TWA	Value 5 mg/m3 for Chemical Substances, Occupational Health and Value 5 mg/m3 and Health Act) Value 5 mg/m3 emical Agents) Value 5 mg/m3 g occupational health and safety) Value 5 mg/m3
Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. British Columbia O Safety Regulation 296/97, as Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. Manitoba OELs (Re Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. Ontario OELs. (Cor Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. Quebec OELs. (Mir Components BENZOYL PEROXIDE (CAS 94-36-0) Canada. Saskatchewan OEL	Type TWA ELs. (Occupational Exposure Limits s amended) Type TWA eg. 217/2006, The Workplace Safety A Type TWA eg. 217/2006, The Workplace Safety A Type TWA htrol of Exposure to Biological or Ch Type TWA htrol of Exposure to Biological or Ch Type TWA htrol of Exposure to Biological or Ch Type TWA htrol of Exposure to Biological or Ch Type TWA htrol of Exposure to Regulation respectin Type TWA htrol of Labor - Regulation respectin Type TWA Ls (Occupational Health and Safety F	Value 5 mg/m3 for Chemical Substances, Occupational Health and Value 5 mg/m3 and Health Act) Value 5 mg/m3 emical Agents) Value 5 mg/m3 g occupational health and safety) Value 5 mg/m3 g occupational health and safety) Value 5 mg/m3 g occupational health and safety) Value 5 mg/m3

Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.
Individual protection measures	s, such as personal protective equipment
Eye/face protection	Wear safety glasses with side shields (or goggles). Face shield is recommended.
Skin protection Hand protection	Wear appropriate chemical resistant gloves.
nand protection	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

•	
Appearance	Viscous. Liquid.
Physical state	Liquid.
Form	Viscous. Liquid.
Colour	Blue.
Odour	Slight.
Odour threshold	Not available.
рН	6
Melting point/freezing point	103 °C (217.4 °F) estimated
Initial boiling point and boiling range	Not available.
Flash point	485.0 °C (905.0 °F) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit – upper (%)	Not available.
Vapour pressure	0.00005 hPa estimated
Vapour density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	80 °C (176 °F) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	1.16 g/cm3 estimated
Explosive properties	Not explosive.
Flammability class	Combustible IIIB estimated

Oxidising propertiesNot oxidising.Specific gravity1.16 estimated

10. Stability	and r	eactivity
---------------	-------	-----------

	•
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Sunlight. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidising agents. Combustible material. Alcohols. Amines.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

<u>y</u>			
Information on likely routes of e	exposure		
Inhalation	Prolonged inhalation may be harmful.		
Skin contact	Causes skin irritation. May cause an allergic skin reaction.		
Eye contact	Causes serious eye irritation.		
Ingestion	Knowledge about health hazard is incomplete.		
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.		
Information on toxicological eff	ects		
Acute toxicity	Not known.		
Components	Species	Test Results	
BENZOYL PEROXIDE (CAS 94-3	6-0)		
<u>Acute</u>			
Oral	_		
LD50	Rat	7710 mg/kg	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes serious eye irritatior	1.	
Respiratory or skin sensitisation	n		
Canada - Alberta OELs: Irrit	ant		
BENZOYL PEROXIDE (0	CAS 94-36-0)	Irritant	
Respiratory sensitisation		ck of data the classification is not possible.	
Skin sensitisation	May cause an allergic skin r		
Germ cell mutagenicity	Due to partial or complete lack of data the classification is not possible.		
Carcinogenicity	Due to partial or complete la	ck of data the classification is not possible.	
ACGIH Carcinogens			
BENZOYL PEROXIDE ((Canada - Manitoba OELs: c		A4 Not classifiable as a human carcinogen.	
BENZOYL PEROXIDE ((IARC Monographs. Overall	CAS 94-36-0) Evaluation of Carcinogenicit	Not classifiable as a human carcinogen. y	
BENZOYL PEROXIDE (C	,	3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity		ck of data the classification is not possible.	
Specific target organ toxicity - single exposure	Due to partial or complete la	ck of data the classification is not possible.	
Specific target organ toxicity - repeated exposure	Due to partial or complete la	ck of data the classification is not possible.	
Aspiration hazard	Due to partial or complete la	ck of data the classification is not possible.	
Chronic effects	Prolonged inhalation may be	e harmful.	

12. Ecological informatio	n	
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.	
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.	
Bioaccumulative potential		
Partition coefficient n-octar BENZOYL PEROXIDE	nol / water (log Kow) 3.46	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	
13. Disposal consideration	ons	
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	

Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

Not applicable.

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated. Export Control List (CEPA 1999, Schedule 3) Not listed. **Greenhouse Gases** Not listed. **Precursor Control Regulations** Not regulated. International regulations **Stockholm Convention** Not applicable. **Rotterdam Convention** Not applicable. **Kyoto Protocol** Not applicable. **Montreal Protocol** Not applicable. **Basel Convention**

International Inventories

Country(s) or region	Inventory name On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information	on
Issue date	10-October-2019
Revision date	04-May-2020
Version No.	03
Disclaimer	ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.