SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® Wear Guard™ 300RTC Hardener-

Other means of identification

SKU# 5209

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers

Address 30 Endicott Street

Danvers, MA 01923 United States

Telephone Customer Service 978-777-1100

Website www.itwperformancepolymers.com

E-mail Not available.

Contact person EHS Department

Emergency phone number Chemtrec 800-424-9300

International 703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1

Serious eye damage/eye irritation Category 1
Sensitization, respiratory Category 1
Sensitization, skin Category 1
Reproductive toxicity Category 2

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements





Signal word Danger

Hazard statement Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious

eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Suspected of damaging fertility or the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear

respiratory protection.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated

clothing before reuse.

Storage Store locked up.

Disposal

Hazard(s) not otherwise classified (HNOC)

Dispose of contents/container in accordance with local/regional/national/international regulations. None known.

Supplemental information

83.03% of the mixture consists of component(s) of unknown acute oral toxicity. 98.46% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 85.36% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
4,4'-methylenedicyclohexaneamine		1761-71-3	10 - 20
N,N'-BIS(3-AMINOPROPYL ENEDIAMINE	L)ETHYL	10563-26-5	1 - 2.5
Titanium Dioxide	TITANIUM DIOXIDE	13463-67-7	0.1 - 1
Other components below reportable levels			80 - 90

4. First-aid measures

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a poison center or doctor/physician.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Difficulty in breathing.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

and precautions for firefighte
Fire fighting

Use water spray to cool unopened containers.

equipment/instructions
Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Following product recovery, flush area with water.

Small Spills: Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

······································	
US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1	1910.1000)

Components	Туре	Value	Form
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 Permissible Ex	xposure Limits (PEL) for Miner	al Dusts (29 CFR 1910.1000)
Components	Туре	Value	Form
Titanium Dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Values	(TLV)		·
	(TLV) Type	Value	Form
Components Titanium Dioxide (CAS	· · ·	Value 2.5 mg/m3	Form Respirable finescale particles
Components Titanium Dioxide (CAS	Туре		Respirable finescale
Components Titanium Dioxide (CAS 13463-67-7)	Type TWA	2.5 mg/m3 0.2 mg/m3	Respirable finescale particles Respirable nanoscale
US. ACGIH Threshold Limit Values Components Titanium Dioxide (CAS 13463-67-7) NIOSH. Immediately Dangerous to Components	Type TWA	2.5 mg/m3 0.2 mg/m3	Respirable finescale particles Respirable nanoscale

Biological limit values

13463-67-7)

Appropriate engineering controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally adequate. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Wear positive pressure self-contained breathing apparatus (SCBA).

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Putty
Physical state Solid.
Form Solid.
Color Grey.

Odor Ammoniacal.
Odor threshold Not available.
pH Not available.
Melting point/freezing point Not available.
Initial boiling point and boiling Not available.

range

Flash point 230.0 °F (110.0 °C) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits
Explosive limit - lower (%) Not available.
Explosive limit - upper (%) Not available.

Vapor pressure 0.0004 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density2.06 g/cm3Explosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.

Specific gravity 2.06

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoidContact with incompatible materials.

Incompatible materials Peroxides. Phenols.

Hazardous decompositionNo hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. May cause allergy or asthma symptoms or

breathing difficulties if inhaled. Prolonged inhalation may be harmful.

Skin contact Causes severe skin burns. May cause an allergic skin reaction.

5209 Version #: 04 Revision date: 08-01-2023 Issue date: 06-06-2023

Causes serious eye damage. Eye contact Ingestion Causes digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Difficulty in breathing.

Information on toxicological effects

Not known. **Acute toxicity**

Components **Species Test Results**

Titanium Dioxide (CAS 13463-67-7)

Acute Dermal

LD50 Hamster >= 10000 mg/kg

Oral

LD50 Rat > 10000 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Suspected of damaging fertility or the unborn child. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential

No data is available on the degradability of any ingredients in the mixture.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Dispose of this material and its container to hazardous or special waste collection point. Incinerate **Disposal instructions**

the material under controlled conditions in an approved incinerator. Dispose of contents/container

in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

D002: Waste Corrosive material [pH ≤2 or =>12.5, or corrosive to steel] Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Material name: DEVCON® Wear Guard™ 300RTC Hardener-

5209 Version #: 04 Revision date: 08-01-2023 Issue date: 06-06-2023

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number UN3263

UN proper shipping name

Corrosive solid, basic, organic, n.o.s. (4,4'-methylenedicyclohexaneamine), Limited Quantity

Transport hazard class(es)

Class 8 Subsidiary risk 8 Label(s) Ш Packing group **Environmental hazards**

> Marine pollutant No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB8, IP3, T1, TP33

Packaging exceptions 154 213 Packaging non bulk 240 Packaging bulk

IATA

UN number UN3263

UN proper shipping name Transport hazard class(es) Corrosive solid, basic, organic, n.o.s. (4,4'-methylenedicyclohexaneamine), Limited Quantity

Class 8 Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 8L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Allowed with restrictions. Cargo aircraft only

IMDG

UN number UN3263

UN proper shipping name CORROSIVE SOLID, BASIC, ORGANIC, N.O.S. (4,4'-methylenedicyclohexaneamine), Limited

Quantity

Transport hazard class(es)

Class 8 Subsidiary risk Ш Packing group **Environmental hazards**

Marine pollutant No. **EmS** F-A. S-B

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Not applicable.


Annex II of MARPOL 73/78 and

the IBC Code

Material name: DEVCON® Wear Guard™ 300RTC Hardener-

6/8 5209 Version #: 04 Revision date: 08-01-2023 Issue date: 06-06-2023

DOT; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Yes

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Classified hazard

categories

Skin corrosion or irritation

Serious eye damage or eye irritation

Respiratory or skin sensitization

Reproductive toxicity

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Titanium Dioxide (CAS 13463-67-7)

Material name: DEVCON® Wear Guard™ 300RTC Hardener-5209 Version #: 04 Revision date: 08-01-2023 Issue date: 06-06-2023

California Proposition 65



WARNING: This product can expose you to Titanium Dioxide, which is known to the State of California to

cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical	Yes

Substances (EINECS)

EuropeEuropean List of Notified Chemical Substances (ELINCS)NoJapanInventory of Existing and New Chemical Substances (ENCS)NoKoreaExisting Chemicals List (ECL)YesNew ZealandNew Zealand InventoryNoPhilippinesPhilippine Inventory of Chemicals and Chemical SubstancesNo

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

16. Other information, including date of preparation or last revision

 Issue date
 06-06-2023

 Revision date
 08-01-2023

Version # 04

HMIS® ratings Health: 3*

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 3

Flammability: 1 Instability: 0

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: DEVCON® Wear Guard™ 300RTC Hardener-5209 Version #: 04 Revision date: 08-01-2023 Issue date: 06-06-2023

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).