# SAFETY DATA SHEET

# 1. Identification

Product identifier DEVCON® Zip Patch™ Activator

Other means of identification

**SKU#** 5310A

**Recommended use** Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number978-777-1100

Fax E-mail

**Emergency telephone** 

number

800-424-9300

Supplier Not available.

# 2. Hazard identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2A

Sensitization, skin Category 1
Specific target organ toxicity following single Category 3 respiratory tract irritation

exposure

Environmental hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction.

Causes serious eye irritation. May cause respiratory irritation.

**Precautionary statement** 

**Prevention** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing mist/vapours. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

**Response** IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF

INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTRE/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to

extinguish.

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Storage

Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information

None.

Static accumulating flammable liquid can become electrostatically charged even in bonded and

grounded equipment. Sparks may ignite liquid and vapour. May cause flash fire or explosion.

# 3. Composition/information on ingredients

#### **Mixtures**

Other hazards

Chemical name	Common name and synonyms	CAS number	%
Methyl methacrylate		80-62-6	80 - < 90
PYRIDINE, 3,5-DIETHYL-1,2-DIHYDRO-1-PHE NYL-2-P ROPYL-	<u> </u>	34562-31-7	10 - < 20
Other components below reportable	e levels		1 - < 3

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison Inhalation

centre or doctor/physician if you feel unwell.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

allergic skin reaction. Dermatitis. Rash.

Symptoms may be delayed.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation.

**General information** 

Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

#### 5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapour.

Material name: DEVCON® Zip Patch™ Activator

5310A Version #: 06 Revision date: 28-July-2023 Issue date: 29-May-2019

SDS CANADA

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

# Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions** 

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

# 7. Handling and storage

#### Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

# Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

100 ppm

# 8. Exposure controls/personal protection

#### Occupational exposure limits

US. ACGIH Threshold Limit Values (TLV)				
Components	Туре	Value		
Methyl methacrylate (CAS 80-62-6)	STEL	100 ppm		
	TWA	50 ppm		
Canada. Alberta OELs (Occupation	onal Health & Safety Code, Sc	hedule 1, Table 2), as amended		
Components	Type	Value		
Methyl methacrylate (CAS 80-62-6)	STEL	410 mg/m3		

Material name: DEVCON® Zip Patch™ Activator

Components	Туре	Value	
	TWA	205 mg/m3	
		50 ppm	
Canada. British Columbia C Safety Regulation 296/97, as Components	s amended)	or Chemical Substances, Occupational Health and Value	
	Туре		
Methyl methacrylate (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
Canada. Manitoba OELs (Re Components	eg. 217/2006, The Workplace Safety Ar Type	nd Health Act), as amended Value	
Methyl methacrylate (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
Canada. New Brunswick OE Publication (New Brunswick		sed on the 1991 and 1997 ACGIH TLVs and BEIs	
Components	Туре	Value	
Methyl methacrylate (CAS 80-62-6)	TWA	410 mg/m3	
00-02-0j		100 ppm	
Canada. Ontario OELs. (Con	ntrol of Exposure to Biological or Che	mical Agents), as amended	
Components	Туре	Value	
Methyl methacrylate (CAS 80-62-6)	STEL	100 ppm	
,	TWA	50 ppm	
Canada. Quebec OELs. (Mir Components	nistry of Labor - Regulation respecting Type	occupational health and safety), as amended Value	
Methyl methacrylate (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
Canada. Saskatchewan OEI Components	_s (Occupational Health and Safety Re Type	gulations, 1996, Table 21), as amended Value	
Methyl methacrylate (CAS	15 minute	100 ppm	
80-62-6)			
	8 hour	50 ppm	
ogical limit values	No biological exposure limits noted for		
osure guidelines	·	relevant to the current physical form of the product.	
propriate engineering trols	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommend exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.		
	such as personal protective equipme		
Eye/face protection	Chemical respirator with organic vapou	ar dararage arra ran radoproco.	
	Chemical respirator with organic vapout Wear appropriate chemical resistant gl		
Eye/face protection Skin protection	Wear appropriate chemical resistant gl	loves.	
Eye/face protection Skin protection Hand protection		oves. othing.	

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

# 9. Physical and chemical properties

Appearance Paste.
Physical state Liquid.
Form Paste.

Colour Not available.

Odour Fragrant
Odour threshold Not available.
pH Not available.

Melting point/freezing point -48 °C (-54.4 °F) estimated Initial boiling point and boiling 100.5 °C (212.9 °F) estimated

range

Flash point 10.0 °C (50.0 °F) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 2.1 % estimated

Explosive limit – upper

8.2 % estimated

(%)

Vapour pressure46 hPa estimatedVapour densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 435 °C (815 °F) estimated

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**Density** 0.94 g/cm3 estimated

**Explosive properties** Not explosive.

Flammability class Flammable IB estimated

Oxidising properties Not oxidising.

Specific gravity 0.94 estimated

VOC 87.9 % estimated

<50 g/l

## 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerisation does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidising agents. Nitrates. Peroxides.

Hazardous decomposition No hazardous decomposition products are known.

products

Material name: DEVCON® Zip Patch™ Activator
5310A Version #: 06 Revision date: 28-July-2023 Issue date: 29-May-2019

# 11. Toxicological information

Information on likely routes of exposure

**Inhalation** May cause irritation to the respiratory system.

**Skin contact** Causes skin irritation. May cause an allergic skin reaction.

**Eye contact** Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an

allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

Methyl methacrylate (CAS 80-62-6)

<u>Acute</u>

Oral

LD50 Rat 7800 mg/kg

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitisation

**ACGIH** sensitisation

Methyl methacrylate (CAS 80-62-6)

Dermal sensitisation

Canada - Manitoba OELs Hazard: Dermal sensitization

Methyl methacrylate (CAS 80-62-6)

Dermal sensitisation

Canada - Quebec OELs: Sensitizer

Methyl methacrylate (CAS 80-62-6) Sensitiser.

Canada - Saskatchewan OELs Hazard Data: Sensitiser

Methyl methacrylate (CAS 80-62-6) Sensitiser.

**Respiratory sensitisation** Not a respiratory sensitiser.

**Skin sensitisation** May cause an allergic skin reaction.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

**ACGIH Carcinogens** 

Methyl methacrylate (CAS 80-62-6)

A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Methyl methacrylate (CAS 80-62-6) Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Methyl methacrylate (CAS 80-62-6) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Methyl methacrylate 1.38

Material name: DEVCON® Zip Patch™ Activator
5310A Version #: 06 Revision date: 28-July-2023 Issue date: 29-May-2019

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. Transport information

**TDG** 

**UN** number **UN1133** 

**UN** proper shipping name Transport hazard class(es) ADHESIVES containing flammable liquid, Limited Quantity

**Class** 3 Subsidiary risk **Packing group** Ш No. **Environmental hazards** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

**UN** number UN1133

**UN proper shipping name** Transport hazard class(es)

Adhesives containing flammable liquid, Limited Quantity

Class 3 Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

**IMDG** 

**UN number** UN1133

**UN proper shipping name** 

ADHESIVES containing flammable liquid, Limited Quantity

Transport hazard class(es) 3 Class Subsidiary risk Ш Packing group

**Environmental hazards** 

Marine pollutant No. F-E, S-D

**EmS** 


Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

5310A Version #: 06 Revision date: 28-July-2023 Issue date: 29-May-2019





# 15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

# **Controlled Drugs and Substances Act**

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

**Greenhouse Gases** 

Not listed.

**Precursor Control Regulations** 

Not regulated.

## International regulations

# **Stockholm Convention**

Not applicable.

# **Rotterdam Convention**

Not applicable.

**Kyoto Protocol** 

Not applicable.

**Montreal Protocol** 

Not applicable.

**Basel Convention** 

Not applicable.

## **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No

Country(s) or region Inventory name On inventory (yes/no)\*

Philippines Philippine Inventory of Chemicals and Chemical Substances Y

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information

Issue date29-May-2019Revision date28-July-2023

Version No. 06

**Disclaimer** ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Material name: DEVCON® Zip Patch™ Activator