# SAFETY DATA SHEET

# 1. Identification

Product identifier DEVCON® Wear Guard™ Fine Load Hardener

Other means of identification

**SKU#** 5367

**Recommended use** Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number978-777-1100

Fax E-mail

Emergency telephone

number

800-424-9300

Supplier Not available.

### 2. Hazard identification

Physical hazards Not classified.

**Health hazards** Acute toxicity, inhalation Category 4

Skin corrosion/irritation Category 1
Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1
Reproductive toxicity Category 2

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious

eye damage. Harmful if inhaled. Suspected of damaging fertility or the unborn child.

**Precautionary statement** 

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe mist/vapours. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

**Response** IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off

contaminated clothing and wash it before reuse.

Storage Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

None known.

# 3. Composition/information on ingredients

### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
CORUNDUM		1302-74-5	40 - < 50
ALUMINATE SILICATE		1327-36-2	10 - < 20
4-tert-butylphenol		98-54-4	5 - < 10
Benzene-1,3-dimethaneam	nine	1477-55-0	5 - < 10
TRIMETHYLHEXAMETHYLENEDIA MINE		25620-58-0	3 - < 5
nonyl phenol		84852-15-3	< 1
Titanium dioxide	Titanium dioxide	13463-67-7	< 1
Other components below reportable levels			10 - < 20

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a poison centre or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a physician

or poison control centre immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control centre immediately.

Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed Indication of immediate

Ingestion

medical attention and special treatment needed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s)

involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. General fire hazards No unusual fire or explosion hazards noted.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: DEVCON® Wear Guard™ Fine Load Hardener 5367 Version #: 06 Revision date: 30-July-2023 Issue date: 16-June-2019

# Methods and materials for containment and cleaning up

Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

# **Environmental precautions**

### •

# 7. Handling and storage Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapours. Do not get in eyes, on skin, or on clothing. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

Components	Туре	Value	Form
ALUMINATE SILICATE (CAS 1327-36-2)	TWA	1 mg/m3	Respirable fraction.
Benzene-1,3-dimethaneami ne (CAS 1477-55-0)	Ceiling	0.018 ppm	
Titanium dioxide (CAS 13463-67-7)	TWA	2.5 mg/m3	Respirable finescale particles
		0.2 mg/m3	Respirable nanoscale particles

# Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended

Components	Туре	Value	
Benzene-1,3-dimethaneami ne (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
CORUNDUM (CAS 1302-74-5)	TWA	10 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

# Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
ALUMINATE SILICATE (CAS 1327-36-2)	TWA	1 mg/m3	Respirable.
Benzene-1,3-dimethaneami ne (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
CORUNDUM (CAS 1302-74-5)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Titanium dioxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.

# Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended Components Type Value

ComponentsTypeValueFormALUMINATE SILICATE<br/>(CAS 1327-36-2)TWA1 mg/m3Respirable fraction.

Material name: DEVCON® Wear Guard™ Fine Load Hardener
5367 Version #: 06 Revision date: 30-July-2023 Issue date: 16-June-2019

Components	Туре	Value	Form
Benzene-1,3-dimethaneami ne (CAS 1477-55-0)	Ceiling	0.018 ppm	
Titanium dioxide (CAS 13463-67-7)	TWA	2.5 mg/m3	Respirable finescale particles
		0.2 mg/m3	Respirable nanoscale particles
Canada. New Brunswick OELs: 1 Publication (New Brunswick Reg		(TLVs) Based on the 1991 and 1997 AC	GIH TLVs and BEIs
Components	Туре	Value	
Benzene-1,3-dimethaneami ne (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. Ontario OELs. (Control Components	of Exposure to Biologic Type	cal or Chemical Agents), as amended Value	Form
ALUMINATE SILICATE (CAS 1327-36-2)	TWA	1 mg/m3	Respirable fraction.
Benzene-1,3-dimethaneami ne (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
CORUNDUM (CAS 1302-74-5)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. Quebec OELs. (Ministry	of Labor - Regulation	respecting occupational health and saf	ety), as amended
Components	Type	Value	Form
Benzene-1,3-dimethaneami ne (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
CORUNDUM (CAS 1302-74-5)	TWA	10 mg/m3	Total dust.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Total dust.
Canada. Saskatchewan OELs (O Components	ccupational Health and Type	Safety Regulations, 1996, Table 21), as Value	s amended Form
ALUMINATE SILICATE	15 minute	20 mg/m3	Dust.
(CAS 1327-36-2)	70 11111413	_0g,	
Benzene-1,3-dimethaneami ne (CAS 1477-55-0)	Ceiling	0.1 mg/m3	
/	15 minute	20 mg/m3	
CORUNDUM (CAS			
CORUNDUM (CAS	8 hour	10 mg/m3	
CORUNDUM (CAS 1302-74-5) Titanium dioxide (CAS		10 mg/m3 20 mg/m3	
CORUNDUM (CAS 1302-74-5) Titanium dioxide (CAS 13463-67-7)	8 hour 15 minute	•	
CORUNDUM (CAS 1302-74-5)  Titanium dioxide (CAS 13463-67-7)  ogical limit values  No	8 hour 15 minute biological exposure limit	20 mg/m3	form of the product.
CORUNDUM (CAS 1302-74-5)  Titanium dioxide (CAS 13463-67-7)  ogical limit values  osure guidelines  Oc	8 hour 15 minute biological exposure limit cupational Exposure Lim	20 mg/m3 s noted for the ingredient(s).	form of the product.
CORUNDUM (CAS 1302-74-5)  Titanium dioxide (CAS 13463-67-7)  ogical limit values  osure guidelines  Canada - Alberta OELs: Skin des  Benzene-1,3-dimethaneamine	8 hour 15 minute biological exposure limit cupational Exposure Lim signation c (CAS 1477-55-0)	20 mg/m3 s noted for the ingredient(s).	form of the product.
CORUNDUM (CAS 1302-74-5)  Titanium dioxide (CAS 13463-67-7)  ogical limit values  osure guidelines  Canada - Alberta OELs: Skin des Benzene-1,3-dimethaneamine Canada - British Columbia OELs  Benzene-1,3-dimethaneamine	8 hour 15 minute biological exposure limit cupational Exposure Lim signation (CAS 1477-55-0) Signation (CAS 1477-55-0)	20 mg/m3 s noted for the ingredient(s). its are not relevant to the current physical	form of the product.
CORUNDUM (CAS 1302-74-5)  Titanium dioxide (CAS 13463-67-7)  ogical limit values  osure guidelines  Canada - Alberta OELs: Skin des  Benzene-1,3-dimethaneamine Canada - British Columbia OELs	8 hour 15 minute biological exposure limit ecupational Exposure Limit (CAS 1477-55-0) CAS 1477-55-0) CAS 1477-55-0) CAS 1477-55-0) CAS 1477-55-0)	20 mg/m3 s noted for the ingredient(s). its are not relevant to the current physical Can be absorbed through the skin.	form of the product.

Canada - Quebec OELs: Skin designation

Benzene-1,3-dimethaneamine (CAS 1477-55-0) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Can be absorbed through the skin.

Benzene-1,3-dimethaneamine (CAS 1477-55-0) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation** 

Benzene-1,3-dimethaneamine (CAS 1477-55-0) Danger of cutaneous absorption

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Chemical respirator with organic vapour cartridge and full facepiece. Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

Chemical respirator with organic vapour cartridge and full facepiece. Respiratory protection

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

# 9. Physical and chemical properties

**Appearance** Paste. Liquid. Physical state Paste. **Form** Colour White

Mild. Ammoniacal. Odour **Odour threshold** Not available. Not available. Melting point/freezing point Not available.

Initial boiling point and boiling

range

274 °C (525.2 °F) estimated

Flash point 96.0 °C (204.8 °F) estimated

**Evaporation rate** Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper

(%)

Vapour pressure 0.05 hPa estimated

Not available. Vapour density Not available. Relative density

Solubility(ies)

Not available. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

**Auto-ignition temperature** Not available. Not available. **Decomposition temperature** Not available. **Viscosity** 

Other information

**Density** 1.11 g/cm3 estimated **Explosive properties** Not explosive.

Combustible IIIB estimated Flammability class

**Oxidising properties** Not oxidising. Specific gravity 1.11 estimated 100 % Solids VOC

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability Possibility of hazardous Hazardous polymerisation does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Alkali metals.

Hazardous decomposition No hazardous decomposition products are known.

products

# 11. Toxicological information

## Information on likely routes of exposure

Harmful if inhaled. Inhalation

Causes severe skin burns. May cause an allergic skin reaction. Skin contact

Eye contact Causes serious eye damage. Causes digestive tract burns. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

### Information on toxicological effects

Harmful if inhaled. Acute toxicity

Components **Species Test Results** 

nonyl phenol (CAS 84852-15-3)

Acute **Dermal** 

LD50 Rabbit 2140 mg/kg

Oral

LD50 Rat 1600 mg/kg

Titanium dioxide (CAS 13463-67-7)

Acute **Dermal** 

LD50 Hamster >= 10000 mg/kg

Oral

LD50 Rat > 10000 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

# Respiratory or skin sensitisation

### Canada - Alberta OELs: Irritant

Benzene-1,3-dimethaneamine (CAS 1477-55-0) Irritant CORUNDUM (CAS 1302-74-5) Irritant Titanium dioxide (CAS 13463-67-7) Irritant

Not a respiratory sensitiser. Respiratory sensitisation

May cause an allergic skin reaction. Skin sensitisation

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

### Carcinogenicity

**ACGIH Carcinogens** 

ALUMINATE SILICATE (CAS 1327-36-2) A4 Not classifiable as a human carcinogen.

Titanium dioxide (CAS 13463-67-7) A3 Confirmed animal carcinogen with unknown relevance to

humans.

Canada - Manitoba OELs: carcinogenicity

ALUMINATE SILICATE (CAS 1327-36-2) Not classifiable as a human carcinogen.

Titanium dioxide (CAS 13463-67-7) Confirmed animal carcinogen with unknown relevance to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** 

Not an aspiration hazard.

# 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

No data is available on the degradability of any ingredients in the mixture. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

nonyl phenol 5.71

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. Transport information

**TDG** 

UN2735 **UN** number

**UN proper shipping name** Transport hazard class(es) AMINES, LIQUID, CORROSIVE, N.O.S. (Benzene-1,3-dimethaneamine), Limited Quantity

8 **Class** Subsidiary risk Ш Packing group

**Environmental hazards** No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

**UN** number

Amines, liquid, corrosive, n.o.s. (Benzene-1,3-dimethaneamine) UN proper shipping name

Transport hazard class(es)

8 **Class** Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 8L

Material name: DEVCON® Wear Guard™ Fine Load Hardener

SDS CANADA

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Allowed with restrictions.

Other information

Passenger and cargo

aircraft

Allowed with restrictions. Cargo aircraft only

**IMDG** 

**UN** number UN2735

AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. **UN proper shipping name** 

(Benzene-1,3-dimethaneamine), MARINE POLLUTANT, Limited Quantity

Transport hazard class(es)

8 Class Subsidiary risk Ш Packing group

**Environmental hazards** 

Marine pollutant Yes F-A, S-B


Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

**IATA** 



IMDG; TDG



### Marine pollutant



**General information** IMDG Regulated Marine Pollutant.

# 15. Regulatory information

This product has been classified in accordance with the hazard criteria of the HPR and the SDS Canadian regulations

contains all the information required by the HPR.

**Controlled Drugs and Substances Act** 

Not regulated.

### Export Control List (CEPA 1999, Schedule 3)

Not listed.

### **Greenhouse Gases**

Not listed.

### **Precursor Control Regulations**

Not regulated.

### International regulations

#### Stockholm Convention

Not applicable.

### **Rotterdam Convention**

Not applicable.

### **Kyoto Protocol**

Not applicable.

### **Montreal Protocol**

Not applicable.

### **Basel Convention**

Not applicable.

### **International Inventories**

Country(s) or region

Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances	No

(PICCS)

Inventory name

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

### 16. Other information

Issue date16-June-2019Revision date30-July-2023

Version No. 06

**Disclaimer** ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

On inventory (yes/no)\*

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).