



NOTES:

^[1]FOR $T_A \leq 1\text{-}\frac{1}{2}$ IN (38-MM), CHOCKFAST GRAY OR CHOCKFAST RED VERSAFLOW RECOMMENDED

^[2]FOR $T_A \geq 1\text{-}\frac{1}{2}$ IN (38-MM), CHOCKFAST RED OR ESCOWELD 7505E/7530 RECOMMENDED

^[3]FOR INFORMATION ON ANCHOR BOLT PULLOUT CALCULATIONS AND FURTHER GENERAL CAST-IN-PLACE ANCHOR BOLT RECOMMENDATIONS, PLEASE SEE TECHNICAL GUIDE 691 AT www.itwpp.com/chockfast.

ITW Performance Polymers

DESCRIPTION

GENERAL RECOMMENDATIONS FOR ANCHOR BOLT INSTALLATION

DRAWN BY

CRME

DATE

28-JUN-24

DWG

D

SCALE

NTS

REV

A

ITW PERFORMANCE POLYMERS PROVIDES THE INFORMATION HEREIN ONLY AS A GOOD FAITH GUIDE, AND IT IS NOT AS A SUBSTITUTE FOR THE CUSTOMER'S OWN TESTING OR CALCULATIONS. THE CUSTOMER ASSUMES ALL RESPONSIBILITIES FOR DETERMINING THE SUITABILITY OF THE INFORMATION, OPINIONS, AND OUR PRODUCTS AS TO THE APPROPRIATE USE IN THEIR APPLICATION. THE ENCLOSED INFORMATION DOES NOT CREATE ANY WARRANTY, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OR FITNESS FOR ANY PARTICULAR PURPOSE OR APPLICATION. UNDER NO CIRCUMSTANCES SHALL ITW PERFORMANCE POLYMERS BE LIABLE FOR ANY DAMAGES, WHETHER DIRECT, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES. OUR PRODUCTS ARE INTENDED FOR USE AND SALE TO INDUSTRIAL AND COMMERCIAL CUSTOMERS.

130 Commerce Drive | Montgomeryville | PA 18936 | USA | T: +1-215-855-8450 | E-mail: customerservice.na@itwpp.com | www.itwpp.com/chockfast

Bay 150 | Shannon Industrial Estate | Shannon | County Clare | Ireland | T: +353 61 771 500 | E-mail: customerservice.shannon@itwpp.com