

# SAFETY DATA SHEET

Version #: 05

Issue date: 05-22-2019

Revision date: 07-31-2023

Supersedes date: 06-25-2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name or designation of the mixture** DEVCON® Flexane® Brushable Resin

**Registration number** -

**Synonyms** None.

**SKU#** 6641N

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Not available.

**Uses advised against** None known.

### 1.3. Details of the supplier of the safety data sheet

**Company Name** ITW Performance Polymers

**Address**  
Bay 150  
Shannon Industrial Estate  
Co. Clare  
Ireland  
V14 DF82

**Contact Person** Customer Service

**Telephone Number**  
353(61)771500  
353(61)471285

**Email** customerservice.shannon@itwpp.com

**Emergency Phone Number** 44(0) 1235 239 670 (24 hours)

### 1.4. Emergency telephone number

**General in EU** 112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Austria National Poisons Information Center** +431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Belgium National Poisons Control Center** 070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Bulgaria National Toxicological Information Center** +359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Croatia Poisons Information Center** +385 1 2348 342 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

**Cyprus Poison Center** 1401 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Czech Republic National Poisons Information Center** +420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

**Denmark National Poisons Control Center** +45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**Estonia National Poisons Information Center** 16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)

**Finland National Poison Information Center** (09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

**France National Poisons Control Center** ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

#### 1.4. Emergency telephone number

<b>Greece Poison Information Centre</b>	(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Hungary National Emergency Phone Number</b>	+36-80-201-199 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Iceland Poison Center</b>	(+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Latvia Emergency medical aid</b>	113
<b>Latvia Poison and Drug Information Center</b>	+371 67042473 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Lithuania Neatidēliotina informacija apsinuodijus</b>	+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
<b>Malta Accident and Emergency Department</b>	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
<b>Netherlands National Poisons Information Center (NVIC)</b>	NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel in cases of acute intoxications)
<b>Norway Norwegian Poison Information Center</b>	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Portugal Poison Center</b>	800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Romania Biroul RSI si Informare Toxicologica</b>	021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be available for the Emergency Service.)
<b>Slovakia National Toxicological Information Center</b>	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Spain Toxicology Information Service</b>	+ 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Sweden National Poison Information Center</b>	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
<b>Switzerland Tox Info Suisse</b>	145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

##### Physical hazards

Flammable liquids	Category 2	H225 - Highly flammable liquid and vapor.
-------------------	------------	---

##### Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Respiratory sensitization	Category 1	H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization	Category 1	H317 - May cause an allergic skin reaction.
Carcinogenicity	Category 2	H351 - Suspected of causing cancer.

##### Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 3	H412 - Harmful to aquatic life with long lasting effects.
--	------------	---

### 2.2. Label elements

**Label according to Regulation (EC) No. 1272/2008 as amended****UFI:**

Austria: 5T05-P18D-R006-FE6W  
Belgium: 5T05-P18D-R006-FE6W  
Bulgaria: 5T05-P18D-R006-FE6W  
Croatia: 5T05-P18D-R006-FE6W  
Cyprus: 5T05-P18D-R006-FE6W  
Czech Republic: 5T05-P18D-R006-FE6W  
Denmark: 5T05-P18D-R006-FE6W  
Estonia: 5T05-P18D-R006-FE6W  
EU: 5T05-P18D-R006-FE6W  
Finland: 5T05-P18D-R006-FE6W  
France: 5T05-P18D-R006-FE6W  
Germany: 5T05-P18D-R006-FE6W  
Greece: 5T05-P18D-R006-FE6W  
Hungary: 5T05-P18D-R006-FE6W  
Iceland: 5T05-P18D-R006-FE6W  
Ireland: 5T05-P18D-R006-FE6W  
Italy: 5T05-P18D-R006-FE6W  
Latvia: 5T05-P18D-R006-FE6W  
Lithuania: 5T05-P18D-R006-FE6W  
Luxembourg: 5T05-P18D-R006-FE6W  
Malta: 5T05-P18D-R006-FE6W  
Netherlands: 5T05-P18D-R006-FE6W  
Norway: 5T05-P18D-R006-FE6W  
Poland: 5T05-P18D-R006-FE6W  
Portugal: 5T05-P18D-R006-FE6W  
Romania: 5T05-P18D-R006-FE6W  
Slovakia: 5T05-P18D-R006-FE6W  
Slovenia: 5T05-P18D-R006-FE6W  
Spain: 5T05-P18D-R006-FE6W  
Sweden: 5T05-P18D-R006-FE6W

**Contains:**

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate, 4,4'-methylened(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-diisocyanate, 4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate, Polyether prepolymer of IPDI, MDI and PICM

**Hazard pictograms****Signal word**

Danger

**Hazard statements**

H225	Highly flammable liquid and vapor.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements****Prevention**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P235	Keep cool.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing mist/vapors.
P264	Wash thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P284	Wear respiratory protection.

## Response

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use appropriate media to extinguish.

## Storage

P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

## Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

**Supplemental label information** None.

## 2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Polyether prepolymer of IPDI, MDI and PICM	60 - < 70	N/A	-	-	
<b>Classification:</b> -					
ethyl acetate	20 - < 30	141-78-6 205-500-4	-	607-022-00-5	#
<b>Classification:</b> Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336					
<b>Supplemental Hazard Statement(s):</b> EUH066					
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate	5 - < 10	4098-71-9 223-861-6	-	615-008-00-5	
<b>Classification:</b> Acute Tox. 4;H302;(ATE: 1000 mg/kg bw), Acute Tox. 4;H312;(ATE: 1060 mg/kg bw), Acute Tox. 3;H331;(ATE: 3 mg/l), Skin Irrit. 2;H315, Eye Irrit. 2;H319, Resp. Sens. 1;H334, Skin Sens. 1;H317, STOT SE 3;H335, Aquatic Chronic 2;H411					
<b>Specific Concentration Limits:</b> Resp. Sens. 1;H334: C ≥ 0.5 %, Skin Sens. 1;H317: C ≥ 0.5 %					
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate	5 - < 10	101-68-8 202-966-0	-	615-005-00-9	
<b>Classification:</b> Acute Tox. 4;H332;(ATE: 11 mg/l), Skin Irrit. 2;H315, Eye Irrit. 2;H319, Resp. Sens. 1;H334, Skin Sens. 1;H317, Carc. 2;H351, STOT SE 3;H335, STOT RE 2;H373					
<b>Specific Concentration Limits:</b> Skin Irrit. 2;H315: C ≥ 5 %, Eye Irrit. 2;H319: C ≥ 5 %, Resp. Sens. 1;H334: C ≥ 0.1 %, STOT SE 3;H335: C ≥ 5 %					

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di-isocyanate	1 - < 3	5124-30-1 225-863-2	-	615-009-00-0	
<b>Classification:</b> Acute Tox. 4;H302;(ATE: 1065 mg/kg bw), Acute Tox. 3;H331;(ATE: 3 mg/l), Skin Irrit. 2;H315, Eye Irrit. 2;H319, Resp. Sens. 1;H334, Skin Sens. 1;H317, STOT SE 3;H335					
<b>Specific Concentration Limits:</b> Resp. Sens. 1;H334: C ≥ 0.5 %, Skin Sens. 1;H317: C ≥ 0.5 %					

#### List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** The full text for all H-statements is displayed in section 16.

### SECTION 4: First aid measures

**General information** Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

#### 4.1. Description of first aid measures

**Inhalation** If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a poison center or doctor/physician.

**Skin contact** Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

**4.2. Most important symptoms and effects, both acute and delayed** Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

**4.3. Indication of any immediate medical attention and special treatment needed** Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

### SECTION 5: Firefighting measures

**General fire hazards** Highly flammable liquid and vapor.

#### 5.1. Extinguishing media

**Suitable extinguishing media** Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Water. Do not use water jet as an extinguisher, as this will spread the fire.

**5.2. Special hazards arising from the substance or mixture** Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

#### 5.3. Advice for firefighters

**Special protective equipment for firefighters** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Special fire fighting procedures** In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

**For emergency responders** Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ventilate closed spaces before entering them. Avoid breathing mist/vapors. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

**6.2. Environmental precautions** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

**6.3. Methods and material for containment and cleaning up** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers.

**6.4. Reference to other sections** For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

**7.2. Conditions for safe storage, including any incompatibilities** Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances  
 Hazard categories in accordance with Regulation (EC) No 1272/2008  
 - P5a, b or c FLAMMABLE LIQUIDS (Lower-tier requirements = 50 tons; Upper-tier requirements = 200 tons)

**7.3. Specific end use(s)** Observe industrial sector guidance on best practices.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001, as amended

Components	Type	Value
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	Ceiling	0,092 mg/m3
		0,01 ppm
	MAK	0,046 mg/m3 0,005 ppm
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di-isocyanate (CAS 5124-30-1)	Ceiling	0,054 mg/m3
		0,005 ppm
	MAK	0,054 mg/m3

**Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001, as amended**

Components	Type	Value
		0,005 ppm
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1]	Ceiling	0,1 mg/m3
2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2]		
o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3]		
methylenediphenyl diisocyanate (CAS 101-68-8)		0,01 ppm
	MAK	0,05 mg/m3
		0,005 ppm
ethyl acetate (CAS 141-78-6)	MAK	734 mg/m3
		200 ppm
	STEL	1468 mg/m3
		400 ppm

**Belgium. OEL. Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1 - Chemical agents, as amended**

Components	Type	Value
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	TWA	0,046 mg/m3
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-diisocyanate (CAS 5124-30-1)	TWA	0,005 ppm 0,055 mg/m3
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1]	TWA	0,005 ppm 0,052 mg/m3
2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2]		
o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3]		
methylenediphenyl diisocyanate (CAS 101-68-8)		0,005 ppm
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m3
		400 ppm
	TWA	734 mg/m3
		200 ppm

**Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as amended**

Components	Type	Value
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	TWA	0,1 mg/m <sup>3</sup>
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1]	STEL	0,07 mg/m <sup>3</sup>
2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2]		
o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3]		
methylenediphenyl diisocyanate (CAS 101-68-8)	TWA	0,05 mg/m <sup>3</sup>
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m <sup>3</sup>
		400 ppm
	TWA	734 mg/m <sup>3</sup>
		200 ppm

**Croatia. OELs (GVI). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and Biological Limit Values, Annex I (NN 91/2018), as amended**

Components	Type	Value
ethyl acetate (CAS 141-78-6)	MAC	734 mg/m <sup>3</sup>
		200 ppm
	STEL	1468 mg/m <sup>3</sup>
		400 ppm

**Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended**

Components	Type	Value
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1]	TWA	0,2 mg/m <sup>3</sup>
2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2]		
o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3]		
methylenediphenyl diisocyanate (CAS 101-68-8)		0,02 ppm

**Cyprus. OELs. Occupational Exposure Limit Values of Chemicals at Work (Safety and Health at Work (Chem. Agents) Reg., Ann. 1, R.A.A. 268/2001, as amended)**

Components	Type	Value
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m <sup>3</sup>
		400 ppm
	TWA	734 mg/m <sup>3</sup>
		200 ppm



**Czech Republic. Occupational exposure limit values of chemicals at work (Decree on protection of health at work, 361/2007, Annex 2, Part A & Annex 3, Part A, as amended)**

Components	Type	Value
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	Ceiling	0,1 mg/m <sup>3</sup>
	TWA	0,05 mg/m <sup>3</sup>
ethyl acetate (CAS 141-78-6)	Ceiling	900 mg/m <sup>3</sup>
	TWA	700 mg/m <sup>3</sup>

**Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, Annex 2**

Components	Type	Value
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	TLV	0,045 mg/m <sup>3</sup>
		0,005 ppm
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-diisocyanate (CAS 5124-30-1)	TLV	0,054 mg/m <sup>3</sup>
		0,005 ppm
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	TLV	0,05 mg/m <sup>3</sup>
		0,005 ppm
ethyl acetate (CAS 141-78-6)	TLV	540 mg/m <sup>3</sup>
		150 ppm

**Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended**

Components	Type	Value
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	STEL	0,09 mg/m <sup>3</sup>
		0,01 ppm
	TWA	0,05 mg/m <sup>3</sup>
		0,005 ppm

**Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended**

Components	Type	Value
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di-isocyanate (CAS 5124-30-1)	STEL	0,01 ppm
	TWA	0,005 ppm
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1]	STEL	0,1 mg/m3
2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2]		
o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3]		
methylenediphenyl diisocyanate (CAS 101-68-8)		0,01 ppm
	TWA	0,05 mg/m3
		0,005 ppm
ethyl acetate (CAS 141-78-6)	STEL	1100 mg/m3
		300 ppm
	TWA	500 mg/m3
		150 ppm

**Finland. HTP-arvot, App 3., Binding Limit Values, Social Affairs and Ministry of Health**

Components	Type	Value
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	STEL	0,035 mg/m3
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di-isocyanate (CAS 5124-30-1)	STEL	0,035 mg/m3
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1]	STEL	0,035 mg/m3
2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2]		
o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3]		
methylenediphenyl diisocyanate (CAS 101-68-8)		
ethyl acetate (CAS 141-78-6)	STEL	1470 mg/m3
		400 ppm
	TWA	730 mg/m3
		200 ppm

**France. OELs. Occupational Exposure Limits as Prescribed by Art. R.4412-149 of Labor Code, as amended**

Components	Type	Value
ethyl acetate (CAS 141-78-6)	VLE	1468 mg/m3

**France. OELs. Occupational Exposure Limits as Prescribed by Art. R.4412-149 of Labor Code, as amended**

Components	Type	Value
		400 ppm
	VME	734 mg/m3
		200 ppm

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

Components	Type	Value
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	VLE	0,18 mg/m3
<b>Regulatory status:</b> Indicative limit (VL)		
		0,02 ppm
<b>Regulatory status:</b> Indicative limit (VL)		
	VME	0,09 mg/m3
<b>Regulatory status:</b> Indicative limit (VL)		
		0,01 ppm
<b>Regulatory status:</b> Indicative limit (VL)		
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1]	VLE	0,2 mg/m3
2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2]		
o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3]		
methylenediphenyl diisocyanate (CAS 101-68-8)		
<b>Regulatory status:</b> Indicative limit (VL)		
		0,02 ppm
<b>Regulatory status:</b> Indicative limit (VL)		
	VME	0,1 mg/m3
<b>Regulatory status:</b> Indicative limit (VL)		
		0,01 ppm
<b>Regulatory status:</b> Indicative limit (VL)		
ethyl acetate (CAS 141-78-6)	VLE	1468 mg/m3
<b>Regulatory status:</b> Regulatory binding (VRC)		
		400 ppm
<b>Regulatory status:</b> Regulatory binding (VRC)		
	VME	734 mg/m3
<b>Regulatory status:</b> Regulatory binding (VRC)		
		200 ppm
<b>Regulatory status:</b> Regulatory binding (VRC)		

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG), as updated**

Components	Type	Value	Form
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	TWA	0,046 mg/m3	Vapor and aerosol.
		0,005 ppm	Vapor and aerosol.

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG), as updated**

Components	Type	Value	Form
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	TWA	0,05 mg/m <sup>3</sup>	Inhalable fraction.
ethyl acetate (CAS 141-78-6)	TWA	750 mg/m <sup>3</sup> 200 ppm	

**Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace**

Components	Type	Value	Form
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone diisocyanate (CAS 4098-71-9)	AGW	0,046 mg/m <sup>3</sup> 0,005 ppm	Vapor and aerosol.
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	AGW	0,05 mg/m <sup>3</sup>	Inhalable fraction.
ethyl acetate (CAS 141-78-6)	AGW	730 mg/m <sup>3</sup> 200 ppm	

**Greece. OELs, Presidential Decree No. 307/1986, as amended**

Components	Type	Value
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone diisocyanate (CAS 4098-71-9)	STEL	0,18 mg/m <sup>3</sup> 0,02 ppm
	TWA	0,09 mg/m <sup>3</sup> 0,01 ppm
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-diisocyanate (CAS 5124-30-1)	STEL	0,11 mg/m <sup>3</sup>
	TWA	0,01 ppm 0,11 mg/m <sup>3</sup> 0,01 ppm

**Greece. OELs, Presidential Decree No. 307/1986, as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	STEL	0,2 mg/m3
		0,02 ppm
	TWA	0,2 mg/m3
ethyl acetate (CAS 141-78-6)	STEL	0,02 ppm 1468 mg/m3
		400 ppm
	TWA	734 mg/m3 200 ppm

**Hungary. OELs. Decree on protection of workers exposed to chemical agents (5/2020. (II.6)), Annex 1&2, as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	STEL	0,05 mg/m3
		0,05 mg/m3
	TWA	0,05 mg/m3
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m3
		734 mg/m3
	TWA	734 mg/m3

**Iceland. OELs. Regulation 390/2009 on Pollution Limits and Measures to Reduce Pollution at the Workplace, as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	STEL	0,09 mg/m3
		0,01 ppm
	TWA	0,05 mg/m3 0,005 ppm
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-diisocyanate (CAS 5124-30-1)	TWA	0,054 mg/m3
		0,005 ppm
		0,005 ppm

**Iceland. OELs. Regulation 390/2009 on Pollution Limits and Measures to Reduce Pollution at the Workplace, as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	STEL	0,1 mg/m <sup>3</sup>
		0,01 ppm
	TWA	0,05 mg/m <sup>3</sup>
		0,005 ppm
ethyl acetate (CAS 141-78-6)	TWA	540 mg/m <sup>3</sup>
		150 ppm

**Ireland. OELVs, Schedules 1 & 2, Code of Practice for Chemical Agents and Carcinogens Regulations**

<b>Components</b>	<b>Type</b>	<b>Value</b>
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	STEL	0,07 mg/m <sup>3</sup>
	TWA	0,005 ppm
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	STEL	0,07 mg/m <sup>3</sup>
	TWA	0,005 ppm
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m <sup>3</sup>
		400 ppm
	TWA	734 mg/m <sup>3</sup>
		200 ppm

**Italy. OELs (Legislative Decree n.81, 9 April 2008), as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	TWA	0,005 ppm
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-diisocyanate (CAS 5124-30-1)	TWA	0,005 ppm

**Italy. OELs (Legislative Decree n.81, 9 April 2008), as amended**

Components	Type	Value
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	TWA	0,005 ppm
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m3
		400 ppm
	TWA	734 mg/m3
		200 ppm

**Latvia. OELs. Occupational Exposure Limits of Chemical Substances at Workplace (Reg. No. 325/ 2007, L.V. 80, Annex 1), as amended**

Components	Type	Value
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m3
		400 ppm
	TWA	200 mg/m3
		54 ppm

**Lithuania. OELs. Occupational Exposure Limit Values for Chemical Substances (Hygiene Norm HN 23:2011; Order No. V-824/A1-389), as amended**

Components	Type	Value
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	Ceiling	0,09 mg/m3
		0,01 ppm
	TWA	0,05 mg/m3
		0,005 ppm
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-diisocyanate (CAS 5124-30-1)	Ceiling	0,01 ppm
	TWA	0,005 ppm
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	Ceiling	0,1 mg/m3
		0,01 ppm
	TWA	0,05 mg/m3
		0,005 ppm

**Lithuania. OELs. Occupational Exposure Limit Values for Chemical Substances (Hygiene Norm HN 23:2011; Order No. V-824/A1-389), as amended**

Components	Type	Value
ethyl acetate (CAS 141-78-6)	Ceiling	1100 mg/m <sup>3</sup>
		300 ppm
	TWA	500 mg/m <sup>3</sup>
		150 ppm

**Luxembourg. OELs. Binding Occupational Exposure Limit Values (Annex I), G.D.R. of 14 November 2016, OJ Memorial A, n ° 235/2016, as amended**

Components	Type	Value
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m <sup>3</sup>
		400 ppm
	TWA	734 mg/m <sup>3</sup>
		200 ppm

**Malta. OELs. Protection of Health and Safety of Workers from Risks related to Chemical Agents at Work (L.N 227/2003 Schedules I and V), as amended**

Components	Type	Value
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m <sup>3</sup>
		400 ppm
	TWA	734 mg/m <sup>3</sup>
		200 ppm

**Netherlands. OELs per Annex XIII of Working Conditions Regulation (Staatscourant no. 252, 29 December 2006), as amended**

Components	Type	Value
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m <sup>3</sup>
	TWA	734 mg/m <sup>3</sup>

**Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended**

Components	Type	Value
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	STEL	0,01 ppm
	TLV	0,045 mg/m <sup>3</sup>
		0,005 ppm
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di-isocyanate (CAS 5124-30-1)	STEL	0,01 ppm
	TLV	0,05 mg/m <sup>3</sup>
		0,005 ppm
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane-2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	STEL	0,01 ppm



**Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended**

Components	Type	Value
	TLV	0,05 mg/m <sup>3</sup> 0,005 ppm
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m <sup>3</sup> 400 ppm
	TLV	734 mg/m <sup>3</sup> 200 ppm

**Poland. Maximum permissible concentrations and intensities of harmful factors in the work environment (Dz.U.Poz. 1286/2018, Annex 1)**

Components	Type	Value
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	TWA	0,04 mg/m <sup>3</sup>
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	STEL	0,09 mg/m <sup>3</sup>
	TWA	0,03 mg/m <sup>3</sup>
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m <sup>3</sup>
	TWA	734 mg/m <sup>3</sup>

**Portugal. Decree-Law No. 24/2012, Occupational Exposure Limit Values, Annex II, as amended**

Components	Type	Value
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m <sup>3</sup> 400 ppm
	TWA	734 mg/m <sup>3</sup> 200 ppm

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796-2014)**

Components	Type	Value
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	TWA	0,005 ppm
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-diisocyanate (CAS 5124-30-1)	TWA	0,005 ppm

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796-2014)**

Components	Type	Value
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	TWA	0,005 ppm
ethyl acetate (CAS 141-78-6)	TWA	400 ppm

**Romania. OELs. Limit Values of Chemical Agents at Workplace (Regulation 1.218/2006, M.O 845, Annex 1, 3&4, as amended)**

Components	Type	Value
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	STEL	0,15 mg/m3
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m3
	TWA	400 ppm 734 mg/m3 200 ppm

**Slovakia. OELs. Maximum permissible exposure limits for chemical factors in workplace air (Regulation No 355/2006, Annex 1, Table 1, as amended)**

Components	Type	Value
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	TWA	0,03 mg/m3
ethyl acetate (CAS 141-78-6)	STEL	0,002 ppm 1468 mg/m3
	TWA	400 ppm 734 mg/m3 200 ppm

**Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Annex I), as amended**

Components	Type	Value
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	TWA	0,046 mg/m <sup>3</sup>
		0,005 ppm
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	TWA	0,05 mg/m <sup>3</sup>
		0,005 ppm
ethyl acetate (CAS 141-78-6)	TWA	734 mg/m <sup>3</sup>
		200 ppm

**Spain. OELs. INSST, Límites de Exposición Profesional Para Agentes Químicos, Table 1-Valores Límites Ambientales (VLAs)**

Components	Type	Value
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	TWA	0,046 mg/m <sup>3</sup>
		0,005 ppm
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-diisocyanate (CAS 5124-30-1)	TWA	0,055 mg/m <sup>3</sup>
		0,005 ppm
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	TWA	0,052 mg/m <sup>3</sup>
		0,005 ppm
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m <sup>3</sup>
		400 ppm
	TWA	734 mg/m <sup>3</sup>
		200 ppm

**Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	Ceiling	0,046 mg/m <sup>3</sup>
		0,005 ppm
	TWA	0,018 mg/m <sup>3</sup> 0,002 ppm
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di-isocyanate (CAS 5124-30-1)	Ceiling	0,005 ppm
	TWA	0,002 ppm
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane-2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	Ceiling	0,05 mg/m <sup>3</sup>
		0,005 ppm
	TWA	0,03 mg/m <sup>3</sup> 0,002 ppm
ethyl acetate (CAS 141-78-6)	Ceiling	1100 mg/m <sup>3</sup>
		300 ppm
	TWA	550 mg/m <sup>3</sup> 150 ppm

**Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte**

<b>Components</b>	<b>Type</b>	<b>Value</b>
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	STEL	0,02 mg/m <sup>3</sup>
	TWA	0,02 mg/m <sup>3</sup>
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di-isocyanate (CAS 5124-30-1)	STEL	0,02 mg/m <sup>3</sup>
	TWA	0,02 mg/m <sup>3</sup>

**Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte**

Components	Type	Value
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	STEL	0,02 mg/m3
	TWA	0,02 mg/m3
ethyl acetate (CAS 141-78-6)	STEL	1460 mg/m3
		400 ppm
	TWA	730 mg/m3
		200 ppm

**UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1**

Components	Type	Value
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	STEL	0,07 mg/m3
	TWA	0,02 mg/m3
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-diisocyanate (CAS 5124-30-1)	STEL	0,07 mg/m3
	TWA	0,02 mg/m3
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	STEL	0,07 mg/m3
	TWA	0,02 mg/m3
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m3
		400 ppm
	TWA	734 mg/m3
		200 ppm

**EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU**

Components	Type	Value
ethyl acetate (CAS 141-78-6)	STEL	1468 mg/m3
		400 ppm
	TWA	734 mg/m3
		200 ppm

**Biological limit values****Hungary. BELs. Decree on protection of workers exposed to chemical agents (5/2020. (II.6)), Annex 3&4, as amended**

Components	Value	Determinant	Specimen	Sampling Time
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	0,05 µmol/l	4,4'-Diaminodiphenyl following hydrolysis	Urine	*
	0,01 mg/l	4,4'-Diaminodiphenyl following hydrolysis	Urine	*

\* - For sampling details, please see the source document.

**Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle BAT-Werte**

Components	Value	Determinant	Specimen	Sampling Time
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	10 µg/g	4,4'-Diaminodiphenylmethane	Creatinine in urine	*

\* - For sampling details, please see the source document.

**UK. BELs. Biological Monitoring Guidance Values (BMGVs) (EH40/2005 (Fourth Edition 2020)), Table 2**

Components	Value	Determinant	Specimen	Sampling Time
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)	1 µmol/mol	Isocyanate-derived diamine	Creatinine in urine	*
4,4'-methylenedi(cyclohexyl)isocyanate); dicyclohexylmethane-4,4'-diisocyanate (CAS 5124-30-1)	1 µmol/mol	Isocyanate-derived diamine	Creatinine in urine	*
4,4'-methylenediphenyl diisocyanate; diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)	1 µmol/mol	Isocyanate-derived diamine	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no effect levels (DNELs)** Not available.

**Predicted no effect concentrations (PNECs)** Not available.

## Exposure guidelines

### Belgium OELs: Skin designation

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; Can be absorbed through the skin.  
isophorone di-isocyanate (CAS 4098-71-9)

### Germany DFG MAK (advisory): Skin designation

4,4'-methylenediphenyl diisocyanate; Can be absorbed through the skin.  
diphenylmethane4,4'-diisocyanate; [1]  
2,2'-methylenediphenyl diisocyanate;  
diphenylmethane2,2'-diisocyanate; [2]  
o-(p-isocyanatobenzyl)phenyl isocyanate;  
diphenylmethane-2,4'-diisocyanate; [3]  
methylenediphenyl diisocyanate (CAS 101-68-8)

### Germany TRGS 900 Limit Values: Skin designation

4,4'-methylenediphenyl diisocyanate; Can be absorbed through the skin.  
diphenylmethane4,4'-diisocyanate; [1]  
2,2'-methylenediphenyl diisocyanate;  
diphenylmethane2,2'-diisocyanate; [2]  
o-(p-isocyanatobenzyl)phenyl isocyanate;  
diphenylmethane-2,4'-diisocyanate; [3]  
methylenediphenyl diisocyanate (CAS 101-68-8)

### Greece OEL: Skin designation

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; Can be absorbed through the skin.  
isophorone di-isocyanate (CAS 4098-71-9)  
ethyl acetate (CAS 141-78-6) Can be absorbed through the skin.

### Iceland OELs: Skin designation

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; Can be absorbed through the skin.  
isophorone di-isocyanate (CAS 4098-71-9)

### Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

4,4'-methylenediphenyl diisocyanate; Can be absorbed through the skin.  
diphenylmethane4,4'-diisocyanate; [1]  
2,2'-methylenediphenyl diisocyanate;  
diphenylmethane2,2'-diisocyanate; [2]  
o-(p-isocyanatobenzyl)phenyl isocyanate;  
diphenylmethane-2,4'-diisocyanate; [3]  
methylenediphenyl diisocyanate (CAS 101-68-8)

### Switzerland SUVA Limit Values at the Workplace: Skin designation

4,4'-methylenediphenyl diisocyanate; Can be absorbed through the skin.  
diphenylmethane4,4'-diisocyanate; [1]  
2,2'-methylenediphenyl diisocyanate;  
diphenylmethane2,2'-diisocyanate; [2]  
o-(p-isocyanatobenzyl)phenyl isocyanate;  
diphenylmethane-2,4'-diisocyanate; [3]  
methylenediphenyl diisocyanate (CAS 101-68-8)

## 8.2. Exposure controls

**Appropriate engineering controls** Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

### Individual protection measures, such as personal protective equipment

**General information** Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

**Eye/face protection** Chemical respirator with organic vapor cartridge and full facepiece.

#### Skin protection

**- Hand protection** Wear appropriate chemical resistant gloves.

**- Other** Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection** Chemical respirator with organic vapor cartridge and full facepiece.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

<b>Hygiene measures</b>	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.
<b>Environmental exposure controls</b>	Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Colorless
<b>Odor</b>	Solvent.
<b>Melting point/freezing point</b>	-117,4 °F (-83 °C) estimated
<b>Boiling point or initial boiling point and boiling range</b>	170,6 °F (77 °C) estimated
<b>Flammability</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Explosive limit - lower (%)</b>	2 %
<b>Explosive limit - upper (%)</b>	11 %
<b>Flash point</b>	24,0 °F (-4,4 °C) estimated
<b>Auto-ignition temperature</b>	800 °F (426,67 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>pH</b>	Not available.
<b>Kinematic viscosity</b>	Not available.
<b>Solubility</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water) (log value)</b>	Not available.
<b>Vapor pressure</b>	86,32 hPa estimated
<b>Density and/or relative density</b>	
<b>Density</b>	0,98 g/cm3 estimated
<b>Vapor density</b>	Not available.
<b>Particle characteristics</b>	Not available.

### 9.2. Other information

**9.2.1. Information with regard to physical hazard classes** No relevant additional information available.

#### 9.2.2. Other safety characteristics

**Specific gravity** 0,98 estimated

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>10.2. Chemical stability</b>	Material is stable under normal conditions.
<b>10.3. Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>10.4. Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>10.5. Incompatible materials</b>	Acids. Strong oxidizing agents. Alcohols. Amides. Amines. Nitrates. Phenols.
<b>10.6. Hazardous decomposition products</b>	No hazardous decomposition products are known.

## SECTION 11: Toxicological information

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

### Information on likely routes of exposure

**Inhalation** May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation may be harmful.



<b>Skin contact</b>	Causes skin irritation. May cause an allergic skin reaction.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
<b>Symptoms</b>	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity** Not known.

Components	Species	Test Results
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate (CAS 4098-71-9)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rat	1060 mg/kg
<b>Oral</b>		
LD50	Rat	> 1000 mg/kg
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di-isocyanate (CAS 5124-30-1)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 10000 mg/kg
<b>Oral</b>		
LD50	Rat	1065 mg/kg
ethyl acetate (CAS 141-78-6)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rabbit	4,9000000000000004 g/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	
<b>Respiratory sensitization</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
<b>Skin sensitization</b>	May cause an allergic skin reaction.	
<b>Germ cell mutagenicity</b>	Due to partial or complete lack of data the classification is not possible.	
<b>Carcinogenicity</b>	Suspected of causing cancer.	

#### Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane-2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8)

#### IARC Monographs. Overall Evaluation of Carcinogenicity

4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane-2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8) 3 Not classifiable as to carcinogenicity to humans.

#### Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane-2,2'-diisocyanate; [2] o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate (CAS 101-68-8) Carcinogenic, Category 2.

**Reproductive toxicity** Due to partial or complete lack of data the classification is not possible.

**Specific target organ toxicity - single exposure** Not applicable.

**Specific target organ toxicity - repeated exposure** Due to partial or complete lack of data the classification is not possible.

**Aspiration hazard** Due to partial or complete lack of data the classification is not possible.

**Mixture versus substance information** No information available.

## 11.2. Information on other hazards

**Endocrine disrupting properties** This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.

**Other information** Not available.

## SECTION 12: Ecological information

**12.1. Toxicity** Harmful to aquatic life with long lasting effects. Based on available data, the classification criteria are not met for hazardous to the aquatic environment, acute hazard.

**12.2. Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

### 12.3. Bioaccumulative potential

#### Partition coefficient

##### n-octanol/water (log Kow)

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; isophorone di-isocyanate 4,75

4,4'-methylenediphenyl diisocyanate; 5,22

diphenylmethane4,4'-diisocyanate; [1] 2,2'-methylenediphenyl diisocyanate; diphenylmethane2,2'-diisocyanate; [2]

o-(p-isocyanatobenzyl)phenyl isocyanate;

diphenylmethane-2,4'-diisocyanate; [3] methylenediphenyl diisocyanate

**Bioconcentration factor (BCF)** Not available.

**12.4. Mobility in soil** No data available.

**12.5. Results of PBT and vPvB assessment** This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

**12.6. Endocrine disrupting properties** This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.

**12.7. Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Residual waste** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**EU waste code** The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Disposal methods/information** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Special precautions** Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

**14.1. UN number** UN1139

**14.2. UN proper shipping name** COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining)

**14.3. Transport hazard class(es)**

**Class** 3

**Subsidiary risk** -

**Label(s)** 3

**Hazard No. (ADR)** 30  
**Tunnel restriction code** D/E  
**14.4. Packing group** III  
**14.5. Environmental hazards** No.  
**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

#### RID

**14.1. UN number** UN1139  
**14.2. UN proper shipping name** COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining), Limited Quantity  
**14.3. Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**Label(s)** 3  
**14.4. Packing group** III  
**14.5. Environmental hazards** No.  
**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

#### ADN

**14.1. UN number** UN1139  
**14.2. UN proper shipping name** COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining)  
**14.3. Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**Label(s)** 3  
**14.4. Packing group** III  
**14.5. Environmental hazards** No.  
**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

#### IATA

**14.1. UN number** UN1139  
**14.2. UN proper shipping name** Coating solution (includes surface treatments or coatings used for industrial or other purposes such as vehicle undercoating, drum or barrel lining), Limited Quantity  
**14.3. Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**14.4. Packing group** III  
**14.5. Environmental hazards** No.  
**ERG Code** 3L  
**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Other information**  
**Passenger and cargo aircraft** Allowed with restrictions.  
**Cargo aircraft only** Allowed with restrictions.


#### IMDG

**14.1. UN number** UN1139  
**14.2. UN proper shipping name** COATING SOLUTION (includes surface treatments or coatings used for industrial purposes such as vehicle under-coating, drum or barrel lining), Limited Quantity  
**14.3. Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**14.4. Packing group** III  
**14.5. Environmental hazards**  
**Marine pollutant** No.  
**EmS** F-E, S-E  
**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**14.7. Maritime transport in bulk according to IMO instruments** Not established.


ADN; ADR



IATA



IMDG; RID



## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

**Regulation (EC) No. 1005/2009** on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

**Regulation (EU) 2019/1021** On persistent organic pollutants (recast), as amended

Not listed.

**Regulation (EU) No. 649/2012** concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

**Regulation (EU) No. 649/2012** concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

**Regulation (EU) No. 649/2012** concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

**Regulation (EU) No. 649/2012** concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

**Regulation (EC) No. 166/2006** Annex II Pollutant Release and Transfer Registry, as amended

ethyl acetate (CAS 141-78-6)

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List** as currently published by ECHA

Not listed.

**UFI:**

Austria: 5T05-P18D-R006-FE6W  
 Belgium: 5T05-P18D-R006-FE6W  
 Bulgaria: 5T05-P18D-R006-FE6W  
 Croatia: 5T05-P18D-R006-FE6W  
 Cyprus: 5T05-P18D-R006-FE6W  
 Czech Republic: 5T05-P18D-R006-FE6W  
 Denmark: 5T05-P18D-R006-FE6W  
 Estonia: 5T05-P18D-R006-FE6W  
 EU: 5T05-P18D-R006-FE6W  
 Finland: 5T05-P18D-R006-FE6W  
 France: 5T05-P18D-R006-FE6W  
 Germany: 5T05-P18D-R006-FE6W  
 Greece: 5T05-P18D-R006-FE6W  
 Hungary: 5T05-P18D-R006-FE6W  
 Iceland: 5T05-P18D-R006-FE6W  
 Ireland: 5T05-P18D-R006-FE6W  
 Italy: 5T05-P18D-R006-FE6W  
 Latvia: 5T05-P18D-R006-FE6W  
 Lithuania: 5T05-P18D-R006-FE6W  
 Luxembourg: 5T05-P18D-R006-FE6W  
 Malta: 5T05-P18D-R006-FE6W  
 Netherlands: 5T05-P18D-R006-FE6W  
 Norway: 5T05-P18D-R006-FE6W  
 Poland: 5T05-P18D-R006-FE6W  
 Portugal: 5T05-P18D-R006-FE6W  
 Romania: 5T05-P18D-R006-FE6W  
 Slovakia: 5T05-P18D-R006-FE6W  
 Slovenia: 5T05-P18D-R006-FE6W  
 Spain: 5T05-P18D-R006-FE6W  
 Sweden: 5T05-P18D-R006-FE6W

**Authorizations****Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

**Restrictions on use****Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered**

4,4'-methylenediphenyl diisocyanate;	56
diphenylmethane-4,4'-diisocyanate; [1]	
2,2'-methylenediphenyl diisocyanate;	
diphenylmethane-2,2'-diisocyanate; [2]	
o-(p-isocyanatobenzyl)phenyl isocyanate;	
diphenylmethane-2,4'-diisocyanate; [3]	
methylenediphenyl diisocyanate (CAS 101-68-8)	

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended**

Not listed.

**Other EU regulations**

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances  
 Hazard categories in accordance with Regulation (EC) No 1272/2008  
 - P5a, b or c FLAMMABLE LIQUIDS

**Other regulations**

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

**National regulations**

According to Directive 92/85/EEC as amended, pregnant women should not work with the product, if there is the least risk of exposure.

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

**France regulations****France INRS Table of Occupational Diseases**

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate;	Affections professionnelles provoquées par les isocyanates organiques 62
isophorone di-isocyanate (CAS 4098-71-9)	
4,4'-methylenedi(cyclohexyl isocyanate);	Affections professionnelles provoquées par les isocyanates organiques 62
dicyclohexylmethane-4,4'-di-isocyanate (CAS 5124-30-1)	

4,4'-methylenediphenyl diisocyanate;  
diphenylmethane4,4'-diisocyanate; [1]  
2,2'-methylenediphenyl diisocyanate;  
diphenylmethane2,2'-diisocyanate; [2]  
o-(p-isocyanatobenzyl)phenyl isocyanate;  
diphenylmethane-2,4'-diisocyanate; [3]  
methylenediphenyl diisocyanate (CAS 101-68-8)  
ethyl acetate (CAS 141-78-6)

Affections professionnelles provoquées par les isocyanates organiques 62

Affections engendrées par les solvants organiques liquides à usage professionnel : hydrocarbures liquides aliphatiques ou cycliques saturés ou insaturés et leurs mélanges; hydrocarbures halogénés liquides; dérivés nitrés des hydrocarbures aliphatiques; al 84

#### Product registration number

<b>Austria</b>	UFI: 5T05-P18D-R006-FE6W
<b>Belgium</b>	UFI: 5T05-P18D-R006-FE6W
<b>Czech Republic</b>	UFI: 5T05-P18D-R006-FE6W
<b>Denmark</b>	UFI: 5T05-P18D-R006-FE6W
<b>European Union</b>	UFI: 5T05-P18D-R006-FE6W
<b>Finland</b>	UFI: 5T05-P18D-R006-FE6W
<b>France</b>	UFI: 5T05-P18D-R006-FE6W
<b>Germany</b>	UFI: 5T05-P18D-R006-FE6W
<b>Greece</b>	UFI: 5T05-P18D-R006-FE6W
<b>Hungary</b>	UFI: 5T05-P18D-R006-FE6W
<b>Italy</b>	UFI: 5T05-P18D-R006-FE6W
<b>Netherlands</b>	UFI: 5T05-P18D-R006-FE6W
<b>Norway</b>	UFI: 5T05-P18D-R006-FE6W
<b>Poland</b>	UFI: 5T05-P18D-R006-FE6W
<b>Portugal</b>	UFI: 5T05-P18D-R006-FE6W
<b>Slovakia</b>	UFI: 5T05-P18D-R006-FE6W
<b>Slovenia</b>	UFI: 5T05-P18D-R006-FE6W
<b>Spain</b>	UFI: 5T05-P18D-R006-FE6W
<b>Sweden</b>	UFI: 5T05-P18D-R006-FE6W
<b>Switzerland</b>	UFI: 5T05-P18D-R006-FE6W

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

### SECTION 16: Other information

#### List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.  
ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.  
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).  
CAS: Chemical Abstract Service.  
CEN: European Committee for Standardization.  
IATA: International Air Transport Association.  
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.  
IMDG: International Maritime Dangerous Goods.  
MAC: Maximum Allowed Concentration.  
MARPOL: International Convention for the Prevention of Pollution from Ships.  
PBT: Persistent, bioaccumulative and toxic.  
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.  
STEL: Short term exposure limit.  
TLV: Threshold Limit Value.  
TWA: Time Weighted Average.  
VLE: Exposure Limit Value.  
VME: Exposure Average Value.  
vPvB: Very persistent and very bioaccumulative.  
Not available.

#### References

#### Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

#### Full text of any statements, which are not written out in full under sections 2 to 15

H225 Highly flammable liquid and vapor.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.

H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

**Revision information**

**Training information**

**Disclaimer**

Physical & Chemical Properties: Multiple Properties

Follow training instructions when handling this material.

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.