SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® Flexane® Brushable Curing Agent

Other means of identification

SKU# 6925N

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number978-777-1100

Fax E-mail

Emergency telephone

800-424-9300

number

Supplier Not available.

2. Hazard identification

Physical hazardsFlammable liquidsCategory 3Health hazardsAcute toxicity, oralCategory 4Serious eye damage/eye irritationCategory 2A

Reproductive toxicity

Category 1

Specific target organ toxicity following

Category 2

Category 2

repeated exposure

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapour. Harmful if swallowed. Causes serious eye irritation. May damage

fertility or the unborn child. May cause damage to organs through prolonged or repeated

exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe mist/vapours. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective

clothing/eye protection/face protection.

Response IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell. Rinse mouth. IF ON SKIN

(or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. If eye irritation persists:

Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

Material name: DEVCON® Flexane® Brushable Curing Agent

SDS CANADA

Store in a well-ventilated place. Keep cool. Store locked up. **Storage**

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information None. Other hazards

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Propylene glycol methyl ether acetate	1-Methoxy-2-propylacetate	108-65-6	60 - < 70
Diethyltoluenediamine		68479-98-1	20 - < 30
Carbon Black		1333-86-4	1 - < 3
2-Methoxy-1-Propylacetate (impuritey)		70657-70-4	< 1
Other components below reportal	ole levels		5 - < 10

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical Skin contact

attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Ingestion

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and delayed

vision. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area, Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

media

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. General fire hazards Flammable liquid and vapour.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapours. Do not taste or swallow. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage. including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US AC	CGIH T	hreshold	I imit	Values	(TI V)
00. A	-	111 6 311014	∟ 111111	v alues	(! L V /

Components	Туре	Value	Form
Carbon Black (CAS	TWA	3 mg/m3	Inhalable fraction.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended Components **Type** Value Carbon Black (CAS TWA 3.5 mg/m3

1333-86-4)

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form	
2-Methoxy-1-Propylacetate (impuritey) (CAS 70657-70-4)	STEL	40 ppm		
	TWA	20 ppm		
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable	
Propylene glycol methyl ether acetate (CAS 108-65-6)	STEL	75 ppm		
	TWA	50 ppm		

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended

Components	Туре	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.

Material name: DEVCON® Flexane® Brushable Curing Agent

SDS CANADA 6925N Version #: 03 Revision date: 15-August-2023 Issue date: 22-May-2019

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs

Publication (New Brunswick Regulation 91-191)

Components Type Value

Carbon Black (CAS TWA 3.5 mg/m3

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended

Components	Туре	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Propylene glycol methyl ether acetate (CAS 108-65-6)	TWA	270 mg/m3	

50 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended Components

Type

Value

Form

Carbon Black (CAS

TWA

3 mg/m3

Inhalable dust.

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended
Components
Type
Value

Carbon Black (CAS 15 minute 7 mg/m3
1333-86-4)

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

1333-86-4)

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapour cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapour cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance Viscous. Liquid.

Physical state Liquid.

Form Viscous. Liquid.

Colour Black.

Odour Pungent.

Odour threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point 46.0 °C (114.8 °F) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper Not available.

(%)

Vapour pressure2.44 hPa estimatedVapour densityNot available.

Relative density

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 1.06 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Combustible II estimated

Oxidising properties Not oxidising.

Specific gravity 1.06 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

Hazardous polymerisation does not occur.

Not available.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidising agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Components Species Test Results

Carbon Black (CAS 1333-86-4)

Acute Oral

LD50 Rat > 8000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Material name: DEVCON® Flexane® Brushable Curing Agent
6925N Version #: 03 Revision date: 15-August-2023 Issue date: 22-May-2019

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant

Carbon Black (CAS 1333-86-4) Irritant

Respiratory sensitisation

Not a respiratory sensitiser.

Skin sensitisation

This product is not expected to cause skin sensitisation.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

Carbon Black (CAS 1333-86-4)

A3 Confirmed animal carcinogen with unknown relevance to

humans.

Canada - Manitoba OELs: carcinogenicity

Carbon Black (CAS 1333-86-4)

Confirmed animal carcinogen with unknown relevance to humans.

Canada - Quebec OELs: Carcinogen category

Carbon Black (CAS 1333-86-4)

Detected carcinogenic effect in animals.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Black (CAS 1333-86-4)

2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Carbon Black (CAS 1333-86-4)

Known To Be Human Carcinogen.

Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

May damage fertility or the unborn child.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

No data is available on the degradability of any ingredients in the mixture.

Assissation because

Aspiration hazard Not an aspiration hazard.

Chronic effects

Prolonged inhalation may be harmful. May cause damage to organs through prolonged or

repeated exposure.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

UN number

UN1139

UN proper shipping name

COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle undercoating, drum or barrel lining), Limited Quantity

Transport hazard class(es)

Class 3 Subsidiary risk -

Material name: DEVCON® Flexane® Brushable Curing Agent

SDS CANADA

6925N Version #: 03 Revision date: 15-August-2023 Issue date: 22-May-2019

Packing group Ш **Environmental hazards** No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN1139

Coating solution (includes surface treatments or coatings used for industrial or other purposes **UN** proper shipping name

such as vehicle undercoating, drum or barrel lining), Limited Quantity

Transport hazard class(es)

3 Class Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 3L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Allowed with restrictions. Cargo aircraft only

IMDG

UN number UN1139

COATING SOLUTION (includes surface treatments or coatings used for industrial purposes such **UN** proper shipping name

as vehicle under-coating, drum or barrel lining), Limited Quantity

Transport hazard class(es)

Class 3 Subsidiary risk Ш Packing group **Environmental hazards**

Marine pollutant No. F-E, S-E **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and


Not established.

the IBC Code

IATA



IMDG; TDG



15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Inventory name

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

Country(s) or region

International Inventories

Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Taiwan Chemical Substance Inventory (TCSI)

Toxic Substances Control Act (TSCA) Inventory

16. Other information

Taiwan

Issue date22-May-2019Revision date15-August-2023

Version No. 03

United States & Puerto Rico

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: DEVCON® Flexane® Brushable Curing Agent
6925N Version #: 03 Revision date: 15-August-2023 Issue date: 22-May-2019

On inventory (yes/no)*

Yes

Yes