# SAFETY DATA SHEET

# 1. Identification

Product identifier PLEXUS® MA8105 Adhesive

Other means of identification

**SKU#** 81051

**Recommended use**Not available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers

Address 30 Endicott Street

Danvers, MA 01923 United States

**Telephone** Customer Service 978-777-1100

Website www.itwperformancepolymers.com

E-mail Not available.

Contact person EHS Department

Emergency phone number Chemtrec 800-424-9300

International 703-527-3887

# 2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsAcute toxicity, dermalCategory 4Acute toxicity, inhalationCategory 4Skin corrosion/irritationCategory 1ASerious eye damage/eye irritationCategory 1Sensitization, skinCategory 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Harmful in contact with skin. Causes severe skin burns and

eye damage. May cause an allergic skin reaction. Causes serious eye damage. Harmful if

inhaled.

**Precautionary statement** 

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

**Response**If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and

keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. In case of fire: Use

appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Material name: PLEXUS® MA8105 Adhesive

#### Disposal

Hazard(s) not otherwise classified (HNOC)

Supplemental information

Dispose of contents/container in accordance with local/regional/national/international regulations.

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

33% of the mixture consists of component(s) of unknown acute oral toxicity. 71.81% of the mixture consists of component(s) of unknown acute dermal toxicity. 64.81% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 79.18% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

# 3. Composition/information on ingredients

ΝЛ	1	ιtι		2	0
IVI	10	LL	41	_	-

Chemical name	Common name and synonyms	CAS number	%
Methyl Methacrylate		80-62-6	20 - 40
2-PHENOXYETHYL METHACRYLATE		10595-06-9	2.5 - 10
DODECYL METHACRYLATE		142-90-5	2.5 - 10
METHACRYLIC ACID		79-41-4	2.5 - 10
HEXADECYL METHACRYLATE		2495-27-4	1 - 2.5
MALEIC ACID		110-16-7	1 - 2.5
Paraffin Wax		8002-74-2	1 - 2.5
Other components below reportab	ole levels		40 - 60

### 4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.

Eye contact

Ingestion

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**General information** 

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

81051 Version #: 04 Revision date: 08-03-2023 Issue date: 11-25-2021

Use standard firefighting procedures and consider the hazards of other involved materials. Highly flammable liquid and vapor.

# 6. Accidental release measures

# Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

## Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

## **Environmental precautions**

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

# 7. Handling and storage

## Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

# Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)				
Components	Туре	Value		
Methyl Methacrylate (CAS 80-62-6)	PEL	410 mg/m3		
		100 ppm		

81051 Version #: 04 Revision date: 08-03-2023 Issue date: 11-25-2021

Components	Туре	Value	Form	
METHACRYLIC ACID (CAS 79-41-4)	TWA	20 ppm		
Methyl Methacrylate (CAS 80-62-6)	STEL	100 ppm		
	TWA	50 ppm		
Paraffin Wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.	
NIOSH. Immediately Danger	ous to Life or Health (IDLH) Values	, as amended		
Components	Туре	Value		
Methyl Methacrylate (CAS 80-62-6)	IDLH	1.7 %		
	IDLH	1.7 % 1000 ppm		
80-62-6)	IDLH  Chemical Hazards Recommended	1000 ppm		
80-62-6) US. NIOSH: Pocket Guide to		1000 ppm	Form	
80-62-6)	o Chemical Hazards Recommended	1000 ppm Exposure Limits (REL)	Form	
WS. NIOSH: Pocket Guide to Components  METHACRYLIC ACID (CAS	o Chemical Hazards Recommended Type	1000 ppm Exposure Limits (REL) Value	Form	
WS. NIOSH: Pocket Guide to Components  METHACRYLIC ACID (CAS	o Chemical Hazards Recommended Type	1000 ppm Exposure Limits (REL) Value 70 mg/m3	Form	
WS. NIOSH: Pocket Guide to Components  METHACRYLIC ACID (CAS 79-41-4)  Methyl Methacrylate (CAS	o Chemical Hazards Recommended Type TWA	1000 ppm Exposure Limits (REL) Value 70 mg/m3 20 ppm	Form	
WS. NIOSH: Pocket Guide to Components  METHACRYLIC ACID (CAS 79-41-4)  Methyl Methacrylate (CAS	o Chemical Hazards Recommended Type TWA	1000 ppm Exposure Limits (REL) Value  70 mg/m3  20 ppm 410 mg/m3	Form	

Bio

**Exposure guidelines** 

US - California OELs: Skin designation

METHACRYLIC ACID (CAS 79-41-4) Can be absorbed through the skin.

US - Tennessee OELs: Skin designation

METHACRYLIC ACID (CAS 79-41-4) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

METHACRYLIC ACID (CAS 79-41-4) Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this

product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield. Face shield is

recommended.

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not

be allowed out of the workplace.

# 9. Physical and chemical properties

**Appearance** 

**Physical state** Liquid.

Liquid. **Form** Color Not available. Not available. Odor Not available. Odor threshold

-54.4 °F (-48 °C) estimated Melting point/freezing point 212.9 °F (100.5 °C) estimated Initial boiling point and boiling

Not available.

range

50.0 °F (10.0 °C) estimated Flash point

**Evaporation rate** Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits Explosive limit - lower (%) 2.1 % estimated Explosive limit - upper (%) 8.2 % estimated Vapor pressure 37.7 hPa estimated

Not available. Vapor density Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** 752 °F (400 °C) estimated

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

0.98 g/cm3 estimated Density

**Explosive properties** Not explosive.

Flammable IB estimated Flammability class

Oxidizing properties Not oxidizing. Specific gravity 0.98 estimated

## 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Strong oxidizing agents. Nitrates. Peroxides. Incompatible materials

Hazardous decomposition No hazardous decomposition products are known.

products

## 11. Toxicological information

## Information on likely routes of exposure

Inhalation Harmful if inhaled.

Causes severe skin burns. Harmful in contact with skin. May cause an allergic skin reaction. Skin contact

Eye contact Causes serious eye damage. Ingestion Causes digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

## Information on toxicological effects

**Acute toxicity** Harmful if inhaled. Harmful in contact with skin.

Components **Species Test Results** 

DODECYL METHACRYLATE (CAS 142-90-5)

**Acute** 

Dermal

LD50 Rabbit > 3 g/kg

Oral

Rat LD50 > 5 g/kg

MALEIC ACID (CAS 110-16-7)

Acute **Dermal** 

Rabbit LD50 1560 mg/kg

Oral

LD50 Rat 708 mg/kg

METHACRYLIC ACID (CAS 79-41-4)

**Acute** Dermal

LD50 Rabbit 500 mg/kg

Inhalation

LC50 Rat 7.1000000000000005 mg/l, 4 Hours

Oral

LD50 Rat 1060 mg/kg

Methyl Methacrylate (CAS 80-62-6)

**Acute** Oral

LD50 Rat 7800 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eve damage/eve

Causes serious eye damage.

irritation

Respiratory or skin sensitization

**ACGIH** sensitization

Methyl methacrylate (CAS 80-62-6) Dermal sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Not classifiable as to carcinogenicity to humans. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Methyl Methacrylate (CAS 80-62-6) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful.

Material name: PLEXUS® MA8105 Adhesive

# 12. Ecological information

**Ecotoxicity** 

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

DODECYL METHACRYLATE 6.45 HEXADECYL METHACRYLATE 8.64 -0.48 MALEIC ACID METHACRYLIC ACID 0.93 1.38 Methyl Methacrylate

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

**Disposal instructions** Dispose of this material and its container to hazardous or special waste collection point. Incinerate

the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

D001: Waste Flammable material with a flash point <140 F Hazardous waste code

D002: Waste Corrosive material [pH ≤2 or =>12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. Transport information

DOT

**UN** number UN2924

**UN proper shipping name** Transport hazard class(es) Flammable liquids, corrosive, n.o.s. (Methyl Methacrylate RQ = 2717 LBS, METHACRYLIC ACID)

3 Subsidiary risk 8 Label(s) 3, 8 Packing group Ш

**Environmental hazards** 

Marine pollutant No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB2, T11, TP2, TP27

Packaging exceptions 150 202 Packaging non bulk 243 Packaging bulk

**IATA** 

**UN** number UN2924

Flammable liquid, corrosive, n.o.s. (Methyl Methacrylate, METHACRYLIC ACID) **UN proper shipping name** 

Transport hazard class(es)

3 Class Subsidiary risk 8 Ш Packing group **Environmental hazards** No. **ERG Code** 3CH

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

81051 Version #: 04 Revision date: 08-03-2023 Issue date: 11-25-2021

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Not established.

Allowed with restrictions. Cargo aircraft only

**IMDG** 

**UN** number UN2924

**UN** proper shipping name FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Methyl Methacrylate, METHACRYLIC ACID)

Transport hazard class(es)

Class 3 8 Subsidiary risk П Packing group

**Environmental hazards** 

Marine pollutant No. F-E, S-C **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



# 15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations

Standard, 29 CFR 1910.1200.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

2-PHENOXYETHYL METHACRYLATE % 1.0 N230

(CAS 10595-06-9)

Methyl Methacrylate (CAS 80-62-6) % 1.0

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

2-PHENOXYETHYL METHACRYLATE Listed. N230

(CAS 10595-06-9)

Methyl Methacrylate (CAS 80-62-6) Listed.

**Toxic Substances Control Act (TSCA)** 

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

2-PHENOXYETHYL METHACRYLATE Listed.

(CAS 10595-06-9)

MALEIC ACID (CAS 110-16-7)

Material name: PLEXUS® MA8105 Adhesive

Listed.

SDS US 8 / 10 Methyl Methacrylate (CAS 80-62-6)

Listed.

# SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

### SARA 302 Extremely hazardous substance

SARA 311/312 Hazardous

Yes

chemical

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization Hazard not otherwise classified (HNOC)

## SARA 313 (TRI reporting)

_	Chemical name	CAS number	% by wt.	
	2-PHENOXYETHYL METHACRYLATE	10595-06-9	2.5 - 10	
	Methyl Methacrylate	80-62-6	20 - 40	

### Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2-PHENOXYETHYL METHACRYLATE (CAS 10595-06-9)

Methyl Methacrylate (CAS 80-62-6)

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

## FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Methyl Methacrylate (CAS 80-62-6) Low priority

## **US** state regulations

## US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-PHENOXYETHYL METHACRYLATE (CAS 10595-06-9)

Methyl Methacrylate (CAS 80-62-6)

### **California Proposition 65**



WARNING: This product can expose you to chemicals including BUTADIENE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go

to www.P65Warnings.ca.gov.

## California Proposition 65 - CRT: Listed date/Carcinogenic substance

BUTADIENE (CAS 106-99-0) Listed: April 1, 1988 Ethyl Acrylate (CAS 140-88-5) Listed: July 1, 1989

California Proposition 65 - CRT: Listed date/Developmental toxin

BUTADIENE (CAS 106-99-0) Listed: April 16, 2004 California Proposition 65 - CRT: Listed date/Female reproductive toxin BUTADIENE (CAS 106-99-0) Listed: April 16, 2004

California Proposition 65 - CRT: Listed date/Male reproductive toxin

BUTADIENE (CAS 106-99-0) Listed: April 16, 2004

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No

Country(s) or regionInventory nameOn inventory (yes/no)\*EuropeEuropean List of Notified Chemical Substances (ELINCS)NoJapanInventory of Existing and New Chemical Substances (ENCS)No

Korea Existing Chemicals List (ECL) No
New Zealand New Zealand Inventory Yes

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

# 16. Other information, including date of preparation or last revision

 Issue date
 11-25-2021

 Revision date
 08-03-2023

Version # 04

HMIS® ratings Health: 3

Flammability: 3 Physical hazard: 0

NFPA ratings Health: 3

Flammability: 3 Instability: 0

**Disclaimer** ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Material name: PLEXUS® MA8105 Adhesive

81051 Version #: 04 Revision date: 08-03-2023 Issue date: 11-25-2021 10 / 10

No

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).