SAFETY DATA SHEET

1. Identification			
	DI EVIIS® MASAGE Anticator		
Product identifier	PLEXUS® MA8105 Activator		
Other means of identification SKU#	81054		
Recommended use	Not available.		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplie			
Company name	ITW Performance Polymers		
Address	35 Brownridge Rd		
	Unit 1		
	Halton Hills, ON L7G 0C6		
Contact person	Customer Service		
Telephone number	978-777-1100		
Fax			
E-mail			
Emergency telephone number	800-424-9300		
Supplier	Not available.		
2. Hazard identification			
Physical hazards	Flammable liquids	Category 2	
Health hazards	Acute toxicity, inhalation	Category 4	
	Skin corrosion/irritation	Category 2	
	Serious eye damage/eye irritation	Category 2B	
	Sensitization, skin	Category 1A	
	Specific target organ toxicity following single exposure	Category 3 respiratory tract irritation	
Environmental hazards	Not classified.		
Label elements			
Signal word	Danger		
Hazard statement	Highly flammable liquid and vapour. Causes s Causes eye irritation. Harmful if inhaled. May	kin irritation. May cause an allergic skin reaction. cause respiratory irritation.	
Precautionary statement			
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing mist/vapours. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.		
Response	INHALED: Remove person to fresh air and ke cautiously with water for several minutes. Rer Continue rinsing. Call a POISON CENTRE/do occurs: Get medical advice/attention. If eye in	contaminated clothing. Rinse skin with water. IF eep comfortable for breathing. IF IN EYES: Rinse nove contact lenses, if present and easy to do. octor if you feel unwell. If skin irritation or rash ritation persists: Get medical advice/attention. Take reuse. In case of fire: Use appropriate media to	

extinguish.

Storage

Disposal

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Supplemental information

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapour. May cause flash fire or explosion.

12.63 % of the mixture consists of component(s) of unknown acute oral toxicity. 85.58 % of the mixture consists of component(s) of unknown acute dermal toxicity. 85.58 % of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 85.58 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtur	es
--------	----

Chemical name	Common name and synonyms	CAS number	%
Methyl methacrylate		80-62-6	60 - 100
Paraffin wax		8002-74-2	1 - 5
Calcium carbonate		471-34-1	0.1 - 1
Other components below rep	oortable levels		15 - 40

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a poison centre or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

5. Fire-ingitting measures	
Suitable extinguishing media	Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapour.

6. Accidental release measures

6. Accidental release mea	sures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
	For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values Components	Туре	Value	Form
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
Paraffin wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.

Components	Туре	Value	Form
Calcium carbonate (CAS 471-34-1)	TWA	10 mg/m3	
METHYL METHACRYLATE (CAS 80-62-6)	STEL	410 mg/m3	
		100 ppm	
	TWA	205 mg/m3	
		50 ppm	
Paraffin wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
Calcium carbonate (CAS 471-34-1)	STEL	20 mg/m3	Total dust.
	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
Paraffin wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Canada Alberta OEL a (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value	Form
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
Paraffin wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	Form
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
Paraffin wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Туре	Value	Form	
Calcium carbonate (CAS 471-34-1)	TWA	10 mg/m3	Total dust.	
METHYL METHACRYLATE (CAS 80-62-6)	TWA	205 mg/m3		
		50 ppm		
Paraffin wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.	
Canada. Saskatchewan OELs (Oco	cupational Health and Safety	Regulations, 1996, Table 21)		

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Туре	Value Form	
Calcium carbonate (CAS 471-34-1)	15 minute	20 mg/m3	
	8 hour	10 mg/m3	
METHYL METHACRYLATE (CAS 80-62-6)	15 minute	100 ppm	
	8 hour	50 ppm	

Canada. Saskatchewan Ol Components	ELs (Occupational Health and Safety Reg Type	ulations, 1996, Table 21) Value	Form
Paraffin wax (CAS 8002-74-2)	15 minute	4 mg/m3	Fume.
	8 hour	2 mg/m3	Fume.
Biological limit values	No biological exposure limits noted for the	ne ingredient(s).	
Appropriate engineering controls	Explosion-proof general and local exhau Ventilation rates should be matched to o exhaust ventilation, or other engineering exposure limits. If exposure limits have r acceptable level. Provide eyewash station	conditions. If applicable, us controls to maintain airboi not been established, main	e process enclosures, local rne levels below recommended
Individual protection measure	s, such as personal protective equipment	t	
Eye/face protection	Chemical respirator with organic vapour	cartridge and full facepiec	e.
Skin protection			
Hand protection	Wear appropriate chemical resistant glo	ves.	
Other	Wear appropriate chemical resistant clo	thing.	
Respiratory protection	Chemical respirator with organic vapour	cartridge and full facepiec	e.
Thermal hazards	Wear appropriate thermal protective clot	thing, when necessary.	
General hygiene considerations	When using do not smoke. Always obse after handling the material and before ea clothing and protective equipment to ren be allowed out of the workplace.	ating, drinking, and/or smol	king. Routinely wash work

9. Physical and chemical properties

-						
Α	p	De	ea	ra	n	ce

Appearance	
Physical state	Liquid.
Form	Liquid.
Colour	Not available.
Odour	Not available.
Odour threshold	Not available.
рН	Not available.
Melting point/freezing point	-48 °C (-54.4 °F) estimated
Initial boiling point and boiling range	100.5 °C (212.9 °F) estimated
Flash point	10.0 °C (50.0 °F) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	2.1 % estimated
Flammability limit - upper (%)	12.5 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit – upper (%)	Not available.
Vapour pressure	51.33 hPa estimated
Vapour density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.

Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.96 g/cm3
Explosive properties	Not explosive.
Flammability class	Flammable IB estimated
Oxidising properties	Not oxidising.
Specific gravity	0.96
10. Stability and reactivit	у

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerisation does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the decomposition temperature. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidising agents. Nitrates. Peroxides.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure			
Inhalation	Harmful if inhaled.		
Skin contact	Causes skin irritation. May cause an allergic skin reaction.		
Eye contact	Causes eye irritation.		
Ingestion	Expected to be a low ingestion hazard.		
Symptoms related to the physical, chemical and toxicological characteristics	Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.		
Information on toxicological effects			
Acute toxicity	Harmful if inhaled.		

Acute toxicity	Harmful if inhaled.	
Components	Species	Test Results
Calcium carbonate (CAS 471-3	34-1)	
Acute		
Oral		
LD50	Rat	6450 mg/kg
Methyl methacrylate (CAS 80-6	62-6)	
<u>Acute</u>		
Inhalation		
LC50	Mouse	18.5 mg/l, 2 Hours
Oral		
LD50	Rat	7800 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes eye irritation.	
Respiratory or skin sensitisa	tion	
ACGIH sensitisation		
Methyl methacrylate (CAS 80-62-6)	Dermal sensitisation
Canada - Alberta OELs:	Irritant	
Calcium carbonate (C		Irritant
	B Hazard: Dermal sensitization	
Methyl methacrylate (CAS 80-62-6)	Dermal sensitisation

Canada - Quebec OELs: Se	nsitizer	
Methyl methacrylate (CA Canada - Saskatchewan OE		Sensitiser.
Methyl methacrylate (CA	S 80-62-6)	Sensitiser.
Respiratory sensitisation	Not a respiratory sensitizer.	
Skin sensitisation	May cause an allergic skin rea	action.
Germ cell mutagenicity	No data available to indicate p mutagenic or genotoxic.	product or any components present at greater than 0.1% are
Carcinogenicity		
ACGIH Carcinogens		
Methyl methacrylate (CA Canada - Manitoba OELs: c		A4 Not classifiable as a human carcinogen.
Methyl methacrylate (CA IARC Monographs. Overall	S 80-62-6) <mark>Evaluation of Carcinogenicity</mark>	Not classifiable as a human carcinogen.
Methyl methacrylate (CA	S 80-62-6)	3 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	This product is not expected t	o cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause respiratory irritatio	n.
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be l	narmful.
12. Ecological information	n	
Ecotoxicity		s environmentally hazardous. However, this does not exclude the nt spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the de	gradability of any ingredients in the mixture.
Bioaccumulative potential		
Partition coefficient n-octar Methyl methacrylate	iol / water (log Kow)	1.38
Mobility in soil	No data available.	
Other adverse effects		tal effects (e.g. ozone depletion, photochemical ozone creation , global warming potential) are expected from this component.
13. Disposal consideratio	ns	
Disposal instructions		in sealed containers at licensed waste disposal site. Dispose of nce with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with a	l applicable regulations.
Hazardous waste code	The waste code should be as disposal company.	signed in discussion between the user, the producer and the waste
Waste from residues / unused products	•	local regulations. Empty containers or liners may retain some al and its container must be disposed of in a safe manner (see:
Contaminated packaging		retain product residue, follow label warnings even after container is ould be taken to an approved waste handling site for recycling or
14. Transport information		
TDG		
UN number UN proper shipping name	UN1133 ADHESIVES containing flamr	nable liquid
Transport hazard class(es)	-	

UN number	UN1133
UN proper shipping name	ADHESIVES containing flammable liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	1
Environmental hazards	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
· ·	

ΙΑΤΑ

IATA	
UN number	UN1133
UN proper shipping name	Adhesives containing flammable liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3L
Special precautions for user Other information	Read safety instructions, SDS and emergency procedures before handling.
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1133
UN proper shipping name	ADHESIVES containing flammable liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	11
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

IATA; IMDG; TDG



15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3) Not listed. Greenhouse Gases Not listed. Precursor Control Regulations Not regulated. International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol Not applicable.

Montreal Protocol Not applicable. Basel Convention Not applicable.

International Inventories

Country(s) or region	Inventory name On inve	ntory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Vaa" indicates that all compo	nente of this product comply with the inventory requiremente administered by the governing cour	tru(a)

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date	25-November-2021
Revision date	29-March-2022
Version No.	02
Disclaimer	ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.
Revision information	HazReg Data: International Inventories