SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® Ultra Quartz™ Surface Primer Hardener

Other means of identification

SKU# 8675 (Hardener) Recommended use Not available. Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

ITW Performance Polymers Company name

30 Endicott Street **Address**

Danvers, MA 01923

United States

978-777-1100 **Telephone Customer Service**

Website www.itwperformancepolymers.com

E-mail Not available. **Contact person EHS Department**

Chemtrec 800-424-9300 **Emergency phone number**

International 703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

> Acute toxicity, dermal Category 4 Skin corrosion/irritation Category 1 Serious eye damage/eye irritation Category 1 Sensitization, skin Category 1 Germ cell mutagenicity Category 2 Specific target organ toxicity, repeated Category 2

exposure

Not classified. **Environmental hazards OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Combustible liquid. Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns

and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing genetic defects. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Obtain special instructions before use. Do not handle until all safety precautions have been read Prevention

and understood. Keep away from flames and hot surfaces. - No smoking. Do not breathe mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective

gloves/protective clothing/eye protection/face protection.

Response Rinse mouth. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off

immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. In case of fire:

Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information N

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Aliphatic Amine		N/A	40 - 60
TRIMETHYLHEXAMETHYL MINE	ENEDIA	25620-58-0	20 - 40
Phenol		108-95-2	10 - 20

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a physician

or poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

ont

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods Use standard

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. Do not breathe mist/vapors. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Type	Contaminants (29 CFR 1910.1000) Value	
Phenol (CAS 108-95-2)	PEL	19 mg/m3	
		5 ppm	
US. ACGIH Threshold Limit Valu	ies (TLV)		
Components	Туре	Value	
Phenol (CAS 108-95-2)	TWA	5 ppm	
NIOSH. Immediately Dangerous Components	to Life or Health (IDLH) Values, Type	as amended Value	
Phenol (CAS 108-95-2)	IDLH	1.8 %	
		250 ppm	
US. NIOSH: Pocket Guide to Che Components	emical Hazards Recommended l Type	Exposure Limits (REL) Value	
Phenol (CAS 108-95-2)	Ceiling	60 mg/m3	
		15.6 ppm	
	TWA	19 mg/m3	
		5 ppm	

Biological limit values

ACGIH Biological Exposure Indices (BEI)

Components	Value	Determinant	Specimen	Sampling Time
Phenol (CAS 108-95-2)	250 mg/g	Phenol with hydrolysis	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Phenol (CAS 108-95-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Phenol (CAS 108-95-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Phenol (CAS 108-95-2) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Phenol (CAS 108-95-2) Danger of cutaneous absorption

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Phenol (CAS 108-95-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Phenol (CAS 108-95-2) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Viscous.

Physical state Liquid.
Form Liquid.
Color Amber

Odor Irritating.
Odor threshold Not available.
pH Not available.

Melting point/freezing point 105.64 °F (40.91 °C) estimated

Initial boiling point and boiling

range

Not available.

Flash point 255.2 °F (124.0 °C)
Evaporation rate Not available.
Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 3 % estimated
Explosive limit - upper (%) 10 % estimated

8675 (Hardener) Version #: 04 Revision date: 07-31-2023 Issue date: 05-29-2019

0.28 hPa estimated Vapor pressure

Not available. Vapor density Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

1319 °F (715 °C) estimated **Auto-ignition temperature**

Not available. **Decomposition temperature** Not available. **Viscosity**

Other information

Density 0.99 g/cm3 **Explosive properties** Not explosive.

Combustible IIIB estimated Flammability class

Oxidizing properties Not oxidizing.

Specific gravity 0.99

VOC 7.5 % estimated

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the Conditions to avoid flash point. Contact with incompatible materials.

Acids. Strong oxidizing agents. Aluminum. Peroxides. Phenols. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

May cause irritation to the respiratory system. Prolonged inhalation may be harmful. Inhalation

Skin contact Causes severe skin burns. Harmful in contact with skin. May cause an allergic skin reaction.

Causes serious eye damage. Eye contact

Ingestion Causes digestive tract burns. Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

Information on toxicological effects

Acute toxicity Harmful in contact with skin. Harmful if swallowed.

Components **Species Test Results**

Phenol (CAS 108-95-2)

Acute Dermal

LD50 Rat 669 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye Causes serious eye damage.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

May cause an allergic skin reaction. Skin sensitization Germ cell mutagenicity Suspected of causing genetic defects.

Material name: DEVCON® Ultra Quartz™ Surface Primer Hardener

SDS US 8675 (Hardener) Version #: 04 Revision date: 07-31-2023 Issue date: 05-29-2019

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Phenol (CAS 108-95-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. May cause damage to organs through prolonged or

repeated exposure.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

No data is available on the degradability of any ingredients in the mixture. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

1.46 Phenol

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Dispose of this material and its container to hazardous or special waste collection point. Incinerate Disposal instructions

the material under controlled conditions in an approved incinerator. Dispose of contents/container

in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

D002: Waste Corrosive material [pH ≤2 or =>12.5, or corrosive to steel] Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN2735 **UN** number

UN proper shipping name Amines, liquid, corrosive, n.o.s, or Polyamines, liquid, corrosive, n.o.s.

(TRIMETHYLHEXAMETHYLENEDIAMINE), Limited Quantity

Transport hazard class(es)

Class 8 Subsidiary risk 8 Label(s) Ш Packing group **Environmental hazards**

> Marine pollutant No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB3, T7, TP1, TP28

Packaging exceptions 154 Packaging non bulk 203 Packaging bulk 241

Material name: DEVCON® Ultra Quartz™ Surface Primer Hardener

SDS US 8675 (Hardener) Version #: 04 Revision date: 07-31-2023 Issue date: 05-29-2019

IATA

UN2735 **UN** number

UN proper shipping name Amines, liquid, corrosive, n.o.s. (TRIMETHYLHEXAMETHYLENEDIAMINE), Limited Quantity

Transport hazard class(es)

Class 8 Subsidiary risk Ш Packing group **Environmental hazards** No. 8L **ERG Code**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

Not established.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN2735

AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. **UN** proper shipping name

(TRIMETHYLHEXAMETHYLENEDIAMINE), Limited Quantity

Transport hazard class(es)

8 Class Subsidiary risk Packing group Ш **Environmental hazards**


Marine pollutant No. F-A, S-B **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT: IMDG





15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

% 1.0 Phenol (CAS 108-95-2)

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Phenol (CAS 108-95-2) Listed.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Phenol (CAS 108-95-2) Listed.

SARA 304 Emergency release notification

Phenol (CAS 108-95-2) 1000 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Yes

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)	
Phenol	108-95-2	1000		500	10000	

SARA 311/312 Hazardous

chemical

Classified hazard categories

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

Germ cell mutagenicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Phenol	108-95-2	10 - 20

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Phenol (CAS 108-95-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Phenol (CAS 108-95-2) Low priority

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Phenol (CAS 108-95-2)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes

Country(s) or region Inventory name On inventory (yes/no)*

New Zealand Inventory Yes

Philippines Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 05-29-2019

 Revision date
 07-31-2023

Version # 04

HMIS® ratings Health: 3*

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 3

Flammability: 1 Instability: 0

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Material name: DEVCON® Ultra Quartz™ Surface Primer Hardener 8675 (Hardener) Version #: 04 Revision date: 07-31-2023 Issue date: 05-29-2019