SAFETY DATA SHEET

1. Identification

Product identifier Chockfast Orange Resin

Other means of identification

SKU# GP101R, GP102R Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information ITW Performance Polymers Company name **Address** 35 Brownridge Road

Unit 1

Halton Hills, ON L7G 0C6

Customer Service Contact person Telephone number 215-855-8450 Fax number 215-855-4688

Emergency Number 800-424-9300 (CHEMTREC)

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Skin corrosion/irritation Category 2 **Health hazards**

> Serious eye damage/eye irritation Category 2 Sensitization, skin Category 1 Category 2

Hazardous to the aquatic environment, acute

Hazardous to the aquatic environment, Category 2

long-term hazard

Label elements

Environmental hazards



Signal word Warning

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Causes **Hazard statement**

eye irritation. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Avoid breathing mist/vapours. Wash thoroughly after handling. Contaminated work clothing

should not be allowed out of the workplace. Avoid release to the environment. Wear eye

protection/face protection. Wear protective gloves.

IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several Response

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse. Collect spillage.

Store away from incompatible materials. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information 98.39 % of the mixture consists of component(s) of unknown acute oral toxicity. 98.39 % of the

mixture consists of component(s) of unknown acute dermal toxicity.

Material name: Chockfast Orange Resin

GP101R, GP102R Version #: 05 Revision date: 15-July-2021 Issue date: 05-March-2019

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Crystalline silica		14808-60-7	30 - 60
Propane, 2,2-bis[p-(2,3-epoxypropoxy)p -, polymers	henyl]	25085-99-8	30 - 60
Limestone		1317-65-3	5 - 15
FIBROUS GLASS		65997-17-3	5 - 10
Epoxy phenol novalac resin		28064-14-4	1 - 5
Other components below repo	rtable levels		< 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

During fire, gases hazardous to health may be formed.

Move containers from fire area if you can do so without risk.

Fire fighting

equipment/instructions

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Methods and materials for containment and cleaning up This product is miscible in water. Prevent entry into waterways, sewer, basements or confined

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occur	national	l exposure	limite
Occu	vativiia	i exposure	IIIIIIII

US. ACGIH Threshold Limit Values Components	Туре	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Canada. Alberta OELs (Occupation	-	•	F
Components	Туре	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles
FIBROUS GLASS (CAS 65997-17-3)	TWA	0.2 fibers/cm3	Fiber.
		5 mg/m3	Fiber, total
		5 mg/m3	Total particulate.
Limestone (CAS 1317-65-3)	TWA	10 mg/m3	
		s for Chemical Substances, Oc	
Safety Regulation 296/97, as amen	ded)		-
Safety Regulation 296/97, as amen Components		Value 0.025 mg/m3	Form
Safety Regulation 296/97, as amen Components Crystalline silica (CAS 14808-60-7)	ded) Type	Value	Form
Safety Regulation 296/97, as amen	ded) Type	Value	Form
Safety Regulation 296/97, as amen Components Crystalline silica (CAS 14808-60-7) FIBROUS GLASS (CAS	Type TWA	Value 0.025 mg/m3	Form Respirable fraction.
Safety Regulation 296/97, as amen Components Crystalline silica (CAS 14808-60-7) FIBROUS GLASS (CAS 65997-17-3)	Type TWA	Value 0.025 mg/m3 0.2 fibers/cm3	Form Respirable fraction. Fiber.
Safety Regulation 296/97, as amen Components Crystalline silica (CAS 14808-60-7) FIBROUS GLASS (CAS	Type TWA TWA	Value 0.025 mg/m3 0.2 fibers/cm3 5 mg/m3	Form Respirable fraction. Fiber. Inhalable fibers. Total dust.
Safety Regulation 296/97, as amen Components Crystalline silica (CAS 14808-60-7) FIBROUS GLASS (CAS 65997-17-3)	Type TWA TWA STEL	Value 0.025 mg/m3 0.2 fibers/cm3 5 mg/m3 20 mg/m3	Form Respirable fraction. Fiber. Inhalable fibers.
Safety Regulation 296/97, as amen Components Crystalline silica (CAS 14808-60-7) FIBROUS GLASS (CAS 65997-17-3) Limestone (CAS 1317-65-3)	Type TWA TWA STEL TWA	Value 0.025 mg/m3 0.2 fibers/cm3 5 mg/m3 20 mg/m3 3 mg/m3 10 mg/m3	Form Respirable fraction. Fiber. Inhalable fibers. Total dust. Respirable fraction.
Safety Regulation 296/97, as amen Components Crystalline silica (CAS 14808-60-7) FIBROUS GLASS (CAS 65997-17-3)	Type TWA TWA STEL TWA	Value 0.025 mg/m3 0.2 fibers/cm3 5 mg/m3 20 mg/m3 3 mg/m3 10 mg/m3	Form Respirable fraction. Fiber. Inhalable fibers. Total dust. Respirable fraction.
Safety Regulation 296/97, as amen Components Crystalline silica (CAS 14808-60-7) FIBROUS GLASS (CAS 65997-17-3) Limestone (CAS 1317-65-3) Canada. Manitoba OELs (Reg. 217/	Type TWA TWA STEL TWA TWA	Value 0.025 mg/m3 0.2 fibers/cm3 5 mg/m3 20 mg/m3 3 mg/m3 10 mg/m3 And Health Act)	Form Respirable fraction. Fiber. Inhalable fibers. Total dust. Respirable fraction. Total dust.
Canada. Manitoba OELs (Reg. 217/Components	Type TWA TWA STEL TWA TWA 2006, The Workplace Safety Type	Value 0.025 mg/m3 0.2 fibers/cm3 5 mg/m3 20 mg/m3 3 mg/m3 10 mg/m3 And Health Act) Value	Form Respirable fraction Fiber. Inhalable fibers. Total dust. Respirable fraction Total dust. Form

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	Form	
Crystalline silica (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.	-
FIBROUS GLASS (CAS 65997-17-3)	TWA	0.5 fibers/cc	Respirable fibers.	
		5 mg/m3	Inhalable fraction.	

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value Form

	• • •			
Crystalline silica (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.	

Material name: Chockfast Orange Resin

65997-17-3)

SDS CANADA

GP101R, GP102R Version #: 05 Revision date: 15-July-2021 Issue date: 05-March-2019

Components	Туре	Value	Form
FIBROUS GLASS (CAS 65997-17-3)	TWA	1 fibers/cm3n	Fiber.
		10 mg/m3	fibers, total dust
Limestone (CAS 1317-65-3)	TWA	10 mg/m3	Total dust.
Canada. Saskatchewan OELs (Occ Components	cupational Health and Safety Ro Type	egulations, 1996, Table 21) Value	Form
	туре	Value	
Crystalline silica (CAS 14808-60-7)	8 hour	0.05 mg/m3	
Crystalline silica (CAS			Respirable fraction.
Crystalline silica (CAS 14808-60-7) FIBROUS GLASS (CAS	8 hour	0.05 mg/m3	Respirable fraction.
Crystalline silica (CAS 14808-60-7) FIBROUS GLASS (CAS	8 hour 15 minute	0.05 mg/m3 10 mg/m3	Respirable fraction.
Crystalline silica (CAS 14808-60-7) FIBROUS GLASS (CAS	8 hour 15 minute	0.05 mg/m3 10 mg/m3 0.2 fibers/cc	Respirable fraction. Inhalable fraction. Respirable fibers.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. **Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Liquid.
Physical state Liquid.

Form Liquid. Viscous.

ColourOrange.OdourSlight.

Odour threshold Not available.

Hq

Melting point/freezing point Not available.

Initial boiling point and boiling

range

> 260 °C (> 500 °F)

Flash point > 204.4 °C (> 400.0 °F) Pensky-Martens Closed Cup

Evaporation rate Not available.
Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper Not available.

(%)

Vapour pressureNot available.Vapour densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) negligible

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 1.64 g/cm3 **Explosive properties** Not explosive.

Flammability class Combustible IIIB estimated

Oxidising properties Not oxidising.

Specific gravity 1.64

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerisation does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the decomposition temperature. Contact with incompatible

materials.

Incompatible materials Strong oxidising agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitisation Canada - Alberta OELs: Irritant

Limestone (CAS 1317-65-3) Irritant

Respiratory sensitisation Not a respiratory sensitizer.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

Crystalline silica (CAS 14808-60-7)

A2 Suspected human carcinogen.

Material name: Chockfast Orange Resin

Canada - Alberta OELs: Carcinogen category

Crystalline silica (CAS 14808-60-7) Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Crystalline silica (CAS 14808-60-7) Suspected human carcinogen.

Canada - Quebec OELs: Carcinogen category

Crystalline silica (CAS 14808-60-7) Suspected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline silica (CAS 14808-60-7) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Crystalline silica (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

12. Ecological information

Toxic to aquatic life with long lasting effects. **Ecotoxicity**

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow **Disposal instructions**

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

UN number

UN proper shipping name

Environmentally hazardous substance, liquid, n.o.s. (Bisphenol A/ Epichlorohydrin Resin)

Transport hazard class(es) 9 Class

Subsidiary risk Ш Packing group **Environmental hazards** Yes 9L **ERG Code**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN number UN3082

SDS CANADA

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A/

Epichlorohydrin Resin), MARINE POLLUTANT (Epoxy Resin)

Transport hazard class(es)

Class 9
Subsidiary risk Packing group III

Environmental hazards

Marine pollutant Yes EmS F-A, S-F


Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Epoxy Resin

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code



Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

Toxic Substances Control Act (TSCA) Inventory

16. Other information

Taiwan

05-March-2019 Issue date 15-July-2021 **Revision date**

Version No. 05

United States & Puerto Rico

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

> product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

GP101R, GP102R Version #: 05 Revision date: 15-July-2021 Issue date: 05-March-2019

Yes

Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).