SAFETY DATA SHEET

Version #: 12

Issue date: 06-24-2013 Revision date: 07-27-2023 Supersedes date: 07-03-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

Synonyms

SKU#

Fmail

Phillybond Orange Resin

Registration number

None. DM014R

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified usesNot available.Uses advised againstNone known.

1.3. Details of the supplier of the safety data sheet

Company Name ITW Performance Polymers

Address Bay 150

Shannon Industrial Estate

Co. Clare Ireland V14 DF82

 Contact Person
 Customer Service

 Telephone Number
 353(61)771500

 353(61)471285

customerservice.shannon@itwpp.com

Emergency Phone Number 44(0) 1235 239 670 (24 hours)

1.4. Emergency telephone number

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons

Information Center

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Belgium National Poisons

Control Center

070 245 245 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Bulgaria National

Toxicological Information

Center

+359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Croatia Poisons Information Center

+385 1 2348 342 (Hours of operation not provided. SDS/Product information may

not be available for the Emergency Service.)

Cyprus Poison Center 1401 (Available 24 hours a day. SDS/Product information may not be available

for the Emergency Service.)

Czech Republic National Poisons Information

Center

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons

+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be

Control Center available for the Emergency Service.)

Estonia National Poisons Information Center

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be

available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Material name: Phillybond Orange Resin

DM014R Version #: 12 Revision date: 07-27-2023 Issue date: 06-24-2013

SDS FII

1.4. Emergency telephone number

Greece Poison Information Centre

(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Hungary National Emergency Phone Number +36-80-201-199 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Iceland Poison Center

(+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Latvia Emergency medical

aid

+371 67042473 (Available 24 hours a day. SDS/Product information may not be

Latvia Poison and Drug available for the Emergency Service.) Information Center

113

Lithuania Neatidėliotina informacija apsinuodijus

+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and **Emergency Department**

2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Netherlands National Poisons Information Center (NVIC)

NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel in cases of acute intoxications)

Norway Norwegian Poison Information Center

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Portugal Poison Center

800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Romania Biroul RSI si Informare Toxicologica 021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be

available for the Emergency Service.)

Slovakia National Toxicological Information Center

+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Spain Toxicology Information Service + 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Sweden National Poison Information Center

112 - and ask for Poison Information (Available 24 hours a day. SDS/Product

information may not be available for the Emergency Service.)

Switzerland Tox Info Suisse

145 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Acute toxicity, dermal Category 4 H312 - Harmful in contact with skin. Skin corrosion/irritation Category 2 H315 - Causes skin irritation. H319 - Causes serious eye Serious eye damage/eye irritation Category 2

irritation.

Skin sensitization Category 1 H317 - May cause an allergic skin

reaction.

Environmental hazards

Hazardous to the aquatic environment, H411 - Toxic to aquatic life with Category 2 long-term aquatic hazard

long lasting effects.

2.2. Label elements

DM014R Version #: 12 Revision date: 07-27-2023 Issue date: 06-24-2013

Material name: Phillybond Orange Resin

Label according to Regulation (EC) No. 1272/2008 as amended

UFI:

Austria: TWD0-S0C2-G00Y-1YHC
Belgium: TWD0-S0C2-G00Y-1YHC
Bulgaria: TWD0-S0C2-G00Y-1YHC
Croatia: TWD0-S0C2-G00Y-1YHC
Cyprus: TWD0-S0C2-G00Y-1YHC

Czech Republic: TWD0-S0C2-G00Y-1YHC Denmark: TWD0-S0C2-G00Y-1YHC Estonia: TWD0-S0C2-G00Y-1YHC EU: TWD0-S0C2-G00Y-1YHC Finland: TWD0-S0C2-G00Y-1YHC France: TWD0-S0C2-G00Y-1YHC Germany: TWD0-S0C2-G00Y-1YHC Greece: TWD0-S0C2-G00Y-1YHC Hungary: TWD0-S0C2-G00Y-1YHC Iceland: TWD0-S0C2-G00Y-1YHC Ireland: TWD0-S0C2-G00Y-1YHC Italy: TWD0-S0C2-G00Y-1YHC Latvia: TWD0-S0C2-G00Y-1YHC Lithuania: TWD0-S0C2-G00Y-1YHC Luxembourg: TWD0-S0C2-G00Y-1YHC Malta: TWD0-S0C2-G00Y-1YHC

Netherlands: TWD0-S0C2-G00Y-1YHC
Norway: TWD0-S0C2-G00Y-1YHC
Poland: TWD0-S0C2-G00Y-1YHC
Portugal: TWD0-S0C2-G00Y-1YHC
Romania: TWD0-S0C2-G00Y-1YHC
Slovakia: TWD0-S0C2-G00Y-1YHC
Slovenia: TWD0-S0C2-G00Y-1YHC
Spain: TWD0-S0C2-G00Y-1YHC
Sweden: TWD0-S0C2-G00Y-1YHC

Contains: 2-propenenitrile Polymer With 1,3-butadiene, Carboxy-terminated Reaction Products With

Epichlorohydrin-2,2'-methylenebis[phenol] Polymer, Butyrolactone, ethylbenzene, Phenol Polymer

With Formaldehyde, Glycidyl Ether, Silicon Dioxide

Hazard pictograms



Signal word Warning

Hazard statements

H312 Harmful in contact with skin.
H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.
P280 Wear eye protection/face protection.
P280 Wear protective gloves/protective clothing.

Response

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Ğet medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage. **Storage** Not available.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information 78,99% of the mixture consists of component(s) of unknown acute oral toxicity. 95,98% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment.

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General	inform	ation
Comorai		utivii

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Phenol Polymer With Formaldehyde, Glycidyl Ether	60 - 100	28064-14-4 -	-	-	
Classification:	-				
2-propenenitrile Polymer With 1,3-butadiene, Carboxy-terminated Reaction Products With Epichlorohydrin-2,2'-methylenebis[phenol] Polymer	10 - 30	68610-73-1 -	-	-	
Classification:	-				
Butyrolactone	5 - 10	96-48-0 202-509-5	-	-	
Classification:		4;H302;(ATE: 1540 000000002 mg/l), Ey	mg/kg bw), Acute Tox. 3;H33 re Irrit. 2;H319	31;(ATE:	
Silicon Dioxide	5 - 10	112945-52-5 231-545-4	-	-	
Classification:	_				
ethylbenzene	0,1 - 1	100-41-4 202-849-4	-	601-023-00-4	#
Classification:			4;H332;(ATE: 11 mg/l), Carc. H304, Aquatic Chronic 2;H41		

Other components below reportable

1 - 5

levels

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical

advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

Rash.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

Material name: Phillybond Orange Resin

DM014R Version #: 12 Revision date: 07-27-2023 Issue date: 06-24-2013

5.1. Extinguishing media

Suitable extinguishing

media

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting

procedures

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

E2 Hazardous to the Aquatic Environment Chronic (Lower-tier requirements = 200 tons;

Upper-tier requirements = 500 tons)

7.3. Specific end use(s)

Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Components	nce (GwV), BGBI. II, no. 184/2001 Type	, as amended Value	Form
ethylbenzene (CAS 100-41-4)	Ceiling	880 mg/m3	
		200 ppm	
	MAK	440 mg/m3	
		100 ppm	
Silicon Dioxide (CAS 112945-52-5)	MAK	4 mg/m3	Inhalable fraction.

Material name: Phillybond Orange Resin

Components	Туре	Value	
ethylbenzene (CAS 100-41-4)	STEL	551 mg/m3	
		125 ppm	
	TWA	87 mg/m3	
		20 ppm	

Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as amended

Components	Туре	Value	Form
ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3	
	TWA	435 mg/m3	
Silicon Dioxide (CAS 112945-52-5)	TWA	10 mg/m3	Inhalable fraction.
		0,07 mg/m3	Respirable fraction.

Croatia. OELs (GVI). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and Biological Limit Values, Annex I (NN 91/2018), as amended

Components	Туре	Value	Form
ethylbenzene (CAS 100-41-4)	MAC	442 mg/m3	
		100 ppm	
	STEL	884 mg/m3	
		200 ppm	
Silicon Dioxide (CAS 112945-52-5)	MAC	6 mg/m3	Total dust.
·		0,1 mg/m3	Respirable dust.

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended Components Type Value

Silicon Dioxide (CAS TWA 2 mg/m3 112945-52-5)

Cyprus. OELs. Occupational Exposure Limit Values of Chemicals at Work (Safety and Health at Work (Chem. Agents) Reg., Ann. 1, R.A.A. 268/2001, as amended)

Components	Туре	Value	
ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
		200 ppm	
	TWA	442 mg/m3	
		100 ppm	

Czech Republic. Occupational exposure limit values of chemicals at work (Decree on protection of health at work, 361/2007, Annex 2, Part A & Annex 3, Part A, as amended)

Components	Туре	Value	Form
ethylbenzene (CAS 100-41-4)	Ceiling	500 mg/m3	
	TWA	200 mg/m3	
Silicon Dioxide (CAS 112945-52-5)	TWA	4 mg/m3	Dust.

Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, Annex 2

Components	Туре	Value	
ethylbenzene (CAS 100-41-4)	TLV	217 mg/m3	
		50 ppm	

Estonia Components	Туре	Value	Form
Silicon Dioxide (CAS 112945-52-5)	TWA	2 mg/m3	Fine dust, respiratory fraction
Estonia. OELs. Occupational Exp Components	oosure Limits of Hazardous Su Type	bstances (Regulation No. 105 Value	/2001, Annex), as amended
ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
,		200 ppm	
	TWA	442 mg/m3	
		100 ppm	
Finland. HTP-arvot, App 3., Bindi Components	ng Limit Values, Social Affairs Type	and Ministry of Health Value	
Butyrolactone (CAS	STEL	70 mg/m3	
96-48-0)		250 ppm	
	TWA	14 mg/m3	
	1777	50 ppm	
ethylbenzene (CAS	STEL	880 mg/m3	
100-41-4)		200 ppm	
	TWA	220 mg/m3	
	IWA	50 ppm	
Silicon Dioxide (CAS	TWA	50 ppm 5 mg/m3	
112945-52-5)	IWA	3 mg/m3	
France. OELs. Occupational Exp Components	osure Limits as Prescribed by Type	Art. R.4412-149 of Labor Cod Value	e, as amended
ethylbenzene (CAS	VLE	442 mg/m3	
100-41-4)		100 ppm	
	VME	88,4 mg/m3	
	VIVIL	20 ppm	
France. Threshold Limit Values (VI ED) for Occupational Expos		NDS ED 004
Components	Type	Value	4K3 ED 904
ethylbenzene (CAS 100-41-4)	VLE	442 mg/m3	
•	ory binding (VRC)		
regulatory status:	(· · · · · · · · · · · · · · · · · · ·	100 ppm	
Regulatory status: Regulat	ory binding (VRC)		
•	VME	88,4 mg/m3	
Regulatory status: Regulation	ory binding (VRC)		
		20 ppm	
•	ory binding (VRC)		
Germany. DFG MAK List (adviso in the Work Area (DFG), as upda		Investigation of Health Hazard	ds of Chemical Compounds
Components	Туре	Value	Form
ethylbenzene (CAS 100-41-4)	TWA	88 mg/m3	
100-T1-T <i>)</i>		20 ppm	
Silicon Dioxide (CAS 112945-52-5)	TWA	4 mg/m3	Inhalable fraction.
Germany. TRGS 900, Limit Value	s in the Amhient Air at the We	rknlace	
Components	s in the Ambient Air at the Wol	rkpiace Value	Form
ethylbenzene (CAS 100-41-4)	AGW	88 mg/m3	

Silicon Dioxide (CAS AGW 4 mg/m3 Inhalable fraction.	Components	Туре	Value	Form
STEL S45 mg/m3 125 ppm		AGW	4 mg/m3	Inhalable fraction.
125 ppm			Value	
TWA		STEL	545 mg/m3	
TWA	100-41-4)		405	
100 ppm		Τ\Λ/Λ		
Section Components Type Value		IVVA	•	
TWA		-	emical agents (5/2020. (II.6)),	Annex 1&2, as amended
TWA	ethylbenzene (CAS	<u> </u>	884 mg/m3	
Celand. OELs. Regulation 390/2009 on Pollution Limits and Measures to Reduce Pollution at the Workplace, as amende Components	100-41-4)	T\A/A	442 mg/m2	
Type			•	
100-41-4) 100-41-4 200 ppm 200 mg/m3 50 ppm				
TWA 200 ppm TWA 200 mg/m3 50 ppm 50		STEL	884 mg/m3	
Silicon Dioxide (CAS TWA 50 ppm 5 mg/m3 Respirable dust.	,		200 ppm	
TWA		TWA	200 mg/m3	
12945-52-5) 10 mg/m3 Total dust. 0,5 mg/m3 Dust.			50 ppm	
Components		TWA	5 mg/m3	Respirable dust.
reland. OELVs, Schedules 1 & 2, Code of Practice for Chemical Agents and Carcinogens Regulations Components Type STEL 884 mg/m3 200 ppm TWA 442 mg/m3 100 ppm	,		10 mg/m3	Total dust.
Type Value Form			0,5 mg/m3	Dust.
100-41-4 200 ppm				
TWA 442 mg/m3 100 ppm 6 mg/m3 Total inhalable dust. 12945-52-5) TWA 6 mg/m3 Total inhalable dust. 2,4 mg/m3 Respirable dust. 1419. OELs (Legislative Decree n.81, 9 April 2008), as amended Components Type Value 100-41-4) TWA 442 mg/m3 100 ppm TWA 200 ppm TWA 442 mg/m3 100 ppm		STEL	884 mg/m3	
100 ppm 100			200 ppm	
TWA 6 mg/m3 Total inhalable dust.		TWA	442 mg/m3	
12945-52-5) 2,4 mg/m3 Respirable dust.			100 ppm	
taly. OELs (Legislative Decree n.81, 9 April 2008), as amended Components Type Value STEL 884 mg/m3 200 ppm TWA 442 mg/m3 100 ppm Latvia. OELs. Occupational Exposure Limits of Chemical Substances at Workplace (Reg. No. 325/ 2007, L.V. 80, Annex I), as amended Components Type Value STEL 884 mg/m3 100 ppm TWA 442 mg/m3 100-41-4) TWA 442 mg/m3 100 ppm Silicon Dioxide (CAS) TWA 1 mg/m3		TWA	6 mg/m3	Total inhalable dust.
Ethylbenzene (CAS STEL 884 mg/m3 200 ppm 200 ppm	,			Poppirable dust
100-41-4 200 ppm	,		2,4 mg/m3	Respirable dust.
100-41-4) 200 ppm 200 ppm 442 mg/m3 100 ppm 200	taly. OELs (Legislative Decree			Respirable dust.
TWA 442 mg/m3 100 ppm Latvia. OELs. Occupational Exposure Limits of Chemical Substances at Workplace (Reg. No. 325/ 2007, L.V. 80, Annex 1), as amended Components Type Value STEL 884 mg/m3 00-41-4) TWA 442 mg/m3 100 ppm TWA 442 mg/m3 100 ppm Silicon Dioxide (CAS TWA 1 mg/m3	taly. OELs (Legislative Decree Components	Туре	Value	Respirable dust.
Latvia. OELs. Occupational Exposure Limits of Chemical Substances at Workplace (Reg. No. 325/ 2007, L.V. 80, Annex I), as amended Components Type Value ethylbenzene (CAS STEL 884 mg/m3 200 ppm TWA 442 mg/m3 100 ppm Silicon Dioxide (CAS TWA 1 mg/m3	taly. OELs (Legislative Decree Components ethylbenzene (CAS	Туре	Value 884 mg/m3	Respirable dust.
Latvia. OELs. Occupational Exposure Limits of Chemical Substances at Workplace (Reg. No. 325/ 2007, L.V. 80, Annex I), as amended Components Type Value STEL 884 mg/m3 200 ppm TWA 442 mg/m3 100 ppm Silicon Dioxide (CAS) TWA 1 mg/m3	taly. OELs (Legislative Decree Components ethylbenzene (CAS	Type STEL	Value 884 mg/m3 200 ppm	Respirable dust.
Type Value	taly. OELs (Legislative Decree Components ethylbenzene (CAS	Type STEL	Value 884 mg/m3 200 ppm 442 mg/m3	Respirable dust.
## STEL 884 mg/m3 200 ppm TWA 442 mg/m3 100 ppm 100 ppm 1 1 mg/m3 1 1 mg/m3	taly. OELs (Legislative Decree Components ethylbenzene (CAS	Type STEL	Value 884 mg/m3 200 ppm 442 mg/m3	Respirable dust.
100-41-4) 200 ppm TWA 442 mg/m3 100 ppm Silicon Dioxide (CAS TWA 1 mg/m3	taly. OELs (Legislative Decree Components ethylbenzene (CAS 100-41-4) Latvia. OELs. Occupational Exp	Type STEL TWA posure Limits of Chemical Substa	Value 884 mg/m3 200 ppm 442 mg/m3 100 ppm ances at Workplace (Reg. No	
TWA 442 mg/m3 100 ppm Silicon Dioxide (CAS TWA 1 mg/m3	taly. OELs (Legislative Decree Components thylbenzene (CAS 00-41-4) Latvia. OELs. Occupational Exp.	Type STEL TWA posure Limits of Chemical Substa	Value 884 mg/m3 200 ppm 442 mg/m3 100 ppm ances at Workplace (Reg. No	
100 ppm Silicon Dioxide (CAS TWA 1 mg/m3	taly. OELs (Legislative Decree Components ethylbenzene (CAS 100-41-4) Latvia. OELs. Occupational Expl.), as amended Components ethylbenzene (CAS	Type STEL TWA posure Limits of Chemical Substa	Value 884 mg/m3 200 ppm 442 mg/m3 100 ppm ances at Workplace (Reg. No	
Silicon Dioxide (CAS TWA 1 mg/m3	taly. OELs (Legislative Decree Components http://docs.com/docs/docs/docs/docs/docs/docs/docs/docs	Type STEL TWA posure Limits of Chemical Substa	Value 884 mg/m3 200 ppm 442 mg/m3 100 ppm ances at Workplace (Reg. No	
	taly. OELs (Legislative Decree Components http://docs.com/docs/docs/docs/docs/docs/docs/docs/docs	Type STEL TWA posure Limits of Chemical Substate Type STEL	Value 884 mg/m3 200 ppm 442 mg/m3 100 ppm ances at Workplace (Reg. No Value 884 mg/m3 200 ppm	
	taly. OELs (Legislative Decree Components ethylbenzene (CAS 100-41-4) Latvia. OELs. Occupational Explain, as amended Components ethylbenzene (CAS 100-41-4)	Type STEL TWA Dosure Limits of Chemical Substate Type STEL TWA	Value 884 mg/m3 200 ppm 442 mg/m3 100 ppm ances at Workplace (Reg. No Value 884 mg/m3 200 ppm 442 mg/m3 100 ppm	

Components	Туре	Value	
ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
		200 ppm	
	TWA	442 mg/m3	
		100 ppm	

Luxembourg. OELs. Binding Occupational Exposure Limit Values (Annex I), G.D.R. of 14 November 2016, OJ Memorial A, $n \circ 235/2016$, as amended

Components	Type	Value	
ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
		200 ppm	
	TWA	442 mg/m3	
		100 ppm	

Malta. OELs. Protection of Health and Safety of Workers from Risks related to Chemical Agents at Work (L.N 227/2003 Schedules I and V), as amended

Components	Туре	Value	
ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
		200 ppm	
	TWA	442 mg/m3	
		100 ppm	

Netherlands. OELs per Annex XIII of Working Conditions Regulation (Staatscourant no. 252, 29 December 2006), as amended

Components	Туре	Value	
ethylbenzene (CAS 100-41-4)	STEL	430 mg/m3	
	TWA	215 mg/m3	

Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended

Components	Туре	Value	Form
ethylbenzene (CAS 100-41-4)	TLV	20 mg/m3	
		5 ppm	
Silicon Dioxide (CAS 112945-52-5)	TLV	1,5 mg/m3	Respirable dust.

Poland. Maximum permissible concentrations and intensities of harmful factors in the work environment (Dz.U.Poz. 1286/2018, Annex 1)

Components	Туре	Value	
ethylbenzene (CAS 100-41-4)	STEL	400 mg/m3	
	TWA	200 mg/m3	

Portugal. Decree-Law No. 24/2012, Occupational Exposure Limit Values, Annex II, as amended Components Type Value

ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3
		200 ppm
	TWA	442 mg/m3
		100 ppm

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796-2014) Components Type Value

ethylbenzene (CAS	TWA	20 ppm
100-41-4)		

Romania. OELs. Limit Values of Chemical Agents at Workplace (Regulation 1.218/2006, M.O 845, Annex 1, 3&4, as amended)

Components	Туре	Value	
ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
		200 ppm	
	TWA	442 mg/m3	
		100 ppm	

Slovakia. OELs. Maximum permissible exposure limits for chemical factors in workplace air (Regulation No 355/2006, Annex 1, Table 1, as amended)

Components	Туре	Value	
ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
		200 ppm	
	TWA	442 mg/m3	
		100 ppm	
Silicon Dioxide (CAS 112945-52-5)	TWA	0,3 mg/m3	

Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Annex I), as amended

Components	Туре	Value	Form
ethylbenzene (CAS 100-41-4)	TWA	442 mg/m3	
		100 ppm	
Silicon Dioxide (CAS 112945-52-5)	TWA	4 mg/m3	Inhalable fraction.

Spain. OELs. INSST, Límites de Exposición Profesional Para Agentes Químicos, Table 1-Valores Límites Ambientales (VLAs)

Components	Туре	Value	
ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
		200 ppm	
	TWA	441 mg/m3	
		100 ppm	

Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended

Components	Туре	Value
ethylbenzene (CAS 100-41-4)	Ceiling	884 mg/m3
		200 ppm
	TWA	220 mg/m3
		50 ppm

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte

Components	Туре	Value	
ethylbenzene (CAS 100-41-4)	STEL	220 mg/m3	
		50 ppm	
	TWA	220 mg/m3	
		50 ppm	

UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1

Components	Type	Value Form
ethylbenzene (CAS 100-41-4)	STEL	552 mg/m3
		125 ppm
	TWA	441 mg/m3

UK. OELs. Workplace Exposul Components	re Limits (WELs) (EH40/2005 (Fou Type	rth Edition 2020)), Table 1 Value	Form
		100 ppm	
Silicon Dioxide (CAS 112945-52-5)	TWA	6 mg/m3	Inhalable dust.
		2,4 mg/m3	Respirable dust.
EU. Indicative Exposure Limit Components	Values in Directives 91/322/EEC, Type	2000/39/EC, 2006/15/EC, 2009 Value	/161/EU, 2017/164/EU
•	•	,	/161/EU, 2017/164/EU
Components ethylbenzene (CAS	Туре	Value	/161/EU, 2017/164/EU
Components ethylbenzene (CAS	Туре	Value 884 mg/m3	/161/EU, 2017/164/EU

Biological limit values

Croatia. BELs (BGV). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and BELs, Annex IV (NN 91/2018), as amended

Components	Value	Determinant	Specimen	Sampling Time	
ethylbenzene (CAS 100-41-4)	1,5 g/g	Mandelic acid	Creatinine in urine	*	
	1,5 mg/l	ethylbenzene	Blood	*	
	1,12 mol/mol	Mandelic acid	Creatinine in urine	*	
	14,1 umol/l	ethylbenzene	Blood	*	

^{* -} For sampling details, please see the source document.

Czech Republic. BELs. Government Decree 432/2003 Sb., as amended

Components	Value	Determinant	Specimen	Sampling Time	
ethylbenzene (CAS 100-41-4)	1100 µmol/mmol	Mandelic acid	Creatinine in urine	*	
	1500 mg/g	Mandelic acid	Creatinine in urine	*	

^{* -} For sampling details, please see the source document.

Finland. HTP-arvot, App 2., Biological Limit Values, Social Affairs and Ministry of Health

Components	Value	Determinant	Specimen	Sampling Time
ethylbenzene (CAS 100-41-4)	5,2 mmol/l	Mandelic acid	Urine	*

^{* -} For sampling details, please see the source document.

France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS), ND 2065)

Components	Value	Determinant	Specimen	Sampling Time
ethylbenzene (CAS 100-41-4)	1500 mg/g	Acide mandélique	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Germany. TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling Time	
ethylbenzene (CAS 100-41-4)	250 mg/g	Mandelsäure plus Phenylglyoxyls äure	Creatinine in urine	*	

^{* -} For sampling details, please see the source document.

Hungary. BELs. Decree on protection of workers exposed to chemical agents (5/2020. (II.6)), Annex 3&4, as amended

Components	Value	Determinant	Specimen	Sampling Time	
ethylbenzene (CAS 100-41-4)	1110 µmol/mmol	mandelic acid	Creatinine in urine	*	
	1500 mg/g	mandelic acid	Creatinine in urine	*	

^{* -} For sampling details, please see the source document.

Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents. Annex 2

Components	Value	Determinant	Specimen	Sampling Time
ethylbenzene (CAS 100-41-4)	8,03 mg/g	2 and 4-ethylphenol	Creatinine in urine	*
	12 mg/l	2 and 4-ethylphenol	Urine	*

^{* -} For sampling details, please see the source document.

Spain. BELs. INSST, L	ímites de Exposició	n Profesional Para Agen	ites Químicos, 1	Γable 3-Valores Límite Biológicos (VLB)
Components	Value	Determinant	Specimen	Sampling Time
ethylbenzene (CAS 100-41-4)	700 mg/g	Suma del acido mandélico y el ácido	Creatinine in urine	*

fenilglioxílico

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle BAT-Werte

Components	Value	Determinant	Specimen	Sampling Time
ethylbenzene (CAS 100-41-4)	600 mg/g	Mandelsäure + Phenylglyoxyls äure	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no effect levels

(DNELs)

Not available.

Predicted no effect Not available.

concentrations (PNECs)

Exposure guidelinesOccupational Exposure Limits are not relevant to the current physical form of the product.

Austria MAK: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Belgium OELs: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Bulgaria OELs: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Croatia ELVs: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Czech Republic PELs: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Denmark GV: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Estonia OELs: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

EU Exposure Limit Values: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Finland Exposure Limit Values: Skin designation

Butyrolactone (CAS 96-48-0)

Can be absorbed through the skin.

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

France INRS: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

France Mandatory OELs (VLEP): Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Germany DFG MAK (advisory): Skin designation

Butyrolactone (CAS 96-48-0)

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Can be absorbed through the skin.

Germany TRGS 900 Limit Values: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin. **Hungary OELs: Skin designation**

Iceland OELs: Skin designation

ethylbenzene (CAS 100-41-4)

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Can be absorbed through the skin.

^{* -} For sampling details, please see the source document.

Ireland Exposure Limit Values: Skin designation

ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Italy OELs: Skin designation

ethylbenzene (CAS 100-41-4)

Danger of cutaneous absorption

Latvia OELs: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Lithuania OELs: Skin designation

ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Luxembourg OELs: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Malta OELs: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Netherlands OELs (binding): Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Norway Exposure Limit Values: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Portugal OELs: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Romania OELs: Skin designation

ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Slovakia OELs: Skin designation

ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Spain OELs: Skin designation ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

Sweden Threshold Limit Values: Skin designation

ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Switzerland SUVA Limit Values at the Workplace: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

UK EH40 WEL: Skin designation

ethylbenzene (CAS 100-41-4)

Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

showe

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

- Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

Environmental exposure

controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Not available.

Material name: Phillybond Orange Resin

DM014R Version #: 12 Revision date: 07-27-2023 Issue date: 06-24-2013

Paste. **Form** Orange. Color Slight. Odor

Melting point/freezing point Not available. Boiling point or initial boiling Not available.

point and boiling range

Flammability Not available. Upper/lower flammability or explosive limits

Explosive limit - upper (%) 16 % estimated

>300,0 °F (>148,9 °C) Flash point

Auto-ignition temperature Not available. Not available. **Decomposition temperature** Not available. Kinematic viscosity Not available.

Solubility

Solubility (water) Not available. Not available. Partition coefficient

(n-octanol/water) (log value)

0,6 hPa Vapor pressure

Density and/or relative density

Density 1,11 g/cm3 Not available. Vapor density **Particle characteristics** Not available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No relevant additional information available.

9.2.2. Other safety characteristics

1.11 Specific gravity

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Contact with incompatible materials.

10.5. Incompatible materials Strong oxidizing agents.

No hazardous decomposition products are known. 10.6. Hazardous

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.

Skin contact Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.

Causes serious eye irritation. Eye contact

May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of Ingestion

occupational exposure.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred **Symptoms**

vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis, Rash.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Harmful in contact with skin.

DM014R Version #: 12 Revision date: 07-27-2023 Issue date: 06-24-2013

Components **Species Test Results**

Butyrolactone (CAS 96-48-0)

Acute

Dermal

LD50 Guinea pig 5640 mg/kg

Inhalation

LC50 Rat > 2680 mg/m3, 4 Hours

Oral

LD50 Rat 1540 mg/kg

ethylbenzene (CAS 100-41-4)

Acute Dermal

Rabbit LD50 17800 mg/kg

Oral

LD50 Rat 3500 mg/kg

Silicon Dioxide (CAS 112945-52-5)

Acute Oral

LD50 > 22500 mg/kg Rat

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Due to partial or complete lack of data the classification is not possible. Respiratory sensitization

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Risk of cancer cannot be excluded with prolonged exposure. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Butyrolactone (CAS 96-48-0) 3 Not classifiable as to carcinogenicity to humans.

ethylbenzene (CAS 100-41-4) 2B Possibly carcinogenic to humans.

Silicon Dioxide (CAS 112945-52-5) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

11.2. Information on other hazards

Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life with long lasting effects. Based on available data, the classification criteria are

not met for hazardous to the aquatic environment, acute hazard.

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

Butyrolactone -0.64ethylbenzene 3,15

Bioconcentration factor (BCF) Not available. 12.4. Mobility in soil No data available. 12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

12.7. Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

12.8. Additional information

Estonia Dangerous substances in soil Data

ethylbenzene (CAS 100-41-4) ETHYLBENZENE 0.1 MG/KG

> ETHYLBENZENE 5 MG/KG ETHYLBENZENE 50 MG/KG

Silicon Dioxide (CAS 112945-52-5) Chemical pesticides (As the total sum of the active substances)

0.5 MG/KG

Chemical pesticides (As the total sum of the active substances) 20

MG/KG

Chemical pesticides (As the total sum of the active substances) 5

MG/KG

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow Disposal methods/information

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN3082

14.2. UN proper shipping

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Phenol Polymer With

Formaldehyde, Glycidyl Ether)

14.3. Transport hazard class(es)

9 Class Subsidiary risk 9 Label(s) Hazard No. (ADR) 90 **Tunnel restriction code** Ш 14.4. Packing group 14.5. Environmental hazards No.

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

name

RID

UN3082 14.1. UN number

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Phenol Polymer With 14.2. UN proper shipping

Formaldehyde, Glycidyl Ether) name

14.3. Transport hazard class(es)

9 Class Subsidiary risk Label(s) q Ш 14.4. Packing group 14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

UN3082 14.1. UN number

14.2. UN proper shipping ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Phenol Polymer With

name Formaldehyde, Glycidyl Ether)

14.3. Transport hazard class(es)

Class 9
Subsidiary risk Label(s) 9
14.4. Packing group III
14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN3082

14.2. UN proper shipping Environmentally hazardous substance, liquid, n.o.s. (Phenol Polymer With Formaldehyde,

name Glycidyl Ether)

14.3. Transport hazard class(es)

Class 9
Subsidiary risk 14.4. Packing group III
14.5. Environmental hazards No.
ERG Code 9L

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

14.1. UN number UN3082

14.2. UN proper shipping ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Phenol Polymer With

name Formaldehyde, Glycidyl Ether)

14.3. Transport hazard class(es)

Class 9
Subsidiary risk 14.4. Packing group III
14.5. Environmental hazards
Marine pollutant No.

EmS F-A, S-F

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

14.7. Maritime transport in bulk according to IMO instruments

Not applicable. Not established.

ADN; ADR; IATA; IMDG; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Material name: Phillybond Orange Resin

SDS EU

DM014R Version #: 12 Revision date: 07-27-2023 Issue date: 06-24-2013

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Silicon Dioxide (CAS 112945-52-5) ethylbenzene (CAS 100-41-4)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

UFI:

Austria: TWD0-S0C2-G00Y-1YHC Belgium: TWD0-S0C2-G00Y-1YHC Bulgaria: TWD0-S0C2-G00Y-1YHC Croatia: TWD0-S0C2-G00Y-1YHC Cyprus: TWD0-S0C2-G00Y-1YHC

Czech Republic: TWD0-S0C2-G00Y-1YHC Denmark: TWD0-S0C2-G00Y-1YHC Estonia: TWD0-S0C2-G00Y-1YHC EU: TWD0-S0C2-G00Y-1YHC Finland: TWD0-S0C2-G00Y-1YHC France: TWD0-S0C2-G00Y-1YHC Germany: TWD0-S0C2-G00Y-1YHC Greece: TWD0-S0C2-G00Y-1YHC Hungary: TWD0-S0C2-G00Y-1YHC Iceland: TWD0-S0C2-G00Y-1YHC Ireland: TWD0-S0C2-G00Y-1YHC Italy: TWD0-S0C2-G00Y-1YHC Latvia: TWD0-S0C2-G00Y-1YHC Lithuania: TWD0-S0C2-G00Y-1YHC Luxembourg: TWD0-S0C2-G00Y-1YHC Malta: TWD0-S0C2-G00Y-1YHC Netherlands: TWD0-S0C2-G00Y-1YHC

Netherlands: TWD0-S0C2-G00Y-1YHC
Norway: TWD0-S0C2-G00Y-1YHC
Poland: TWD0-S0C2-G00Y-1YHC
Portugal: TWD0-S0C2-G00Y-1YHC
Romania: TWD0-S0C2-G00Y-1YHC
Slovakia: TWD0-S0C2-G00Y-1YHC
Slovenia: TWD0-S0C2-G00Y-1YHC
Spain: TWD0-S0C2-G00Y-1YHC
Sweden: TWD0-S0C2-G00Y-1YHC

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

ethylbenzene (CAS 100-41-4)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Other EU regulations Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- E2 Hazardous to the Aquatic Environment Chronic

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Young people under 18 years old are not allowed to work with this product according to EU

Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

Contains a substance which is included on the TRGS 905 list of carcinogenic, germ cell mutagenic and reproductive toxic substances

Silicon Dioxide (CAS 112945-52-5)

Anorganische Faserstäube, soweit nicht erwähnt (ausgenommen Gipsfasernund Wollastonitfasern)

Material name: Phillybond Orange Resin

France regulations

France INRS Table of Occupational Diseases

ethylbenzene (CAS 100-41-4)

Affections engendrées par les solvants organiques liquides à usage professionnel: hydrocarbures liquides aliphatiques ou cycliques saturés ou insaturés et leurs mélanges; hydrocarbures halogénés liquides; dérivés nitrés des hydrocarbures aliphatiques; al 84

Phenol Polymer With Formaldehyde, Glycidyl Ether (CAS 28064-14-4)

Maladies professionnelles provoquées par les résines époxydiques et leurs constituants 51

Product registration number

UFI: TWD0-S0C2-G00Y-1YHC Austria UFI: TWD0-S0C2-G00Y-1YHC Belgium Czech Republic UFI: TWD0-S0C2-G00Y-1YHC **Denmark** UFI: TWD0-S0C2-G00Y-1YHC **European Union** UFI: TWD0-S0C2-G00Y-1YHC **Finland** UFI: TWD0-S0C2-G00Y-1YHC **France** UFI: TWD0-S0C2-G00Y-1YHC Germany UFI: TWD0-S0C2-G00Y-1YHC UFI: TWD0-S0C2-G00Y-1YHC Greece UFI: TWD0-S0C2-G00Y-1YHC Hungary UFI: TWD0-S0C2-G00Y-1YHC Italy UFI: TWD0-S0C2-G00Y-1YHC Netherlands UFI: TWD0-S0C2-G00Y-1YHC Norway **Poland** UFI: TWD0-S0C2-G00Y-1YHC **Portugal** UFI: TWD0-S0C2-G00Y-1YHC UFI: TWD0-S0C2-G00Y-1YHC Slovakia Slovenia UFI: TWD0-S0C2-G00Y-1YHC Spain UFI: TWD0-S0C2-G00Y-1YHC Sweden UFI: TWD0-S0C2-G00Y-1YHC UFI: TWD0-S0C2-G00Y-1YHC Switzerland

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H331 Toxic if inhaled. H332 Harmful if inhaled.

Material name: Phillybond Orange Resin

SDS FII

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Physical & Chemical Properties: Multiple Properties

Revision information Training information Disclaimer

Follow training instructions when handling this material.

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: Phillybond Orange Resin

SDS EU DM014R Version #: 12 Revision date: 07-27-2023 Issue date: 06-24-2013