SAFETY DATA SHEET

Version #: 11

Issue date: 07-25-2013 Revision date: 09-02-2024 Supersedes date: 08-04-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

Expansion Joint Compound Resin

Registration number

Synonyms None.

SKU# DM015R, DM016R

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified usesNot available.Uses advised againstNone known.

1.3. Details of the supplier of the safety data sheet

Company Name ITW Performance Polymers

Address Bay 150

Shannon Industrial Estate

Co. Clare Ireland V14 DF82

Contact Person Customer Service
Telephone Number 353(61)771500

353(61)471285

Email customerservice.shannon@itwpp.com

Emergency Phone Number 44(0) 1235 239 670 (24 hours)

1.4. Emergency telephone number

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons Information Center

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Belgium National Poisons Control Center

070 245 245 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Bulgaria National

Toxicological Information

Center

+359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Croatia Poisons Information Center

+385 1 2348 342 (Hours of operation not provided. SDS/Product information may

not be available for the Emergency Service.)

Cyprus Poison Center 1401 (Available 24 hours a day. SDS/Product information may not be available

for the Emergency Service.)

Czech Republic National Poisons Information Center

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons Control Center +45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Estonia National Poisons Information Center

 $16662\ or\ abroad:\ (+372)\ 626\ 9390\ (Monday\ 9:00AM\ to\ Saturday\ 9:00AM\ (closed\ on\ Sundays\ and\ on\ national\ holidays).\ SDS/Product\ information\ may\ not\ be$

available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Material name: Expansion Joint Compound Resin

1.4. Emergency telephone number

Greece Poison Information

Centre

(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Hungary National Emergency Phone Number +36-80-201-199 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Iceland Poison Center

(+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Latvia Emergency medical

aid

113

Latvia Poison and Drug Information Center

+371 67042473 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Lithuania Neatidėliotina informacija apsinuodijus

+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and **Emergency Department**

2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Netherlands National Poisons Information Center (NVIC)

NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel

in cases of acute intoxications)

Norway Norwegian Poison Information Center

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Portugal Poison Center

800 250 250 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Romania Biroul RSI si Informare Toxicologica 021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be

available for the Emergency Service.)

Slovakia National Toxicological Information Center

+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Spain Toxicology Information Service + 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Sweden National Poison Information Center

112 - and ask for Poison Information (Available 24 hours a day. SDS/Product

information may not be available for the Emergency Service.)

Switzerland Tox Info Suisse

145 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Skin corrosion/irritation Category 2 H315 - Causes skin irritation. Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Skin sensitization Category 1 H317 - May cause an allergic skin

reaction.

Environmental hazards

Hazardous to the aquatic environment, Category 2 H411 - Toxic to aquatic life with long-term aquatic hazard

long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

UFI:

EU: 5T05-P18D-R006-FE6W

Contains: Blocked polyisocyanate, Talc, Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers

Hazard pictograms



Signal word Warning

Material name: Expansion Joint Compound Resin

Hazard statements

Causes skin irritation. H315

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Toxic to aquatic life with long lasting effects. H411

Precautionary statements

Prevention

P261 Avoid breathing mist/vapors. P264 Wash thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment. P280 Wear eye protection/face protection.

Wear protective gloves. P280

Response

P302 + P352 IF ON SKIN: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and P305 + P351 + P338

easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P337 + P313 If eye irritation persists: Get medical advice/attention. P362 + P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage. Storage Not available.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

32,92681% of the mixture consists of component(s) of unknown acute oral toxicity. Supplemental label information

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation 2.3. Other hazards

(EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a

concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Blocked polyisocyanate	30 - 60	N/A	-	-	
Classificat	tion: -				
Talc	10 - 30	14807-96-6 238-877-9	-	-	
Classificat	t ion: Carc. 2;H3	51			
Propane, 2,2-bis[p-(2,3-epoxypropoxy)pher polymers	10 - < 20 nyl]-,	25085-99-8 -	01-2119456619-26-0000	-	
Classificat	tion: Skin Irrit. 2 Chronic 2;		319, Skin Sens. 1;H317, Aqua	atic	
Butyrolactone	5 - 10	96-48-0 202-509-5	-	-	
Classificat		4;H302;(ATE: 1540 Irrit. 2;H319	mg/kg bw), Acute Tox. 3;H33	31;(ATE: 2,68	
nonylphenol; [1] 4-nonylphenol, branched [2]	1 - <3	84852-15-3 284-325-5	-	601-053-00-8	ED
Classificat			ng/kg bw), Skin Corr. 1B;H31 ic Acute 1;H400, Aquatic Chr		
Other components below reportal	ole 1 - 5				

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

levels

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Material name: Expansion Joint Compound Resin

SDS EU

SECTION 4: First aid measures

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

Rash.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

5.1. Extinguishing media

No unusual fire or explosion hazards noted.

Suitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Ensure adequate ventilation. Avoid breathing mist/vapors. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Material name: Expansion Joint Compound Resin

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- E2 Hazardous to the Aquatic Environment Chronic (Lower-tier requirements = 200 tons;

Upper-tier requirements = 500 tons)

7.3. Specific end use(s)

Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinand Components	Type	Value	Form		
Гаlc (CAS 14807-96-6)	MAK	2 mg/m3	Respirable fraction.		
	STEL	20 mg/m3	Inhalable fraction.		
		10 mg/m3	Respirable fraction.		
Belgium. OEL. Exposure Limit V Chemical agents, as amended	alues to Chemical Substances a	at Work, Code of Well-being at v	work, Book VI, Title 1 -		
Components	Туре	Value			
Talc (CAS 14807-96-6)	TWA	2 mg/m3			
Bulgaria. OELs. Ordinance No 13 amended	on protection of workers again	nst risks of exposure to chemic	al agents at work, as		
Components	Туре	Value	Form		
Talc (CAS 14807-96-6)	TWA	1 fibers/cm3	Respirable fraction.		
		6 mg/m3	Inhalable fraction.		
		3 mg/m3	Respirable fraction.		
Croatia. OELs (GVI). Regulation (Biological Limit Values, Annex I	(NN 91/2018), as amended				
Components	Туре	Value	Form		
Гalc (CAS 14807-96-6)	MAC	1 mg/m3	Respirable dust.		
Cyprus. OELs. Control of factory Components	atmosphere and dangerous su Type	ubstances in factories regulatio Value	n, PI 311/73, as amende		
Talc (CAS 14807-96-6)	TWA	706 part/cm3	706 part/cm3		
Czech Republic. Occupational ex 361/2007, Annex 2, Part A & Ann		als at work (Decree on protectio	n of health at work,		
Components	Type	Value	Form		
alc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable dust.		
		10 mg/m3	Total dust.		
Denmark. Work Environment Au	thority. Exposure Limits for Sul	hstances & Materials, Annex 2			
Components	Type	Value	Form		
Talc (CAS 14807-96-6)	OTEL	0,006 mg/m3	- "		
	STEL	0,000 1119/1113	Fiber.		
,	TLV	0,000 filers/cm3	Fiber. Fiber.		
Estonia. OELs. Occupational Exp	TLV	0,003 fibers/cm3	Fiber.		
Estonia. OELs. Occupational Exp Components Talc (CAS 14807-96-6)	TLV posure Limits of Hazardous Sub	0,003 fibers/cm3	Fiber. 001, Annex), as amende		
Estonia. OELs. Occupational Ex Components	TLV posure Limits of Hazardous Sul Type	0,003 fibers/cm3 bstances (Regulation No. 105/20 Value	Fiber. 001, Annex), as amende Form Fine dust, respiratory		
Estonia. OELs. Occupational Exp Components Talc (CAS 14807-96-6) Finland. HTP-arvot, App 3., Bind	TLV posure Limits of Hazardous Sub Type TWA	0,003 fibers/cm3 bstances (Regulation No. 105/20 Value 5 mg/m3 10 mg/m3	Fiber. 001, Annex), as amende Form Fine dust, respiratory fraction		
Estonia. OELs. Occupational Ex Components	TLV posure Limits of Hazardous Sub Type TWA ing Limit Values, Social Affairs	0,003 fibers/cm3 bstances (Regulation No. 105/20 Value 5 mg/m3 10 mg/m3 and Ministry of Health	Fiber. 001, Annex), as amende Form Fine dust, respiratory fraction Total dust.		

Material name: Expansion Joint Compound Resin

Finland. HTP-arvot, App 3., Binding Components	Type	Value	Form	
	TWA	14 mg/m3		
		50 ppm		
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Inhalable dust.	
		1 mg/m3	Respirable.	
Germany. DFG MAK List (advisory in the Work Area (DFG), as updated		nvestigation of Health Hazard	s of Chemical Compounds	
Components	Туре	Value	Form	
Talc (CAS 14807-96-6)	TWA	4 mg/m3	Inhalable dust.	
Germany. TRGS 900, Limit Values i Components	n the Ambient Air at the Wor Type	kplace Value	Form	
Talc (CAS 14807-96-6)	<u> </u>		Inhalable fraction.	
1410 (0/10 1400/-30 0)	7.OW	10 mg/m3 1,25 mg/m3	Respirable fraction.	
Greece. OELs, Presidential Decree Components	No. 307/1986, as amended Type	Value	Form	
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.	
,		10 mg/m3	Inhalable	
Hungary. OELs. Decree on protecti Components	on of workers exposed to ch Type		Annex 1&2, as amended Form	
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable dust.	
celand. OELs. Regulation 390/2009 Components	on Pollution Limits and Mea Type	asures to Reduce Pollution at t Value	the Workplace, as amende Form	
Talc (CAS 14807-96-6)	TWA	0,3 fibers/cm3	Fiber.	
		5 mg/m3	Respirable dust.	
		10 mg/m3	Total dust.	
ireland. OELVs, Schedules 1 & 2, C Components	ode of Practice for Chemical Type	Agents and Carcinogens Reg Value	ulations Form	
Talc (CAS 14807-96-6)	TWA	10 mg/m3	Total inhalable dust.	
, ,		0,8 mg/m3	Respirable dust.	
taly. OELs (Legislative Decree n.81	I 9 Δnril 2008) as amended		·	
Components	Type	Value	Form	
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.	
Lithuania. OELs. Occupational Exp		· ·	•	
V-824/A1-389), as amended	Osure Limit values for Chem	iicai Substances (Hygiene Noi	iii fin 23.2011, Older No.	
Components	Туре	Value	Form	
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Inhalable fraction.	
		1 mg/m3	Respirable fraction.	
Netherlands. OELs per Annex XIII c amended	of Working Conditions Regula	ation (Staatscourant no. 252, 2	9 December 2006), as	
Components	Туре	Value	Form	
Talc (CAS 14807-96-6)	TWA	0,25 mg/m3	Respirable dust.	
Poland. Maximum permissible cond 1286/2018, Annex 1)	centrations and intensities of	f harmful factors in the work e	nvironment (Dz.U.Poz.	
Components	Туре	Value	Form	
Talc (CAS 14807-96-6)	TWA	4 mg/m3	Inhalable fraction.	
		1 mg/m3	Respirable fraction.	
Portugal. VLEs. Norm on occupatio Components	onal exposure to chemical ag Type	ents (NP 1796-2014) Value	Form	
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.	
14.5 (0/10 1 1001 -00-0)	1 ¥ # / \	2 mg/mo	respirable fraction.	

Romania. OELs. Limit Values of Chemical Agents at Workplace (Regulation 1.218/2006, M.O 845, Annex 1, 3&4, as amended) **Form** Components **Type** Value Talc (CAS 14807-96-6) TWA 2 mg/m3 Respirable fraction. Slovakia. OELs. Maximum permissible exposure limits for chemical factors in workplace air (Regulation No 355/2006, Annex 1, Table 1, as amended) Components Value **Type** Talc (CAS 14807-96-6) TWA 2 mg/m3 Respirable fraction. 2 mg/m3 Respirable fraction. 10 mg/m3 Total Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Ann. I 100/2001), as amended Form Components **Type** Value Talc (CAS 14807-96-6) **KTV** 20 mg/m3 Inhalable fraction. 2,5 mg/m3 Respirable fraction. Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Annex I), as amended Form Components Value Type Talc (CAS 14807-96-6) TWA Inhalable fraction. 10 mg/m3 1,25 mg/m3 Respirable fraction. Spain. OELs. INSST, Límites de Exposición Profesional Para Agentes Químicos, Table 1-Valores Límites Ambientales (VLAs) Form Components Value **Type** Talc (CAS 14807-96-6) TWA 2 mg/m3 Respirable fraction. Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended Components **Form Type** Value Talc (CAS 14807-96-6) **TWA** 2 mg/m3 Total dust. Respirable dust. 1 mg/m3 Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte Components Value **Form** Type Talc (CAS 14807-96-6) **TWA** 3 mg/m3 Respirable fraction. UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1 **Form** Components **Type** Value Talc (CAS 14807-96-6) **TWA** 1 mg/m3 Respirable dust. No biological exposure limits noted for the ingredient(s). **Recommended monitoring** Follow standard monitoring procedures. procedures Not available. Derived no effect levels (DNELs)

Biological limit values

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines

Finland Exposure Limit Values: Skin designation

Butyrolactone (CAS 96-48-0)

Germany DFG MAK (advisory): Skin designation

Butyrolactone (CAS 96-48-0) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Can be absorbed through the skin.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. - Other

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

Environmental exposure

controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid. Form Liquid. Color Red or Gray Odor Slight.

Not available. Melting point/freezing point

Boiling point or initial boiling

point and boiling range

>400 °F (>204,44 °C)

Not applicable. **Flammability** Upper/lower flammability or explosive limits

Not available Explosive limit - lower (%) 16 % estimated Explosive limit - upper (%)

Flash point >400,0 °F (>204,4 °C) Pensky-Martens Closed Cup

Auto-ignition temperature Not available. Not available. **Decomposition temperature** Not available. pН Not available. Kinematic viscosity

Solubility

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water) (log value)

Vapor pressure 3 mm Hg

Density and/or relative density

10,16 lb/gal Density Not available. Vapor density **Particle characteristics** Not available.

9.2 Other information

No relevant additional information available. 9.2.1. Information with regard to physical hazard classes

9.2.2. Other safety characteristics

Evaporation rate <1 BuAc Specific gravity 1 22

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions. 10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Contact with incompatible materials.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous

Strong oxidizing agents.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

No hazardous decomposition products are known.

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not known.

Components Species Test Results

Butyrolactone (CAS 96-48-0)

Acute Dermal

LD50 Guinea pig 5640 mg/kg

Inhalation

LC50 Rat > 2680 mg/m3, 4 Hours

Oral

LD50 Rat 1540 mg/kg

nonylphenol; [1] 4-nonylphenol, branched [2] (CAS 84852-15-3)

<u>Acute</u>

Dermal

LD50 Rabbit 2140 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitization Due to partial or complete lack of data the classification is not possible.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Butyrolactone (CAS 96-48-0) 3 Not classifiable as to carcinogenicity to humans.

Talc (CAS 14807-96-6) 2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

Specific target organ toxicity -

single exposure

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

repeated exposure

Aspiration hazardDue to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

11.2. Information on other hazards

Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life with long lasting effects. Based on available data, the classification criteria are

not met for hazardous to the aquatic environment, acute hazard.

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

-0,64Butyrolactone nonylphenol; [1] 4-nonylphenol, branched [2] 5,71

Bioconcentration factor (BCF) Not available 12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.

12.7. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

The Waste code should be assigned in discussion between the user, the producer and the waste EU waste code

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number

14.2. UN proper shipping

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:--reaction

Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))

14.3. Transport hazard class(es)

Class 9 **Subsidiary hazard** 9 Label(s) 90 Hazard No. (ADR) **Tunnel restriction code** Ε 14.4. Packing group Ш 14.5. Environmental hazards No.

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

name

RID

UN3082 14.1. UN number

14.2. UN proper shipping

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:--reaction

Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))

Material name: Expansion Joint Compound Resin

14.3. Transport hazard class(es)

Subsidiary hazard 9 Label(s) 14.4. Packing group Ш 14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. UN number UN3082

Environmentally Hazardous Liquid, N.o.s. (Epoxy Resin:--reaction Product Of Bisphenol A And 14.2. UN proper shipping

Epichlorohydrin (refer To Epichlorohydrin)) name

14.3. Transport hazard class(es)

9 Class Subsidiary hazard Label(s) 9 14.4. Packing group Ш 14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN3082

Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin:--reaction Product Of 14.2. UN proper shipping

Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)) name

14.3. Transport hazard class(es)

9 Class **Subsidiary hazard** Ш 14.4. Packing group 14.5. Environmental hazards No. **ERG Code**

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN3082 14.1. UN number

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:--reaction 14.2. UN proper shipping

name

Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)), MARINE POLLUTANT

14.3. Transport hazard class(es)


Class 9 Subsidiary hazard 14.4. Packing group Ш 14.5. Environmental hazards Marine pollutant **EmS** F-A. S-F

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

Not established. 14.7. Maritime transport in bulk

according to IMO instruments ADN; ADR; IATA; IMDG; RID



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended nonylphenol; [1] 4-nonylphenol, branched [2] (CAS 84852-15-3)

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended nonylphenol; [1] 4-nonylphenol, branched [2] (CAS 84852-15-3)

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Talc (CAS 14807-96-6)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA nonylphenol; [1] 4-nonylphenol, branched [2] (CAS 84852-15-3)

UFI:

EU: 5T05-P18D-R006-FE6W

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Not listed

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex I, as amended

Not listed.

Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex II, as amended

Not listed.

Other EU regulations Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- E2 Hazardous to the Aquatic Environment Chronic

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Young people under 18 years old are not allowed to work with this product according to EU

Directive 94/33/EC on the protection of young people at work, as amended. Use of this product by young persons under the age of 18 is not allowed in accordance with the Management of Health and Safety at Work Regulations 1999 [SI 1999/3242], as amended. Follow national regulation for

work with chemical agents in accordance with Directive 98/24/EC, as amended.

Material name: Expansion Joint Compound Resin

Contains a substance which is included on the TRGS 905 list of carcinogenic, germ cell mutagenic and reproductive toxic substances

Talc (CAS 14807-96-6)

Anorganische Faserstäube, soweit nicht erwähnt (ausgenommen Gipsfasernund Wollastonitfasern)

France regulations

France INRS Table of Occupational Diseases

Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers Maladies professionnelles provoquées par les résines (CAS 25085-99-8)

Talc (CAS 14807-96-6)

époxydiques et leurs constituants 51

Affections consécutives à l'inhalation de poussières minérales renfermant de la silicecristalline (quartz, cristobalite, tridymite), des silicates cristallins (kaolin, talc), du graphite ou de la houille

Product registration number

UFI: 5T05-P18D-R006-FE6W **Austria Belgium** UFI: 5T05-P18D-R006-FE6W **Czech Republic** UFI: 5T05-P18D-R006-FE6W UFI: 5T05-P18D-R006-FE6W **Denmark European Union** UFI: 5T05-P18D-R006-FE6W **Finland** UFI: 5T05-P18D-R006-FE6W UFI: 5T05-P18D-R006-FE6W France UFI: 5T05-P18D-R006-FE6W Germany Greece UFI: 5T05-P18D-R006-FE6W UFI: 5T05-P18D-R006-FE6W Hungary UFI: 5T05-P18D-R006-FE6W Italy **Netherlands** UFI: 5T05-P18D-R006-FE6W Norway UFI: 5T05-P18D-R006-FE6W **Poland** UFI: 5T05-P18D-R006-FE6W **Portugal** UFI: 5T05-P18D-R006-FE6W Slovakia UFI: 5T05-P18D-R006-FE6W Slovenia UFI: 5T05-P18D-R006-FE6W UFI: 5T05-P18D-R006-FE6W Spain UFI: 5T05-P18D-R006-FE6W Sweden Switzerland UFI: 5T05-P18D-R006-FE6W

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert - Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

Not available.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

Material name: Expansion Joint Compound Resin

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

This document has undergone significant changes and should be reviewed in its entirety.

Follow training instructions when handling this material.

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or

in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information Training information Disclaimer

Material name: Expansion Joint Compound Resin