SAFETY DATA SHEET

1. Identification

Product identifier Phillymastic TG-7B Liquid Resin

Other means of identification

SKU# DM030R

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor informationCompany nameITW Performance PolymersAddress35 Brownridge Road

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number215-855-8450Fax number215-855-4688

Emergency Number 800-424-9300 (CHEMTREC)

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2
Sensitization, skin Category 1
Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment,

long-term hazard

Label elements

Environmental hazards



Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to

aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Avoid breathing mist/vapours. Wash thoroughly after handling. Contaminated work clothing

should not be allowed out of the workplace. Avoid release to the environment. Wear eye

protection/face protection. Wear protective gloves.

Response IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

Category 2

Take off contaminated clothing and wash it before reuse. Collect spillage.

Storage Not available.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information 81.75 % of the mixture consists of component(s) of unknown acute inhalation toxicity.

Other hazards None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Glass, Oxide		65997-17-3	30 - < 40
Epoxy resin		25085-99-8	20 - < 30
Alumina Trihydrate		21645-51-2	10 - < 20
ACETIC ACID, C11-14-BRANCHED ALKYL ESTER, C13-RICH		108419-35-8	5 - < 10
Aluminium oxide		1344-28-1	5 - < 10
Quartz		14808-60-7	5 - < 10
Other components below reportable I	evels		< 0.2

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Value

Value

Form

Form

Form

8. Exposure controls/personal protection

Occupational exposure li	mite

Components

Components

US. ACGIH Threshold Limit Values (TLV)
--

Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Canada. Alberta OELs (Occupatio Components	onal Health & Safety Code, Scl Type	nedule 1, Table 2), as amended Value	Form
Alumina Trihydrate (CAS 21645-51-2)	TWA	3 mg/m3	Respirable particles.
		10 mg/m3	Total
Aluminium oxide (CAS 1344-28-1)	TWA	10 mg/m3	
Glass, Oxide (CAS 65997-17-3)	TWA	1 fibers/cm3	Fiber.
		5 mg/m3	Fiber, total
		5 mg/m3	Total particulate.
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

<u>'</u>	••		
Glass, Oxide (CAS 65997-17-3)	TWA	1 fibers/cm3	Fiber.
		5 mg/m3	Inhalable fibers.
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended Components Type Value

Type

Type

Glass, Oxide (CAS	TWA	5 mg/m3	Inhalable fraction.
65997-17-3)			
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191)

Components	Туре	Value	Form
Alumina Trihydrate (CAS 21645-51-2)	TWA	3 mg/m3	Respirable.
		10 mg/m3	Inhalable

Material name: Phillymastic TG-7B Liquid Resin

SDS CANADA

DM030R Version #: 05 Revision date: 28-July-2023 Issue date: 15-March-2023

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs

Components	Туре	Value	Form
Aluminium oxide (CAS 1344-28-1)	TWA	10 mg/m3	
Quartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
Canada. Ontario OELs. (Co	ontrol of Exposure to Biological or Che	mical Agents), as amended	
Components	Туре	Value	Form
Quartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.
Canada. Quebec OELs. (M	inistry of Labor - Regulation respecting	occupational health and s	afety), as amended
Components	Туре	Value	Form
Alumina Trihydrate (CAS 21645-51-2)	TWA	10 mg/m3	Total dust.
Aluminium oxide (CAS 1344-28-1)	TWA	10 mg/m3	Total dust.
Quartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.
Canada. Saskatchewan OE	ELs (Occupational Health and Safety Re	gulations, 1996, Table 21),	as amended
Components	Туре	Value	Form
Aluminium oxide (CAS 1344-28-1)	15 minute	20 mg/m3	
Glass, Oxide (CAS 65997-17-3)	15 minute	3 mg/m3	Respirable fibers.
		10 mg/m3	Inhalable fraction.
ogical limit values	No biological exposure limits noted for	the ingredient(s).	
ropriate engineering trols	Good general ventilation should be us applicable, use process enclosures, lo	cal exhaust ventilation, or oth	er engineering controls to

Bio

App

con

maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level. Provide eyewash station and safety

shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

9. Physical and chemical properties

Appearance

Liquid. Physical state **Form** Liquid. Colour Not available. Odour Not available. **Odour threshold** Not available. Not available. Melting point/freezing point Not available.

Initial boiling point and boiling

range

320 °C (608 °F) estimated

Flash point 129.4 °C (265.0 °F) estimated

Material name: Phillymastic TG-7B Liquid Resin

SDS CANADA

Evaporation rate Not available.
Flammability (solid, gas) Not applicable.

Upper/legize flammability or explosive limits.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)
Explosive limit - upper

Not available. Not available.

(%)

Vapour pressure 0.01 hPa estimated

Vapour density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 1.52 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Combustible IIIB estimated

Oxidising properties Not oxidising.

Specific gravity 1.52 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Strong oxidising agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

Alumina Trihydrate (CAS 21645-51-2)

Acute Oral

LD50 Rat > 5000 mg/kg

Components Species Test Results

Aluminium oxide (CAS 1344-28-1)

Acute Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye Causes serious eye irritation.

irritation

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant

Alumina Trihydrate (CAS 21645-51-2) Irritant
Aluminium oxide (CAS 1344-28-1) Irritant
Glass, Oxide (CAS 65997-17-3) Irritant

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

Alumina Trihydrate (CAS 21645-51-2)

Aluminium oxide (CAS 1344-28-1)

Aluminium oxide (CAS 1344-28-1)

Aluminium oxide (CAS 1344-28-1)

Aluminium oxide (CAS 1344-28-1)

Glass, Oxide (CAS 65997-17-3)

Quartz (CAS 14808-60-7)

A2 Suspected human carcinogen.

A2 Suspected human carcinogen.

Canada - Alberta OELs: Carcinogen category

Quartz (CAS 14808-60-7) Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Alumina Trihydrate (CAS 21645-51-2)

Not classifiable as a human carcinogen.

Not classifiable as a human carcinogen.

Glass, Oxide (CAS 65997-17-3)

Quartz (CAS 14808-60-7)

Suspected human carcinogen.

Suspected human carcinogen.

Canada - Quebec OELs: Carcinogen category

Glass, Oxide (CAS 65997-17-3)

Quartz (CAS 14808-60-7)

Detected carcinogenic effect in animals.

Suspected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (CAS 14808-60-7) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Quartz (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

UN number UN3082

UN proper shipping name

Transport hazard class(es)

9 **Class** Subsidiary risk Packing group Ш **Environmental hazards** Yes **ERG Code** 9L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin)

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN3082 **UN** number

UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin), MARINE

POLLUTANT (Epoxy Resin)

Transport hazard class(es)

Class 9 Subsidiary risk Ш Packing group **Environmental hazards**

Marine pollutant Yes


EmS F-A, S-F Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Epoxy Resin

Transport in bulk according to Annex II of MARPOL 73/78 and Not established.

the IBC Code

IATA; IMDG



Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Glass, Oxide (CAS 65997-17-3)

International Inventories

Country(s) or region	Inventory name On invento	ry (yes/no)*		
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes		
Canada	Domestic Substances List (DSL)	Yes		
Canada	Non-Domestic Substances List (NDSL)	No		
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes		
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No		
Europe	European List of Notified Chemical Substances (ELINCS)	No		
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No		
Korea	Existing Chemicals List (ECL)	No		
New Zealand	New Zealand Inventory	Yes		
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes		
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes		
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes		
*A "Voc" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)				

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information

Issue date 15-March-2023

Material name: Phillymastic TG-7B Liquid Resin

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Revision date 28-July-2023

Version No. 0

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information Physical & Chemical Properties: Multiple Properties