SAFETY DATA SHEET

1. Identification

Product identifier Chockfast Gray Resin

Other means of identification

GP103R SKU# Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information **ITW Performance Polymers** Company name **Address** 35 Brownridge Road

Unit 1

Halton Hills, ON L7G 0C6

Customer Service Contact person Telephone number 215-855-8450 Fax number 215-855-4688

Emergency Number 800-424-9300 (CHEMTREC)

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Skin corrosion/irritation Category 2 **Health hazards**

> Serious eye damage/eye irritation Category 2A Sensitization, skin Category 1 Category 2

Environmental hazards Hazardous to the aquatic environment, acute

Hazardous to the aquatic environment, Category 2

long-term hazard

Label elements



Signal word Warning

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to **Hazard statement**

aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Avoid breathing mist/vapours. Wash thoroughly after handling. Contaminated work clothing

should not be allowed out of the workplace. Avoid release to the environment. Wear eye

protection/face protection. Wear protective gloves.

IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several Response

> minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse. Collect spillage.

Not available. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information None

Other hazards None known.

Material name: Chockfast Gray Resin SDS CANADA 1 / 10 GP103R Version #: 08 Revision date: 26-July-2023 Issue date: 04-April-2019

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Crystalline SiO2 (Quartz)		14808-60-7	30 - 60
Glass, Oxide		65997-17-3	15 - 30
Epoxy Resin: Reaction product of bisphenol A and epichlorohydrin (refer to epichlorohydrin)		25068-38-6	10 - 30
Magnesium silicate hydrate		14807-96-6	5 - 10
Butyrolactone		96-48-0	1 - 5
Cyclic ester		14228-73-0	1 - 5
Titanium dioxide	Titanium dioxide	13463-67-7	1 - 5
3-(trimethoxysilyl)propyl Glycidyl Ether		2530-83-8	0.1 - 1
Carbon Black		1333-86-4	0.1 - 1
Silica, amorphous		7631-86-9	< 0.2
Other components below reportable	e levels		< 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

Hazardous Materials Information Review Commission. This product has been granted a trade secret exemption. A CLAIM FOR EXEMPTION(CLAIM 8572) FROM DISCLOSING THE IDENTITY OF ALICYCLIC GLYCIDYL ETHER WAS GRANTED BY THE HMIRC ON APRIL 30, 2013.

14. I II St-alu III Easul es	4.	First-aid	measures
------------------------------	----	-----------	----------

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to **General information** protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

and precautions for firefighters Fire fighting

Move containers from fire area if you can do so without risk.

equipment/instructions Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: Chockfast Gray Resin GP103R Version #: 08 Revision date: 26-July-2023 Issue date: 04-April-2019

Methods and materials for containment and cleaning up

Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into

drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

13463-67-7)

US. ACGIH Threshold Limit Values (TLV)

Components	Туре	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	2.5 mg/m3	Respirable finescale particles
		0.2 mg/m3	Respirable nanoscale particles

Canada. Alberta OELs (Occupatio Components	nal Health & Safety Code, Sc Type	hedule 1, Table 2), as amended Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.
Glass, Oxide (CAS 65997-17-3)	TWA	1 fibers/cm3	Fiber.
		5 mg/m3	Total particulate.
		5 mg/m3	Fiber, total
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable particles.
Silica, amorphous (CAS 7631-86-9)	TWA	3 mg/m3	Respirable particles.
		10 mg/m3	Total
Titanium dioxide (CAS	TWA	10 mg/m3	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

Material name: Chockfast Gray Resin

GP103R Version #: 08 Revision date: 26-July-2023 Issue date: 04-April-2019

SDS CANADA

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Safety Regulation 296/97, as amen	•		
Components	Туре	Value	Form
Glass, Oxide (CAS 65997-17-3)	TWA	1 fibers/cm3	Fiber.
		5 mg/m3	Inhalable fibers.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.
Silica, amorphous (CAS 7631-86-9)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Titanium dioxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Canada. Manitoba OELs (Reg. 217	/2006, The Workplace Safety	And Health Act), as amended	
Components	Туре	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Glass, Oxide (CAS 65997-17-3)	TWA	5 mg/m3	Inhalable fraction.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	2.5 mg/m3	Respirable finescale particles
		0.2 mg/m3	Respirable nanoscale particles
Canada. New Brunswick OELs: Th	reshold Limit Values (TLVs)	Based on the 1991 and 1997 AC	GIH TLVs and BEIs
Publication (New Brunswick Regu	lation 91-191)		
Components	Туре	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.
Silica, amorphous (CAS 7631-86-9)	TWA	3 mg/m3	Respirable.
		10 mg/m3	Inhalable
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. Ontario OELs. (Control of Components	Exposure to Biological or C Type	hemical Agents), as amended Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.
(CAC 1 1 000-00-7)			
Magnesium silicate hydrate	TWA	2 fibers/cc	
Magnesium silicate hydrate	TWA	2 fibers/cc 2 mg/m3	Respirable fraction.
Magnesium silicate hydrate (CAS 14807-96-6) Titanium dioxide (CAS	TWA TWA		Respirable fraction.

Components	of Labor - Regulation respecti Type	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable dust.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable dust
Silica, amorphous (CAS 7631-86-9)	TWA	10 mg/m3	Total dust.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Total dust.

Canada. Saskatchewan OELs (Occ Components	cupational Health and Safety Ro Type	egulations, 1996, Table 21), Value	as amended Form
Carbon Black (CAS 1333-86-4)	15 minute	7 mg/m3	
Glass, Oxide (CAS 65997-17-3)	15 minute	3 mg/m3	Respirable fibers.
		10 mg/m3	Inhalable fraction.
Magnesium silicate hydrate (CAS 14807-96-6)	15 minute	6 mg/m3	Respirable fraction.
		20 mg/m3	Inhalable fraction.
Silica, amorphous (CAS 7631-86-9)	15 minute	6 mg/m3	Respirable fraction.
		20 mg/m3	Inhalable fraction.
Titanium dioxide (CAS 13463-67-7)	15 minute	20 mg/m3	

Biological limit values

Appropriate engineering

controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

Thermal hazards

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

In case of insufficient ventilation, wear suitable respiratory equipment.

Respiratory protection

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Liquid.
Physical state Liquid.
Form Liquid.
Colour Grey.
Odour Slight.

Odour threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling >204.44 °C (>400 °F)

range

Flash point >204.4 °C (>400.0 °F) Pensky-Martens Closed Cup

Evaporation rate <1

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper Not available.

(%)

Vapour pressure Not available.

Vapour density >1

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.
(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 1.96 g/cm3 **Explosive properties** Not explosive.

Flammability class Combustible IIIB estimated

Oxidising properties Not oxidising.

Specific gravity 1.96

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Strong oxidising agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

Information on toxicological effects

Acute toxicity

Components Species Test Results

Butyrolactone (CAS 96-48-0)

Acute Dermal

LD50 Guinea pig 5640 mg/kg

Material name: Chockfast Gray Resin

SDS CANADA

Components **Species Test Results** Inhalation LC50 Rat > 2680 mg/m3, 4 Hours Oral Rat LD50 1540 mg/kg Carbon Black (CAS 1333-86-4) Acute Oral LD50 Rat > 8000 mg/kg Silica, amorphous (CAS 7631-86-9) **Acute** Oral Rat LD50 > 22500 mg/kg Titanium dioxide (CAS 13463-67-7) **Acute Dermal** LD50 Hamster >= 10000 mg/kg Oral LD50 Rat > 10000 mg/kg Skin corrosion/irritation Causes skin irritation. Causes serious eye irritation. Serious eye damage/eye irritation Respiratory or skin sensitisation Canada - Alberta OELs: Irritant Carbon Black (CAS 1333-86-4) Irritant Magnesium silicate hydrate (CAS 14807-96-6) Irritant Silica, amorphous (CAS 7631-86-9) Irritant Titanium dioxide (CAS 13463-67-7) Irritant Respiratory sensitisation Not a respiratory sensitiser. Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

Carbon Black (CAS 1333-86-4) A3 Confirmed animal carcinogen with unknown relevance to

humans.

Crystalline SiO2 (Quartz) (CAS 14808-60-7) A2 Suspected human carcinogen. Magnesium silicate hydrate (CAS 14807-96-6) A1 Confirmed human carcinogen.

A4 Not classifiable as a human carcinogen.

Titanium dioxide (CAS 13463-67-7) A3 Confirmed animal carcinogen with unknown relevance to

humans.

Canada - Alberta OELs: Carcinogen category

Crystalline SiO2 (Quartz) (CAS 14808-60-7) Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Carbon Black (CAS 1333-86-4) Confirmed animal carcinogen with unknown relevance to humans.

Crystalline SiO2 (Quartz) (CAS 14808-60-7) Suspected human carcinogen. Magnesium silicate hydrate (CAS 14807-96-6) Confirmed human carcinogen.

Not classifiable as a human carcinogen.

Confirmed animal carcinogen with unknown relevance to humans. Titanium dioxide (CAS 13463-67-7)

Canada - Quebec OELs: Carcinogen category

Detected carcinogenic effect in animals. Carbon Black (CAS 1333-86-4) Crystalline SiO2 (Quartz) (CAS 14808-60-7) Suspected carcinogenic effect in humans. Magnesium silicate hydrate (CAS 14807-96-6) Detected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Butyrolactone (CAS 96-48-0) 3 Not classifiable as to carcinogenicity to humans.

Carbon Black (CAS 1333-86-4) 2B Possibly carcinogenic to humans. Crystalline SiO2 (Quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

Magnesium silicate hydrate (CAS 14807-96-6) 2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

Silica, amorphous (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans. Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Carbon Black (CAS 1333-86-4) Known To Be Human Carcinogen. Crystalline SiO2 (Quartz) (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

12. Ecological information

Toxic to aquatic life with long lasting effects. **Ecotoxicity**

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Butyrolactone -0.64

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow **Disposal instructions**

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

UN3082 **UN number**

Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin:--reaction Product Of **UN proper shipping name**

Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))

Transport hazard class(es)

Class 9 Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 91

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

Material name: Chockfast Gray Resin GP103R Version #: 08 Revision date: 26-July-2023 Issue date: 04-April-2019

IMDG

UN3082 **UN** number

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:--reaction **UN** proper shipping name

Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)), MARINE POLLUTANT

Transport hazard class(es)

9 Class Subsidiary risk **Packing group** Ш

Environmental hazards

Marine pollutant Yes F-A, S-F


Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and the IBC Code

Not established.

IATA; IMDG



Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

This product has been classified in accordance with the hazard criteria of the HPR and the SDS Canadian regulations contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Greenhouse Gases

Not listed.

Precursor Control Regulations

Butyrolactone (CAS 96-48-0) Class A

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Material name: Chockfast Gray Resin SDS CANADA

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

Country(s) or region

Inventory name

Domestic Substances List (DSL)

International Inventories

Australia

Canada

Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Australian Inventory of Industrial Chemicals (AICIS)

Toxic Substances Control Act (TSCA) Inventory

16. Other information

04-April-2019 Issue date **Revision date** 26-July-2023

Version No. 80

United States & Puerto Rico

ITW Performance Polymers cannot anticipate all conditions under which this information and its Disclaimer

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

GP103R Version #: 08 Revision date: 26-July-2023 Issue date: 04-April-2019

On inventory (yes/no)*

Yes

Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).