SAFETY DATA SHEET

Version # 12

Issue date: 03-11-2013 Revision date: 07-26-2023 Supersedes date: 07-12-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

Address

Chockfast Gray Resin

Registration number

None.

Synonyms

GP103R SKU#

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Not available. Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

ITW Performance Polymers Company Name

Bay 150

Shannon Industrial Estate

Co. Clare Ireland V14 DF82

Contact Person Customer Service Telephone Number 353(61)771500

353(61)471285

customerservice.shannon@itwpp.com **Fmail**

Emergency Phone Number 44(0) 1235 239 670 (24 hours)

1.4. Emergency telephone number

General in EU

112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons

Information Center

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Belgium National Poisons

Control Center

070 245 245 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Bulgaria National

Toxicological Information

Center

+359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Croatia Poisons Information Center +385 1 2348 342 (Hours of operation not provided. SDS/Product information may

not be available for the Emergency Service.)

Cyprus Poison Center

1401 (Available 24 hours a day. SDS/Product information may not be available

for the Emergency Service.)

Czech Republic National Poisons Information

Center

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons

Control Center

+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Estonia National Poisons Information Center

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed

available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

on Sundays and on national holidays). SDS/Product information may not be

France National Poisons Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Material name: Chockfast Gray Resin

SDS FII

1.4. Emergency telephone number

Greece Poison Information Centre

(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Hungary National

Emergency Phone Number

+36-80-201-199 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Iceland Poison Center

(+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Latvia Emergency medical

aid

113

Latvia Poison and Drug Information Center

+371 67042473 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Lithuania Neatidėliotina informacija apsinuodijus

+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and **Emergency Department** 2545 4030 (Hours of operation not provided. SDS/Product information may not be

available for the Emergency Service.)

Netherlands National Poisons Information Center (NVIC)

NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel

in cases of acute intoxications)

Norway Norwegian Poison Information Center

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Portugal Poison Center

800 250 250 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Romania Biroul RSI si Informare Toxicologica 021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be

available for the Emergency Service.)

Slovakia National Toxicological Information Center

+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Spain Toxicology Information Service + 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Sweden National Poison Information Center

112 - and ask for Poison Information (Available 24 hours a day. SDS/Product

information may not be available for the Emergency Service.)

Switzerland Tox Info Suisse

145 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Skin corrosion/irritation Category 2 H315 - Causes skin irritation. Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Category 1

H317 - May cause an allergic skin

reaction.

Environmental hazards

Skin sensitization

Hazardous to the aquatic environment, Category 2 long-term aquatic hazard

H411 - Toxic to aquatic life with

long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Austria: H050-60UJ-A00F-6JWE Belgium: H050-60UJ-A00F-6JWE Bulgaria: H050-60UJ-A00F-6JWE Croatia: H050-60UJ-A00F-6JWE Cyprus: H050-60UJ-A00F-6JWE

Czech Republic: H050-60UJ-A00F-6JWE Denmark: H050-60UJ-A00F-6JWE Estonia: H050-60UJ-A00F-6JWE EU: H050-60UJ-A00F-6JWE Finland: H050-60UJ-A00F-6JWE France: H050-60UJ-A00F-6JWE Germany: H050-60UJ-A00F-6JWE Greece: H050-60UJ-A00F-6JWE Hungary: H050-60UJ-A00F-6JWE Iceland: H050-60UJ-A00F-6JWE Ireland: H050-60UJ-A00F-6JWE

Italy: H050-60UJ-A00F-6JWE Latvia: H050-60UJ-A00F-6JWE Lithuania: H050-60UJ-A00F-6JWE Luxembourg: H050-60UJ-A00F-6JWE Malta: H050-60UJ-A00F-6JWE Netherlands: H050-60UJ-A00F-6JWE Norway: H050-60UJ-A00F-6JWE Poland: H050-60UJ-A00F-6JWE Portugal: H050-60UJ-A00F-6JWE Romania: H050-60UJ-A00F-6JWE Slovakia: H050-60UJ-A00F-6JWE

Slovenia: H050-60UJ-A00F-6JWE Spain: H050-60UJ-A00F-6JWE Sweden: H050-60UJ-A00F-6JWE

Contains: Butyrolactone, CARBON BLACK, Crystalline SiO2 (Quartz), Epoxy Resin: Reaction product of

bisphenol A and epichlorohydrin (refer to epichlorohydrin), titanium dioxide [in powder form

containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Hazard pictograms



Signal word Warning

Hazard statements

Causes skin irritation. H315

May cause an allergic skin reaction. H317 Causes serious eye irritation. H319

Toxic to aquatic life with long lasting effects. H411

Precautionary statements

Prevention

P261 Avoid breathing mist/vapors. P264 Wash thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace. P272

Avoid release to the environment. P273 Wear eye protection/face protection. P280

Wear protective gloves. P280

Response

IF ON SKIN: Wash with plenty of water. P302 + P352

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present P305 + P351 + P338

and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. P333 + P313 If eye irritation persists: Get medical advice/attention. P337 + P313 Take off contaminated clothing and wash it before reuse. P362 + P364

Collect spillage. P391 Not available. Storage

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Supplemental label information

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General	infor	mation

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Crystalline SiO2 (Quartz)	30 - 60	14808-60-7 238-878-4	-	-	#
Classification:	Carc. 1A;F	1350			
Epoxy Resin: Reaction product of bisphenol A and epichlorohydrin (refer to epichlorohydrin)	10 - 30	25068-38-6 -	01-2119456619-26-0000	-	
Classification:	Skin Irrit. 2	;H315, Eye Irrit. 2;H3	319, Skin Sens. 1;H317		
Butyrolactone	1 - 5	96-48-0 202-509-5	-	-	
Classification:		. 4;H302;(ATE: 1540 0000000002 mg/l), Ey	mg/kg bw), Acute Tox. 3;H3 /e Irrit. 2;H319	31;(ATE:	
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	1 - 5	13463-67-7 236-675-5	01-2119489379-17-0000	022-006-002	
Classification:	Carc. 2;H3	51			
CARBON BLACK	0,1 - 1	1333-86-4 215-609-9	-	-	
Classification:	Carc. 2;H3	51			

Other components below reportable levels

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

< 25

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

Hazardous Materials Information Review Commission. This product has been granted a trade secret exemption. A CLAIM FOR EXEMPTION(CLAIM 8572) FROM DISCLOSING THE IDENTITY OF ALICYCLIC GLYCIDYL ETHER WAS GRANTED BY THE HMIRC ON APRIL 30, 2013.

SECTION 4: First aid measures

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

Rasn

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

media

Material name: Chockfast Gray Resin

GP103R Version #: 12 Revision date: 07-26-2023 Issue date: 03-11-2013

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Ensure adequate ventilation. Avoid breathing mist/vapors. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- E2 Hazardous to the Aquatic Environment Chronic (Lower-tier requirements = 200 tons;

Upper-tier requirements = 500 tons)

7.3. Specific end use(s) Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBI. II, no. 184/2001, as amended Components Value **Form** Type Crystalline SiO2 (Quartz) MAK 0,05 mg/m3 Respirable dust. (CAS 14808-60-7) Magnesium silicate hydrate MAK 2 mg/m3 Respirable fraction. (CAS 14807-96-6) STEL 20 mg/m3 Inhalable fraction. 10 mg/m3 Respirable fraction. titanium dioxide [in powder MAK 5 mg/m3 Respirable dust. form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)

Components	Туре	Value	Form
	STEL	10 mg/m3	Respirable dust.

Belgium. OEL. Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1 - Chemical agents, as amended

Components	Type	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	3 mg/m3	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	10 mg/m3	

Bulgaria. OEL values of carcinogens and mutagens at work (Reg. 10/2003 on prot. from carcinogens and mutagens at work, Ann. 1), as amended

Components	Туре	Value	Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction and dust

Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as amended

Components	Туре	Value	Form
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	1 fibers/cm3	Respirable fraction.
		6 mg/m3	Inhalable fraction.
		3 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	10 mg/m3	Respirable dust.

Croatia. OELs (GVI). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and Biological Limit Values, Annex I (NN 91/2018), as amended

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	MAC	3,5 mg/m3	
	STEL	7 mg/m3	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	MAC	0,1 mg/m3	
Magnesium silicate hydrate (CAS 14807-96-6)	MAC	1 mg/m3	Respirable dust.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	MAC	4 mg/m3	Respirable dust.
		10 mg/m3	Total dust.

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended

Components	туре	value	
CARBON BLACK (CAS 1333-86-4)	TWA	3,5 mg/m3	
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	706 part/cm3	
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	10 mg/m3	

Czech Republic. Occupational exposure limit values of chemicals at work (Decree on protection of health at work, 361/2007, Annex 2, Part A & Annex 3, Part A, as amended)

Components	Туре	Value	Form
CARBON BLACK (CAS 333-86-4)	TWA	10 mg/m3	Dust.
crystalline SiO2 (Quartz) CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
lagnesium silicate hydrate CAS 14807-96-6)	TWA	2 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
enmark. Work Environment Auth components	nority. Exposure Limits for Su Type	ıbstances & Materials, Annex 2 Value	Form
ARBON BLACK (CAS 333-86-4)	TLV	3,5 mg/m3	
rystalline SiO2 (Quartz) CAS 14808-60-7)	TLV	0,3 mg/m3	Total
		0,1 mg/m3	Respirable.
lagnesium silicate hydrate CAS 14807-96-6)	TLV	0,003 fibers/cm3	Fiber.
tanium dioxide [in powder orm containing 1 % or nore of particles with erodynamic diameter ≤ 10 m] (CAS 13463-67-7)	TLV	6 mg/m3	
stonia. OELs. Occupational Expo components	osure Limits of Hazardous Su Type	bstances (Regulation No. 105/20 Value	001, Annex), as amende Form
rystalline SiO2 (Quartz) CAS 14808-60-7)	TWA	0,1 mg/m3	Fine dust, respiratory fraction
tanium dioxide [in powder	TWA	5 mg/m3	
nore of particles with erodynamic diameter ≤ 10			
nore of particles with erodynamic diameter ≤ 10 m] (CAS 13463-67-7) inland. HTP-arvot, App 3., Bindin	g Limit Values, Social Affairs Type	and Ministry of Health Value	Form
nore of particles with erodynamic diameter ≤ 10 m] (CAS 13463-67-7) finland. HTP-arvot, App 3., Bindin components	_		Form
nore of particles with erodynamic diameter ≤ 10 m] (CAS 13463-67-7) inland. HTP-arvot, App 3., Bindin components	Туре	Value	Form
nore of particles with erodynamic diameter ≤ 10 m] (CAS 13463-67-7) inland. HTP-arvot, App 3., Bindin components utyrolactone (CAS	Туре	Value 70 mg/m3	Form
nore of particles with erodynamic diameter ≤ 10 m] (CAS 13463-67-7) inland. HTP-arvot, App 3., Bindin components utyrolactone (CAS	Type STEL	Value 70 mg/m3 250 ppm	Form
nore of particles with erodynamic diameter ≤ 10 m] (CAS 13463-67-7) inland. HTP-arvot, App 3., Bindin components uttyrolactone (CAS 6-48-0) CARBON BLACK (CAS	Type STEL	Value 70 mg/m3 250 ppm 14 mg/m3	Form
nore of particles with erodynamic diameter ≤ 10 m] (CAS 13463-67-7) inland. HTP-arvot, App 3., Bindin components utyrolactone (CAS 6-48-0) ARBON BLACK (CAS	Type STEL TWA	Value 70 mg/m3 250 ppm 14 mg/m3 50 ppm	Form
nore of particles with erodynamic diameter ≤ 10 m] (CAS 13463-67-7) inland. HTP-arvot, App 3., Bindin components sutyrolactone (CAS 6-48-0) ARBON BLACK (CAS 333-86-4) crystalline SiO2 (Quartz)	Type STEL TWA STEL	70 mg/m3 250 ppm 14 mg/m3 50 ppm 7 mg/m3	Form Respirable.
nore of particles with erodynamic diameter ≤ 10 m] (CAS 13463-67-7) inland. HTP-arvot, App 3., Bindin components Butyrolactone (CAS 6-48-0) CARBON BLACK (CAS 333-86-4) Crystalline SiO2 (Quartz) CAS 14808-60-7) Magnesium silicate hydrate	Type STEL TWA STEL TWA	Value 70 mg/m3 250 ppm 14 mg/m3 50 ppm 7 mg/m3 3,5 mg/m3	
nore of particles with erodynamic diameter ≤ 10 m] (CAS 13463-67-7) inland. HTP-arvot, App 3., Bindin components dutyrolactone (CAS 6-48-0) CARBON BLACK (CAS 333-86-4) Crystalline SiO2 (Quartz) CAS 14808-60-7) dagnesium silicate hydrate	Type STEL TWA STEL TWA TWA	70 mg/m3 250 ppm 14 mg/m3 50 ppm 7 mg/m3 3,5 mg/m3 0,05 mg/m3	Respirable.
nore of particles with erodynamic diameter ≤ 10 m] (CAS 13463-67-7) finland. HTP-arvot, App 3., Bindin components Sutyrolactone (CAS 6-48-0) Crystalline SiO2 (Quartz) CAS 14808-60-7) Magnesium silicate hydrate CAS 14807-96-6) tanium dioxide [in powder orm containing 1 % or nore of particles with erodynamic diameter ≤ 10	Type STEL TWA STEL TWA TWA	Value 70 mg/m3 250 ppm 14 mg/m3 50 ppm 7 mg/m3 3,5 mg/m3 0,05 mg/m3 2 mg/m3	Respirable. Inhalable dust.
orm containing 1 % or nore of particles with perodynamic diameter ≤ 10 μm] (CAS 13463-67-7) Finland. HTP-arvot, App 3., Bindin Components Butyrolactone (CAS 136-48-0) CARBON BLACK (CAS 333-86-4) Crystalline SiO2 (Quartz) CAS 14808-60-7) Magnesium silicate hydrate CAS 14807-96-6) Itanium dioxide [in powder form containing 1 % or nore of particles with perodynamic diameter ≤ 10 μm] (CAS 13463-67-7) France. OELs. Occupational Exponomponents	Type STEL TWA STEL TWA TWA TWA TWA	70 mg/m3 250 ppm 14 mg/m3 50 ppm 7 mg/m3 3,5 mg/m3 0,05 mg/m3 2 mg/m3 1 mg/m3 10 mg/m3	Respirable. Inhalable dust. Respirable. Dust.

Components	Values (VLEP) for Occupational Exposi Type	Value	Form
CARBON BLACK (CAS 1333-86-4)	VME	3,5 mg/m3	
Regulatory status:	Indicative limit (VL)		
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	VME	0,1 mg/m3	Respirable fraction.
Regulatory status:	Regulatory binding (VRC)		
Magnesium silicate hydrat (CAS 14807-96-6)	e VME	4 mg/m3	Total dust.
Regulatory status:	Regulatory binding (VRC)		
		0,9 mg/m3	Respirable dust.
Regulatory status:	Regulatory binding (VRC)		
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 1 μm] (CAS 13463-67-7)		10 mg/m3	

Regulatory status: Indicative limit (VL)

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG), as updated

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	4 mg/m3	Inhalable dust.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	4 mg/m3	Inhalable dust.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	0,3 mg/m3	Respirable fraction.
Germany. TRGS 900, Limit Values		•	_
Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.
Magnesium silicate hydrate (CAS 14807-96-6)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.
Greece. OELs, Presidential Decree	No. 307/1986, as amended		
Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	STEL	7 mg/m3	
	TWA	3,5 mg/m3	
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.

		1,=0 1119,1110	
Greece. OELs, Presidential Decre Components	e No. 307/1986, as amended Type	Value	Form
CARBON BLACK (CAS 1333-86-4)	STEL	7 mg/m3	_
	TWA	3,5 mg/m3	
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.
		10 mg/m3	Inhalable
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	5 mg/m3	Respirable.
,		10 mg/m3	Inhalable

3 mg/m3 0,1 mg/m3 2 mg/m3 2 mg/m3 2 mg/m3 2 mg/m3 3,5 mg/m3 0,3 mg/m3 0,3 fibers/cm3 5 mg/m3 10 mg/m3 0,1 mg/m3 0,1 mg/m3 10 mg/m3	Inhalable dust. Respirable dust. Respirable dust. Workplace, as amend Form Total dust. Respirable dust. Fiber. Respirable dust. Total dust. Total dust. Total dust. Total dust. Respirable dust. Total inhalable dust. Respirable dust. Respirable dust. Respirable dust. Respirable dust. Respirable dust. Respirable dust.
2 mg/m3 ce Pollution at the /alue 3,5 mg/m3 0,3 mg/m3 0,3 fibers/cm3 5 mg/m3 10 mg/m3 6 mg/m3 arcinogens Regula /alue 3 mg/m3 0,1 mg/m3 0,1 mg/m3 0,1 mg/m3	Respirable dust. Workplace, as amend Form Total dust. Respirable dust. Fiber. Respirable dust. Total dust. Inhalable fraction. Respirable dust. Total inhalable dust. Respirable dust. Respirable dust.
ce Pollution at the Value 3,5 mg/m3 0,3 mg/m3 0,1 mg/m3 0,3 fibers/cm3 5 mg/m3 10 mg/m3 6 mg/m3 0,1 mg/m3 0,1 mg/m3 0,1 mg/m3 0,1 mg/m3 0,1 mg/m3	Workplace, as amend Form Total dust. Respirable dust. Fiber. Respirable dust. Total dust. Inhalable fraction. Respirable dust. Total inhalable dust. Respirable dust.
/alue 3,5 mg/m3 0,3 mg/m3 0,1 mg/m3 0,3 fibers/cm3 5 mg/m3 10 mg/m3 6 mg/m3 0,1 mg/m3 0,1 mg/m3 0,1 mg/m3 0,1 mg/m3	Total dust. Respirable dust. Fiber. Respirable dust. Total dust. Inhalable fraction. Respirable dust. Total inhalable dust. Respirable dust. Respirable dust.
0,3 mg/m3 0,1 mg/m3 0,3 fibers/cm3 5 mg/m3 10 mg/m3 6 mg/m3 arcinogens Regula /alue 3 mg/m3 0,1 mg/m3 10 mg/m3	Respirable dust. Fiber. Respirable dust. Total dust. Attions Form Inhalable fraction. Respirable dust. Total inhalable dust. Respirable dust.
0,1 mg/m3 0,3 fibers/cm3 5 mg/m3 10 mg/m3 6 mg/m3 arcinogens Regula /alue 8 mg/m3 0,1 mg/m3 10 mg/m3 10 mg/m3	Respirable dust. Fiber. Respirable dust. Total dust. Attions Form Inhalable fraction. Respirable dust. Total inhalable dust. Respirable dust.
0,3 fibers/cm3 5 mg/m3 10 mg/m3 6 mg/m3 arcinogens Regula //alue 3 mg/m3 0,1 mg/m3 10 mg/m3 0,8 mg/m3	Fiber. Respirable dust. Total dust. Attions Form Inhalable fraction. Respirable dust. Total inhalable dust. Respirable dust.
5 mg/m3 10 mg/m3 5 mg/m3 6 mg/m3 6 mg/m3 7 mg/m3 10 mg/m3 10 mg/m3 10,8 mg/m3	Respirable dust. Total dust. Intions Form Inhalable fraction. Respirable dust. Total inhalable dust. Respirable dust.
arcinogens Regula /alue 3 mg/m3 0,1 mg/m3 10 mg/m3	Total dust. Ations Form Inhalable fraction. Respirable dust. Total inhalable dust. Respirable dust.
arcinogens Regula /alue 3 mg/m3 0,1 mg/m3 10 mg/m3	Inhalable fraction. Respirable dust. Total inhalable dust. Respirable dust.
arcinogens Regula Value 3 mg/m3 0,1 mg/m3 10 mg/m3 0,8 mg/m3	Form Inhalable fraction. Respirable dust. Total inhalable dust. Respirable dust.
/alue 3 mg/m3 0,1 mg/m3 10 mg/m3 0,8 mg/m3	Form Inhalable fraction. Respirable dust. Total inhalable dust. Respirable dust.
0,1 mg/m3 10 mg/m3 0,8 mg/m3	Respirable dust. Total inhalable dust. Respirable dust.
10 mg/m3),8 mg/m3	Total inhalable dust.
0,8 mg/m3	Respirable dust.
	·
1 mg/m3	Respirable dust.
10 mg/m3	Total inhalable dust.
/alue	Form
3 mg/m3	Inhalable fraction.
),025 mg/m3	Respirable fraction.
2 mg/m3	Respirable fraction.
2,5 mg/m3	Respirable finescale particles
),2 mg/m3	Respirable nanoscale particles
lace (Reg. No. 325	5/ 2007, L.V. 80, Annex
	Form
	2,5 mg/m3 0,2 mg/m3

Latvia. OELs. Occupational Exposure Limits of Chemical Substances at Workplace (Reg. No. 325/ 2007, L.V. 80, Annex 1), as amended

Components	Туре	Value Form	
titanium dioxide [in powder	TWA	10 mg/m3	
form containing 1 % or			
more of particles with			
aerodynamic diameter ≤ 10			
μm] (ČAS 13463-67-7)			

Lithuania. OELs. Occupational Exposure Limit Values for Chemical Substances (Hygiene Norm HN 23:2011; Order No. V-824/A1-389), as amended

Components	Туре	Value	Form
CARBON BLACK (CAS TWA 1333-86-4)	5 mg/m3	Respirable fraction.	
		10 mg/m3	Inhalable fraction.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Inhalable fraction.
		1 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	5 mg/m3	

Luxembourg. Chemical Substances Prohibited at Work (Annex III), G.D.R. of 14 November 2016, OJ Memorial A, n ° 235/2016, as amended

Components	Туре	Value	Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.

Netherlands. OELs per Annex XIII of Working Conditions Regulation (Staatscourant no. 252, 29 December 2006), as amended

Components	Туре	Value	Form	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,075 mg/m3	Respirable dust.	
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	0,25 mg/m3	Respirable dust.	

Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TLV	3,5 mg/m3	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TLV	0,3 mg/m3	Total dust.
		0,05 mg/m3	Respirable dust.
Magnesium silicate hydrate (CAS 14807-96-6)	TLV	6 mg/m3	Total dust.
		2 mg/m3	Respirable dust.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 uml (CAS 13463-67-7)	TLV	5 mg/m3	

Poland. Maximum permissible concentrations and intensities of harmful factors in the work environment (Dz.U.Poz. 1286/2018, Annex 1)

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	4 mg/m3	Inhalable fraction.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	4 mg/m3	Inhalable fraction.

Poland. Maximum permissible concentrations and intensities of harmful factors in the work environment (Dz.U.Poz. 1286/2018, Annex 1)

Components	Туре	Value	Form
		1 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	STEL	30 mg/m3	
,	TWA	10 mg/m3	Inhalable fraction.
Portugal. VLEs. Norm on occupat	ional exposure to chemical ag	gents (NP 1796-2014)	
Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	3 mg/m3	Fume.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,025 mg/m3	Respirable fraction.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	10 mg/m3	

Romania. OELs. Limit Values of Chemical Agents at Workplace (Regulation 1.218/2006, M.O 845, Annex 1, 3&4, as amended)

Components	Туре	Value	Form
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	STEL	15 mg/m3	
	TWA	10 mg/m3	

Slovakia. OELs for carcinogens and mutagens. Regulation No. 356/2006 on carcinogenic and mutagenic substances, as amended

Components	Туре	Value	Form	
Crystalline SiO2 (Quartz)	TWA	0,1 mg/m3	Respirable fraction.	
(CAS 14808-60-7)				

Slovakia. OELs. Maximum permissible exposure limits for chemical factors in workplace air (Regulation No 355/2006, Annex 1, Table 1, as amended)

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	2 mg/m3	
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
		2 mg/m3	Respirable fraction.
		10 mg/m3	Total
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 uml (CAS 13463-67-7)	TWA	5 mg/m3	

Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work. Annex I). as amended

ade to Exp. to oriented at Work, Africa 1), as africada				
Components	Туре	Value	Form	
CARBON BLACK (CAS 1333-86-4)	TWA	10 mg/m3	Inhalable fraction.	
		1,25 mg/m3	Respirable fraction.	
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	10 mg/m3	Inhalable fraction.	

Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Annex I), as amended

Components	Type	Value	Form
		1,25 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.

Spain. OELs. INSST, Límites de Exposición Profesional Para Agentes Químicos, Table 1-Valores Límites Ambientales (VLAs)

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	3,5 mg/m3	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,05 mg/m3	Respirable fraction.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	10 mg/m3	

Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	5 mg/m3	Inhalable dusts and mists.
		1 mg/m3	Inhalable dust.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Total dust.
		1 mg/m3	Respirable dust.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	5 mg/m3	Total dust.

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	TWA	3 mg/m3	Respirable dust.
		10 mg/m3	Inhalable dust.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,15 mg/m3	Respirable fraction.
Magnesium silicate hydrate (CAS 14807-96-6)	TWA	3 mg/m3	Respirable fraction.
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)	TWA	3 mg/m3	Respirable dust.

UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1

Components	Туре	Value	Form
CARBON BLACK (CAS 1333-86-4)	STEL	7 mg/m3	
	TWA	3,5 mg/m3	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable.

UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1 Form Components **Type** Value Magnesium silicate hydrate **TWA** 1 mg/m3 Respirable dust. (CAS 14807-96-6) titanium dioxide [in powder **TWA** 4 mg/m3 Respirable. form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7) 10 mg/m3 Inhalable

EU. OELs, Directive 2004/37/EC on carcinogen and mutagens from Annex III, Part A, as amended Components

Type

Value

Form

Crystalline SiO2 (Quartz)

(CAS 14808-60-7)

TWA

0,1 mg/m3

Respirable fraction and dust

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring

Follow standard monitoring procedures.

procedures

Derived no effect levels (DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

Exposure guidelines

Finland Exposure Limit Values: Skin designation

Butyrolactone (CAS 96-48-0)

Can be absorbed through the skin.

Germany DFG MAK (advisory): Skin designation

Butyrolactone (CAS 96-48-0)

Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

SHOW

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

Environmental exposure

controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquid.FormLiquid.ColorGrey.OdorSlight.

Melting point/freezing point Not available.

Material name: Chockfast Gray Resin

SDS EU

GP103R Version #: 12 Revision date: 07-26-2023 Issue date: 03-11-2013

Boiling point or initial boiling point and boiling range

>400 °F (>204,44 °C)

Flammability

Not applicable.

>400,0 °F (>204,4 °C) Pensky-Martens Closed Cup Flash point

Auto-ignition temperature Not available. Not available **Decomposition temperature** Not available Not available. Kinematic viscosity

Solubility

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water) (log value)

Vapor pressure Not available.

Density and/or relative density

Density 1,96 g/cm3

Vapor density

Particle characteristics Not available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No relevant additional information available.

9.2.2. Other safety characteristics

Evaporation rate Specific gravity 1,96

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Contact with incompatible materials. 10.4. Conditions to avoid

10.5. Incompatible materials Strong oxidizing agents.

10.6. Hazardous

decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

Occupational exposure to the substance or mixture may cause adverse effects. **General information**

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Causes skin irritation. May cause an allergic skin reaction. Skin contact

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred **Symptoms**

vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Component

Species	Test Results
0)	
Guinea pig	5640 mg/kg
Rat	> 2680 mg/m3, 4 Hours
Rat	1540 mg/kg
	Guinea pig

Material name: Chockfast Gray Resin

SDS FU

GP103R Version #: 12 Revision date: 07-26-2023 Issue date: 03-11-2013

Components Species Test Results

CARBON BLACK (CAS 1333-86-4)

Acute Oral

LD50 Rat > 8000 mg/kg

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)

Acute Dermal

LD50 Hamster >= 10000 mg/kg

Oral

LD50 Rat > 10000 mg/kg

Skin corrosion/irritationCauses skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitizationDue to partial or complete lack of data the classification is not possible.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classified.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μ m] (CAS 13463-67-7)

IARC Monographs. Overall Evaluation of Carcinogenicity

Butyrolactone (CAS 96-48-0) 3 Not classifiable as to carcinogenicity to humans.

CARBON BLACK (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

Crystalline SiO2 (Quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

titanium dioxide [in powder form containing 1 % or more 2B Possibly carcinogenic to humans.

of particles with aerodynamic diameter ≤ 10 μm]

(CAS 13463-67-7)

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

11.2. Information on other hazards

Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life with long lasting effects.

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

Butyrolactone -0,64

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

Material name: Chockfast Gray Resin

SDS EU

12.6. Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

12.7. Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste codeThe Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN3082

14.2. UN proper shipping

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:--reaction

Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))

14.3. Transport hazard class(es)

Class 9
Subsidiary risk Label(s) 9
Hazard No. (ADR) 90
Tunnel restriction code E
14.4. Packing group III
14.5. Environmental hazards No.

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

name

RID

14.1. UN number UN3082

14.2. UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:--reaction

Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))

14.3. Transport hazard class(es)

Class 9
Subsidiary risk Label(s) 9
14.4. Packing group III
14.5. Environmental hazards No.

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. UN number UN3082

14.2. UN proper shipping Environmentally Hazardous Liquid, N.o.s. (Epoxy Resin:--reaction Product Of Bisphenol A And

name Epichlorohydrin (refer To Epichlorohydrin))

14.3. Transport hazard class(es)

Class 9
Subsidiary risk Label(s) 9
14.4. Packing group III
14.5. Environmental hazards No.

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN3082

14.2. UN proper shipping Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin:--reaction Product Of

name Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))

14.3. Transport hazard class(es)

Class 9
Subsidiary risk 14.4. Packing group III
14.5. Environmental hazards No.
ERG Code 9L

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

Other information Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

14.1. UN number UN3082

14.2. UN proper shipping ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:--reaction

name Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)), MARINE POLLUTANT

14.3. Transport hazard class(es)

Class 9
Subsidiary risk 14.4. Packing group III
14.5. Environmental hazards
Marine pollutant Yes
EmS F-A, S-F


14.6. Special precautions

for user

tions Read safety instructions, SDS and emergency procedures before handling.

14.7. Maritime transport in bulk Not established. according to IMO instruments

ADN; ADR; IATA; IMDG; RID



Marine pollutant



General information IMDG Regulated Marine Pollutant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

CARBON BLACK (CAS 1333-86-4)

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (CAS 13463-67-7)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

UFI:

Austria: H050-60UJ-A00F-6JWE Belgium: H050-60UJ-A00F-6JWE Bulgaria: H050-60UJ-A00F-6JWE Croatia: H050-60UJ-A00F-6JWE Cyprus: H050-60UJ-A00F-6JWE

Czech Republic: H050-60UJ-A00F-6JWE Denmark: H050-60UJ-A00F-6JWE Estonia: H050-60UJ-A00F-6JWE EU: H050-60UJ-A00F-6JWE Finland: H050-60UJ-A00F-6JWE France: H050-60UJ-A00F-6JWE Germany: H050-60UJ-A00F-6JWE Greece: H050-60UJ-A00F-6JWE Hungary: H050-60UJ-A00F-6JWE Iceland: H050-60UJ-A00F-6JWE Ireland: H050-60UJ-A00F-6JWE Italy: H050-60UJ-A00F-6JWE Latvia: H050-60UJ-A00F-6JWE Lithuania: H050-60UJ-A00F-6JWE Luxembourg: H050-60UJ-A00F-6JWE Malta: H050-60UJ-A00F-6JWE Netherlands: H050-60UJ-A00F-6JWE Norway: H050-60UJ-A00F-6JWE Poland: H050-60UJ-A00F-6JWE Portugal: H050-60UJ-A00F-6JWE Romania: H050-60UJ-A00F-6JWE Slovakia: H050-60UJ-A00F-6JWE Slovenia: H050-60UJ-A00F-6JWE Spain: H050-60UJ-A00F-6JWE

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Sweden: H050-60UJ-A00F-6JWE

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Crystalline SiO2 (Quartz) (CAS 14808-60-7)

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended Other EU regulations

ANNEX 1. PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- E2 Hazardous to the Aquatic Environment Chronic

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Other regulations

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

Young people under 18 years old are not allowed to work with this product according to EU **National regulations**

Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

Contains a substance which is included on the TRGS 905 list of carcinogenic, germ cell mutagenic and reproductive toxic substances

CARBON BLACK (CAS 1333-86-4)

Anorganische Faserstäube, soweit nicht erwähnt (ausgenommen

Gipsfasernund Wollastonitfasern)

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]

Anorganische Faserstäube, soweit nicht erwähnt (ausgenommen

(CAS 13463-67-7)

Gipsfasernund Wollastonitfasern)

France regulations

France INRS Table of Occupational Diseases

Crystalline SiO2 (Quartz) (CAS 14808-60-7)

Affections consécutives à l'inhalation de poussières minérales renfermant de la silicecristalline (quartz, cristobalite, tridymite), des silicates cristallins (kaolin, talc), du graphite ou de la houille 25

Epoxy Resin: Reaction product of bisphenol A and epichlorohydrin (refer to epichlorohydrin)

(CAS 25068-38-6)

Maladies professionnelles provoquées par les résines époxydiques et leurs constituants 51

Product registration number

UFI: H050-60UJ-A00F-6JWE Austria Belgium UFI: H050-60UJ-A00F-6JWE Czech Republic UFI: H050-60UJ-A00F-6JWE **Denmark** UFI: H050-60UJ-A00F-6JWE **European Union** UFI: H050-60UJ-A00F-6JWE **Finland** UFI: H050-60UJ-A00F-6JWE **France** UFI: H050-60UJ-A00F-6JWE Germany UFI: H050-60UJ-A00F-6JWE UFI: H050-60UJ-A00F-6JWE Greece UFI: H050-60UJ-A00F-6JWE Hungary UFI: H050-60UJ-A00F-6JWE Italy UFI: H050-60UJ-A00F-6JWE Netherlands Norway UFI: H050-60UJ-A00F-6JWE **Poland** UFI: H050-60UJ-A00F-6JWE **Portugal** UFI: H050-60UJ-A00F-6JWE UFI: H050-60UJ-A00F-6JWE Slovakia Slovenia UFI: H050-60UJ-A00F-6JWE Spain UFI: H050-60UJ-A00F-6JWE Sweden UFI: H050-60UJ-A00F-6JWE UFI: H050-60UJ-A00F-6JWE Switzerland

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H331 Toxic if inhaled. H350 May cause cancer.

Revision information
Training information

Disclaimer

H351 Suspected of causing cancer.

None.

Follow training instructions when handling this material.

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: Chockfast Gray Resin
GP103R Version #: 12 Revision date: 07-26-2023 Issue date: 03-11-2013