# SAFETY DATA SHEET

1. Identification		
Product identifier	Chockfast Black Resin	
Other means of identification		
SKU#	GP104R	
Recommended use	Not available.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier	/Distributor information	
Company name	ITW Performance Polymers	
Address	35 Brownridge Road	
	Unit 1	
	Halton Hills, ON L7G 0C6	
Contact person	Customer Service	
Telephone number	215-855-8450	
Fax number	215-855-4688	
Emergency Number	800-424-9300 (CHEMTREC)	
Supplier	Not available.	
2. Hazard identification		
Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
Label elements		
Signal word	Warning	
Hazard statement		kin reaction. Causes serious eye irritation. Causes ns () through prolonged or repeated exposure. Toxic sting effects.
Precautionary statement		
Prevention	Avoid breathing mist/vapours. Wash thorough should not be allowed out of the workplace. Av protection/face protection. Wear protective glo	void release to the environment. Wear eye
Response	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Collect spillage.	
Storage	Not available.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Supplemental information	None.	
Other hazards	None known.	

# 3. Composition/information on ingredients

ixtures			
Chemical name	Common name and synonyms	CAS number	%
Crystalline SiO2 (Quartz)		14808-60-7	30 - 60
Epoxy Resin: reaction pro bisphenol A and epichloro (refer to epichlorohydrin)		25068-38-6	20 - < 30
Glass, Oxide		65997-17-3	15 - 30
Alicyclic glycidyl ether		14228-73-0	1 - 5
Butyrolactone		96-48-0	1 - 5
Carbon Black		1333-86-4	0.1 - 1
Other components below	reportable levels		< 1
dditional components			
Chemical name	Common name and synonyms	CAS number	%

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures	
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.
6. Accidental release mea	sures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Prevent entry into waterways, sewer, basements or confined areas.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

### 8. Exposure controls/personal protection

Crystalline SiO2 (Quartz)

(CAS 14808-60-7)

# Occupational exposure limits US. ACGIH Threshold Limit Values (TLV) Components Type Value Carbon Black (CAS TWA 3 mg/m3 1333-86-4) TWA 3 mg/m3

# Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended

TWA

Components	Туре	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.
Glass, Oxide (CAS 65997-17-3)	TWA	1 fibers/cm3	Fiber.
		5 mg/m3	Total particulate.
		5 mg/m3	Fiber, total

0.025 mg/m3

Respirable fraction.

# Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Glass, Oxide (CAS 65997-17-3)	TWA	1 fibers/cm3	Fiber.
		5 mg/m3	Inhalable fibers.

# Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended

Components	Туре	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Glass, Oxide (CAS 65997-17-3)	TWA	5 mg/m3	Inhalable fraction.

Components	Туре	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
Canada. Ontario OELs. (Co Components	ontrol of Exposure to Biological or Chen Type	nical Agents), as amended Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.
Canada. Quebec OELs. (Mi Components	inistry of Labor - Regulation respecting Type	occupational health and sa Value	afety), as amended Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable dust.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.
Canada. Saskatchewan OE Components	Ls (Occupational Health and Safety Reg Type	gulations, 1996, Table 21), a Value	as amended Form
Carbon Black (CAS	15 minute	7 mg/m3	
1333-86-4)		·	
	15 minute	3 mg/m3	Respirable fibers.
1333-86-4) Glass, Oxide (CAS		· ·	Respirable fibers.
1333-86-4) Glass, Oxide (CAS		3 mg/m3 10 mg/m3	
1333-86-4) Glass, Oxide (CAS 65997-17-3)	15 minute	3 mg/m3 10 mg/m3 the ingredient(s). d. Ventilation rates should be al exhaust ventilation, or oth ended exposure limits. If exp	Inhalable fraction. e matched to conditions. If er engineering controls to posure limits have not been
1333-86-4) Glass, Oxide (CAS 65997-17-3) logical limit values propriate engineering trols	15 minute No biological exposure limits noted for the Good general ventilation should be use applicable, use process enclosures, loc maintain airborne levels below recomme established, maintain airborne levels to	3 mg/m3 10 mg/m3 the ingredient(s). d. Ventilation rates should be al exhaust ventilation, or oth ended exposure limits. If exp an acceptable level. Provide	Inhalable fraction. e matched to conditions. If er engineering controls to oosure limits have not been e eyewash station and safety
1333-86-4) Glass, Oxide (CAS 65997-17-3) logical limit values propriate engineering trols	15 minute No biological exposure limits noted for the Good general ventilation should be use applicable, use process enclosures, loc maintain airborne levels below recomm established, maintain airborne levels to shower. <b>5, such as personal protective equipmen</b>	3 mg/m3 10 mg/m3 the ingredient(s). d. Ventilation rates should be al exhaust ventilation, or oth ended exposure limits. If exp an acceptable level. Provide <b>nt</b> or goggles). Face shield is re	Inhalable fraction. e matched to conditions. If er engineering controls to oosure limits have not been e eyewash station and safety
1333-86-4) Glass, Oxide (CAS 65997-17-3) logical limit values propriate engineering trols vidual protection measures Eye/face protection Skin protection	15 minute No biological exposure limits noted for the Good general ventilation should be use applicable, use process enclosures, loc maintain airborne levels below recomm established, maintain airborne levels to shower. <b>5, such as personal protective equipmer</b> Wear safety glasses with side shields (e	3 mg/m3 10 mg/m3 the ingredient(s). d. Ventilation rates should be al exhaust ventilation, or oth ended exposure limits. If exp an acceptable level. Provide <b>nt</b> or goggles). Face shield is re	Inhalable fraction. e matched to conditions. If er engineering controls to oosure limits have not been e eyewash station and safety commended.
1333-86-4) Glass, Oxide (CAS 65997-17-3) logical limit values propriate engineering trols vidual protection measures Eye/face protection Skin protection Hand protection	15 minute No biological exposure limits noted for t Good general ventilation should be use applicable, use process enclosures, loc maintain airborne levels below recomm established, maintain airborne levels to shower. <b>5, such as personal protective equipmer</b> Wear safety glasses with side shields ( Wear appropriate chemical resistant glo	3 mg/m3 10 mg/m3 the ingredient(s). d. Ventilation rates should be al exhaust ventilation, or oth ended exposure limits. If exp an acceptable level. Provide <b>nt</b> for goggles). Face shield is re oves.	Inhalable fraction. e matched to conditions. If er engineering controls to posure limits have not been e eyewash station and safety commended.
1333-86-4) Glass, Oxide (CAS 65997-17-3) logical limit values propriate engineering trols vidual protection measures Eye/face protection Skin protection Hand protection Other	15 minute No biological exposure limits noted for the Good general ventilation should be use applicable, use process enclosures, loc maintain airborne levels below recommendation established, maintain airborne levels to shower. <b>5, such as personal protective equipment</b> Wear safety glasses with side shields (wear appropriate chemical resistant glac Wear appropriate chemical resistant glac	3 mg/m3 10 mg/m3 the ingredient(s). d. Ventilation rates should be al exhaust ventilation, or oth ended exposure limits. If exp an acceptable level. Provide <b>nt</b> or goggles). Face shield is re oves. othing. Use of an impervious suitable respiratory equipmer	Inhalable fraction. e matched to conditions. If er engineering controls to posure limits have not been e eyewash station and safety commended.

Appearance	Liquid.
Physical state	Liquid.
Form	Liquid.
Colour	Black.
Odour	Slight.
Odour threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.

Initial boiling point and boiling range	>204.44 °C (>400 °F)
Flash point	>204.4 °C (>400.0 °F)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Explosive limit - lower ( %)	Not available.
Explosive limit – upper (%)	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	1.88 g/cm3
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
pH in aqueous solution	7
Specific gravity	1.88
10 Stability and reactivity	-

# 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidising agents.
Hazardous decomposition products	No hazardous decomposition products are known.

# 11. Toxicological information

Information on likely routes of e	exposure
Inhalation	No adverse effects due to inhalation are expected.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Information on toxicological eff	ects
Acute toxicity	

Components	Species	Test Results
Butyrolactone (CAS 96-48-0)		
Acute		
Dermal		
LD50	Guinea pig	5640 mg/kg

Components	Species	Test Results	
Inhalation			
LC50	Rat	> 2680 mg/m3, 4 Hours	
Oral			
LD50	Rat	1540 mg/kg	
Carbon Black (CAS 1333-86-4)			
Acute			
Oral	Det	> 9000 mm//m	
LD50	Rat	> 8000 mg/kg	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye rritation	Causes serious eye irritation.		
Respiratory or skin sensitisatior	ו		
Canada - Alberta OELs: Irrit			
Carbon Black (CAS 1333	-86-4)	Irritant	
Respiratory sensitisation	Not a respiratory sensitiser.		
Skin sensitisation	May cause an allergic skin reaction.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity			
ACGIH Carcinogens			
Carbon Black (CAS 1333		A3 Confirmed animal carcinogen with unknown relevance to humans.	
Crystalline SiO2 (Quartz) Canada - Alberta OELs: Car		A2 Suspected human carcinogen.	
Crystalline SiO2 (Quartz) Canada - Manitoba OELs: ca	,	Suspected human carcinogen.	
Carbon Black (CAS 1333-86-4) Crystalline SiO2 (Quartz) (CAS 14808-60-7) Canada - Quebec OELs: Carcinogen category		Confirmed animal carcinogen with unknown relevance to humans Suspected human carcinogen.	
Carbon Black (CAS 1333-86-4) Crystalline SiO2 (Quartz) (CAS 14808-60-7)		Detected carcinogenic effect in animals. Suspected carcinogenic effect in humans.	
IARC Monographs. Overall I	Evaluation of Carcinogenicity		
Butyrolactone (CAS 96-48-0) Carbon Black (CAS 1333-86-4) Crystalline SiO2 (Quartz) (CAS 14808-60-7)		3 Not classifiable as to carcinogenicity to humans. 2B Possibly carcinogenic to humans. 1 Carcinogenic to humans.	
	ogram (NTP) Report on Carcin		
Carbon Black (CAS 1333		Known To Be Human Carcinogen.	
Crystalline SiO2 (Quartz)	(CAS 14808-60-7)	Known To Be Human Carcinogen.	
Reproductive toxicity	This product is not expected t	o cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - epeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
12. Ecological information	ו ו		
Ecotoxicity	Toxic to aquatic life with long lasting effects.		
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.		
Bioaccumulative potential			
Partition coefficient n-octan Butyrolactone	ol / water (log Kow)	-0.64	
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmen	tal effects (e.g. ozone depletion, photochemical ozone creation n, global warming potential) are expected from this component.	
Material name: Chockfast Black Resir		SDS CAN.	

13. Disposal considerations		
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).	
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.	

# 14. Transport information

# TDG

Not regulated as dangerous goods.

### ΙΑΤΑ

UN number	UN3082
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin:reaction Product Of
	Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Packing group	
Environmental hazards	No.
ERG Code	9L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:reaction
	Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)), MARINE POLLUTANT
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Packing group	
Environmental hazards	
Marine pollutant	Yes
EmS	F-A, S-F
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not established.
Annex II of MARPOL 73/78 and	
the IBC Code	

# IATA; IMDG



## Marine pollutant



**General information** 

IMDG Regulated Marine Pollutant.

15. Regulatory informatio			
Canadian regulations	This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.		
Controlled Drugs and Subst	ances Act		
Not regulated. Export Control List (CEPA 1	999, Schedule 3)		
Not listed. Greenhouse Gases			
Not listed.			
Precursor Control Regulation			
Butyrolactone (CAS 96-4	8-0) Class A		
nternational regulations			
Stockholm Convention			
Not applicable. Rotterdam Convention			
Not applicable. <b>Kyoto Protocol</b>			
Not applicable. Montreal Protocol			
Not applicable. Basel Convention			
Not applicable.			
nternational Inventories			
Country(s) or region	Inventory name	On inventory (yes/no	
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Ye	
Canada	Domestic Substances List (DSL)	Ye	
Canada	Non-Domestic Substances List (NDSL)	Ν	
China	Inventory of Existing Chemical Substances in China (IECSC)	Ye	
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Ye	
Europe	European List of Notified Chemical Substances (ELINCS)	Ν	
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Ν	
Korea	Existing Chemicals List (ECL)	Ye	
New Zealand	New Zealand Inventory	Ye	
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Ye	
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Ye	

# 16. Other information

04-April-2019

**Revision date** 

Version No.

Disclaimer

26-July-2023

08

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.