SAFETY DATA SHEET

Version #: 11

Issue date: 10-02-2013 Revision date: 07-26-2023 Supersedes date: 07-12-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

Chockfast Black Resin

Registration number

Synonyms None.
SKU# GP104R

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified usesNot available.Uses advised againstNone known.

1.3. Details of the supplier of the safety data sheet

Company Name ITW Performance Polymers

Address Bay 150

Shannon Industrial Estate

Co. Clare Ireland V14 DF82

 Contact Person
 Customer Service

 Telephone Number
 353(61)771500

 353(61)471285

customerservice.shannon@itwpp.com

Emergency Phone Number 44(0) 1235 239 670 (24 hours)

1.4. Emergency telephone number

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons

Information Center

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Belgium National Poisons

Control Center

070 245 245 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Bulgaria National

Toxicological Information

Center

Fmail

+359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Croatia Poisons Information Center

+385 1 2348 342 (Hours of operation not provided. SDS/Product information may

not be available for the Emergency Service.)

Cyprus Poison Center 1401 (Available :

1401 (Available 24 hours a day. SDS/Product information may not be available

for the Emergency Service.)

Czech Republic National Poisons Information

Center

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons

Control Center

+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Estonia National Poisons Information Center

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be

available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Material name: Chockfast Black Resin
GP104R Version #: 11 Revision date: 07-26-2023 Issue date: 10-02-2013

1.4. Emergency telephone number

Greece Poison Information Centre

(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Hungary National Emergency Phone Number +36-80-201-199 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Iceland Poison Center

(+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Latvia Emergency medical

aid

+371 67042473 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.) Information Center

113

Lithuania Neatidėliotina informacija apsinuodijus

Latvia Poison and Drug

+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and **Emergency Department**

2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Netherlands National Poisons Information Center (NVIC)

NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel in cases of acute intoxications)

Norway Norwegian Poison Information Center

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Portugal Poison Center

800 250 250 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Romania Biroul RSI si Informare Toxicologica 021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be

available for the Emergency Service.)

Slovakia National Toxicological Information Center

+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Spain Toxicology Information Service

+ 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

112 - and ask for Poison Information (Available 24 hours a day. SDS/Product **Sweden National Poison** information may not be available for the Emergency Service.)

Information Center Switzerland Tox Info

145 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Suisse

Skin corrosion/irritation Category 2 H315 - Causes skin irritation. Serious eye damage/eye irritation Category 2 H319 - Causes serious eye irritation.

> Category 1 H317 - May cause an allergic skin

> > reaction.

Environmental hazards

Skin sensitization

Hazardous to the aquatic environment, Category 2 H411 - Toxic to aquatic life with

long lasting effects. long-term aquatic hazard

2.2. Label elements

Material name: Chockfast Black Resin GP104R Version #: 11 Revision date: 07-26-2023 Issue date: 10-02-2013

SDS FII

Label according to Regulation (EC) No. 1272/2008 as amended

Austria: 6PC0-P0PH-7002-S6CF Belgium: 6PC0-P0PH-7002-S6CF Bulgaria: 6PC0-P0PH-7002-S6CF Croatia: 6PC0-P0PH-7002-S6CF Cyprus: 6PC0-P0PH-7002-S6CF

Czech Republic: 6PC0-P0PH-7002-S6CF Denmark: 6PC0-P0PH-7002-S6CF Estonia: 6PC0-P0PH-7002-S6CF EU: 6PC0-P0PH-7002-S6CF Finland: 6PC0-P0PH-7002-S6CF France: 6PC0-P0PH-7002-S6CF Germany: 6PC0-P0PH-7002-S6CF Greece: 6PC0-P0PH-7002-S6CF Hungary: 6PC0-P0PH-7002-S6CF Iceland: 6PC0-P0PH-7002-S6CF

Ireland: 6PC0-P0PH-7002-S6CF Italy: 6PC0-P0PH-7002-S6CF Latvia: 6PC0-P0PH-7002-S6CF Lithuania: 6PC0-P0PH-7002-S6CF Luxembourg: 6PC0-P0PH-7002-S6CF Malta: 6PC0-P0PH-7002-S6CF Netherlands: 6PC0-P0PH-7002-S6CF

Norway: 6PC0-P0PH-7002-S6CF Poland: 6PC0-P0PH-7002-S6CF Portugal: 6PC0-P0PH-7002-S6CF Romania: 6PC0-P0PH-7002-S6CF Slovakia: 6PC0-P0PH-7002-S6CF Slovenia: 6PC0-P0PH-7002-S6CF Spain: 6PC0-P0PH-7002-S6CF

Sweden: 6PC0-P0PH-7002-S6CF

Crystalline SiO2 (Quartz), Epoxy Resin: reaction product of bisphenol A and epichlorohydrin (refer Contains:

to epichlorohydrin)

Hazard pictograms



Signal word Warning

Hazard statements

Causes skin irritation. H315

May cause an allergic skin reaction. H317 Causes serious eye irritation. H319 Causes damage to organs (). H370

Causes damage to organs () through prolonged or repeated exposure. H372

Toxic to aquatic life with long lasting effects. H411

Precautionary statements

Prevention

P261 Avoid breathing mist/vapors. P264 Wash thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace. P272

Avoid release to the environment. P273 Wear eye protection/face protection. P280

Wear protective gloves. P280

Response

IF ON SKIN: Wash with plenty of water. P302 + P352

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present P305 + P351 + P338

and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/attention. P333 + P313 If eye irritation persists: Get medical advice/attention. P337 + P313 Take off contaminated clothing and wash it before reuse. P362 + P364 Collect spillage.

Storage Not available.

Disposal

P391

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Supplemental label information None.

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

_				4.
Gen	orai	Into	rma	ti∩n

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Crystalline SiO2 (Quartz)	30 - 60	14808-60-7 238-878-4	-	-	#
Classification:	Carc. 1A;H	350			
Epoxy Resin: reaction product of bisphenol A and epichlorohydrin (refer to epichlorohydrin)	20 - < 30	25068-38-6 -	01-2119456619-26-0000	-	
Classification:	Skin Irrit. 2	;H315, Eye Irrit. 2;H3	319, Skin Sens. 1;H317		
Butyrolactone	1 - 5	96-48-0 202-509-5	-	-	
		4;H302;(ATE: 1540 000000002 mg/l), Ey	mg/kg bw), Acute Tox. 3;H33 e Irrit. 2;H319	1;(ATE:	

Other components below reportable

levels

Additional components

Chemical name % CAS-No. / EC No. REACH Registration No. Index No. Notes

-

> 10

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders. Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and

delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

Rash.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

During fire, gases hazardous to health may be formed.

GP104R Version #: 11 Revision date: 07-26-2023 Issue date: 10-02-2013

Material name: Chockfast Black Resin

5.3. Advice for firefighters

Special protective equipment for firefighters

Special fire fighting procedures

Move containers from fire area if you can do so without risk.

Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Ensure adequate ventilation. Avoid breathing mist/vapors. Local authorities should be advised if significant spillages cannot be contained. Use personal

protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into

drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid

release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008
- E2 Hazardous to the Aquatic Environment Chronic (Lower-tier requirements = 200 tons;

Upper-tier requirements = 500 tons)

7.3. Specific end use(s) Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBI. II, no. 184/2001, as amended

ComponentsTypeValueFormCrystalline SiO2 (Quartz)MAK0,05 mg/m3Respirable dust.(CAS 14808-60-7)

Belgium. OEL. Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1 - Chemical agents, as amended

ComponentsTypeValueFormCrystalline SiO2 (Quartz)
(CAS 14808-60-7)TWA0,1 mg/m3Respirable dust.

Bulgaria. OEL values of carcinogens and mutagens at work (Reg. 10/2003 on prot. from carcinogens and mutagens at work. Ann. 1), as amended

Components	Туре	Value	Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction and dust

Components	Туре	Value	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	MAC	0,1 mg/m3	
Czech Republic. Occupational ex 361/2007, Annex 2, Part A & Anne		s at work (Decree on protecti	ion of health at work,
Components	Туре	Value	Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
Denmark. Work Environment Aut Components	hority. Exposure Limits for Sub Type	stances & Materials, Annex 2 Value	? Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TLV	0,3 mg/m3	Total
		0,1 mg/m3	Respirable.
Estonia. OELs. Occupational Exp Components	osure Limits of Hazardous Subs	stances (Regulation No. 105/ Value	2001, Annex), as amended Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Fine dust, respiratory fraction
Finland. HTP-arvot, App 3., Bindi	na Limit Values Social Affairs a	nd Ministry of Health	iraction
Components	Type	Value	Form
Butyrolactone (CAS 96-48-0)	STEL	70 mg/m3	
		250 ppm	
	TWA	14 mg/m3	
		50 ppm	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,05 mg/m3	Respirable.
France. OELs. Occupational Expo Components	osure Limits as Prescribed by A Type	rt. R.4412-149 of Labor Code Value	, as amended Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	VME	0,1 mg/m3	Respirable dust.
France. Threshold Limit Values (\ Components	/LEP) for Occupational Exposu Type	re to Chemicals in France, IN Value	RS ED 984 Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	VME	0,1 mg/m3	Respirable fraction.
` '	ory binding (VRC)		
Hungary. OELs. Decree on protec			
Components	Туре	Value	Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
lceland. OELs. Regulation 390/20 Components	09 on Pollution Limits and Meas Type	sures to Reduce Pollution at Value	the Workplace, as amende Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,3 mg/m3	Total dust.
(6.15.1.000.00.1)		0,1 mg/m3	Respirable dust.
reland. OELVs, Schedules 1 & 2, Components	Code of Practice for Chemical A	Agents and Carcinogens Reg Value	julations Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
` Italy. OELs (Legislative Decree n. Components	81, 9 April 2008), as amended Type	Value	Form
Crystalline SiO2 (Quartz)	TWA	0,025 mg/m3	Respirable fraction.

1), as amended Components	Туре	Value	Form
Crystalline SiO2 (Quartz) CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
ithuania. OELs. Occupational Ex /-824/A1-389), as amended	posure Limit Values for Chem	ical Substances (Hygiene Nor	m HN 23:2011; Order No.
Components	Туре	Value	Form
Crystalline SiO2 (Quartz) CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction.
uxembourg. Chemical Substanc 35/2016, as amended	es Prohibited at Work (Annex l	III), G.D.R. of 14 November 201	6, OJ Memorial A, n °
Components	Туре	Value	Form
Crystalline SiO2 (Quartz) CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
letherlands. OELs per Annex XIII mended	of Working Conditions Regula	ation (Staatscourant no. 252, 2	9 December 2006), as
Components	Туре	Value	Form
Crystalline SiO2 (Quartz) CAS 14808-60-7)	TWA	0,075 mg/m3	Respirable dust.
Norway. Regulation No. 1358 on I nfection Groups for Biological Fa		Physical and Chemical Factor	s in Work Environment a
Components	Туре	Value	Form
Crystalline SiO2 (Quartz) CAS 14808-60-7)	TLV	0,3 mg/m3	Total dust.
,		0,05 mg/m3	Respirable dust.
Poland. Maximum permissible co 286/2018, Annex 1)	ncentrations and intensities of	f harmful factors in the work e	nvironment (Dz.U.Poz.
Components	Туре	Value	Form
Crystalline SiO2 (Quartz) CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction.
Portugal. VLEs. Norm on occupat	-		
Components	Туре	Value	Form
Crystalline SiO2 (Quartz) CAS 14808-60-7)	TWA	0,025 mg/m3	Respirable fraction.
Slovakia. OELs for carcinogens a	nd mutagens. Regulation No. 3	356/2006 on carcinogenic and	mutagenic substances, a
mended			
	Туре	Value	Form
Components Crystalline SiO2 (Quartz)	Type TWA	Value 0,1 mg/m3	Form Respirable fraction.
Components Crystalline SiO2 (Quartz) CAS 14808-60-7) Spain. OELs. INSST, Límites de E	TWA	0,1 mg/m3	Respirable fraction.
Components Crystalline SiO2 (Quartz) CAS 14808-60-7) Spain. OELs. INSST, Límites de E VLAs)	TWA	0,1 mg/m3	Respirable fraction.
Components Crystalline SiO2 (Quartz) CAS 14808-60-7) Spain. OELs. INSST, Límites de E VLAs) Components Crystalline SiO2 (Quartz) CAS 14808-60-7)	TWA xposición Profesional Para Ag	0,1 mg/m3 gentes Químicos, Table 1-Valo	Respirable fraction. res Límites Ambientales
Components Crystalline SiO2 (Quartz) CAS 14808-60-7) Spain. OELs. INSST, Límites de E VLAs) Components Crystalline SiO2 (Quartz)	TWA xposición Profesional Para Ag Type TWA	0,1 mg/m3 gentes Químicos, Table 1-Valor Value 0,05 mg/m3	Respirable fraction. res Límites Ambientales Form Respirable fraction.
Components Crystalline SiO2 (Quartz) CAS 14808-60-7) Spain. OELs. INSST, Límites de EVLAs) Components Crystalline SiO2 (Quartz) CAS 14808-60-7) Sweden. OELs (Annex 1). Work Emended	TWA xposición Profesional Para Ag Type TWA	0,1 mg/m3 gentes Químicos, Table 1-Valor Value 0,05 mg/m3	Respirable fraction. res Límites Ambientales Form Respirable fraction.
Components Crystalline SiO2 (Quartz) CAS 14808-60-7) Spain. OELs. INSST, Límites de EVLAs) Components Crystalline SiO2 (Quartz) CAS 14808-60-7) Sweden. OELs (Annex 1). Work E	TWA Exposición Profesional Para Ag Type TWA nvironment Authority (AV), Oc	0,1 mg/m3 Jentes Químicos, Table 1-Valor Value 0,05 mg/m3 cupational Exposure Limit Valor	Respirable fraction. res Límites Ambientales Form Respirable fraction. ues (AFS 2018:1), as
Components Crystalline SiO2 (Quartz) CAS 14808-60-7) Spain. OELs. INSST, Límites de EVLAs) Components Crystalline SiO2 (Quartz) CAS 14808-60-7) Sweden. OELs (Annex 1). Work Eumended Components Crystalline SiO2 (Quartz) CAS 14808-60-7) Switzerland. SUVA Grenzwerte ar	TWA Exposición Profesional Para Ag Type TWA Invironment Authority (AV), Oct Type TWA TWA TWA TARA ARTORITA ARTORITA ARTORITA AG	0,1 mg/m3 yentes Químicos, Table 1-Valor Value 0,05 mg/m3 cupational Exposure Limit Val Value 0,1 mg/m3 Verte	Respirable fraction. res Límites Ambientales Form Respirable fraction. lues (AFS 2018:1), as Form Respirable dust.
Components Crystalline SiO2 (Quartz) CAS 14808-60-7) Spain. OELs. INSST, Límites de EVLAs) Components Crystalline SiO2 (Quartz) CAS 14808-60-7) Sweden. OELs (Annex 1). Work Emended Components Crystalline SiO2 (Quartz)	TWA Exposición Profesional Para Ag Type TWA Invironment Authority (AV), Oct Type TWA	0,1 mg/m3 gentes Químicos, Table 1-Valor Value 0,05 mg/m3 cupational Exposure Limit Val Value 0,1 mg/m3	Respirable fraction. res Límites Ambientales Form Respirable fraction. ues (AFS 2018:1), as Form

UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1
Components Type Value Form

Crystalline SiO2 (Quartz) TWA 0,1 mg/m3 Respirable.

(CAS 14808-60-7)

EU. OELs, Directive 2004/37/EC on carcinogen and mutagens from Annex III, Part A, as amended Components

Type

Value

F

ComponentsTypeValueFormCrystalline SiO2 (Quartz)
(CAS 14808-60-7)TWA0,1 mg/m3Respirable fraction and dust

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures

Follow standard monitoring procedures.

Derived no effect levels

(DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

Exposure guidelines

Finland Exposure Limit Values: Skin designation

Butyrolactone (CAS 96-48-0) Can be absorbed through the skin.

Germany DFG MAK (advisory): Skin designation

Butyrolactone (CAS 96-48-0)

Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

- Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. **Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

Environmental exposure

controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable

levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquid.FormLiquid.ColorBlack.OdorSlight.

Melting point/freezing point Not av

Not available.

Boiling point or initial boiling

Material name: Chockfast Black Resin

point and boiling range

>400 °F (>204,44 °C)

Flammability Not applicable.

Flash point >400,0 °F (>204,4 °C)

Auto-ignition temperature Not available.

Decomposition temperatureNot available.pHNot available.Kinematic viscosityNot available.

Solubility

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water) (log value)

Vapor pressure Not available.

Density and/or relative density

Density1,88 g/cm3Vapor densityNot available.Particle characteristicsNot available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No relevant additional information available.

9.2.2. Other safety characteristicspH in aqueous solutionSpecific gravity1,88

SECTION 10: Stability and reactivity

10.1. ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoidContact with incompatible materials.

10.5. Incompatible materials Strong oxidizing agents.

10.6. Hazardous No hazardous decomposition products are known.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Components Species Test Results

Butyrolactone (CAS 96-48-0)

Acute

Dermal

LD50 Guinea pig 5640 mg/kg

Inhalation

LC50 Rat > 2680 mg/m3, 4 Hours

Oral

LD50 Rat 1540 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitizationDue to partial or complete lack of data the classification is not possible.

Skin sensitization May cause an allergic skin reaction.

Material name: Chockfast Black Resin

GP104R Version #: 11 Revision date: 07-26-2023 Issue date: 10-02-2013

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Carcinogenicity Not classified.

IARC Monographs. Overall Evaluation of Carcinogenicity

Butyrolactone (CAS 96-48-0) 3 Not classifiable as to carcinogenicity to humans.

Crystalline SiO2 (Quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

Reproductive toxicityDue to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazardDue to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

11.2. Information on other hazards

Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

Butyrolactone -0,64

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

12.7. Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste codeThe Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Special precautionsDispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN3082

14.2. UN proper shipping

Material name: Chockfast Black Resin

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:--reaction

Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin))

14.3. Transport hazard class(es)

Class 9

Subsidiary risk 9 Label(s) Hazard No. (ADR) 90 Ε **Tunnel restriction code** 14.4. Packing group Ш 14.5. Environmental hazards No. Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions for user RID 14.1. UN number UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:--reaction 14.2. UN proper shipping Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)) name 14.3. Transport hazard class(es) 9 Class Subsidiary risk 9 Label(s) Ш 14.4. Packing group 14.5. Environmental hazards No. 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user LIN3082

ADN

14.1. UN number

14.2. UN proper shipping Environmentally Hazardous Liquid, N.o.s. (Epoxy Resin:--reaction Product Of Bisphenol A And

Epichlorohydrin (refer To Epichlorohydrin)) name

14.3. Transport hazard class(es)

9 Class Subsidiary risk 9 Label(s) Ш 14.4. Packing group 14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

UN3082 14.1. UN number

14.2. UN proper shipping Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin:--reaction Product Of

Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)) name

14.3. Transport hazard class(es)

Class 9 Subsidiary risk Ш 14.4. Packing group 14.5. Environmental hazards No. 9L **FRG Code**

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Allowed with restrictions. Cargo aircraft only

IMDG

UN3082 14.1. UN number

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin:--reaction 14.2. UN proper shipping

Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)), MARINE POLLUTANT name

14.3. Transport hazard class(es)

9 Class Subsidiary risk Ш 14.4. Packing group 14.5. Environmental hazards Marine pollutant Yes

F-A. S-F **EmS**


14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

14.7. Maritime transport in bulk Not established.

according to IMO instruments

Material name: Chockfast Black Resin GP104R Version #: 11 Revision date: 07-26-2023 Issue date: 10-02-2013 ADN; ADR; IATA; IMDG; RID



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Material name: Chockfast Black Resin

SDS EU 12 / 14

UFI:

Austria: 6PC0-P0PH-7002-S6CF
Belgium: 6PC0-P0PH-7002-S6CF
Bulgaria: 6PC0-P0PH-7002-S6CF
Croatia: 6PC0-P0PH-7002-S6CF
Cyprus: 6PC0-P0PH-7002-S6CF
Czech Republic: 6PC0-P0PH-7002-S6CF
Denmark: 6PC0-P0PH-7002-S6CF
Estonia: 6PC0-P0PH-7002-S6CF
EU: 6PC0-P0PH-7002-S6CF
Finland: 6PC0-P0PH-7002-S6CF
France: 6PC0-P0PH-7002-S6CF
Germany: 6PC0-P0PH-7002-S6CF
Greece: 6PC0-P0PH-7002-S6CF
Lungary: 6PC0-P0PH-7002-S6CF
Lungary: 6PC0-P0PH-7002-S6CF
Lungary: 6PC0-P0PH-7002-S6CF

Hungary: 6PC0-P0PH-7002-S6CF Iceland: 6PC0-P0PH-7002-S6CF Ireland: 6PC0-P0PH-7002-S6CF Ireland: 6PC0-P0PH-7002-S6CF Italy: 6PC0-P0PH-7002-S6CF Latvia: 6PC0-P0PH-7002-S6CF Lithuania: 6PC0-P0PH-7002-S6CF Luxembourg: 6PC0-P0PH-7002-S6CF Malta: 6PC0-P0PH-7002-S6CF Netherlands: 6PC0-P0PH-7002-S6CF Norway: 6PC0-P0PH-7002-S6CF Poland: 6PC0-P0PH-7002-S6CF Portugal: 6PC0-P0PH-7002-S6CF

Slovakia: 6PC0-P0PH-7002-S6CF Slovenia: 6PC0-P0PH-7002-S6CF Spain: 6PC0-P0PH-7002-S6CF Sweden: 6PC0-P0PH-7002-S6CF

Romania: 6PC0-P0PH-7002-S6CF

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Crystalline SiO2 (Quartz) (CAS 14808-60-7)

Other EU regulations Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- E2 Hazardous to the Aquatic Environment Chronic

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Young people under 18 years old are not allowed to work with this product according to EU

Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

France regulations

France INRS Table of Occupational Diseases

Crystalline SiO2 (Quartz) (CAS 14808-60-7)

Affections

Affections consécutives à l'inhalation de poussières minérales renfermant de la silicecristalline (quartz, cristobalite, tridymite), des silicates cristallins (kaolin, talc), du graphite ou de la houille

25

Epoxy Resin: reaction product of bisphenol A and

epichlorohydrin (refer to epichlorohydrin)

(CAS 25068-38-6)

Maladies professionnelles provoquées par les résines époyydiques et leurs constituents 51

époxydiques et leurs constituants 51

Product registration number

 Austria
 UFI: 6PC0-P0PH-7002-S6CF

 Czech Republic
 UFI: 6PC0-P0PH-7002-S6CF

 Denmark
 UFI: 6PC0-P0PH-7002-S6CF

 European Union
 UFI: 6PC0-P0PH-7002-S6CF

 Finland
 UFI: 6PC0-P0PH-7002-S6CF

 France
 UFI: 6PC0-P0PH-7002-S6CF

UFI: 6PC0-P0PH-7002-S6CF Germany Greece UFI: 6PC0-P0PH-7002-S6CF UFI: 6PC0-P0PH-7002-S6CF Hungary UFI: 6PC0-P0PH-7002-S6CF Italy UFI: 6PC0-P0PH-7002-S6CF **Netherlands** Norway UFI: 6PC0-P0PH-7002-S6CF **Poland** UFI: 6PC0-P0PH-7002-S6CF UFI: 6PC0-P0PH-7002-S6CF **Portugal** Slovakia UFI: 6PC0-P0PH-7002-S6CF UFI: 6PC0-P0PH-7002-S6CF Slovenia UFI: 6PC0-P0PH-7002-S6CF Spain Sweden UFI: 6PC0-P0PH-7002-S6CF **Switzerland** UFI: 6PC0-P0PH-7002-S6CF

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland

Waterways.

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

Not available.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full

under sections 2 to 15

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled. H350 May cause cancer.

Revision information

Training information

Follow training instructions when handling this material.

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: Chockfast Black Resin