SAFETY DATA SHEET

1. Identification

Product identifier Chockfast Red Resin

Other means of identification

SKU# GP107R

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name

ITW Performance Polymers

Address

35 Brownridge Road

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number215-855-8450Fax number215-855-4688

Emergency Number 800-424-9300 (CHEMTREC)

Supplier Not available.

2. Hazard identification

Physical hazards Flammable liquids Category 4 **Health hazards** Acute toxicity, dermal Category 4 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Sensitization, skin Category 1 **Environmental hazards** Hazardous to the aquatic environment, acute Category 2 hazard Hazardous to the aquatic environment, Category 2

Label elements



long-term hazard

Signal word Warning

Hazard statement Combustible liquid. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin

reaction. May be harmful if inhaled. Toxic to aquatic life. Toxic to aquatic life with long lasting

effects.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Avoid breathing mist/vapours. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective

gloves/protective clothing/eye protection/face protection.

Response IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to

extinguish.

Storage Store in a well-ventilated place.

GP107R Version #: 11 Revision date: 26-July-2023 Issue date: 25-March-2019

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: Chockfast Red Resin

SDS CANADA

95 % of the mixture consists of component(s) of unknown acute oral toxicity. 95 % of the mixture

consists of component(s) of unknown acute dermal toxicity.

Other hazards

None known.

3. Composition/information on ingredients

|--|

Chemical name	Common name and synonyms	CAS number	%
Epoxy Resin: Reaction product bisphenol A and epichlorohydrin (refer to epichlorohydrin)		25068-38-6	60 - 100
Xylene	XYLENE	1330-20-7	1 - 5
Ethyl benzene		100-41-4	< 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

	4.	Firs	t-aid	measur	es
--	----	------	-------	--------	----

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Get medical advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Eye contact

Ingestion

delayed

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and

Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated

clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

General information

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters Do not use water jet as an extinguisher, as this will spread the fire.

The product is combustible, and heating may generate vapours which may form explosive vapour/air mixtures. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: Chockfast Red Resin SDS CANADA

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH	Threshold	I imit	Values	(TI V)
OO. ACCIII	IIIIESIIOIU	∟ !!!!	v alues	(I 🗕 V /

Components	Туре	Value
Ethyl benzene (CAS 100-41-4)	TWA	20 ppm
Xylene (CAS 1330-20-7)	TWA	20 ppm

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended

Components	Туре	Value	
Ethyl benzene (CAS 100-41-4)	STEL	543 mg/m3	
		125 ppm	
	TWA	434 mg/m3	
		100 ppm	
Xylene (CAS 1330-20-7)	STEL	651 mg/m3	
		150 ppm	
	TWA	434 mg/m3	
		100 ppm	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	
Ethyl benzene (CAS 100-41-4)	TWA	20 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended

Components	Type	Value
Ethyl benzene (CAS 100-41-4)	TWA	20 ppm
Xylene (CAS 1330-20-7)	TWA	20 ppm

Material name: Chockfast Red Resin

GP107R Version #: 11 Revision date: 26-July-2023 Issue date: 25-March-2019

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191)

Components	Туре	Value
Ethyl benzene (CAS 100-41-4)	STEL	543 mg/m3
		125 ppm
	TWA	434 mg/m3
		100 ppm
Xylene (CAS 1330-20-7)	STEL	651 mg/m3
		150 ppm
	TWA	434 mg/m3
		100 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended

Components	Value
Ethyl benzene (CAS TWA 100-41-4)	20 ppm
Xylene (CAS 1330-20-7) STEL	150 ppm
TWA	100 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended Components Type Value

Components	туре	value
Ethyl benzene (CAS 100-41-4)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	651 mg/m3
		150 ppm
	TWA	434 mg/m3
		100 ppm

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended Components Type Value

•	* •		
Ethyl benzene (CAS 100-41-4)	15 minute	125 ppm	
	8 hour	100 ppm	
Xylene (CAS 1330-20-7)	15 minute	150 ppm	
	8 hour	100 ppm	

Biological limit values

ACGIH Biological Exposure Indices (BEI)

Components	Value (BEI)	Determinant	Specimen	Sampling Time
Ethyl benzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Material name: Chockfast Red Resin SDS CANADA

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Viscous. Liquid.

Physical state Liquid.
Form Liquid.

Colour Colourless to light yellow.

Odour Aromatic. Hydrocarbon-like.

Odour threshold Not available.

pH 7

Melting point/freezing point Not available.

Initial boiling point and boiling 138 °C (280.4 °F)

range

Flash point 65.6 °C (150.0 °F) Pensky-Martens Closed Cup

Evaporation rate 0.6

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper Not available.

(%)

Vapour pressure 5.6 hPa estimated

Vapour density 3.5

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.
(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Flammability class Combustible IIIA estimated Combustible IIIA estimated

Oxidising properties Not oxidising.

Specific gravity 1.2 VOC 52 g/l

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidAvoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Material name: Chockfast Red Resin SDS CANADA

Incompatible materials

Strong acids. Strong oxidising agents. Halogens.

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Harmful in contact with skin.

Components Species Test Results

Ethyl benzene (CAS 100-41-4)

<u>Acute</u>

Dermal

LD50 Rabbit 17800 mg/kg

Oral

LD50 Rat 3500 mg/kg

Xylene (CAS 1330-20-7)

<u>Acute</u>

Dermal

LD50 Rabbit > 43 g/kg

Oral

LD50 Rat 3523 - 8600 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitisation

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

Ethyl benzene (CAS 100-41-4)

A3 Confirmed animal carcinogen with unknown relevance to

humans.

Xylene (CAS 1330-20-7) A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Ethyl benzene (CAS 100-41-4) Confirmed animal carcinogen with unknown relevance to humans.

Xylene (CAS 1330-20-7) Not classifiable as a human carcinogen.

Canada - Quebec OELs: Carcinogen category

Ethyl benzene (CAS 100-41-4) Detected carcinogenic effect in animals.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethyl benzene (CAS 100-41-4) 2B Possibly carcinogenic to humans.

Xylene (CAS 1330-20-7) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in

laboratory animals.

Specific target organ toxicity -

single exposure

Not classified.

Material name: Chockfast Red Resin SDS CANADA

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Toxic to aquatic life with long lasting effects. **Ecotoxicity**

No data is available on the degradability of any ingredients in the mixture. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Ethyl benzene 3.15 **Xylene** 3.12 - 3.2

Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Allowed with restrictions.

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

UN3082 **UN** number

UN proper shipping name

Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin)

Transport hazard class(es)

Class 9 Subsidiary risk Packing group Ш **Environmental hazards** Yes 9I **ERG Code**

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions. Cargo aircraft only

IMDG

UN3082 **UN** number

UN proper shipping name Transport hazard class(es) Environmentally hazardous substances, liquid, n.o.s. (Epoxy Resin), MARINE POLLUTANT

9 Class Subsidiary risk 9 Label(s) Packing group Ш

Environmental hazards


Marine pollutant Yes

EmS Not assigned.

Material name: Chockfast Red Resin SDS CANADA **Special precautions for user** Read safety instructions, SDS and emergency procedures before handling. **nsport in bulk according to** Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)

Ethyl benzene (CAS 100-41-4)

Xylene (CAS 1330-20-7)

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
A 4 1! -	A (): 1 () () () () () () () () () (\/

Australia Australian Inventory of Industrial Chemicals (AICIS)

Canada Domestic Substances List (DSL)

Yes

Material name: Chockfast Red Resin

SDS CANADA

On inventory (yes/no)* Country(s) or region Inventory name Canada Non-Domestic Substances List (NDSL) China Inventory of Existing Chemical Substances in China (IECSC) Yes European Inventory of Existing Commercial Chemical Europe No Substances (EINECS)

European List of Notified Chemical Substances (ELINCS) Europe No Japan Inventory of Existing and New Chemical Substances (ENCS) No Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes Yes

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information

25-March-2019 Issue date **Revision date** 26-July-2023

Version No.

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information Physical & Chemical Properties: Multiple Properties

Material name: Chockfast Red Resin SDS CANADA

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).